
Logtalk APIs

Release v3.92.0

Paulo Moura

May 28, 2025

CONTENTS

| | | |
|--------|----------------------------|----|
| 1 | Libraries | 1 |
| 1.1 | arbitrary | 1 |
| 1.1.1 | arbitrary | 1 |
| 1.2 | assertions | 7 |
| 1.2.1 | assertions | 8 |
| 1.2.2 | assertions(Mode) | 9 |
| 1.2.3 | assertions_messages | 11 |
| 1.3 | assignvars | 12 |
| 1.3.1 | assignvars | 12 |
| 1.3.2 | assignvarsp | 13 |
| 1.4 | base64 | 17 |
| 1.4.1 | base64 | 17 |
| 1.4.2 | base64url | 19 |
| 1.5 | cbor | 21 |
| 1.5.1 | cbor | 21 |
| 1.5.2 | cbor(StringRepresentation) | 22 |
| 1.6 | code_metrics | 24 |
| 1.6.1 | cc_metric | 24 |
| 1.6.2 | code_metric | 26 |
| 1.6.3 | code_metrics | 39 |
| 1.6.4 | code_metrics_messages | 40 |
| 1.6.5 | code_metrics_utilities | 41 |
| 1.6.6 | coupling_metric | 46 |
| 1.6.7 | dit_metric | 48 |
| 1.6.8 | doc_metric | 49 |
| 1.6.9 | halstead_metric | 54 |
| 1.6.10 | halstead_metric(Stroud) | 55 |
| 1.6.11 | noc_metric | 57 |
| 1.6.12 | nor_metric | 58 |
| 1.6.13 | size_metric | 60 |
| 1.6.14 | upn_metric | 61 |
| 1.7 | core | 63 |
| 1.7.1 | core_messages | 63 |
| 1.7.2 | expanding | 64 |
| 1.7.3 | forwarding | 66 |
| 1.7.4 | logtalk | 67 |
| 1.7.5 | monitoring | 82 |
| 1.7.6 | user | 84 |
| 1.8 | coroutining | 85 |
| 1.8.1 | coroutining | 85 |

| | | |
|---------|--------------------------------------|-----|
| 1.9 | csv | 88 |
| 1.9.1 | csv | 89 |
| 1.9.2 | csv(Header,Separator,IgnoreQuotes) | 90 |
| 1.9.3 | csv_guess_questions | 91 |
| 1.9.4 | csv_protocol | 93 |
| 1.10 | dates | 103 |
| 1.10.1 | date | 103 |
| 1.10.2 | datep | 104 |
| 1.10.3 | time | 108 |
| 1.10.4 | timep | 109 |
| 1.11 | dead_code_scanner | 111 |
| 1.11.1 | dead_code_scanner | 112 |
| 1.11.2 | dead_code_scanner_messages | 119 |
| 1.12 | debug_messages | 120 |
| 1.12.1 | debug_messages | 120 |
| 1.13 | debugger | 125 |
| 1.13.1 | debugger | 125 |
| 1.13.2 | debugger_messages | 133 |
| 1.13.3 | debuggerp | 134 |
| 1.13.4 | dump_trace | 146 |
| 1.14 | dependents | 148 |
| 1.14.1 | observer | 148 |
| 1.14.2 | subject | 150 |
| 1.15 | diagrams | 153 |
| 1.15.1 | d2_graph_language | 153 |
| 1.15.2 | diagram(Format) | 155 |
| 1.15.3 | diagrams | 178 |
| 1.15.4 | diagrams(Format) | 179 |
| 1.15.5 | directory_dependency_diagram | 189 |
| 1.15.6 | directory_dependency_diagram(Format) | 191 |
| 1.15.7 | directory_diagram(Format) | 192 |
| 1.15.8 | directory_load_diagram | 196 |
| 1.15.9 | directory_load_diagram(Format) | 197 |
| 1.15.10 | dot_graph_language | 199 |
| 1.15.11 | entity_diagram | 201 |
| 1.15.12 | entity_diagram(Format) | 202 |
| 1.15.13 | file_dependency_diagram | 206 |
| 1.15.14 | file_dependency_diagram(Format) | 207 |
| 1.15.15 | file_diagram(Format) | 209 |
| 1.15.16 | file_load_diagram | 213 |
| 1.15.17 | file_load_diagram(Format) | 214 |
| 1.15.18 | graph_language_protocol | 216 |
| 1.15.19 | graph_language_registry | 220 |
| 1.15.20 | inheritance_diagram | 221 |
| 1.15.21 | inheritance_diagram(Format) | 223 |
| 1.15.22 | library_dependency_diagram | 224 |
| 1.15.23 | library_dependency_diagram(Format) | 226 |
| 1.15.24 | library_diagram(Format) | 227 |
| 1.15.25 | library_load_diagram | 232 |
| 1.15.26 | library_load_diagram(Format) | 233 |
| 1.15.27 | modules_diagram_support | 235 |
| 1.15.28 | uses_diagram | 237 |
| 1.15.29 | uses_diagram(Format) | 239 |
| 1.15.30 | xref_diagram | 240 |

| | | |
|---------|----------------------------|-----|
| 1.15.31 | xref_diagram(Format) | 241 |
| 1.16 | dictionaries | 245 |
| 1.16.1 | avltree | 245 |
| 1.16.2 | bintree | 246 |
| 1.16.3 | dictionaryp | 249 |
| 1.16.4 | rbtree | 261 |
| 1.17 | dif | 263 |
| 1.17.1 | dif | 263 |
| 1.18 | doclet | 265 |
| 1.18.1 | doclet | 265 |
| 1.19 | edcg | 267 |
| 1.19.1 | edcg | 268 |
| 1.20 | events | 271 |
| 1.20.1 | after_event_registry | 271 |
| 1.20.2 | before_event_registry | 272 |
| 1.20.3 | event_registry | 274 |
| 1.20.4 | event_registryp | 275 |
| 1.20.5 | monitor | 279 |
| 1.20.6 | monitorp | 280 |
| 1.21 | expand_library_alias_paths | 284 |
| 1.21.1 | expand_library_alias_paths | 284 |
| 1.22 | expecteds | 285 |
| 1.22.1 | either | 285 |
| 1.22.2 | expected | 288 |
| 1.22.3 | expected(Expected) | 293 |
| 1.23 | fcube | 301 |
| 1.23.1 | fcube | 301 |
| 1.24 | flags | 305 |
| 1.24.1 | flags | 305 |
| 1.24.2 | flags_validator | 312 |
| 1.25 | format | 314 |
| 1.25.1 | format | 314 |
| 1.26 | genint | 316 |
| 1.26.1 | genint | 316 |
| 1.26.2 | genint_core | 318 |
| 1.27 | gensym | 320 |
| 1.27.1 | gensym | 320 |
| 1.27.2 | gensym_core | 321 |
| 1.28 | git | 324 |
| 1.28.1 | git | 324 |
| 1.28.2 | git_protocol | 325 |
| 1.29 | grammars | 329 |
| 1.29.1 | blank_grammars(Format) | 329 |
| 1.29.2 | ip_grammars(Format) | 336 |
| 1.29.3 | number_grammars(Format) | 337 |
| 1.29.4 | sequence_grammars | 343 |
| 1.30 | heaps | 347 |
| 1.30.1 | heap(Order) | 347 |
| 1.30.2 | heapp | 348 |
| 1.30.3 | maxheap | 354 |
| 1.30.4 | minheap | 355 |
| 1.31 | help | 356 |
| 1.31.1 | help | 356 |
| 1.31.2 | help_info_support | 363 |

| | | |
|---------|--|-----|
| 1.32 | hierarchies | 366 |
| 1.32.1 | class_hierarchy | 366 |
| 1.32.2 | class_hierarchyp | 367 |
| 1.32.3 | hierarchyp | 374 |
| 1.32.4 | proto_hierarchy | 377 |
| 1.32.5 | proto_hierarchyp | 379 |
| 1.33 | hook_flows | 381 |
| 1.33.1 | hook_pipeline(Pipeline) | 382 |
| 1.33.2 | hook_set(Set) | 383 |
| 1.34 | hook_objects | 384 |
| 1.34.1 | backend_adapter_hook | 385 |
| 1.34.2 | default_workflow_hook | 386 |
| 1.34.3 | grammar_rules_hook | 387 |
| 1.34.4 | identity_hook | 389 |
| 1.34.5 | object_wrapper_hook | 390 |
| 1.34.6 | object_wrapper_hook(Protocol) | 391 |
| 1.34.7 | object_wrapper_hook(Name,Relations) | 393 |
| 1.34.8 | print_goal_hook | 394 |
| 1.34.9 | prolog_module_hook(Module) | 396 |
| 1.34.10 | suppress_goal_hook | 397 |
| 1.34.11 | write_to_file_hook(File) | 398 |
| 1.34.12 | write_to_file_hook(File,Options) | 400 |
| 1.34.13 | write_to_stream_hook(Stream) | 401 |
| 1.34.14 | write_to_stream_hook(Stream,Options) | 403 |
| 1.35 | html | 404 |
| 1.35.1 | html | 404 |
| 1.35.2 | html5 | 407 |
| 1.35.3 | xhtml11 | 408 |
| 1.36 | ids | 409 |
| 1.36.1 | ids | 409 |
| 1.36.2 | ids(Representation,Bytes) | 411 |
| 1.37 | intervals | 412 |
| 1.37.1 | interval | 413 |
| 1.37.2 | intervalp | 414 |
| 1.38 | iso8601 | 421 |
| 1.38.1 | iso8601 | 421 |
| 1.39 | issue_creator | 432 |
| 1.39.1 | issue_creator | 432 |
| 1.40 | java | 434 |
| 1.40.1 | java | 434 |
| 1.40.2 | java(Reference) | 435 |
| 1.40.3 | java(Reference,ReturnValue) | 437 |
| 1.40.4 | java_access_protocol | 438 |
| 1.40.5 | java_hook | 441 |
| 1.40.6 | java_utils_protocol | 443 |
| 1.41 | json | 452 |
| 1.41.1 | json | 452 |
| 1.41.2 | json(StringRepresentation) | 453 |
| 1.41.3 | json(ObjectRepresentation,PairRepresentation,StringRepresentation) | 454 |
| 1.41.4 | json_protocol | 456 |
| 1.42 | json_lines | 458 |
| 1.42.1 | json_lines | 458 |
| 1.42.2 | json_lines(StringRepresentation) | 459 |
| 1.42.3 | json_lines(ObjectRepresentation,PairRepresentation,StringRepresentation) | 460 |

| | | |
|---------|----------------------------|-----|
| 1.42.4 | json_lines_protocol | 462 |
| 1.43 | lgtdoc | 464 |
| 1.43.1 | lgtdoc | 464 |
| 1.43.2 | lgtdoc_messages | 467 |
| 1.43.3 | lgtdocp | 468 |
| 1.44 | lgtunit | 480 |
| 1.44.1 | automation_report | 480 |
| 1.44.2 | coverage_report | 481 |
| 1.44.3 | lgtunit | 483 |
| 1.44.4 | lgtunit_messages | 532 |
| 1.44.5 | minimal_output | 533 |
| 1.44.6 | tap_output | 535 |
| 1.44.7 | tap_report | 537 |
| 1.44.8 | xunit_net_v2_output | 539 |
| 1.44.9 | xunit_net_v2_report | 541 |
| 1.44.10 | xunit_output | 542 |
| 1.44.11 | xunit_report | 544 |
| 1.45 | library | 546 |
| 1.45.1 | cloning | 546 |
| 1.45.2 | counters | 547 |
| 1.45.3 | streamvars | 551 |
| 1.46 | listing | 554 |
| 1.46.1 | listing | 554 |
| 1.47 | logging | 557 |
| 1.47.1 | logger | 557 |
| 1.47.2 | logging | 559 |
| 1.47.3 | loggingp | 561 |
| 1.48 | loops | 565 |
| 1.48.1 | loop | 565 |
| 1.48.2 | loopp | 566 |
| 1.49 | meta | 572 |
| 1.49.1 | meta | 572 |
| 1.49.2 | metap | 573 |
| 1.50 | meta_compiler | 584 |
| 1.50.1 | meta_compiler | 584 |
| 1.51 | metagol | 586 |
| 1.51.1 | metagol | 586 |
| 1.51.2 | metagol_example_protocol | 593 |
| 1.52 | mutations | 595 |
| 1.52.1 | default_atom_mutations | 595 |
| 1.52.2 | default_compound_mutations | 597 |
| 1.52.3 | default_float_mutations | 598 |
| 1.52.4 | default_integer_mutations | 599 |
| 1.52.5 | default_list_mutations | 601 |
| 1.52.6 | mutations | 602 |
| 1.52.7 | mutations_store | 604 |
| 1.53 | nested_dictionaries | 607 |
| 1.53.1 | navltree | 607 |
| 1.53.2 | nbintree | 608 |
| 1.53.3 | nested_dictionary_protocol | 610 |
| 1.53.4 | nrbtree | 614 |
| 1.54 | optionals | 616 |
| 1.54.1 | maybe | 616 |
| 1.54.2 | optional | 618 |

| | | |
|------|-------------------------------|-----|
| | 1.54.3 optional(Optional) | 622 |
| 1.55 | options | 630 |
| | 1.55.1 options | 630 |
| | 1.55.2 options_protocol | 631 |
| 1.56 | os | 637 |
| | 1.56.1 os | 638 |
| | 1.56.2 os_types | 639 |
| | 1.56.3 osp | 641 |
| 1.57 | packs | 660 |
| | 1.57.1 pack_protocol | 660 |
| | 1.57.2 packs | 664 |
| | 1.57.3 packs_common | 692 |
| | 1.57.4 packs_messages | 704 |
| | 1.57.5 packs_specs_hook | 705 |
| | 1.57.6 registries | 707 |
| | 1.57.7 registry_loader_hook | 718 |
| | 1.57.8 registry_protocol | 720 |
| 1.58 | pddl_parser | 723 |
| | 1.58.1 pddl | 723 |
| | 1.58.2 read_file | 726 |
| 1.59 | ports_profiler | 728 |
| | 1.59.1 ports_profiler | 728 |
| 1.60 | queues | 734 |
| | 1.60.1 queue | 734 |
| | 1.60.2 queuep | 735 |
| 1.61 | random | 742 |
| | 1.61.1 backend_random | 742 |
| | 1.61.2 fast_random | 744 |
| | 1.61.3 pseudo_random_protocol | 746 |
| | 1.61.4 random | 748 |
| | 1.61.5 random_protocol | 751 |
| | 1.61.6 sampling_protocol | 760 |
| 1.62 | reader | 773 |
| | 1.62.1 reader | 773 |
| 1.63 | recorded_database | 782 |
| | 1.63.1 recorded_database | 782 |
| | 1.63.2 recorded_database_core | 783 |
| 1.64 | redis | 789 |
| | 1.64.1 redis | 789 |
| 1.65 | sets | 792 |
| | 1.65.1 set | 792 |
| | 1.65.2 set(Type) | 794 |
| | 1.65.3 setp | 796 |
| 1.66 | statistics | 806 |
| | 1.66.1 population | 806 |
| | 1.66.2 sample | 807 |
| | 1.66.3 statistics | 809 |
| | 1.66.4 statisticsp | 811 |
| 1.67 | term_io | 822 |
| | 1.67.1 term_io | 822 |
| | 1.67.2 term_io_protocol | 824 |
| 1.68 | timeout | 834 |
| | 1.68.1 timeout | 834 |
| 1.69 | toychr | 836 |

| | | | |
|------|------------------------|---------------------------------|-----|
| | 1.69.1 | toychrdb | 837 |
| 1.70 | tsv | | 842 |
| | 1.70.1 | tsv | 842 |
| | 1.70.2 | tsv(Header) | 843 |
| | 1.70.3 | tsv_protocol | 845 |
| 1.71 | tutor | | 854 |
| | 1.71.1 | tutor | 854 |
| 1.72 | types | | 856 |
| | 1.72.1 | atom | 856 |
| | 1.72.2 | atomic | 858 |
| | 1.72.3 | callable | 859 |
| | 1.72.4 | character | 860 |
| | 1.72.5 | characterp | 862 |
| | 1.72.6 | comparingp | 871 |
| | 1.72.7 | compound | 874 |
| | 1.72.8 | difflist | 875 |
| | 1.72.9 | float | 878 |
| | 1.72.10 | integer | 880 |
| | 1.72.11 | list | 884 |
| | 1.72.12 | list(Type) | 886 |
| | 1.72.13 | listp | 887 |
| | 1.72.14 | natural | 910 |
| | 1.72.15 | number | 911 |
| | 1.72.16 | numberlist | 915 |
| | 1.72.17 | numberlistp | 917 |
| | 1.72.18 | pairs | 927 |
| | 1.72.19 | term | 932 |
| | 1.72.20 | termp | 934 |
| | 1.72.21 | type | 941 |
| | 1.72.22 | varlist | 946 |
| | 1.72.23 | varlistp | 948 |
| 1.73 | ulid | | 958 |
| | 1.73.1 | ulid | 958 |
| | 1.73.2 | ulid(Representation) | 959 |
| | 1.73.3 | ulid_protocol | 961 |
| | 1.73.4 | ulid_types | 964 |
| 1.74 | union_find | | 965 |
| | 1.74.1 | union_find | 965 |
| | 1.74.2 | union_find_protocol | 967 |
| 1.75 | uuid | | 971 |
| | 1.75.1 | uuid | 971 |
| | 1.75.2 | uuid(Representation) | 972 |
| | 1.75.3 | uuid_protocol | 974 |
| 1.76 | verdi_neruda | | 976 |
| | 1.76.1 | a_star_interpreter(W) | 977 |
| | 1.76.2 | benchmark_generators | 978 |
| | 1.76.3 | best_first | 979 |
| | 1.76.4 | bfs_interpreter | 981 |
| | 1.76.5 | bup_interpreter | 982 |
| | 1.76.6 | counter | 983 |
| | 1.76.7 | databasep | 987 |
| | 1.76.8 | debug_expansion(Mode) | 989 |
| | 1.76.9 | demodb | 991 |
| | 1.76.10 | dfs_interpreter | 992 |

| | | |
|---------|-------------------------------------|------|
| 1.76.11 | flatting | 993 |
| 1.76.12 | heuristic_expansion(Mode) | 995 |
| 1.76.13 | iddfs_interpreter(Increment) | 996 |
| 1.76.14 | interpreterp | 997 |
| 1.76.15 | magic | 999 |
| 1.76.16 | magic_expansion(Mode) | 1001 |
| 1.76.17 | rule_expansion(Mode) | 1002 |
| 1.76.18 | shell | 1003 |
| 1.76.19 | shell(Interpreters) | 1005 |
| 1.76.20 | shell_expansion(Mode) | 1006 |
| 1.77 | wrapper | 1008 |
| 1.77.1 | wrapper | 1008 |
| 1.78 | xml_parser | 1020 |
| 1.78.1 | xml | 1020 |
| 1.79 | zippers | 1028 |
| 1.79.1 | zipperp | 1028 |
| 1.79.2 | zlist | 1038 |
| 2 | Directories | 1041 |
| 2.1 | contributions/flags/ | 1043 |
| 2.2 | contributions/iso8601/ | 1043 |
| 2.3 | contributions/pddl_parser/ | 1043 |
| 2.4 | contributions/verdi_neruda/ | 1043 |
| 2.5 | contributions/xml_parser/ | 1043 |
| 2.6 | core/ | 1043 |
| 2.7 | library/ | 1043 |
| 2.8 | library/arbitrary/ | 1043 |
| 2.9 | library/assignvars/ | 1043 |
| 2.10 | library/base64/ | 1043 |
| 2.11 | library/cbor/ | 1043 |
| 2.12 | library/coroutining/ | 1043 |
| 2.13 | library/csv/ | 1043 |
| 2.14 | library/dates/ | 1043 |
| 2.15 | library/dependents/ | 1043 |
| 2.16 | library/dictionaries/ | 1043 |
| 2.17 | library/dif/ | 1043 |
| 2.18 | library/edcg/ | 1043 |
| 2.19 | library/events/ | 1043 |
| 2.20 | library/expand_library_alias_paths/ | 1043 |
| 2.21 | library/expecteds/ | 1043 |
| 2.22 | library/format/ | 1043 |
| 2.23 | library/genint/ | 1043 |
| 2.24 | library/gensym/ | 1043 |
| 2.25 | library/git/ | 1043 |
| 2.26 | library/grammars/ | 1043 |
| 2.27 | library/heaps/ | 1043 |
| 2.28 | library/hierarchies/ | 1043 |
| 2.29 | library/hook_flows/ | 1043 |
| 2.30 | library/hook_objects/ | 1043 |
| 2.31 | library/html/ | 1043 |
| 2.32 | library/ids/ | 1043 |
| 2.33 | library/intervals/ | 1043 |
| 2.34 | library/java/ | 1043 |
| 2.35 | library/json/ | 1043 |

| | | |
|------|------------------------------|------|
| 2.36 | library/json_lines/ | 1043 |
| 2.37 | library/listing/ | 1043 |
| 2.38 | library/logging/ | 1043 |
| 2.39 | library/loops/ | 1043 |
| 2.40 | library/meta/ | 1043 |
| 2.41 | library/meta_compiler/ | 1043 |
| 2.42 | library/mutations/ | 1043 |
| 2.43 | library/nested_dictionaries/ | 1043 |
| 2.44 | library/optionals/ | 1043 |
| 2.45 | library/options/ | 1043 |
| 2.46 | library/os/ | 1043 |
| 2.47 | library/queues/ | 1043 |
| 2.48 | library/random/ | 1043 |
| 2.49 | library/reader/ | 1043 |
| 2.50 | library/recorded_database/ | 1043 |
| 2.51 | library/redis/ | 1043 |
| 2.52 | library/sets/ | 1043 |
| 2.53 | library/statistics/ | 1043 |
| 2.54 | library/term_io/ | 1043 |
| 2.55 | library/timeout/ | 1043 |
| 2.56 | library/tsv/ | 1043 |
| 2.57 | library/types/ | 1043 |
| 2.58 | library/ulid/ | 1043 |
| 2.59 | library/union_find/ | 1043 |
| 2.60 | library/uuid/ | 1043 |
| 2.61 | library/zippers/ | 1043 |
| 2.62 | ports/fcube/ | 1043 |
| 2.63 | ports/metagol/ | 1043 |
| 2.64 | ports/toychr/ | 1043 |
| 2.65 | tools/assertions/ | 1043 |
| 2.66 | tools/code_metrics/ | 1043 |
| 2.67 | tools/dead_code_scanner/ | 1043 |
| 2.68 | tools/debug_messages/ | 1043 |
| 2.69 | tools/debugger/ | 1043 |
| 2.70 | tools/diagrams/ | 1043 |
| 2.71 | tools/doclet/ | 1043 |
| 2.72 | tools/help/ | 1043 |
| 2.73 | tools/issue_creator/ | 1043 |
| 2.74 | tools/lgtdoc/ | 1043 |
| 2.75 | tools/lgtunit/ | 1043 |
| 2.76 | tools/packs/ | 1043 |
| 2.77 | tools/ports_profiler/ | 1043 |
| 2.78 | tools/tutor/ | 1043 |
| 2.79 | tools/wrapper/ | 1043 |
| 3 | Entities | 1045 |
| 3.1 | Categories | 1045 |
| 3.2 | Objects | 1045 |
| 3.3 | Protocols | 1045 |
| 4 | Predicates | 1047 |
| 4.1 | (/)/2 | 1047 |
| 4.2 | (//)/2 | 1047 |
| 4.3 | (<)/2 | 1047 |

| | | |
|------|--------------------------|------|
| 4.4 | (<=)/2 | 1047 |
| 4.5 | (==)/2 | 1047 |
| 4.6 | (=<)/2 | 1048 |
| 4.7 | (=>)/2 | 1048 |
| 4.8 | (=\=)/2 | 1048 |
| 4.9 | =~/2 | 1048 |
| 4.10 | (>)/2 | 1048 |
| 4.11 | (>=)/2 | 1048 |
| 4.12 | absolute_file_name/2 | 1048 |
| 4.13 | activate_debug_handler/1 | 1048 |
| 4.14 | activate_monitor/0 | 1049 |
| 4.15 | active_debug_handler/1 | 1049 |
| 4.16 | add/1 | 1049 |
| 4.17 | add/2 | 1049 |
| 4.18 | add/3 | 1049 |
| 4.19 | addDependent/1 | 1049 |
| 4.20 | after/2 | 1049 |
| 4.21 | after/3 | 1049 |
| 4.22 | all/0 | 1050 |
| 4.23 | all/1 | 1050 |
| 4.24 | all_files/0 | 1050 |
| 4.25 | all_files/1 | 1050 |
| 4.26 | all_libraries/0 | 1050 |
| 4.27 | all_libraries/1 | 1050 |
| 4.28 | all_score/1 | 1051 |
| 4.29 | ancestor/1 | 1051 |
| 4.30 | ancestors/1 | 1051 |
| 4.31 | apis/0 | 1051 |
| 4.32 | apis/1 | 1051 |
| 4.33 | append/2 | 1051 |
| 4.34 | append/3 | 1051 |
| 4.35 | apply/2 | 1051 |
| 4.36 | apply/4 | 1052 |
| 4.37 | approximately_equal/2 | 1052 |
| 4.38 | approximately_equal/3 | 1052 |
| 4.39 | arbitrary/1 | 1052 |
| 4.40 | arbitrary/2 | 1052 |
| 4.41 | archive/1 | 1052 |
| 4.42 | arithmetic_mean/2 | 1052 |
| 4.43 | array_list/2 | 1052 |
| 4.44 | array_to_list/2 | 1053 |
| 4.45 | array_to_terms/2 | 1053 |
| 4.46 | array_to_terms/3 | 1053 |
| 4.47 | as_curly_bracketed/2 | 1053 |
| 4.48 | as_dictionary/2 | 1053 |
| 4.49 | as_difflist/2 | 1053 |
| 4.50 | as_heap/2 | 1053 |
| 4.51 | as_list/2 | 1053 |
| 4.52 | as_nested_dictionary/2 | 1054 |
| 4.53 | as_set/2 | 1054 |
| 4.54 | ask_question/5 | 1054 |
| 4.55 | assertion/1 | 1054 |
| 4.56 | assertion/2 | 1054 |
| 4.57 | assignable/1 | 1054 |

| | | |
|-------|------------------------------|------|
| 4.58 | assignable/2 | 1054 |
| 4.59 | available/0 | 1054 |
| 4.60 | available/1 | 1055 |
| 4.61 | available/2 | 1055 |
| 4.62 | average/2 | 1055 |
| 4.63 | average_deviation/3 | 1055 |
| 4.64 | before/2 | 1055 |
| 4.65 | before/3 | 1055 |
| 4.66 | bench_goal/1 | 1055 |
| 4.67 | benchmark/2 | 1055 |
| 4.68 | benchmark/3 | 1056 |
| 4.69 | benchmark/4 | 1056 |
| 4.70 | benchmark_reified/3 | 1056 |
| 4.71 | bernoulli/2 | 1056 |
| 4.72 | beta/3 | 1056 |
| 4.73 | between/3 | 1056 |
| 4.74 | between/4 | 1056 |
| 4.75 | binomial/3 | 1056 |
| 4.76 | bit//1 | 1057 |
| 4.77 | bits//1 | 1057 |
| 4.78 | blank//0 | 1057 |
| 4.79 | blanks//0 | 1057 |
| 4.80 | body_pred/1 | 1057 |
| 4.81 | branch/2 | 1057 |
| 4.82 | built_in_directive/4 | 1057 |
| 4.83 | built_in_flag/2 | 1057 |
| 4.84 | built_in_method/4 | 1058 |
| 4.85 | built_in_non_terminal/4 | 1058 |
| 4.86 | built_in_predicate/4 | 1058 |
| 4.87 | calendar_month/3 | 1058 |
| 4.88 | call_with_timeout/2 | 1058 |
| 4.89 | call_with_timeout/3 | 1058 |
| 4.90 | cat/2 | 1058 |
| 4.91 | change_directory/1 | 1058 |
| 4.92 | changed/0 | 1059 |
| 4.93 | changed/1 | 1059 |
| 4.94 | chebyshev_distance/3 | 1059 |
| 4.95 | chebyshev_norm/2 | 1059 |
| 4.96 | check/1 | 1059 |
| 4.97 | check/2 | 1059 |
| 4.98 | check/3 | 1059 |
| 4.99 | check_option/1 | 1059 |
| 4.100 | check_options/1 | 1060 |
| 4.101 | chi_squared/2 | 1060 |
| 4.102 | chr_is/2 | 1060 |
| 4.103 | chr_no_spy/1 | 1060 |
| 4.104 | chr_nospy/0 | 1060 |
| 4.105 | chr_notrace/0 | 1060 |
| 4.106 | chr_option/2 | 1060 |
| 4.107 | chr_spy/1 | 1060 |
| 4.108 | chr_trace/0 | 1061 |
| 4.109 | circular_uniform_cartesian/3 | 1061 |
| 4.110 | circular_uniform_polar/3 | 1061 |
| 4.111 | class/1 | 1061 |

| | | |
|-------|--------------------------------|------|
| 4.112 | classes/1 | 1061 |
| 4.113 | clause/5 | 1061 |
| 4.114 | clause_location/6 | 1061 |
| 4.115 | clean/0 | 1061 |
| 4.116 | clean/1 | 1062 |
| 4.117 | clean/2 | 1062 |
| 4.118 | clone/1 | 1062 |
| 4.119 | clone/3 | 1062 |
| 4.120 | clone/4 | 1062 |
| 4.121 | coefficient_of_variation/2 | 1062 |
| 4.122 | command_line_arguments/1 | 1062 |
| 4.123 | commit_author/2 | 1062 |
| 4.124 | commit_date/2 | 1063 |
| 4.125 | commit_hash/2 | 1063 |
| 4.126 | commit_hash_abbreviated/2 | 1063 |
| 4.127 | commit_log/3 | 1063 |
| 4.128 | commit_message/2 | 1063 |
| 4.129 | compile_aux_clauses/1 | 1063 |
| 4.130 | compile_predicate_heads/4 | 1063 |
| 4.131 | compile_predicate_indicators/3 | 1063 |
| 4.132 | completion/2 | 1064 |
| 4.133 | completions/2 | 1064 |
| 4.134 | connect/1 | 1064 |
| 4.135 | connect/3 | 1064 |
| 4.136 | console/1 | 1064 |
| 4.137 | contains/2 | 1064 |
| 4.138 | control//0 | 1064 |
| 4.139 | control_construct/4 | 1064 |
| 4.140 | controls//0 | 1065 |
| 4.141 | copy_file/2 | 1065 |
| 4.142 | counter/2 | 1065 |
| 4.143 | cover/1 | 1065 |
| 4.144 | cpu_time/1 | 1065 |
| 4.145 | current/2 | 1065 |
| 4.146 | data/0 | 1065 |
| 4.147 | data/1 | 1065 |
| 4.148 | data/2 | 1066 |
| 4.149 | date/4 | 1066 |
| 4.150 | date/5 | 1066 |
| 4.151 | date/6 | 1066 |
| 4.152 | date/7 | 1066 |
| 4.153 | date_string/3 | 1066 |
| 4.154 | date_time/7 | 1066 |
| 4.155 | days_in_month/3 | 1066 |
| 4.156 | deactivate_debug_handler/0 | 1067 |
| 4.157 | debug/0 | 1067 |
| 4.158 | debug_handler/1 | 1067 |
| 4.159 | debug_handler/3 | 1067 |
| 4.160 | debugging/0 | 1067 |
| 4.161 | debugging/1 | 1067 |
| 4.162 | decide/1 | 1067 |
| 4.163 | decide/2 | 1067 |
| 4.164 | decode_exception/2 | 1068 |
| 4.165 | decode_exception/3 | 1068 |

| | | |
|-------|----------------------------------|------|
| 4.166 | decompile_predicate_heads/4 | 1068 |
| 4.167 | decompile_predicate_indicators/4 | 1068 |
| 4.168 | decompose_file_name/3 | 1068 |
| 4.169 | decompose_file_name/4 | 1068 |
| 4.170 | decrement_counter/1 | 1068 |
| 4.171 | default_option/1 | 1068 |
| 4.172 | default_options/1 | 1069 |
| 4.173 | define_log_file/2 | 1069 |
| 4.174 | defined/4 | 1069 |
| 4.175 | defined_flag/6 | 1069 |
| 4.176 | del_monitors/0 | 1069 |
| 4.177 | del_monitors/4 | 1069 |
| 4.178 | del_spy_points/4 | 1069 |
| 4.179 | delete/0 | 1069 |
| 4.180 | delete/1 | 1070 |
| 4.181 | delete/2 | 1070 |
| 4.182 | delete/3 | 1070 |
| 4.183 | delete/4 | 1070 |
| 4.184 | delete_all_after/2 | 1070 |
| 4.185 | delete_all_after_and_unzip/2 | 1070 |
| 4.186 | delete_all_before/2 | 1070 |
| 4.187 | delete_all_before_and_unzip/2 | 1070 |
| 4.188 | delete_and_next/2 | 1071 |
| 4.189 | delete_and_previous/2 | 1071 |
| 4.190 | delete_and_unzip/2 | 1071 |
| 4.191 | delete_directory/1 | 1071 |
| 4.192 | delete_directory_and_contents/1 | 1071 |
| 4.193 | delete_directory_contents/1 | 1071 |
| 4.194 | delete_file/1 | 1071 |
| 4.195 | delete_in/4 | 1071 |
| 4.196 | delete_matches/3 | 1072 |
| 4.197 | delete_max/4 | 1072 |
| 4.198 | delete_min/4 | 1072 |
| 4.199 | dependents/1 | 1072 |
| 4.200 | dependents/2 | 1072 |
| 4.201 | dependents/3 | 1072 |
| 4.202 | depth/2 | 1072 |
| 4.203 | descendant/1 | 1072 |
| 4.204 | descendant_class/1 | 1073 |
| 4.205 | descendant_classes/1 | 1073 |
| 4.206 | descendant_instance/1 | 1073 |
| 4.207 | descendant_instances/1 | 1073 |
| 4.208 | descendants/1 | 1073 |
| 4.209 | describe/1 | 1073 |
| 4.210 | describe/2 | 1073 |
| 4.211 | description/1 | 1073 |
| 4.212 | deterministic/1 | 1074 |
| 4.213 | deterministic/2 | 1074 |
| 4.214 | diagram_description/1 | 1074 |
| 4.215 | diagram_name_suffix/1 | 1074 |
| 4.216 | dif/1 | 1074 |
| 4.217 | dif/2 | 1074 |
| 4.218 | digit//1 | 1074 |
| 4.219 | digits//1 | 1074 |

| | | |
|-------|----------------------------------|------|
| 4.220 | directories/1 | 1075 |
| 4.221 | directories/2 | 1075 |
| 4.222 | directories/3 | 1075 |
| 4.223 | directory/1 | 1075 |
| 4.224 | directory/2 | 1075 |
| 4.225 | directory/3 | 1076 |
| 4.226 | directory_exists/1 | 1076 |
| 4.227 | directory_files/2 | 1076 |
| 4.228 | directory_files/3 | 1076 |
| 4.229 | directory_score/2 | 1076 |
| 4.230 | dirichlet/2 | 1076 |
| 4.231 | disable/1 | 1076 |
| 4.232 | disable/2 | 1076 |
| 4.233 | disable_logging/1 | 1077 |
| 4.234 | disconnect/1 | 1077 |
| 4.235 | disjoint/2 | 1077 |
| 4.236 | disjoint_sets/2 | 1077 |
| 4.237 | doc_goal/1 | 1077 |
| 4.238 | dot//1 | 1077 |
| 4.239 | dowhile/2 | 1077 |
| 4.240 | drop/3 | 1077 |
| 4.241 | during/2 | 1078 |
| 4.242 | easter_day/3 | 1078 |
| 4.243 | edge/6 | 1078 |
| 4.244 | edge_case/2 | 1078 |
| 4.245 | either/3 | 1078 |
| 4.246 | empty/1 | 1078 |
| 4.247 | enable/1 | 1079 |
| 4.248 | enable/2 | 1079 |
| 4.249 | enable_logging/1 | 1079 |
| 4.250 | enabled/1 | 1079 |
| 4.251 | enabled/2 | 1079 |
| 4.252 | ensure_directory/1 | 1079 |
| 4.253 | ensure_file/1 | 1079 |
| 4.254 | entity/1 | 1079 |
| 4.255 | entity/2 | 1080 |
| 4.256 | entity_info_pair_score_hook/3 | 1080 |
| 4.257 | entity_info_score_hook/2 | 1080 |
| 4.258 | entity_predicates_weights_hook/2 | 1080 |
| 4.259 | entity_prefix/2 | 1080 |
| 4.260 | entity_score/2 | 1080 |
| 4.261 | enumerate/2 | 1080 |
| 4.262 | environment_variable/2 | 1080 |
| 4.263 | epsilon/1 | 1081 |
| 4.264 | equal/2 | 1081 |
| 4.265 | erase/1 | 1081 |
| 4.266 | essentially_equal/3 | 1081 |
| 4.267 | euclidean_distance/3 | 1081 |
| 4.268 | euclidean_norm/2 | 1081 |
| 4.269 | exclude/3 | 1081 |
| 4.270 | execution_context/7 | 1081 |
| 4.271 | expand_library_path/2 | 1082 |
| 4.272 | expected/1 | 1082 |
| 4.273 | expecteds/2 | 1082 |

| | | |
|-------|--------------------------|------|
| 4.274 | explain//1 | 1082 |
| 4.275 | exponential/2 | 1082 |
| 4.276 | extension/1 | 1082 |
| 4.277 | extensions/1 | 1082 |
| 4.278 | false/1 | 1082 |
| 4.279 | fcube/0 | 1083 |
| 4.280 | file/1 | 1083 |
| 4.281 | file/2 | 1083 |
| 4.282 | file_exists/1 | 1083 |
| 4.283 | file_footer/3 | 1083 |
| 4.284 | file_header/3 | 1083 |
| 4.285 | file_modification_time/2 | 1084 |
| 4.286 | file_permission/2 | 1084 |
| 4.287 | file_score/2 | 1084 |
| 4.288 | file_size/2 | 1084 |
| 4.289 | file_to_bytes/2 | 1084 |
| 4.290 | file_to_bytes/3 | 1084 |
| 4.291 | file_to_chars/2 | 1084 |
| 4.292 | file_to_chars/3 | 1084 |
| 4.293 | file_to_codes/2 | 1085 |
| 4.294 | file_to_codes/3 | 1085 |
| 4.295 | file_to_terms/2 | 1085 |
| 4.296 | file_to_terms/3 | 1085 |
| 4.297 | file_type_extension/2 | 1085 |
| 4.298 | files/1 | 1085 |
| 4.299 | files/2 | 1085 |
| 4.300 | files/3 | 1086 |
| 4.301 | filter/2 | 1086 |
| 4.302 | find/4 | 1086 |
| 4.303 | find/5 | 1086 |
| 4.304 | findall_member/4 | 1086 |
| 4.305 | findall_member/5 | 1086 |
| 4.306 | finished_by/2 | 1086 |
| 4.307 | finishes/2 | 1086 |
| 4.308 | fisher/3 | 1087 |
| 4.309 | flag_group_chk/1 | 1087 |
| 4.310 | flag_groups/1 | 1087 |
| 4.311 | flat_map/2 | 1087 |
| 4.312 | flatten/2 | 1087 |
| 4.313 | float//1 | 1087 |
| 4.314 | fold_left/4 | 1087 |
| 4.315 | fold_left_1/3 | 1087 |
| 4.316 | fold_right/4 | 1088 |
| 4.317 | fold_right_1/3 | 1088 |
| 4.318 | fordownto/3 | 1088 |
| 4.319 | fordownto/4 | 1088 |
| 4.320 | fordownto/5 | 1088 |
| 4.321 | foreach/3 | 1088 |
| 4.322 | foreach/4 | 1088 |
| 4.323 | format/2 | 1088 |
| 4.324 | format/3 | 1089 |
| 4.325 | format_entity_score//2 | 1089 |
| 4.326 | format_object/1 | 1089 |
| 4.327 | format_to_atom/3 | 1089 |

| | | |
|-------|----------------------------|------|
| 4.328 | format_to_chars/3 | 1089 |
| 4.329 | format_to_chars/4 | 1089 |
| 4.330 | format_to_codes/3 | 1089 |
| 4.331 | format_to_codes/4 | 1089 |
| 4.332 | forto/3 | 1090 |
| 4.333 | forto/4 | 1090 |
| 4.334 | forto/5 | 1090 |
| 4.335 | forward/1 | 1090 |
| 4.336 | forward/2 | 1090 |
| 4.337 | forward/3 | 1090 |
| 4.338 | fractile/3 | 1090 |
| 4.339 | freeze/2 | 1090 |
| 4.340 | from_generator/2 | 1091 |
| 4.341 | from_generator/3 | 1091 |
| 4.342 | from_generator/4 | 1091 |
| 4.343 | from_goal/2 | 1091 |
| 4.344 | from_goal/3 | 1091 |
| 4.345 | from_goal/4 | 1091 |
| 4.346 | frozen/2 | 1091 |
| 4.347 | full_device_path/1 | 1092 |
| 4.348 | func_test/3 | 1092 |
| 4.349 | functional/0 | 1092 |
| 4.350 | gamma/3 | 1092 |
| 4.351 | generate/1 | 1092 |
| 4.352 | generate/2 | 1092 |
| 4.353 | generate/8 | 1093 |
| 4.354 | genint/2 | 1093 |
| 4.355 | gensym/2 | 1093 |
| 4.356 | geometric/2 | 1093 |
| 4.357 | geometric_mean/2 | 1093 |
| 4.358 | get/1 | 1093 |
| 4.359 | get_field/2 | 1093 |
| 4.360 | get_flag_value/2 | 1093 |
| 4.361 | get_seed/1 | 1094 |
| 4.362 | gnu/0 | 1094 |
| 4.363 | goal_expansion/2 | 1094 |
| 4.364 | graph_footer/5 | 1094 |
| 4.365 | graph_header/5 | 1094 |
| 4.366 | ground/1 | 1094 |
| 4.367 | group_by_key/2 | 1094 |
| 4.368 | group_consecutive_by_key/2 | 1094 |
| 4.369 | group_sorted_by_key/2 | 1095 |
| 4.370 | guess_arity/2 | 1095 |
| 4.371 | guess_separator/2 | 1095 |
| 4.372 | gumbel/3 | 1095 |
| 4.373 | hamming_distance/3 | 1095 |
| 4.374 | handbook/0 | 1095 |
| 4.375 | handbook/1 | 1095 |
| 4.376 | harmonic_mean/2 | 1095 |
| 4.377 | head/2 | 1096 |
| 4.378 | head_pred/1 | 1096 |
| 4.379 | help/0 | 1096 |
| 4.380 | hex_digit//1 | 1096 |
| 4.381 | hex_digits//1 | 1096 |

| | | |
|-------|-------------------------|------|
| 4.382 | home/1 | 1096 |
| 4.383 | hypergeometric/4 | 1096 |
| 4.384 | ibk/3 | 1096 |
| 4.385 | if_empty/1 | 1097 |
| 4.386 | if_expected/1 | 1097 |
| 4.387 | if_expected_or_else/2 | 1097 |
| 4.388 | if_present/1 | 1097 |
| 4.389 | if_present_or_else/2 | 1097 |
| 4.390 | if_unexpected/1 | 1097 |
| 4.391 | include/3 | 1097 |
| 4.392 | increase/1 | 1097 |
| 4.393 | increment/0 | 1098 |
| 4.394 | increment_counter/1 | 1098 |
| 4.395 | init/0 | 1098 |
| 4.396 | init_log_file/2 | 1098 |
| 4.397 | inorder/2 | 1098 |
| 4.398 | insert/3 | 1098 |
| 4.399 | insert/4 | 1098 |
| 4.400 | insert_after/3 | 1098 |
| 4.401 | insert_all/3 | 1099 |
| 4.402 | insert_before/3 | 1099 |
| 4.403 | insert_in/4 | 1099 |
| 4.404 | install/1 | 1099 |
| 4.405 | install/2 | 1099 |
| 4.406 | install/3 | 1099 |
| 4.407 | install/4 | 1099 |
| 4.408 | installed/0 | 1099 |
| 4.409 | installed/1 | 1100 |
| 4.410 | installed/3 | 1100 |
| 4.411 | installed/4 | 1100 |
| 4.412 | instance/1 | 1100 |
| 4.413 | instance/2 | 1100 |
| 4.414 | instances/1 | 1100 |
| 4.415 | integer//1 | 1100 |
| 4.416 | internal_os_path/2 | 1100 |
| 4.417 | intersect/2 | 1101 |
| 4.418 | intersection/2 | 1101 |
| 4.419 | intersection/3 | 1101 |
| 4.420 | intersection/4 | 1101 |
| 4.421 | invoke/1 | 1101 |
| 4.422 | invoke/2 | 1101 |
| 4.423 | ipv4//1 | 1101 |
| 4.424 | ipv6//1 | 1101 |
| 4.425 | is_absolute_file_name/1 | 1102 |
| 4.426 | is_alpha/1 | 1102 |
| 4.427 | is_alphanumeric/1 | 1102 |
| 4.428 | is_ascii/1 | 1102 |
| 4.429 | is_bin_digit/1 | 1102 |
| 4.430 | is_control/1 | 1102 |
| 4.431 | is_dec_digit/1 | 1102 |
| 4.432 | is_empty/0 | 1102 |
| 4.433 | is_end_of_line/1 | 1103 |
| 4.434 | is_expected/0 | 1103 |
| 4.435 | is_false/1 | 1103 |

| | | |
|-------|-------------------------|------|
| 4.436 | is_hex_digit/1 | 1103 |
| 4.437 | is_layout/1 | 1103 |
| 4.438 | is_letter/1 | 1103 |
| 4.439 | is_lower_case/1 | 1103 |
| 4.440 | is_newline/1 | 1103 |
| 4.441 | is_null/1 | 1104 |
| 4.442 | is_object/1 | 1104 |
| 4.443 | is_octal_digit/1 | 1104 |
| 4.444 | is_period/1 | 1104 |
| 4.445 | is_present/0 | 1104 |
| 4.446 | is_punctuation/1 | 1104 |
| 4.447 | is_quote/1 | 1104 |
| 4.448 | is_true/1 | 1104 |
| 4.449 | is_unexpected/0 | 1105 |
| 4.450 | is_upper_case/1 | 1105 |
| 4.451 | is_void/1 | 1105 |
| 4.452 | is_vowel/1 | 1105 |
| 4.453 | is_white_space/1 | 1105 |
| 4.454 | iterator_element/2 | 1105 |
| 4.455 | join/3 | 1105 |
| 4.456 | join_all/3 | 1105 |
| 4.457 | jump/3 | 1106 |
| 4.458 | jump_all/3 | 1106 |
| 4.459 | jump_all_block/3 | 1106 |
| 4.460 | key/2 | 1106 |
| 4.461 | keys/2 | 1106 |
| 4.462 | keys_values/3 | 1106 |
| 4.463 | keysort/2 | 1106 |
| 4.464 | kurtosis/2 | 1106 |
| 4.465 | language_object/2 | 1107 |
| 4.466 | last/2 | 1107 |
| 4.467 | leaf/1 | 1107 |
| 4.468 | leaf_class/1 | 1107 |
| 4.469 | leaf_classes/1 | 1107 |
| 4.470 | leaf_instance/1 | 1107 |
| 4.471 | leaf_instances/1 | 1107 |
| 4.472 | leap_year/1 | 1107 |
| 4.473 | learn/0 | 1108 |
| 4.474 | learn/1 | 1108 |
| 4.475 | learn/2 | 1108 |
| 4.476 | learn/3 | 1108 |
| 4.477 | learn_seq/2 | 1108 |
| 4.478 | learn_with_timeout/4 | 1108 |
| 4.479 | leash/1 | 1108 |
| 4.480 | leashing/1 | 1108 |
| 4.481 | least_common_multiple/2 | 1109 |
| 4.482 | leaves/1 | 1109 |
| 4.483 | length/2 | 1109 |
| 4.484 | libraries/1 | 1109 |
| 4.485 | libraries/2 | 1109 |
| 4.486 | libraries/3 | 1109 |
| 4.487 | library/0 | 1110 |
| 4.488 | library/1 | 1110 |
| 4.489 | library/2 | 1110 |

| | | |
|-------|------------------------|------|
| 4.490 | library_score/2 | 1110 |
| 4.491 | license/1 | 1110 |
| 4.492 | line_to_chars/2 | 1110 |
| 4.493 | line_to_chars/3 | 1111 |
| 4.494 | line_to_codes/2 | 1111 |
| 4.495 | line_to_codes/3 | 1111 |
| 4.496 | lint/0 | 1111 |
| 4.497 | lint/1 | 1111 |
| 4.498 | lint/2 | 1111 |
| 4.499 | list/0 | 1111 |
| 4.500 | list_to_array/2 | 1111 |
| 4.501 | listing/0 | 1112 |
| 4.502 | listing/1 | 1112 |
| 4.503 | loaded_file/1 | 1112 |
| 4.504 | loaded_file_property/2 | 1112 |
| 4.505 | log/3 | 1112 |
| 4.506 | log_event/2 | 1112 |
| 4.507 | log_file/2 | 1112 |
| 4.508 | logging/1 | 1112 |
| 4.509 | logging/3 | 1113 |
| 4.510 | logistic/3 | 1113 |
| 4.511 | lognormal/3 | 1113 |
| 4.512 | logseries/2 | 1113 |
| 4.513 | logtalk_packs/0 | 1113 |
| 4.514 | logtalk_packs/1 | 1113 |
| 4.515 | lookup/2 | 1113 |
| 4.516 | lookup/3 | 1113 |
| 4.517 | lookup_in/3 | 1114 |
| 4.518 | lower_upper/2 | 1114 |
| 4.519 | magic/2 | 1114 |
| 4.520 | magicise/4 | 1114 |
| 4.521 | make_directory/1 | 1114 |
| 4.522 | make_directory_path/1 | 1114 |
| 4.523 | make_set/3 | 1114 |
| 4.524 | man/1 | 1114 |
| 4.525 | manhattan_distance/3 | 1115 |
| 4.526 | manhattan_norm/2 | 1115 |
| 4.527 | manuals/0 | 1115 |
| 4.528 | map/2 | 1115 |
| 4.529 | map/3 | 1115 |
| 4.530 | map/4 | 1115 |
| 4.531 | map/5 | 1116 |
| 4.532 | map/6 | 1116 |
| 4.533 | map/7 | 1116 |
| 4.534 | map/8 | 1116 |
| 4.535 | map_element/2 | 1116 |
| 4.536 | map_reduce/5 | 1116 |
| 4.537 | max/2 | 1116 |
| 4.538 | max/3 | 1116 |
| 4.539 | max_clauses/1 | 1117 |
| 4.540 | max_inv_preds/1 | 1117 |
| 4.541 | max_size/1 | 1117 |
| 4.542 | maybe/0 | 1117 |
| 4.543 | maybe/1 | 1117 |

| | | |
|-------|-------------------------|------|
| 4.544 | maybe/2 | 1117 |
| 4.545 | maybe_call/1 | 1117 |
| 4.546 | maybe_call/2 | 1117 |
| 4.547 | mean_deviation/2 | 1118 |
| 4.548 | median/2 | 1118 |
| 4.549 | median_deviation/2 | 1118 |
| 4.550 | meets/2 | 1118 |
| 4.551 | member/2 | 1118 |
| 4.552 | memberchk/2 | 1118 |
| 4.553 | merge/3 | 1118 |
| 4.554 | message_hook/4 | 1119 |
| 4.555 | message_prefix_file/6 | 1119 |
| 4.556 | message_prefix_stream/4 | 1119 |
| 4.557 | message_tokens//2 | 1119 |
| 4.558 | met_by/2 | 1119 |
| 4.559 | meta_type/3 | 1119 |
| 4.560 | metarule/6 | 1119 |
| 4.561 | metarule_next_id/1 | 1119 |
| 4.562 | min/2 | 1120 |
| 4.563 | min/3 | 1120 |
| 4.564 | min_clauses/1 | 1120 |
| 4.565 | min_max/3 | 1120 |
| 4.566 | modes/2 | 1120 |
| 4.567 | module_property/2 | 1120 |
| 4.568 | monitor/1 | 1120 |
| 4.569 | monitor/4 | 1121 |
| 4.570 | monitor_activated/0 | 1121 |
| 4.571 | monitored/1 | 1121 |
| 4.572 | monitors/1 | 1121 |
| 4.573 | msort/2 | 1121 |
| 4.574 | msort/3 | 1121 |
| 4.575 | mutation/3 | 1121 |
| 4.576 | name/1 | 1121 |
| 4.577 | name_of_day/3 | 1122 |
| 4.578 | name_of_month/3 | 1122 |
| 4.579 | natural//1 | 1122 |
| 4.580 | new/1 | 1122 |
| 4.581 | new/2 | 1122 |
| 4.582 | new/3 | 1122 |
| 4.583 | new_line//0 | 1122 |
| 4.584 | new_lines//0 | 1123 |
| 4.585 | next/2 | 1123 |
| 4.586 | next/3 | 1123 |
| 4.587 | next/4 | 1123 |
| 4.588 | nextto/3 | 1123 |
| 4.589 | node/7 | 1123 |
| 4.590 | nodebug/0 | 1123 |
| 4.591 | nolog/3 | 1123 |
| 4.592 | nologall/0 | 1124 |
| 4.593 | non_blank//1 | 1124 |
| 4.594 | non_blanks//1 | 1124 |
| 4.595 | normal/3 | 1124 |
| 4.596 | normal_element/2 | 1124 |
| 4.597 | normalize_range/2 | 1124 |

| | | |
|-------|----------------------------|------|
| 4.598 | normalize_range/4 | 1124 |
| 4.599 | normalize_scalar/2 | 1124 |
| 4.600 | normalize_unit/2 | 1125 |
| 4.601 | nospy/1 | 1125 |
| 4.602 | nospy/3 | 1125 |
| 4.603 | nospy/4 | 1125 |
| 4.604 | nospyall/0 | 1125 |
| 4.605 | note/2 | 1125 |
| 4.606 | note/3 | 1125 |
| 4.607 | notrace/0 | 1125 |
| 4.608 | now/3 | 1126 |
| 4.609 | nth0/3 | 1126 |
| 4.610 | nth0/4 | 1126 |
| 4.611 | nth1/3 | 1126 |
| 4.612 | nth1/4 | 1126 |
| 4.613 | null/1 | 1126 |
| 4.614 | null_device_path/1 | 1126 |
| 4.615 | number//1 | 1127 |
| 4.616 | number_of_tests/1 | 1127 |
| 4.617 | numbervars/1 | 1127 |
| 4.618 | numbervars/3 | 1127 |
| 4.619 | occurrences/2 | 1127 |
| 4.620 | occurrences/3 | 1127 |
| 4.621 | occurs/2 | 1127 |
| 4.622 | of/2 | 1127 |
| 4.623 | of_expected/2 | 1128 |
| 4.624 | of_unexpected/2 | 1128 |
| 4.625 | one_or_more//0 | 1128 |
| 4.626 | one_or_more//1 | 1128 |
| 4.627 | one_or_more//2 | 1128 |
| 4.628 | operating_system_machine/1 | 1128 |
| 4.629 | operating_system_name/1 | 1128 |
| 4.630 | operating_system_release/1 | 1128 |
| 4.631 | operating_system_type/1 | 1129 |
| 4.632 | option/2 | 1129 |
| 4.633 | option/3 | 1129 |
| 4.634 | or/2 | 1129 |
| 4.635 | or_else/2 | 1129 |
| 4.636 | or_else_call/2 | 1129 |
| 4.637 | or_else_fail/1 | 1129 |
| 4.638 | or_else_get/2 | 1130 |
| 4.639 | or_else_throw/1 | 1130 |
| 4.640 | or_else_throw/2 | 1130 |
| 4.641 | orphaned/0 | 1130 |
| 4.642 | orphaned/2 | 1130 |
| 4.643 | outdated/0 | 1130 |
| 4.644 | outdated/1 | 1130 |
| 4.645 | outdated/2 | 1130 |
| 4.646 | outdated/4 | 1131 |
| 4.647 | outdated/5 | 1131 |
| 4.648 | output_file_name/2 | 1131 |
| 4.649 | overlapped_by/2 | 1131 |
| 4.650 | overlaps/2 | 1131 |
| 4.651 | parent/1 | 1131 |

| | | |
|-------|----------------------------------|------|
| 4.652 | parenthesis/2 | 1131 |
| 4.653 | parents/1 | 1131 |
| 4.654 | parse/2 | 1132 |
| 4.655 | parse/3 | 1132 |
| 4.656 | parse_domain/2 | 1132 |
| 4.657 | parse_domain/3 | 1132 |
| 4.658 | parse_problem/2 | 1132 |
| 4.659 | parse_problem/3 | 1132 |
| 4.660 | partial_map/4 | 1132 |
| 4.661 | partition/3 | 1133 |
| 4.662 | partition/4 | 1133 |
| 4.663 | partition/5 | 1133 |
| 4.664 | partition/6 | 1133 |
| 4.665 | path_concat/3 | 1133 |
| 4.666 | permutation/2 | 1133 |
| 4.667 | pid/1 | 1133 |
| 4.668 | pin/0 | 1133 |
| 4.669 | pin/1 | 1134 |
| 4.670 | pinned/1 | 1134 |
| 4.671 | plus/3 | 1134 |
| 4.672 | poisson/2 | 1134 |
| 4.673 | port/5 | 1134 |
| 4.674 | portray_clause/1 | 1134 |
| 4.675 | postorder/2 | 1134 |
| 4.676 | power/2 | 1134 |
| 4.677 | power_sequence/4 | 1135 |
| 4.678 | powerset/2 | 1135 |
| 4.679 | pp/1 | 1135 |
| 4.680 | pprint/1 | 1135 |
| 4.681 | predicate/2 | 1135 |
| 4.682 | predicate_info_pair_score_hook/4 | 1135 |
| 4.683 | predicate_info_score_hook/3 | 1135 |
| 4.684 | predicate_mode_score_hook/3 | 1135 |
| 4.685 | predicate_mode_score_hook/5 | 1136 |
| 4.686 | predicates/2 | 1136 |
| 4.687 | prefix/0 | 1136 |
| 4.688 | prefix/1 | 1136 |
| 4.689 | prefix/2 | 1136 |
| 4.690 | prefix/3 | 1136 |
| 4.691 | preorder/2 | 1136 |
| 4.692 | previous/2 | 1136 |
| 4.693 | previous/3 | 1137 |
| 4.694 | previous/4 | 1137 |
| 4.695 | print_flags/0 | 1137 |
| 4.696 | print_flags/1 | 1137 |
| 4.697 | print_message/3 | 1137 |
| 4.698 | print_message_token/4 | 1137 |
| 4.699 | print_message_tokens/3 | 1137 |
| 4.700 | product/2 | 1137 |
| 4.701 | product/3 | 1138 |
| 4.702 | program_to_clauses/2 | 1138 |
| 4.703 | proper_prefix/2 | 1138 |
| 4.704 | proper_prefix/3 | 1138 |
| 4.705 | proper_suffix/2 | 1138 |

| | | |
|-------|-------------------------------|------|
| 4.706 | proper_suffix/3 | 1138 |
| 4.707 | prove/2 | 1138 |
| 4.708 | prove/3 | 1138 |
| 4.709 | provides/2 | 1139 |
| 4.710 | question_hook/6 | 1139 |
| 4.711 | question_prompt_stream/4 | 1139 |
| 4.712 | quick_check/1 | 1139 |
| 4.713 | quick_check/2 | 1139 |
| 4.714 | quick_check/3 | 1139 |
| 4.715 | random/1 | 1139 |
| 4.716 | random/3 | 1139 |
| 4.717 | random_node/1 | 1140 |
| 4.718 | random_tree/1 | 1140 |
| 4.719 | randomize/1 | 1140 |
| 4.720 | randseq/4 | 1140 |
| 4.721 | randset/4 | 1140 |
| 4.722 | range/2 | 1140 |
| 4.723 | rdirectories/1 | 1140 |
| 4.724 | rdirectories/2 | 1140 |
| 4.725 | rdirectory/1 | 1141 |
| 4.726 | rdirectory/2 | 1141 |
| 4.727 | rdirectory/3 | 1141 |
| 4.728 | rdirectory_score/2 | 1141 |
| 4.729 | read_file/2 | 1141 |
| 4.730 | read_file/3 | 1142 |
| 4.731 | read_file_by_line/2 | 1142 |
| 4.732 | read_file_by_line/3 | 1142 |
| 4.733 | read_from_atom/2 | 1142 |
| 4.734 | read_from_chars/2 | 1142 |
| 4.735 | read_from_codes/2 | 1142 |
| 4.736 | read_only_device_path/1 | 1142 |
| 4.737 | read_stream/2 | 1143 |
| 4.738 | read_stream/3 | 1143 |
| 4.739 | read_stream_by_line/2 | 1143 |
| 4.740 | read_stream_by_line/3 | 1143 |
| 4.741 | read_term_from_atom/3 | 1143 |
| 4.742 | read_term_from_chars/3 | 1143 |
| 4.743 | read_term_from_chars/4 | 1143 |
| 4.744 | read_term_from_codes/3 | 1144 |
| 4.745 | read_term_from_codes/4 | 1144 |
| 4.746 | readme/1 | 1144 |
| 4.747 | readme/2 | 1144 |
| 4.748 | recorda/2 | 1144 |
| 4.749 | recorda/3 | 1144 |
| 4.750 | recorded/2 | 1144 |
| 4.751 | recorded/3 | 1144 |
| 4.752 | recordz/2 | 1145 |
| 4.753 | recordz/3 | 1145 |
| 4.754 | relative_standard_deviation/2 | 1145 |
| 4.755 | removeDependent/1 | 1145 |
| 4.756 | remove_duplicates/2 | 1145 |
| 4.757 | rename_file/2 | 1145 |
| 4.758 | replace/3 | 1145 |
| 4.759 | replace_sub_atom/4 | 1145 |

| | |
|--------------------------------|------|
| 4.760 rescale/3 | 1146 |
| 4.761 reset/0 | 1146 |
| 4.762 reset/1 | 1146 |
| 4.763 reset_counter/1 | 1146 |
| 4.764 reset_counters/0 | 1146 |
| 4.765 reset_flags/0 | 1146 |
| 4.766 reset_flags/1 | 1146 |
| 4.767 reset_genint/0 | 1147 |
| 4.768 reset_genint/1 | 1147 |
| 4.769 reset_gensym/0 | 1147 |
| 4.770 reset_gensym/1 | 1147 |
| 4.771 reset_monitor/0 | 1147 |
| 4.772 reset_seed/0 | 1147 |
| 4.773 restore/1 | 1147 |
| 4.774 restore/2 | 1147 |
| 4.775 reverse/2 | 1148 |
| 4.776 rewind/2 | 1148 |
| 4.777 rewind/3 | 1148 |
| 4.778 rlibraries/1 | 1148 |
| 4.779 rlibraries/2 | 1148 |
| 4.780 rlibrary/1 | 1148 |
| 4.781 rlibrary/2 | 1148 |
| 4.782 rlibrary_score/2 | 1149 |
| 4.783 rule/2 | 1149 |
| 4.784 rule/3 | 1149 |
| 4.785 rule/4 | 1149 |
| 4.786 run/0 | 1149 |
| 4.787 run/1 | 1149 |
| 4.788 run/2 | 1149 |
| 4.789 run_test_sets/1 | 1149 |
| 4.790 same_length/2 | 1150 |
| 4.791 same_length/3 | 1150 |
| 4.792 save/0 | 1150 |
| 4.793 save/1 | 1150 |
| 4.794 save/2 | 1150 |
| 4.795 scalar_product/3 | 1150 |
| 4.796 scan_left/4 | 1150 |
| 4.797 scan_left_1/3 | 1150 |
| 4.798 scan_right/4 | 1151 |
| 4.799 scan_right_1/3 | 1151 |
| 4.800 search/1 | 1151 |
| 4.801 select/3 | 1151 |
| 4.802 select/4 | 1151 |
| 4.803 selectchk/3 | 1151 |
| 4.804 selectchk/4 | 1151 |
| 4.805 send/3 | 1152 |
| 4.806 sequence/3 | 1152 |
| 4.807 sequence/4 | 1152 |
| 4.808 sequence/5 | 1152 |
| 4.809 sequential_occurrences/2 | 1152 |
| 4.810 sequential_occurrences/3 | 1152 |
| 4.811 serve/3 | 1152 |
| 4.812 set/1 | 1152 |
| 4.813 set/4 | 1153 |

| | | |
|-------|--------------------------|------|
| 4.814 | set_element/2 | 1153 |
| 4.815 | set_field/2 | 1153 |
| 4.816 | set_flag_value/2 | 1153 |
| 4.817 | set_flag_value/3 | 1153 |
| 4.818 | set_monitor/4 | 1153 |
| 4.819 | set_seed/1 | 1153 |
| 4.820 | set_spy_point/4 | 1153 |
| 4.821 | set_write_max_depth/1 | 1154 |
| 4.822 | setup/0 | 1154 |
| 4.823 | shell/1 | 1154 |
| 4.824 | shell/2 | 1154 |
| 4.825 | shell_command/1 | 1154 |
| 4.826 | shrink/3 | 1154 |
| 4.827 | shrink_sequence/3 | 1154 |
| 4.828 | shrinker/1 | 1154 |
| 4.829 | sign//1 | 1155 |
| 4.830 | singletons/2 | 1155 |
| 4.831 | size/2 | 1155 |
| 4.832 | skewness/2 | 1155 |
| 4.833 | sleep/1 | 1155 |
| 4.834 | softmax/2 | 1155 |
| 4.835 | softmax/3 | 1155 |
| 4.836 | sort/2 | 1155 |
| 4.837 | sort/3 | 1156 |
| 4.838 | sort/4 | 1156 |
| 4.839 | source_file_extension/1 | 1156 |
| 4.840 | space//0 | 1156 |
| 4.841 | spaces//0 | 1156 |
| 4.842 | split/3 | 1156 |
| 4.843 | split/4 | 1156 |
| 4.844 | spy/1 | 1156 |
| 4.845 | spy/3 | 1157 |
| 4.846 | spy/4 | 1157 |
| 4.847 | spy_point/4 | 1157 |
| 4.848 | spying/1 | 1157 |
| 4.849 | spying/3 | 1157 |
| 4.850 | spying/4 | 1157 |
| 4.851 | standard_cauchy/3 | 1157 |
| 4.852 | standard_deviation/2 | 1157 |
| 4.853 | standard_exponential/1 | 1158 |
| 4.854 | standard_gamma/2 | 1158 |
| 4.855 | standard_normal/1 | 1158 |
| 4.856 | standard_t/2 | 1158 |
| 4.857 | start/0 | 1158 |
| 4.858 | start_redirect_to_file/2 | 1158 |
| 4.859 | started_by/2 | 1158 |
| 4.860 | starts/2 | 1158 |
| 4.861 | stop/0 | 1159 |
| 4.862 | stop_redirect_to_file/0 | 1159 |
| 4.863 | stream_to_bytes/2 | 1159 |
| 4.864 | stream_to_bytes/3 | 1159 |
| 4.865 | stream_to_chars/2 | 1159 |
| 4.866 | stream_to_chars/3 | 1159 |
| 4.867 | stream_to_codes/2 | 1159 |

| | |
|-----------------------------|------|
| 4.868 stream_to_codes/3 | 1159 |
| 4.869 stream_to_terms/2 | 1160 |
| 4.870 stream_to_terms/3 | 1160 |
| 4.871 subclass/1 | 1160 |
| 4.872 subclasses/1 | 1160 |
| 4.873 sublist/2 | 1160 |
| 4.874 subsequence/3 | 1160 |
| 4.875 subsequence/4 | 1160 |
| 4.876 subset/2 | 1160 |
| 4.877 substitute/4 | 1161 |
| 4.878 subsumes/2 | 1161 |
| 4.879 subterm/2 | 1161 |
| 4.880 subtract/3 | 1161 |
| 4.881 succ/2 | 1161 |
| 4.882 suffix/2 | 1161 |
| 4.883 suffix/3 | 1161 |
| 4.884 sum/2 | 1162 |
| 4.885 superclass/1 | 1162 |
| 4.886 superclasses/1 | 1162 |
| 4.887 suspend_monitor/0 | 1162 |
| 4.888 swap/2 | 1162 |
| 4.889 swap_consecutive/2 | 1162 |
| 4.890 symdiff/3 | 1162 |
| 4.891 tab/0 | 1162 |
| 4.892 tabs/0 | 1163 |
| 4.893 take/3 | 1163 |
| 4.894 temporary_directory/1 | 1163 |
| 4.895 term_expansion/2 | 1163 |
| 4.896 terms_to_array/2 | 1163 |
| 4.897 test/1 | 1163 |
| 4.898 time_stamp/1 | 1163 |
| 4.899 timeout/1 | 1163 |
| 4.900 timestamp/2 | 1164 |
| 4.901 timestamp/8 | 1164 |
| 4.902 today/3 | 1164 |
| 4.903 tolerance_equal/4 | 1164 |
| 4.904 top/3 | 1164 |
| 4.905 top_next/5 | 1164 |
| 4.906 trace/0 | 1164 |
| 4.907 trace_event/2 | 1164 |
| 4.908 transpose/2 | 1165 |
| 4.909 triangular/4 | 1165 |
| 4.910 true/1 | 1165 |
| 4.911 type/1 | 1165 |
| 4.912 unexpected/1 | 1165 |
| 4.913 unexpecteds/2 | 1165 |
| 4.914 uniform/1 | 1165 |
| 4.915 uniform/3 | 1165 |
| 4.916 uninstall/0 | 1166 |
| 4.917 uninstall/1 | 1166 |
| 4.918 uninstall/2 | 1166 |
| 4.919 union/3 | 1166 |
| 4.920 union/4 | 1166 |
| 4.921 union_all/3 | 1166 |

| | |
|--|------|
| 4.922 unpin/0 | 1166 |
| 4.923 unpin/1 | 1166 |
| 4.924 unzip/2 | 1167 |
| 4.925 update/0 | 1167 |
| 4.926 update/1 | 1167 |
| 4.927 update/2 | 1167 |
| 4.928 update/3 | 1167 |
| 4.929 update/4 | 1167 |
| 4.930 update/5 | 1167 |
| 4.931 update_in/4 | 1168 |
| 4.932 update_in/5 | 1168 |
| 4.933 uuid_null/1 | 1168 |
| 4.934 uuid_v1/2 | 1168 |
| 4.935 uuid_v4/1 | 1168 |
| 4.936 valid/1 | 1168 |
| 4.937 valid/2 | 1168 |
| 4.938 valid/3 | 1169 |
| 4.939 valid_date/3 | 1169 |
| 4.940 valid_option/1 | 1169 |
| 4.941 valid_options/1 | 1169 |
| 4.942 validate/1 | 1169 |
| 4.943 value/1 | 1169 |
| 4.944 value/3 | 1169 |
| 4.945 value_reference/2 | 1169 |
| 4.946 values/2 | 1170 |
| 4.947 variables/2 | 1170 |
| 4.948 variance/2 | 1170 |
| 4.949 variant/2 | 1170 |
| 4.950 varnumbers/2 | 1170 |
| 4.951 varnumbers/3 | 1170 |
| 4.952 verify_commands_availability/0 | 1170 |
| 4.953 version/6 | 1170 |
| 4.954 versions/3 | 1171 |
| 4.955 void/1 | 1171 |
| 4.956 void_element/1 | 1171 |
| 4.957 von_mises/3 | 1171 |
| 4.958 wald/3 | 1171 |
| 4.959 wall_time/1 | 1171 |
| 4.960 weibull/3 | 1171 |
| 4.961 weighted_mean/3 | 1171 |
| 4.962 welcome/0 | 1172 |
| 4.963 when/2 | 1172 |
| 4.964 whiledo/2 | 1172 |
| 4.965 white_space//0 | 1172 |
| 4.966 white_spaces//0 | 1172 |
| 4.967 with_output_to/2 | 1172 |
| 4.968 without//2 | 1172 |
| 4.969 working_directory/1 | 1172 |
| 4.970 write_file/3 | 1173 |
| 4.971 write_max_depth/1 | 1173 |
| 4.972 write_stream/3 | 1173 |
| 4.973 write_term_to_atom/3 | 1173 |
| 4.974 write_term_to_chars/3 | 1173 |
| 4.975 write_term_to_chars/4 | 1173 |

| | |
|-----------------------------|------|
| 4.976 write_term_to_codes/3 | 1173 |
| 4.977 write_term_to_codes/4 | 1173 |
| 4.978 write_to_atom/2 | 1174 |
| 4.979 write_to_chars/2 | 1174 |
| 4.980 write_to_codes/2 | 1174 |
| 4.981 z_normalization/2 | 1174 |
| 4.982 zero_or_more//0 | 1174 |
| 4.983 zero_or_more//1 | 1174 |
| 4.984 zero_or_more//2 | 1174 |
| 4.985 zip/2 | 1174 |
| 4.986 zip/3 | 1175 |
| 4.987 zip_at_index/4 | 1175 |
| 5 Indices and tables | 1177 |
| Index | 1179 |

LIBRARIES

To load any library (including developer tools, ports, and contributions), use the goal `logtalk_load(library_name(loader))`. To run the library tests, use the goal `logtalk_load(library_name(tester))`. To load an entity, always load the loader file of the library that includes it to ensure that all required dependencies are also loaded and that any required flags are used. The loading goal can be found in the entity documentation.

1.1 arbitrary

category

1.1.1 arbitrary

Adds predicates for generating and shrinking random values for selected types to the library type object. User extensible.

Availability:

`logtalk_load(arbitrary(loader))`

Author: Paulo Moura

Version: 2:35:1

Date: 2024-08-13

Compilation flags:

`static`

Complements:

`type`

Uses:

`fast_random`

`integer`

`list`

`type`

Remarks:

- Logtalk specific types: `entity`, `object`, `protocol`, `category`, `entity_identifier`, `object_identifier`, `protocol_identifier`, `category_identifier`, `event`, `predicate`.
- Prolog module related types (when the backend compiler supports modules): `module`, `module_identifier`, `qualified_callable`.
- Prolog base types: `term`, `var`, `nonvar`, `atomic`, `atom`, `number`, `integer`, `float`, `compound`, `callable`, `ground`.
- Atom derived types: `non_quoted_atom`, `non_empty_atom`, `non_empty_atom(CharSet)`, `boolean`, `character`, `in_character`, `char`, `operator_specifier`, `hex_char`.
- Atom derived parametric types: `atom(CharSet)`, `atom(CharSet,Length)`, `non_empty_atom(CharSet)`, `character(CharSet)`, `in_character(CharSet)`, `char(CharSet)`.
- Number derived types: `positive_number`, `negative_number`, `non_positive_number`, `non_negative_number`.
- Float derived types: `positive_float`, `negative_float`, `non_positive_float`, `non_negative_float`, `probability`.
- Integer derived types: `positive_integer`, `negative_integer`, `non_positive_integer`, `non_negative_integer`, `byte`, `in_byte`, `character_code`, `in_character_code`, `code`, `operator_priority`, `hex_code`.
- Integer derived parametric types: `character_code(CharSet)`, `in_character_code(CharSet)`, `code(CharSet)`.
- List types (compound derived types): `list`, `non_empty_list`, `partial_list`, `list_or_partial_list`, `list(Type)`, `list(Type,Length)`, `list(Type,Min,Max)`, `list(Type,Length,Min,Max)`, `non_empty_list(Type)`, `codes`, `chars`.
- Difference list types (compound derived types): `difference_list`, `difference_list(Type)`.
- List and difference list types length: The types that do not take a fixed length generate lists with a length in the `[0,MaxSize]` interval (`[1,MaxSize]` for non-empty list types).
- Predicate and non-terminal indicator types arity: These types generate indicators with an arity in the `[0,MaxSize]` interval.
- Other compound derived types: `compound(Name,Types)`, `predicate_indicator`, `non_terminal_indicator`, `predicate_or_non_terminal_indicator`, `clause`, `grammar_rule`, `pair`, `pair(KeyType,ValueType)`.
- Other types: `Object::Closure`, `between(Type,Lower,Upper)`, `property(Type,LambdaExpression)`, `one_of(Type,Set)`, `var_or(Type)`, `ground(Type)`, `types(Types)`, `types_frequency(Pairs)`, `transform(Type,Closure)`, `constrain(Type,Closure)`.
- Type `Object::Closure` notes: Allows calling public object predicates as generators and shrinkers. The `Closure` closure is extended with either a single argument, the generated arbitrary value, or with two arguments, when shrinking a value.
- Type `compound(Name,Types)` notes: Generate a random compound term with the given name with a random argument for each type.
- Type `types_frequency(Pairs)` notes: Generate a random term for one of the types in a list of Type-Frequency pairs. The type is randomly selected taking into account the types frequency.
- Type `transform(Type,Closure)` notes: Generate a random term by transforming the term generated for the given type using the given closure.

- `Type constrain(Type,Closure)` notes: Generate a random term for the given type that satisfy the given closure.
- Registering new types: Add clauses for the arbitrary/1-2 multifile predicates and optionally for the shrinker/1 and shrink/3 multifile predicates. The clauses must have a bound first argument to avoid introducing spurious choice-points.
- Shrinking values: The shrink/3 should either succeed or fail but never throw an exception.
- Character sets: `ascii_identifier`, `ascii_printable`, `ascii_full`, `byte`, `unicode_bmp`, `unicode_full`.
- Default character sets: The default character set when using a parameterizable type that takes a character set parameter depends on the type.
- Default character sets: Entity, predicate, and non-terminal identifier types plus compound and callable types default to an `ascii_identifier` functor. Character and character code types default to `ascii_full`. Other types default to `ascii_printable`.
- Caveats: The type argument (and any type parameterization) to the predicates is not type-checked (or checked for consistency) for performance reasons.
- Unicode limitations: Currently, correct character/code generation is only ensured for XVM and SWI-Prolog as other backends do not provide support for querying a Unicode code point category.

Inherited public predicates:

(none)

- Public predicates
 - `arbitrary/1`
 - `arbitrary/2`
 - `shrinker/1`
 - `shrink/3`
 - `shrink_sequence/3`
 - `edge_case/2`
 - `get_seed/1`
 - `set_seed/1`
 - `max_size/1`
- Protected predicates
- Private predicates
- Operators

Public predicates

arbitrary/1

Table of defined types for which an arbitrary value can be generated. A new type can be registered by defining a clause for this predicate and adding a clause for the arbitrary/2 multifile predicate.

Compilation flags:

static, multifile

Template:

arbitrary(Type)

Mode and number of proofs:

arbitrary(?callable) - zero_or_more

arbitrary/2

Generates an arbitrary term of the specified type. Fails if the type is not supported. A new generator can be defined by adding a clause for this predicate and registering it via the arbitrary/1 predicate.

Compilation flags:

static, multifile

Template:

arbitrary(Type,Term)

Meta-predicate template:

arbitrary(:,*)

Mode and number of proofs:

arbitrary(@callable,-term) - zero_or_one

shrinker/1

Table of defined types for which a shrinker is provided. A new shrinker can be registered by defining a clause for this predicate and adding a definition for the shrink/3 multifile predicate.

Compilation flags:

static, multifile

Template:

shrinker(Type)

Mode and number of proofs:

shrinker(?callable) - zero_or_more

shrink/3

Shrinks a value to a smaller value if possible. Must generate a finite number of solutions. Fails if the type is not supported. A new shrinker can be defined by adding a clause for this predicate and registering it via the shrinker/1 predicate.

Compilation flags:

static, multifile

Template:

shrink(Type, Large, Small)

Mode and number of proofs:

shrink(@callable, @term, -term) - zero_or_more

shrink_sequence/3

Shrinks a value repeatedly until shrinking is no longer possible returning the sequence of values (ordered from larger to smaller value). Fails if the type is not supported.

Compilation flags:

static

Template:

shrink_sequence(Type, Value, Sequence)

Mode and number of proofs:

shrink_sequence(@callable, @term, -list(term)) - zero_or_one

edge_case/2

Table of type edge cases. Fails if the given type have no defined edge cases. New edge cases for existing or new types can be added by defining a clause for this multifile predicate.

Compilation flags:
static, multifile

Template:
edge_case(Type,Term)
Mode and number of proofs:
edge_case(?callable,?term) - zero_or_more

get_seed/1

Gets the current random generator seed. Seed should be regarded as an opaque ground term.

Compilation flags:
static

Template:
get_seed(Seed)
Mode and number of proofs:
get_seed(-ground) - one

set_seed/1

Sets the random generator seed to a given value returned by calling the get_seed/1 predicate.

Compilation flags:
static

Template:
set_seed(Seed)
Mode and number of proofs:
set_seed(+ground) - one

`max_size/1`

User defined maximum size for types where its meaningful and implicit. When not defined, defaults to 42. When multiple definitions exist, the first valid one found is used.

Compilation flags:
 static, multifile

Template:
 max_size(Size)
 Mode and number of proofs:
 max_size(?positive_integer) - zero_or_one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

[type](#)

1.2 assertions

object

1.2.1 assertions

Proxy object for simplifying the use of the assertion meta-predicates.

Availability:

```
logtalk_load(assertions(loader))
```

Author: Paulo Moura

Version: 2:0:0

Date: 2014-04-03

Compilation flags:

```
static, context_switching_calls
```

Extends:

```
public assertions(_)
```

Remarks:

```
(none)
```

Inherited public predicates:

```
assertion/1 assertion/2 goal_expansion/2 term_expansion/2
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.2.2 assertions(*Mode*)

A simple assertions framework. Can be used as a hook object for either suppressing assertions (production mode) or expanding them with file context information (debug mode).

Availability:

```
logtalk_load(assertions(loader))
```

Author: Paulo Moura

Version: 2:2:2

Date: 2022-07-04

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public expanding
```

Uses:

```
logtalk
```

Remarks:

```
(none)
```

Inherited public predicates:

```
goal_expansion/2 term_expansion/2
```

- Public predicates
 - assertion/1
 - assertion/2
- Protected predicates
- Private predicates
- Operators

Public predicates

assertion/1

Checks that an assertion is true. Uses the structured message printing mechanism for printing the results using a silent message for assertion success and a error message for assertion failure.

Compilation flags:

static

Template:

assertion(Goal)

Meta-predicate template:

assertion(0)

Mode and number of proofs:

assertion(@callable) - one

assertion/2

Checks that an assertion is true. Uses the structured message printing mechanism for printing the results using a silent message for assertion success and a error message for assertion failure. The context argument can be used to e.g. pass location data.

Compilation flags:

static

Template:

assertion(Context,Goal)

Meta-predicate template:

assertion(*,0)

Mode and number of proofs:

assertion(@term,@callable) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.2.3 assertions_messages

Assertions framework default message translations.

Availability:

logtalk_load(assertions(loader))

Author: Paulo Moura

Version: 2:2:0

Date: 2018-02-20

Compilation flags:

static

Provides:

logtalk::message_prefix_stream/4

logtalk::message_tokens//2

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.3 assignvars

object

1.3.1 assignvars

Assignable variables (supporting backtracable assignment of non-variable terms).

Availability:

```
logtalk_load(assignvars(loader))
```

Author: Nobukuni Kino and Paulo Moura

Version: 1:7:0

Date: 2018-07-11

Compilation flags:

```
static, context_switching_calls
```

Implements:

public assignvarsp

Remarks:

(none)

Inherited public predicates:

(\leq)/2 ($=$)/2 assignable/1 assignable/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.3.2 assignvarsp

Assignable variables (supporting backtracable assignment of non-variable terms) protocol.

Availability:

logtalk_load(assignvars(loader))

Author: Nobukuni Kino and Paulo Moura

Version: 1:0:1

Date: 2019-06-10

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - assignable/1
 - assignable/2
 - (\leq)/2
 - (\geq)/2
- Protected predicates
- Private predicates
- Operators
 - op(100,xfx, \leq)
 - op(100,xfx, \geq)

Public predicates

assignable/1

Makes Variable an assignable variable. Initial state will be empty.

Compilation flags:

static

Template:

assignable(Variable)

Mode and number of proofs:

assignable(--assignvar) - one

Exceptions:

Variable is not a variable:

`type__error(variable,Variable)`

`assignable/2`

Makes Variable an assignable variable and sets its initial state to Value.

Compilation flags:

`static`

Template:

`assignable(Variable,Value)`

Mode and number of proofs:

`assignable(--assignvar,@nonvar) - one`

Exceptions:

Variable is not a variable:

`type__error(variable,Variable)`

Value is not instantiated:

`instantiation__error`

`(<=)/2`

Sets the state of the assignable variable Variable to Value (initializing the variable if needed).

Compilation flags:

`static`

Template:

`Variable<=Value`

Mode and number of proofs:

`(?assignvar)<=(@nonvar) - one`

Exceptions:

Value is not instantiated:

`instantiation__error`

$(=>)/2$

Unifies Value with the current state of the assignable variable Variable.

Compilation flags:

static

Template:

Variable=>Value

Mode and number of proofs:

+assignvar=> ?nonvar - zero_or_one

Exceptions:

Variable is not instantiated:

instantiation_error

Protected predicates

(none)

Private predicates

(none)

Operators

op(100,xfx,<=)

Scope:

public

`op(100,xfx,=>)`

Scope:

public

➡ See also

[assignvars](#)

1.4 base64

object

1.4.1 base64

Base64 parser and generator.

Availability:

`logtalk_load(base64(loader))`

Author: Paulo Moura

Version: 0:10:0

Date: 2021-03-22

Compilation flags:

`static, context_switching_calls`

Uses:

[reader](#)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - parse/2
 - generate/2
- Protected predicates
- Private predicates
- Operators

Public predicates

parse/2

Parses the Base64 data from the given source (atom(Atom), chars(List), codes(List), stream(Stream), or file(Path)) into a list of bytes.

Compilation flags:

static

Template:

parse(Source,Bytes)

Mode and number of proofs:

parse(++compound,--list(byte)) - one_or_error

generate/2

Generates Base64 in the representation specified in the first argument (atom(Atom), chars(List), codes(List), stream(Stream), or file(Path)) for the list of bytes in the second argument.

Compilation flags:

static

Template:

generate(Sink,Bytes)

Mode and number of proofs:

generate(+compound,+list(byte)) - one_or_error

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.4.2 base64url

Base64URL parser and generator.

Availability:

`logtalk_load(base64(loader))`

Author: Paulo Moura

Version: 0:9:0

Date: 2021-03-10

Compilation flags:

`static, context_switching_calls`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - `parse/2`
 - `generate/2`

- Protected predicates
- Private predicates
- Operators

Public predicates

`parse/2`

Parses the Base64URL data from the given source (`atom(Atom)`, `chars(List)`, or `codes(List)`) into a URL (using the same format as the source).

Compilation flags:

`static`

Template:

`parse(Source,URL)`

Mode and number of proofs:

`parse(++compound,--types([atom,chars,codes])) - one_or_error`

`generate/2`

Generates Base64URL data in the representation specified in the first argument (`atom(Atom)`, `chars(List)`, or `codes(List)`) for the given URL (given in the same format as the sink).

Compilation flags:

`static`

Template:

`generate(Sink,URL)`

Mode and number of proofs:

`generate(+compound,+types([atom,chars,codes])) - one_or_error`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.5 cbor

object

1.5.1 cbor

Concise Binary Object Representation (CBOR) format exporter and importer. Uses atoms to represent decoded CBOR strings.

Availability:

`logtalk__load(cbor(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2021-03-04

Compilation flags:

`static, context_switching_calls`

Extends:

`public cbor(atom)`

Remarks:

(none)

Inherited public predicates:

`generate/2 parse/2`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.5.2 cbor(StringRepresentation)

- StringRepresentation - Text representation to be used when decoding CBOR strings. Possible values are atom (default), chars, and codes.

Concise Binary Object Representation (CBOR) format exporter and importer.

Availability:

`logtalk_load(cbor(loader))`

Author: Paulo Moura

Version: 0:11:1

Date: 2021-12-06

Compilation flags:

`static, context_switching_calls`

Uses:

[list](#)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - parse/2
 - generate/2
- Protected predicates
- Private predicates
- Operators

Public predicates

parse/2

Parses a list of bytes in the CBOR format returning the corresponding term representation. Throws an error when parsing is not possible (usually due to an invalid byte sequence).

Compilation flags:

static

Template:

parse(Bytes,Term)

Mode and number of proofs:

parse(@list(byte),-ground) - one_or_error

generate/2

Generates a list of bytes in the CBOR format representing the given term. Throws an error when generating is not possible (usually due to a term that have no CBOR corresponding representation).

Compilation flags:

static

Template:

```
generate(Term,Bytes)
Mode and number of proofs:
generate(@ground,-list(byte)) - one_or_error
```

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.6 code_metrics

object

1.6.1 cc_metric

Cyclomatic complexity metric. All defined predicates that are not called or updated are counted as graph connected components (the reasoning being that these predicates can be considered entry points). The score is represented by a non-negative integer.

Availability:

```
logtalk_load(code_metrics(loader))
```

Author: Paulo Moura

Version: 0:5:2

Date: 2024-05-15

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public code_metrics_utilities
public code_metric
```

Provides:

logtalk::message_tokens//2

Uses:

list
logtalk
numberlist

Remarks:

(none)

Inherited public predicates:

all/0 all/1 all_score/1 check_option/1 check_options/1 default_option/1 default_options/1
directory/1 directory/2 directory_score/2 entity/1 entity_score/2 file/1 file/2 file_score/2
format_entity_score//2 library/1 library/2 library_score/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory_score/2 rlibrary/1 rlibrary/2 rlibrary_score/2 valid_option/1
valid_options/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.6.2 code_metric

Core predicates for computing source code metrics.

Availability:

```
logtalk_load(code_metrics(loader))
```

Author: Ebrahim Azarisooreh and Paulo Moura

Version: 0:12:1

Date: 2024-05-08

Compilation flags:

```
static
```

Extends:

```
public code_metrics_utilities
```

```
public options
```

Uses:

```
list
```

```
logtalk
```

```
os
```

```
type
```

Remarks:

```
(none)
```

Inherited public predicates:

```
check_option/1 check_options/1 default_option/1 default_options/1 option/2 option/3  
valid_option/1 valid_options/1
```

- Public predicates
 - entity/1
 - file/2
 - file/1
 - directory/2
 - directory/1
 - rdirectory/2
 - rdirectory/1
 - library/2

- library/1
- rlibrary/2
- rlibrary/1
- all/1
- all/0
- entity_score/2
- library_score/2
- rlibrary_score/2
- file_score/2
- directory_score/2
- rdirectory_score/2
- all_score/1
- format_entity_score//2
- Protected predicates
 - process_entity/2
 - process_file/2
 - process_directory/2
 - process_rdirectory/2
 - process_library/2
 - process_rlibrary/2
 - process_all/1
 - sub_directory/2
 - sub_library/2
- Private predicates
- Operators

Public predicates

entity/1

Scans an entity and prints its metric score.

Compilation flags:

static

Template:

entity(Entity)

Mode and number of proofs:

entity(+term) - zero_or_one

file/2

Prints metric scores for all the entities defined in a loaded source file using the given options.

Compilation flags:

static

Template:

file(File,Options)

Mode and number of proofs:

file(+atom,+list(compound)) - zero_or_one

file/1

Prints metric scores for all the entities defined in a loaded source file using default options.

Compilation flags:

static

Template:

file(File)

Mode and number of proofs:

file(+atom) - zero_or_one

directory/2

Scans a directory and prints metric scores for all entities defined in its loaded source files using the given options.

Compilation flags:

static

Template:

directory(Directory,Options)

Mode and number of proofs:

directory(+atom,+list(compound)) - one

directory/1

Scans a directory and prints metric scores for all entities defined in its loaded source files using default options.

Compilation flags:

static

Template:

directory(Directory)

Mode and number of proofs:

directory(+atom) - one

rdirectory/2

Recursive version of the directory/1 predicate using the given options.

Compilation flags:

static

Template:

rdirectory(Directory,Options)

Mode and number of proofs:

rdirectory(+atom,+list(compound)) - one

`rdirectory/1`

Recursive version of the `directory/1` predicate using default options.

Compilation flags:

`static`

Template:

`rdirectory(Directory)`

Mode and number of proofs:

`rdirectory(+atom) - one`

`library/2`

Prints metrics scores for all loaded entities from a given library using the given options.

Compilation flags:

`static`

Template:

`library(Library,Options)`

Mode and number of proofs:

`library(+atom,+list(compound)) - one`

`library/1`

Prints metrics scores for all loaded entities from a given library using default options.

Compilation flags:

`static`

Template:

`library(Library)`

Mode and number of proofs:

library(+atom) - one

rlibrary/2

Recursive version of the library/1 predicate using the given options.

Compilation flags:

static

Template:

rlibrary(Library,Options)

Mode and number of proofs:

rlibrary(+atom,+list(compound)) - one

rlibrary/1

Recursive version of the library/1 predicate using default options.

Compilation flags:

static

Template:

rlibrary(Library)

Mode and number of proofs:

rlibrary(+atom) - one

all/1

Scans all loaded entities and prints their metric scores using the given options.

Compilation flags:

static

Template:

all(Options)

Mode and number of proofs:

all(+list(compound)) - one

all/0

Scans all loaded entities and prints their metric scores using default options.

Compilation flags:

static

Mode and number of proofs:

all - one

entity_score/2

Score is a term that represents the metric score associated with a loaded entity. Fails if the metric does not apply.

Compilation flags:

static

Template:

entity_score(Entity,Score)

Mode and number of proofs:

entity_score(@entity_identifier,-ground) - zero_or_one

library_score/2

Score is a term that represents the metric score associated with a loaded library source files. Fails if the metric does not apply.

Compilation flags:

static

Template:

library_score(Library,Score)

Mode and number of proofs:

library_score(@atom,-ground) - zero_or_one

rlibrary_score/2

Score is a term that represents the metric score associated with loaded source files from a library and its sub-libraries. Fails if the metric does not apply.

Compilation flags:

static

Template:

rlibrary_score(Library,Score)

Mode and number of proofs:

rlibrary_score(@atom,-ground) - zero_or_one

file_score/2

Score is a term that represents the metric score associated with a loaded source file. Fails if the metric does not apply.

Compilation flags:

static

Template:

file_score(File,Score)

Mode and number of proofs:

file_score(@atom,-ground) - zero_or_one

directory_score/2

Score is a term that represents the metric score associated with loaded source files from a directory. Fails if the metric does not apply.

Compilation flags:

static

Template:

directory_score(Directory,Score)

Mode and number of proofs:

directory_score(@atom,-ground) - zero_or_one

rdirectory_score/2

Score is a term that represents the metric score associated with loaded source files from a directory and its sub-directories. Fails if the metric does not apply.

Compilation flags:

static

Template:

rdirectory_score(Directory,Score)

Mode and number of proofs:

rdirectory_score(@atom,-ground) - zero_or_one

all_score/1

Score is a term that represents the metric score associated with all loaded source files. Fails if the metric does not apply.

Compilation flags:

static

Template:

all_score(Score)

Mode and number of proofs:

`all_score(-ground) - zero_or_one`

`format_entity_score//2`

Formats the entity score for pretty printing.

Compilation flags:

`static`

Template:

`format_entity_score(Entity,Score)`

Mode and number of proofs:

`format_entity_score(@entity_identifier,+ground) - one`

Protected predicates

`process_entity/2`

Processes an entity of the given kind.

Compilation flags:

`static`

Template:

`process_entity(Kind,Entity)`

Mode and number of proofs:

`process_entity(+atom,@entity_identifier) - one`

`process_file/2`

Processes a source file using the given options.

Compilation flags:

`static`

Template:

`process_file(Path,Options)`

Mode and number of proofs:

`process_file(+atom,+list(compound)) - one`

`process_directory/2`

Processes a directory of source files using the given options.

Compilation flags:

`static`

Template:

`process_directory(Path,Options)`

Mode and number of proofs:

`process_directory(+atom,+list(compound)) - one`

`process_rdirectory/2`

Recursively process a directory of source files using the given options.

Compilation flags:

`static`

Template:

`process_rdirectory(Path,Options)`

Mode and number of proofs:

`process_rdirectory(+atom,+list(compound)) - one`

`process_library/2`

Processes a library of source files using the given options.

Compilation flags:

`static`

Template:

`process_library(Library,Options)`

Mode and number of proofs:

`process_library(+atom,+list(compound)) - one`

`process_rlibrary/2`

Recursively process a library of source files using the given options.

Compilation flags:

`static`

Template:

`process_rlibrary(Library,Options)`

Mode and number of proofs:

`process_rlibrary(+atom,+list(compound)) - one`

`process_all/1`

Processes all loaded source code using the given options.

Compilation flags:

`static`

Template:

`process_all(Options)`

Mode and number of proofs:

`process_all(+list(compound)) - one`

`sub_directory/2`

Enumerates, by backtracking, all directory sub-directories containing loaded files.

Compilation flags:

`static`

Template:

`sub_directory(Directory,SubDirectory)`

Mode and number of proofs:

`sub_directory(+atom,-atom) - one`

`sub_library/2`

Enumerates, by backtracking, all library sub-libraries.

Compilation flags:

`static`

Template:

`sub_library(Library,SubLibrary)`

Mode and number of proofs:

`sub_library(+atom,-atom) - one`

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.6.3 code_metrics

Helper object to apply all loaded code metrics.

Availability:

```
logtalk_load(code_metrics(loader))
```

Author: Ebrahim Azarisooreh and Paulo Moura

Version: 0:1:0

Date: 2017-12-31

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public code_metric
```

Uses:

```
logtalk
```

Remarks:

```
(none)
```

Inherited public predicates:

```
all/0 all/1 all_score/1 check_option/1 check_options/1 default_option/1 default_options/1
directory/1 directory/2 directory_score/2 entity/1 entity_score/2 file/1 file/2 file_score/2
format_entity_score//2 library/1 library/2 library_score/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory_score/2 rlibrary/1 rlibrary/2 rlibrary_score/2 valid_option/1
valid_options/1
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.6.4 code_metrics_messages

Message translations for the code_metrics tool.

Availability:

logtalk_load(code_metrics(loader))

Author: Ebrahim Azarisooreh and Paulo Moura

Version: 0:8:0

Date: 2022-05-05

Compilation flags:

static

Provides:

logtalk::message_prefix_stream/4

logtalk::message_tokens//2

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.6.5 code_metrics_utilities

Internal predicates for analyzing source code.

Availability:

```
logtalk_load(code_metrics(loader))
```

Author: Ebrahim Azarisooreh

Version: 0:7:0

Date: 2024-03-28

Compilation flags:

```
static
```

Uses:

```
list
```

```
logtalk
```

Remarks:

- Usage: This is meant to be imported by any metric added to the system.
- Predicate Scope: This is meant for internal use by metrics only. As such, all provided predicates are protected.

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
 - ancestor/4
 - current_entity/1
 - declares_predicate/2
 - defines_predicate/2
 - defines_predicate/3
 - entity_calls/3
 - entity_kind/2
 - entity_property/2
 - entity_updates/3
 - not_excluded_file/3
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

ancestor/4

True if Entity descends from Ancestor, and EntityKind and AncestorKind unify with their respective entity types.

Compilation flags:

static

Template:

ancestor(EntityKind,Entity,AncestorKind,Ancestor)

Mode and number of proofs:

ancestor(?entity,?entity__identifier,?entity,?entity__identifier) - zero_or_more

current_entity/1

True if Entity is a currently loaded entity.

Compilation flags:

static

Template:

current_entity(Entity)

Mode and number of proofs:

current_entity(?entity__identifier) - zero_or_more

declares_predicate/2

True if Entity declares Predicate internally.

Compilation flags:

static

Template:

declares_predicate(Entity,Predicate)

Mode and number of proofs:

declares_predicate(?entity__identifier,?predicate_indicator) - zero_or_more

`defines__predicate/2`

True if Entity defines an implementation of Predicate internally. Auxiliary predicates are excluded from results.

Compilation flags:

static

Template:

`defines__predicate(Entity,Predicate)`

Mode and number of proofs:

`defines__predicate(?entity__identifier,?predicate__indicator) - zero_or_more`

`defines__predicate/3`

Same as `defines__predicate/2`, except Property is unified with a property of the predicate.

Compilation flags:

static

Template:

`defines__predicate(Entity,Predicate,Property)`

Mode and number of proofs:

`defines__predicate(?entity__identifier,?predicate__indicator,?term) - zero_or_more`

`entity__calls/3`

True if a predicate Caller within Entity makes a Call.

Compilation flags:

static

Template:

`entity__calls(Entity,Caller,Call)`

Mode and number of proofs:

`entity__calls(?entity__identifier,?predicate__indicator,?predicate__indicator) - zero_or_one`

`entity_kind/2`

True if Kind defines Entity and is one of category, protocol, or object.

Compilation flags:

static

Template:

entity_kind(Entity,Kind)

Mode and number of proofs:

entity_kind(+entity_identifier,-entity) - zero_or_one

`entity_property/2`

True if Property is a valid property of Entity. Entity can be either a category, a protocol, or an object.

Compilation flags:

static

Template:

entity_property(Entity,Property)

Mode and number of proofs:

entity_property(+entity_identifier,-term) - zero_or_more

`entity_updates/3`

True if a predicate Updater within Entity makes a dynamic update to Updated (by using e.g. the asserta/1 or retract/1 predicates).

Compilation flags:

static

Template:

entity_updates(Entity,Updater,Updated)

Mode and number of proofs:

`entity_updates(+entity_identifier,?predicate_indicator,?predicate_indicator) - zero_or_one`

`not_excluded_file/3`

True if the file is not being excluded.

Compilation flags:

`static`

Template:

`not_excluded_file(ExcludedFiles,Path,Basename)`

Mode and number of proofs:

`not_excluded_file(+list(atom),+atom,+atom) - zero_or_one`

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.6.6 `coupling_metric`

Computes entity efferent coupling, afferent coupling, and instability.

Availability:

`logtalk_load(code_metrics(loader))`

Author: Ebrahim Azarisooreh and Paulo Moura

Version: 0:14:0

Date: 2024-03-27

Compilation flags:

`static, context_switching_calls`

Imports:

```
public code_metrics_utilities
public code_metric
```

Uses:

```
list
```

Remarks:

- Efferent coupling (Ce): Number of entities that an entity depends on.
- Afferent coupling (Ca): Number of entities that depend on an entity.
- Instability (I): Computed as $Ce / (Ce + Ca)$. Measures the entity resilience to change. Ranging from 0 to 1, with 0 indicating a maximally stable entity and 1 indicating a maximally unstable entity. Ideally, an entity is either maximally stable or maximally unstable.
- Abstractness (A): Computed as the ratio between the number of static predicates with scope directives without a local definition and the number of static predicates with scope directives. Measures the rigidity of an entity. Ranging from 0 to 1, with 0 indicating a fully concrete entity and 1 indicating a fully abstract entity.
- Entity score: Represented as the compound term `ce_ca_i_a(Ce,Ca,I,A)`.
- Dependencies count: Includes direct entity relations plus calls or dynamic updates to predicates in external objects or categories.

Inherited public predicates:

```
all/0 all/1 all_score/1 check_option/1 check_options/1 default_option/1 default_options/1
directory/1 directory/2 directory_score/2 entity/1 entity_score/2 file/1 file/2 file_score/2
format_entity_score//2 library/1 library/2 library_score/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory_score/2 rlibrary/1 rlibrary/2 rlibrary_score/2 valid_option/1
valid_options/1
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.6.7 dit__metric

Analyzes the depth of inheritance for objects, protocols, and categories.

Availability:

```
logtalk__load(code__metrics(loader))
```

Author: Ebrahim Azarisooreh

Version: 0:6:1

Date: 2024-03-28

Compilation flags:

```
static, context__switching__calls
```

Imports:

```
public code__metrics__utilities  
public code__metric
```

Uses:

```
numberlist
```

Remarks:

- Depth: The depth is the maximum length of a node to the root entity. Lower scores are generally better.
- Inheritance: A level of inheritance defined by either one of specialization, instantiation, extension, importation, or implementation.

- Scoring: The maximum path length is determined for each entity in question.

Inherited public predicates:

```
all/0 all/1 all_score/1 check_option/1 check_options/1 default_option/1 default_options/1
directory/1 directory/2 directory_score/2 entity/1 entity_score/2 file/1 file/2 file_score/2
format_entity_score//2 library/1 library/2 library_score/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory_score/2 rlibrary/1 rlibrary/2 rlibrary_score/2 valid_option/1
valid_options/1
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.6.8 doc_metric

Entity and entity predicates documentation score.

Availability:

```
logtalk_load(code_metrics(loader))
```

Author: Paulo Moura

Version: 0:13:0

Date: 2022-05-05

Compilation flags:

static, context_switching_calls

Imports:

public code_metrics_utilities
public code_metric

Uses:

list
numberlist

Remarks:

- Score range: Score is a integer percentage where a 100% score means that all expected documentation information is present.
- Score weights: The score is split by default between 20% for the entity documentation and 80% for the entity predicates documentation, Can be customized using the predicate `entity_predicates_weights_hook/2`.
- Score customization: The individual scores of entity info/1 pairs and predicate info/2 pairs can be customized using the `entity_info_pair_score_hook/3` and `predicate_info_pair_score_hook/4` predicates.

Inherited public predicates:

all/0 all/1 all_score/1 check_option/1 check_options/1 default_option/1 default_options/1
directory/1 directory/2 directory_score/2 entity/1 entity_score/2 file/1 file/2 file_score/2
format_entity_score//2 library/1 library/2 library_score/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory_score/2 rlibrary/1 rlibrary/2 rlibrary_score/2 valid_option/1
valid_options/1

- Public predicates
 - `entity_predicates_weights_hook/2`
 - `entity_info_score_hook/2`
 - `entity_info_pair_score_hook/3`
 - `predicate_mode_score_hook/3`
 - `predicate_mode_score_hook/5`
 - `predicate_info_score_hook/3`
 - `predicate_info_pair_score_hook/4`
- Protected predicates
- Private predicates
- Operators

Public predicates

`entity_predicates_weights_hook/2`

Relative weight between entity documentation and predicates documentation in percentage. The sum of the two values must be equal to 100.

Compilation flags:

dynamic, multifile

Template:

`entity_predicates_weights_hook(EntityWeight,PredicatesWeight)`

Mode and number of proofs:

`entity_predicates_weights_hook(?integer,?integer) - zero_or_one`

`entity_info_score_hook/2`

Maximum score for entity info/1 directives.

Compilation flags:

dynamic, multifile

Template:

`entity_info_score_hook(Entity,MaximumScore)`

Mode and number of proofs:

`entity_info_score_hook(?term,?integer) - zero_or_one`

`entity_info_pair_score_hook/3`

Score for relevant entity info/1 directive pairs. If defined, the `entity_info_score_hook/2` predicate should be defined accordingly.

Compilation flags:

dynamic, multifile

Template:

`entity_info_pair_score_hook(Pair,Entity,Score)`

Mode and number of proofs:

entity_info_pair_score_hook(?callable,?term,?integer) - zero_or_more

predicate_mode_score_hook/3

Maximum score for predicate mode/2 directives.

Compilation flags:

dynamic, multifile

Template:

predicate_mode_score_hook(Entity,Predicate,MaximumScore)

Mode and number of proofs:

predicate_mode_score_hook(?term,?term,?integer) - zero_or_more

predicate_mode_score_hook/5

Score for a predicate mode/2 directive. If defined, the predicate_mode_score_hook/3 predicate should be defined accordingly.

Compilation flags:

dynamic, multifile

Template:

predicate_mode_score_hook(Template,Solutions,Entity,Predicate,Score)

Mode and number of proofs:

predicate_mode_score_hook(?term,?term,?term,?term,?integer) - zero_or_one

`predicate_info_score_hook/3`

Maximum score for predicate info/2 directives.

Compilation flags:
dynamic, multifile

Template:
predicate_info_score_hook(Entity,Predicate,MaximumScore)
Mode and number of proofs:
predicate_info_score_hook(?term,?term,?integer) - zero_or_one

`predicate_info_pair_score_hook/4`

Score for a predicate info/2 directive pairs. If defined, the predicate_info_score_hook/3 predicate should be defined accordingly.

Compilation flags:
dynamic, multifile

Template:
predicate_info_pair_score_hook(Pair,Entity,Predicate,Score)
Mode and number of proofs:
predicate_info_pair_score_hook(?callable,?term,?term,?integer) - zero_or_more

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.6.9 halstead_metric

Computes Halstead complexity numbers for an entity using a Stroud of 18.

Availability:

`logtalk_load(code_metrics(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2018-06-08

Compilation flags:

`static, context_switching_calls`

Extends:

`public halstead_metric(18)`

Remarks:

(none)

Inherited public predicates:

`all/0 all/1 all_score/1 check_option/1 check_options/1 default_option/1 default_options/1
directory/1 directory/2 directory_score/2 entity/1 entity_score/2 file/1 file/2 file_score/2
format_entity_score//2 library/1 library/2 library_score/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory_score/2 rlibrary/1 rlibrary/2 rlibrary_score/2 valid_option/1
valid_options/1`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.6.10 `halstead_metric`(Stroud)

- Stroud - Coefficient for computing the time required to program.

Computes Halstead complexity numbers for an entity.

Availability:

```
logtalk_load(code_metrics(loader))
```

Author: Paulo Moura

Version: 0:10:0

Date: 2025-01-04

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public code_metrics_utilities
```

```
public code_metric
```

Uses:

```
list
```

```
numberlist
```

```
pairs
```

Remarks:

- Definition of operators: Predicates declared, user-defined, and called are interpreted as operators. Built-in predicates and built-in control constructs are ignored.
- Definition of operands: Predicate arguments are abstracted and interpreted as operands. Note that this definition of operands is a significant deviation from the original definition, which used syntactic literals.
- Pn: Number of distinct predicates (declared, defined, called, or updated).
- PAn: Number of predicate arguments (assumed distinct).
- Cn: Number of predicate calls/updates + number of clauses.
- CAn: Number of predicate call/update arguments + number of clause head arguments.
- EV: Entity vocabulary: $EV = Pn + PAn$.
- EL: Entity length: $EL = Cn + CAn$.
- V: Volume: $V = EL * \log_2(EV)$.
- D: Difficulty: $D = (Pn/2) * (CAn/An)$.
- E: Effort: $E = D * V$.
- T: Time required to program: $T = E/k$ seconds (k is the Stroud number; defaults to 18).
- B: Number of delivered bugs: $B = V/3000$.
- Entity score: Represented as the compound term `pn_pan_cn_can_ev_el_v_d_e_t_b/11`.

Inherited public predicates:

```
all/0 all/1 all_score/1 check_option/1 check_options/1 default_option/1 default_options/1
directory/1 directory/2 directory_score/2 entity/1 entity_score/2 file/1 file/2 file_score/2
format_entity_score/2 library/1 library/2 library_score/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory_score/2 rlibrary/1 rlibrary/2 rlibrary_score/2 valid_option/1
valid_options/1
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.6.11 `noc_metric`

Number of entity clauses metric. The score is represented using the compound term `number_of_clauses(Total, User)`.

Availability:

```
logtalk_load(code_metrics(loader))
```

Author: Ebrahim Azarisooreh and Paulo Moura

Version: 0:14:1

Date: 2024-05-08

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public code_metrics_utilities
```

```
public code_metric
```

Provides:

```
logtalk::message_tokens//2
```

Uses:

```
list
```

```
logtalk
```

Remarks:

(none)

Inherited public predicates:

```
all/0 all/1 all_score/1 check_option/1 check_options/1 default_option/1 default_options/1
directory/1 directory/2 directory_score/2 entity/1 entity_score/2 file/1 file/2 file_score/2
format_entity_score//2 library/1 library/2 library_score/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory_score/2 rlibrary/1 rlibrary/2 rlibrary_score/2 valid_option/1
valid_options/1
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.6.12 nor__metric

Number of entity rules metric. The score is represented using the compound term `number_of_rules(Total, User)`.

Availability:

```
logtalk_load(code_metrics(loader))
```

Author: Paulo Moura

Version: 0:5:1

Date: 2024-05-08

Compilation flags:

static, context_switching_calls

Imports:

public code_metrics_utilities
public code_metric

Provides:

logtalk::message_tokens//2

Uses:

list
logtalk

Remarks:

(none)

Inherited public predicates:

all/0 all/1 all_score/1 check_option/1 check_options/1 default_option/1 default_options/1
directory/1 directory/2 directory_score/2 entity/1 entity_score/2 file/1 file/2 file_score/2
format_entity_score//2 library/1 library/2 library_score/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory_score/2 rlibrary/1 rlibrary/2 rlibrary_score/2 valid_option/1
valid_options/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.6.13 size_metric

Source code size metric. Returned scores are upper bounds and based solely in source file sizes (expressed in bytes).

Availability:

```
logtalk_load(code_metrics(loader))
```

Author: Paulo Moura

Version: 0:7:1

Date: 2024-05-08

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public code_metrics_utilities
```

```
public code_metric
```

Provides:

```
logtalk::message_tokens//2
```

Uses:

```
list
```

```
logtalk
```

```
numberlist
```

```
os
```

Remarks:

(none)

Inherited public predicates:

```
all/0 all/1 all_score/1 check_option/1 check_options/1 default_option/1 default_options/1
directory/1 directory/2 directory_score/2 entity/1 entity_score/2 file/1 file/2 file_score/2
format_entity_score//2 library/1 library/2 library_score/2 option/2 option/3 rdirectory/1
```

```
rdirectory/2 rdirectory_score/2 rlibrary/1 rlibrary/2 rlibrary_score/2 valid_option/1
valid_options/1
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.6.14 upn_metric

Number of unique predicates nodes metric. The nodes include called and updated predicates independently of where they are defined. The score is represented by a non-negative integer.

Availability:

```
logtalk_load(code_metrics(loader))
```

Author: Paulo Moura

Version: 0:6:2

Date: 2024-05-15

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public code_metrics_utilities
public code_metric
```

Provides:

```
logtalk::message_tokens//2
```

Uses:

```
list
logtalk
numberlist
```

Remarks:

(none)

Inherited public predicates:

```
all/0 all/1 all_score/1 check_option/1 check_options/1 default_option/1 default_options/1
directory/1 directory/2 directory_score/2 entity/1 entity_score/2 file/1 file/2 file_score/2
format_entity_score//2 library/1 library/2 library_score/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory_score/2 rlibrary/1 rlibrary/2 rlibrary_score/2 valid_option/1
valid_options/1
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.7 core

category

1.7.1 core__messages

Logtalk core (compiler and runtime) default message tokenization.

Availability:

built_in

Author: Paulo Moura

Version: 1:143:0

Date: 2025-01-02

Compilation flags:

static

Provides:

logtalk::message_prefix_stream/4

logtalk::message_tokens//2

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)
protocol

1.7.2 expanding

Term and goal expansion protocol.

Availability:
built_in

Author: Paulo Moura
Version: 1:1:0
Date: 2016-07-12

Compilation flags:
static, built_in

Dependencies:
(none)

Remarks:
(none)

Inherited public predicates:
(none)

- Public predicates
 - goal_expansion/2
 - term_expansion/2
- Protected predicates
- Private predicates
- Operators

Public predicates

goal_expansion/2

Defines a goal expansion. Called recursively until a fixed point is reached on goals found while compiling a source file (except for goals wrapped using the `{}/1` compiler bypass control construct).

Compilation flags:

static

Template:

goal_expansion(Goal,ExpandedGoal)

Mode and number of proofs:

goal_expansion(+callable,-callable) - zero_or_one

term_expansion/2

Defines a term expansion. Called until it succeeds on all terms read while compiling a source file (except for terms skipped by using the conditional compilation directives or wrapped using the `{}/1` compiler bypass control construct).

Compilation flags:

static

Template:

term_expansion(Term,ExpandedTerms)

Mode and number of proofs:

term_expansion(+term,-term) - zero_or_one

term_expansion(+term,-list(term)) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

protocol

1.7.3 forwarding

Message forwarding protocol.

Availability:

built_in

Author: Paulo Moura

Version: 1:0:1

Date: 2025-05-15

Compilation flags:

static, built_in

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - forward/1
- Protected predicates

- Private predicates
- Operators

Public predicates

`forward/1`

User-defined message forwarding handler, automatically called (if defined) by the runtime for any message that the receiving object does not understand.

Compilation flags:

`static`

Template:

`forward(Message)`

Mode and number of proofs:

`forward(+callable) - zero_or_more`

Protected predicates

`(none)`

Private predicates

`(none)`

Operators

`(none)`

`object`

1.7.4 logtalk

Built-in object providing message printing, debugging, library, source file, and hacking methods.

Availability:

`built_in`

Author: Paulo Moura

Version: 3:2:0

Date: 2025-05-20

Compilation flags:

static, built_in, context_switching_calls, threaded

Dependencies:

(none)

Remarks:

- Default message kinds: `silent`, `silent(Key)`, `banner`, `help`, `comment`, `comment(Key)`, `information`, `information(Key)`, `warning`, `warning(Key)`, `error`, `error(Key)`, `debug`, `debug(Key)`, `question`, and `question(Key)`.
- Printing of silent messages: By default, silent messages are not printed. These messages are only useful when intercepted.
- Printing of banner and comment messages: By default, banner and comment messages are only printed when the report flag is turned on.
- Printing of help, information, and question messages: These messages are always printed by default as they provide requested output.
- Printing of warning messages: By default, warning messages are not printed when the report flag is turned off.
- Printing of error messages: These messages are always printed by default.
- Printing of debug messages: By default, debug messages are only printed when the debug flag is turned on. The compiler suppresses debug message printing goals when compiling in optimized mode.
- Meta messages: A meta message is a message that have another message as argument and is typically used for debugging messages. Meta messages avoid the need of defining tokenizer rules for every message but can be intercepted as any other message.
- Meta message `@Message`: By default, the message is printed as passed to the `write/1` predicate followed by a newline.
- Meta message `Key-Value`: By default, the message is printed as “Key: Value” followed by a newline. The key is printed as passed to the `write/1` predicate while the value is printed as passed to the `writeln/1` predicate.
- Meta message `Format+Arguments`: By default, the message is printed as passed to the `format/2` predicate.
- Meta message `List`: By default, the list items are printed indented one per line. The items are preceded by a dash and can be `@Message`, `Key-Value`, or `Format+Arguments` messages. If that is not the case, the item is printed as passed to the `writeln/1` predicate.
- Meta message `Title::List`: By default, the title is printed followed by a newline and the indented list items, one per line. The items are printed as in the `List` meta message.
- Meta message `[Stream,Prefix]>>Goal`: By default, call user-defined `Goal` in the context of `user`. The use of a lambda expression allows passing the message stream and prefix. Printing the prefix is delegated to the goal.

- Meta message [Stream]>>Goal: By default, call user-defined Goal in the context of user. The use of a lambda expression allows passing the message stream.
- Message tokens: `at_same_line`, `tab(Expression)`, `nl`, `flush`, `Format-Arguments`, `term(Term,Options)`, `ansi(Attributes,Format,Arguments)`, `begin(Kind,Variable)`, and `end(Variable)`.
- Multi-threading applications: Predicates calling methods such as `print_message/3`, `ask_question/5`, or `compile_aux_clauses/1` may need to be declared synchronized in order to avoid race conditions.

Inherited public predicates:

(none)

- Public predicates
 - `print_message/3`
 - `print_message_tokens/3`
 - `print_message_token/4`
 - `message_tokens//2`
 - `message_prefix_stream/4`
 - `message_prefix_file/6`
 - `message_hook/4`
 - `ask_question/5`
 - `question_hook/6`
 - `question_prompt_stream/4`
 - `trace_event/2`
 - `debug_handler/1`
 - `active_debug_handler/1`
 - `activate_debug_handler/1`
 - `deactivate_debug_handler/0`
 - `debug_handler/3`
 - `expand_library_path/2`
 - `loaded_file/1`
 - `loaded_file_property/2`
 - `file_type_extension/2`
 - `compile_aux_clauses/1`
 - `entity_prefix/2`
 - `compile_predicate_heads/4`
 - `compile_predicate_indicators/3`
 - `decompile_predicate_heads/4`

- decompile_predicate_indicators/4
 - execution_context/7
- Protected predicates
- Private predicates
 - active_debug_handler_/1
- Operators

Public predicates

`print_message/3`

Prints a message of the given kind for the specified component.

Compilation flags:

`static`

Template:

`print_message(Kind,Component,Message)`

Mode and number of proofs:

`print_message(+nonvar,+nonvar,+nonvar) - one`

`print_message_tokens/3`

Print the messages tokens to the given stream, prefixing each line with the specified atom.

Compilation flags:

`static`

Template:

`print_message_tokens(Stream,Prefix,Tokens)`

Mode and number of proofs:

`print_message_tokens(@stream_or_alias,+atom,@list(nonvar)) - one`

`print_message_token/4`

User-defined hook predicate for printing a message token (see this object remarks).

Compilation flags:
dynamic, multifile

Template:
 `print_message_token(Stream,Prefix,Token,Tokens)`
Mode and number of proofs:
 `print_message_token(@stream_or_alias,@atom,@nonvar,@list(nonvar)) - zero_or_one`

`message_tokens//2`

User-defined hook grammar rule for converting a message into a list of tokens (see this object remarks).

Compilation flags:
dynamic, multifile

Template:
 `message_tokens(Message,Component)`
Mode and number of proofs:
 `message_tokens(+nonvar,+nonvar) - zero_or_one`

`message_prefix_stream/4`

Message line prefix and output stream to be used when printing a message given its kind and component.

Compilation flags:
dynamic, multifile

Template:
 `message_prefix_stream(Kind,Component,Prefix,Stream)`
Mode and number of proofs:
 `message_prefix_stream(?nonvar,?nonvar,?atom,?stream_or_alias) - zero_or_more`

`message_prefix_file/6`

Message line prefix and output file to be used when printing a message given its kind and component.

Compilation flags:

dynamic, multifile

Template:

`message_prefix_file(Kind,Component,Prefix,File,Mode,Options)`

Mode and number of proofs:

`message_prefix_file(?nonvar,?nonvar,?atom,?atom,?atom,?list(compound)) - zero_or_more`

`message_hook/4`

User-defined hook predicate for intercepting message printing calls.

Compilation flags:

dynamic, multifile

Template:

`message_hook(Message,Kind,Component,Tokens)`

Mode and number of proofs:

`message_hook(+nonvar,+nonvar,+nonvar,+list(nonvar)) - zero_or_one`

`ask_question/5`

Asks a question and reads the answer until the check predicate is true.

Compilation flags:

static

Template:

`ask_question(Kind,Component,Question,Check,Answer)`

Meta-predicate template:

`ask_question(*,*,*,1,*)`

Mode and number of proofs:

`ask_question(+nonvar,+nonvar,+nonvar,+callable,-term) - one`

`question_hook/6`

User-defined hook predicate for intercepting question asking calls.

Compilation flags:

dynamic, multifile

Template:

```
question_hook(Question,Kind,Component,Tokens,Check,Answer)
```

Meta-predicate template:

```
question_hook(*,*,*,*,1,*)
```

Mode and number of proofs:

```
question_hook(+nonvar,+nonvar,+nonvar,+list(nonvar),+callable,-term) - zero_or_one
```

`question_prompt_stream/4`

Prompt and input stream to be used when asking a question given its kind and component.

Compilation flags:

dynamic, multifile

Template:

```
question_prompt_stream(Kind,Component,Prompt,Stream)
```

Mode and number of proofs:

```
question_prompt_stream(?nonvar,?nonvar,?atom,?stream_or_alias) - zero_or_more
```

`trace_event/2`

Trace event handler. The runtime calls all trace event handlers using a failure-driven loop before calling the debug event handler.

Compilation flags:

dynamic, multifile

Template:

```
trace_event(Event,ExecutionContext)
```

Mode and number of proofs:

```
trace_event(@callable,@execution_context) - zero
```

Remarks:

- Unification events: Generated after a successful unification with a fact - fact(Entity,Fact,Clause,File,Line) - or a rule head - rule(Entity,Head,Clause,File,Line).
 - Goal events: Generated when calling a goal: top_goal(Goal,CompiledGoal) or goal(Goal,CompiledGoal).
-

`debug_handler/1`

Enumerates, by backtracking, all declared debug handler providers. Define a clause for this predicate to declare a new debug handler provider.

Compilation flags:

```
static, multifile
```

Template:

```
debug_handler(Provider)
```

Mode and number of proofs:

```
debug_handler(?object_identifier) - zero_or_more
```

```
debug_handler(?category_identifier) - zero_or_more
```

`active_debug_handler/1`

Current active debug handler provider if any. There is at most one active debug handler provider at any given moment.

Compilation flags:

```
static
```

Template:

```
active_debug_handler(Provider)
```

Mode and number of proofs:

```
active_debug_handler(?category_identifier) - zero_or_one
```

```
active_debug_handler(?category_identifier) - zero_or_one
```

`activate__debug__handler/1`

Activates the given debug handler provider. There is at most one active debug handler provider at any given moment. Fails if the object or category is not declared as a debug handler provider.

Compilation flags:

`static`

Template:

`activate__debug__handler(Provider)`

Mode and number of proofs:

`activate__debug__handler(@object__identifier) - zero_or_one`

`activate__debug__handler(@category__identifier) - zero_or_one`

`deactivate__debug__handler/0`

Deactivates the current debug handler provider if any.

Compilation flags:

`static`

Mode and number of proofs:

`deactivate__debug__handler - one`

`debug__handler/3`

Debug event handler. Called by the runtime when the given provider is active.

Compilation flags:

`static, multifile`

Template:

`debug__handler(Provider,Event,ExecutionContext)`

Mode and number of proofs:

`debug_handler(+object_identifier,+callable,+execution_context) - zero_or_more`
`debug_handler(+category_identifier,+callable,+execution_context) - zero_or_more`

Remarks:

- Unification events: Generated after a successful unification with a fact - `fact(Entity,Fact,Clause,File,Line)` - or a rule head - `rule(Entity,Head,Clause,File,Line)`.
 - Goal events: Generated when calling a goal: `top_goal(Goal,CompiledGoal)` or `goal(Goal,CompiledGoal)`.
-

`expand_library_path/2`

Expands a library alias (an atom) or a compound term (using library notation) into its absolute path. Uses a depth bound to prevent loops.

Compilation flags:

`static`

Template:

`expand_library_path(LibraryAlias,AbsolutePath)`

Mode and number of proofs:

`expand_library_path(+atom,?atom) - zero_or_one`

`expand_library_path(+callable,?atom) - zero_or_one`

`loaded_file/1`

Enumerates, by backtracking, all loaded files, returning their full paths.

Compilation flags:

`static`

Template:

`loaded_file(Path)`

Mode and number of proofs:

`loaded_file(?atom) - zero_or_more`

loaded_file_property/2

Enumerates, by backtracking, loaded file properties.

Compilation flags:

static

Template:

loaded_file_property(Path,Property)

Mode and number of proofs:

loaded_file_property(?atom,?compound) - zero_or_more

Remarks:

- Property basename/1: Basename of the file (includes the file extension, if any).
- Property directory/1: Directory of the file (ending with a slash).
- Property mode/1: Compilation mode of the file (possible values are optimal, normal, and debug).
- Property flags/1: Explicit flags used for compiling the file.
- Property text_properties/1: List of the file text properties (encoding/1 and bom/1). Empty if no encoding/1 directive is present and the stream used for reading the file does not have a bom/1 (or equivalent) property.
- Property target/1: Full path of the generated intermediate Prolog file.
- Property modified/1: File modification time stamp (should be regarded as an opaque but otherwise comparable term).
- Property parent/1: Full path of the parent file that loaded the file.
- Property includes/2: Full path of a file included by the file and the line of the include/1 directive.
- Property includes/1: Full path of a file included by the file.
- Property library/1: Library alias for the library that includes the file.
- Property object/3: Identifier for an object defined in the file and the start and end lines of its definition.
- Property object/1: Identifier for an object defined in the file.
- Property protocol/3: Identifier for a protocol defined in the file and the start and end lines of its definition.
- Property protocol/1: Identifier for a protocol defined in the file.
- Property category/3: Identifier for a category defined in the file and the start and end lines of its definition.
- Property category/1: Identifier for a category defined in the file.

`file_type_extension/2`

Enumerates, by backtracking, all defined file type extensions. The defined types are: source, object, logtalk, prolog, and tmp. The source type returns both logtalk and prolog type extensions.

Compilation flags:

static

Template:

`file_type_extension(Type,Extension)`

Mode and number of proofs:

`file_type_extension(?atom,?atom) - zero_or_more`

`compile_aux_clauses/1`

Compiles a list of auxiliary clauses. Can only be called during source file compilation, usually from `term_expansion/2` or `goal_expansion/2` hook predicate definitions.

Compilation flags:

static

Template:

`compile_aux_clauses(Clauses)`

Mode and number of proofs:

`compile_aux_clauses(@list(clause)) - one`

`entity_prefix/2`

Converts between an entity identifier and the entity prefix that is used for its compiled code. When none of the arguments is instantiated, it returns the identifier and the prefix of the entity under compilation, if any.

Compilation flags:

static

Template:

`entity_prefix(Entity,Prefix)`

Mode and number of proofs:

`entity_prefix(?entity_identifier,?atom) - zero_or_one`

`compile_predicate_heads/4`

Compiles clause heads. The heads are compiled in the context of the entity under compilation when the entity argument is not instantiated.

Compilation flags:

`static`

Template:

`compile_predicate_heads(Heads,Entity,CompiledHeads,ExecutionContext)`

Mode and number of proofs:

`compile_predicate_heads(@list(callable),?entity_identifier,-list(callable),@execution_context) - zero_or_one`

`compile_predicate_heads(@conjunction(callable),?entity_identifier,-conjunction(callable),@execution_context) - zero_or_one`

`compile_predicate_heads(@callable,?entity_identifier,-callable,@execution_context) - zero_or_one`

`compile_predicate_indicators/3`

Compiles predicate indicators. The predicate are compiled in the context of the entity under compilation when the entity argument is not instantiated.

Compilation flags:

`static`

Template:

`compile_predicate_indicators(PredicateIndicators,Entity,CompiledPredicateIndicators)`

Mode and number of proofs:

`compile_predicate_indicators(@list(predicate_indicator),?entity_identifier,-list(predicate_indicator)) - zero_or_one`

`compile_predicate_indicators(@conjunction(predicate_indicator),?entity_identifier,-conjunction(predicate_indicator)) - zero_or_one`

`compile_predicate_indicators(@predicate_indicator,?entity_identifier,-predicate_indicator) - zero_or_one`

`decompile_predicate_heads/4`

Decompiles clause heads. All compiled clause heads must belong to the same entity, which must be loaded.

Compilation flags:

static

Template:

`decompile_predicate_heads(CompiledHeads,Entity,Type,Heads)`

Mode and number of proofs:

`decompile_predicate_heads(@list(callable),-entity_identifier,-atom,-list(callable)) - zero_or_one`

`decompile_predicate_heads(@conjunction(callable),-entity_identifier,-atom,-conjunction(callable)) - zero_or_one`

`decompile_predicate_heads(@callable,-entity_identifier,-atom,-callable) - zero_or_one`

`decompile_predicate_indicators/4`

Decompiles predicate indicators. All compiled predicate indicators must belong to the same entity, which must be loaded.

Compilation flags:

static

Template:

`decompile_predicate_indicators(CompiledPredicateIndicators,Entity,Type,PredicateIndicators)`

Mode and number of proofs:

`decompile_predicate_indicators(@list(predicate_indicator),-entity_identifier,-atom,-list(predicate_indicator)) - zero_or_one`

`decompile_predicate_indicators(@conjunction(predicate_indicator),-entity_identifier,-atom,-conjunction(predicate_indicator)) - zero_or_one`

`decompile_predicate_indicators(@predicate_indicator,-entity_identifier,-atom,-predicate_indicator) - zero_or_one`

`execution_context/7`

Execution context term data. Execution context terms should be considered opaque terms subject to change without notice.

Compilation flags:

`static`

Template:

`execution_context(ExecutionContext,Entity,Sender,This,Self,MetaCallContext,CoinductionStack)`

Mode and number of proofs:

`execution_context(?nonvar,?entity__identifier,?object__identifier,?object__identifier,?object__identifier,
@list(callable),@list(callable)) - zero_or_one`

Protected predicates

(none)

Private predicates

`active_debug_handler_/1`

Current active debug handler provider. There is at most one active debug handler provider at any given moment.

Compilation flags:

`dynamic`

Template:

`active_debug_handler_(Provider)`

Mode and number of proofs:

`active_debug_handler_(?entity__identifier) - zero_or_one`

Operators

(none)

protocol

1.7.5 monitoring

Event handlers protocol. The handlers are automatically called by the runtime for messages sent using the `::/2` control construct from objects or categories compiled with the events flag set to allow.

Availability:

built_in

Author: Paulo Moura

Version: 1:2:0

Date: 2018-11-29

Compilation flags:

static, built_in

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - before/3
 - after/3
- Protected predicates
- Private predicates
- Operators

Public predicates

before/3

Event handler for before events. A before event handler may prevent a method from being looked up or called by failing.

Compilation flags:

static

Template:

before(Object,Message,Sender)

Mode and number of proofs:

before(?term,?term,?term) - zero_or_more

after/3

Event handler for after events. An after event handler may prevent a method from succeeding by failing.

Compilation flags:

static

Template:

after(Object,Message,Sender)

Mode and number of proofs:

after(?term,?term,?term) - zero_or_more

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

object

1.7.6 user

Pseudo-object representing the plain Prolog database. Can be used as a monitor by defining `before/3` and `after/3` predicates. Can be used as a hook object by defining `term_expansion/2` and `goal_expansion/2` multifile and dynamic predicates.

Availability:

`built_in`

Author: Paulo Moura

Version: 1:6:0

Date: 2024-11-11

Compilation flags:

`static`, `built_in`, `context_switching_calls`, `dynamic_declarations`, `threaded`

Implements:

public `expanding`

public `forwarding`

public `monitoring`

Uses:

`user`

Remarks:

(none)

Inherited public predicates:

`after/3` `before/3` `forward/1` `goal_expansion/2` `term_expansion/2`

- Public predicates
- Protected predicates

- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.8 coroutining

object

1.8.1 coroutining

Coroutining predicates.

Availability:

`logtalk__load(coroutining(loader))`

Author: Paulo Moura

Version: 0:5:0

Date: 2021-12-17

Compilation flags:

`static, context__switching__calls`

Dependencies:

(none)

Remarks:

- Supported backend Prolog systems: ECLiPSe, XVM, SICStus Prolog, SWI-Prolog, Trealla Prolog, and YAP.

Inherited public predicates:

(none)

- Public predicates
 - dif/2
 - dif/1
 - freeze/2
 - frozen/2
 - when/2
- Protected predicates
- Private predicates
- Operators

Public predicates

dif/2

Sets a constraint that is true iff the two terms are different.

Compilation flags:

static

Template:

dif(Term1,Term2)

Mode and number of proofs:

dif(+term,+term) - zero_or_one

`dif/1`

Sets a set of constraints that are true iff all terms in a list are different.

Compilation flags:

`static`

Template:

`dif(Terms)`

Mode and number of proofs:

`dif(+list(term)) - zero_or_one`

`freeze/2`

Delays the execution of a goal until a variable is bound.

Compilation flags:

`static`

Template:

`freeze(Variable,Goal)`

Meta-predicate template:

`freeze(*,0)`

Mode and number of proofs:

`freeze(+term,+callable) - zero_or_more`

`frozen/2`

Unifies Goal with the goal delayed by Variable. When no goals are frozen on Variable, Goal is unified with true.

Compilation flags:

`static`

Template:

`frozen(Variable,Goal)`

Mode and number of proofs:

frozen(@var,--callable) - one

when/2

Calls Goal when Condition becomes true. The portable conditions are: nonvar/1, ground/1, (,)/2, and (;)/2.

Compilation flags:

static

Template:

when(Condition,Goal)

Meta-predicate template:

when(*,0)

Mode and number of proofs:

when(+callable,+callable) - zero_or_more

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.9 csv

object

1.9.1 csv

CSV files reading and writing predicates using the options Header - keep, Separator - comma, and Ignore-Quotes - false.

Availability:

```
logtalk_load(csv(loader))
```

Author: Jacinto Dávila

Version: 1:0:0

Date: 2021-02-02

Compilation flags:

```
static, context_switching_calls
```

Extends:

```
public csv(keep,comma,false)
```

Remarks:

```
(none)
```

Inherited public predicates:

```
guess_arity/2 guess_separator/2 read_file/2 read_file/3 read_file_by_line/2
read_file_by_line/3 read_stream/2 read_stream/3 read_stream_by_line/2
read_stream_by_line/3 write_file/3 write_stream/3
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.9.2 csv(Header,Separator,IgnoreQuotes)

- Header - Header handling option with possible values missing, skip, and keep (default).
- Separator - Separator handling option with possible values comma (default for non .tsv and non .tab files or when no file name extension is available), tab (default for .tsv and .tab files), semicolon, and colon.
- IgnoreQuotes - Double-quotes handling option to ignore (true) or preserve (false; default) double quotes surrounding data.

CSV file and stream reading and writing predicates.

Availability:

```
logtalk_load(csv(loader))
```

Author: Jacinto Dávila and Paulo Moura

Version: 2:1:0

Date: 2023-11-15

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public csv_protocol
```

Uses:

```
list  
logtalk  
os  
reader  
type
```

Remarks:

(none)

Inherited public predicates:

```
guess_arity/2 guess_separator/2 read_file/2 read_file/3 read_file_by_line/2
read_file_by_line/3 read_stream/2 read_stream/3 read_stream_by_line/2
read_stream_by_line/3 write_file/3 write_stream/3
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.9.3 csv_guess_questions

Support for asking questions when guessing the separator and the record arity of CSV files.

Availability:

```
logtalk_load(csv(loader))
```

Author: Jacinto Dávila

Version: 1:0:0

Date: 2021-02-03

Compilation flags:

static

Provides:

logtalk::message_tokens//2

logtalk::question_prompt_stream/4

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.9.4 csv_protocol

CSV file and stream reading and writing protocol.

Availability:

```
logtalk_load(csv(loader))
```

Author: Jacinto Dávila and Paulo Moura

Version: 2:0:1

Date: 2025-05-07

Compilation flags:

```
static
```

Dependencies:

```
(none)
```

Remarks:

- Type-checking: Some of the predicate file and stream argument type-checking exceptions depend on the Prolog backend compliance with standards.

Inherited public predicates:

```
(none)
```

- Public predicates
 - read_file/3
 - read_stream/3
 - read_file/2
 - read_stream/2
 - read_file_by_line/3
 - read_stream_by_line/3
 - read_file_by_line/2
 - read_stream_by_line/2
 - write_file/3
 - write_stream/3
 - guess_separator/2

- guess_arity/2
- Protected predicates
- Private predicates
- Operators

Public predicates

read_file/3

Reads a CSV file saving the data as clauses for the specified object predicate. Fails if the file cannot be parsed.

Compilation flags:

static

Template:

read_file(File,Object,Predicate)

Mode and number of proofs:

read_file(+atom,+object_identifier,+predicate_indicator) - zero_or_one

Exceptions:

File is a variable:

instantiation_error

File is neither a variable nor an atom:

type_error(atom,File)

File is an atom but not an existing file:

existence_error(file,File)

File is an existing file but cannot be opened for reading:

permission_error(open,source_sink,File)

Object is a variable:

instantiation_error

Object is neither a variable nor an object identifier:

type_error(object_identifier,Object)

Object is a valid object identifier but not an existing object:

existence_error(object,Object)

Predicate is a variable:

instantiation_error

Predicate is neither a variable nor a predicate indicator:

type_error(predicate_indicator,Predicate)

Predicate is a valid predicate indicator but not an existing public predicate:

existence_error(predicate,Predicate)

`read_stream/3`

Reads a CSV stream saving the data as clauses for the specified object predicate. Fails if the stream cannot be parsed.

Compilation flags:

`static`

Template:

`read_stream(Stream,Object,Predicate)`

Mode and number of proofs:

`read_stream(+stream_or_alias,+object_identifier,+predicate_indicator) - zero_or_one`

Exceptions:

Stream is a variable:

`instantiation_error`

Stream is neither a variable nor a stream-term or alias:

`domain_error(stream_or_alias,Stream)`

Stream is not an open stream:

`existence_error(stream,Stream)`

Stream is an output stream:

`permission_error(input,stream,Stream)`

Stream is a binary stream:

`permission_error(input,binary_stream,Stream)`

Object is a variable:

`instantiation_error`

Object is neither a variable nor an object identifier:

`type_error(object_identifier,Object)`

Object is a valid object identifier but not an existing object:

`existence_error(object,Object)`

Predicate is a variable:

`instantiation_error`

Predicate is neither a variable nor a predicate indicator:

`type_error(predicate_indicator,Predicate)`

Predicate is a valid predicate indicator but not an existing public predicate:

`existence_error(predicate,Predicate)`

`read_file/2`

Reads a CSV file returning the data as a list of rows, each row a list of fields. Fails if the file cannot be parsed.

Compilation flags:

`static`

Template:

`read_file(File,Rows)`

Mode and number of proofs:

`read_file(+atom,-list(list)) - zero_or_one`

Exceptions:

File is a variable:

`instantiation_error`

File is neither a variable nor an atom:

`type_error(atom,File)`

File is an atom but not an existing file:

`existence_error(file,File)`

File is an existing file but cannot be opened for reading:

`permission_error(open,source_sink,File)`

`read_stream/2`

Reads a CSV stream returning the data as a list of rows, each row a list of fields. Fails if the stream cannot be parsed.

Compilation flags:

`static`

Template:

`read_stream(Stream,Rows)`

Mode and number of proofs:

`read_stream(+stream_or_alias,-list(list)) - zero_or_one`

Exceptions:

Stream is a variable:

`instantiation_error`

Stream is neither a variable nor a stream-term or alias:

```

    domain_error(stream_or_alias,Stream)
Stream is not an open stream:
    existence_error(stream,Stream)
Stream is an output stream:
    permission_error(input,stream,Stream)
Stream is a binary stream:
    permission_error(input,binary_stream,Stream)

```

`read_file_by_line/3`

Reads a CSV file saving the data as clauses for the specified object predicate. The file is read line by line. Fails if the file cannot be parsed.

Compilation flags:
static

Template:

```
read_file_by_line(File,Object,Predicate)
```

Mode and number of proofs:

```
read_file_by_line(+atom,+object_identifier,+predicate_indicator) - zero_or_one
```

Exceptions:

File is a variable:

```
instantiation_error
```

File is neither a variable nor an atom:

```
type_error(atom,File)
```

File is an atom but not an existing file:

```
existence_error(file,File)
```

File is an existing file but cannot be opened for reading:

```
permission_error(open,source_sink,File)
```

Object is a variable:

```
instantiation_error
```

Object is neither a variable nor an object identifier:

```
type_error(object_identifier,Object)
```

Object is a valid object identifier but not an existing object:

```
existence_error(object,Object)
```

Predicate is a variable:

```
instantiation_error
```

Predicate is neither a variable nor a predicate indicator:

```
type_error(predicate_indicator,Predicate)
```

Predicate is a valid predicate indicator but not an existing public predicate:

```
existence_error(predicate,Predicate)
```

`read_stream_by_line/3`

Reads a CSV stream saving the data as clauses for the specified object predicate. The stream is read line by line. Fails if the stream cannot be parsed.

Compilation flags:

`static`

Template:

`read_stream_by_line(Stream,Object,Predicate)`

Mode and number of proofs:

`read_stream_by_line(+stream_or_alias,+object_identifier,+predicate_indicator) - zero_or_one`

Exceptions:

Stream is a variable:

`instantiation_error`

Stream is neither a variable nor a stream-term or alias:

`domain_error(stream_or_alias,Stream)`

Stream is not an open stream:

`existence_error(stream,Stream)`

Stream is an output stream:

`permission_error(input,stream,Stream)`

Stream is a binary stream:

`permission_error(input,binary_stream,Stream)`

Object is a variable:

`instantiation_error`

Object is neither a variable nor an object identifier:

`type_error(object_identifier,Object)`

Object is a valid object identifier but not an existing object:

`existence_error(object,Object)`

Predicate is a variable:

`instantiation_error`

Predicate is neither a variable nor a predicate indicator:

`type_error(predicate_indicator,Predicate)`

Predicate is a valid predicate indicator but not an existing public predicate:

`existence_error(predicate,Predicate)`

`read_file_by_line/2`

Reads a CSV file returning the data as a list of rows, each row a list of fields. The file is read line by line. Fails if the file cannot be parsed.

Compilation flags:

`static`

Template:

`read_file_by_line(File,Rows)`

Mode and number of proofs:

`read_file_by_line(+atom,-list(list)) - zero_or_one`

Exceptions:

File is a variable:

`instantiation_error`

File is neither a variable nor an atom:

`type_error(atom,File)`

File is an atom but not an existing file:

`existence_error(file,File)`

File is an existing file but cannot be opened for reading:

`permission_error(open,source_sink,File)`

`read_stream_by_line/2`

Reads a CSV stream returning the data as a list of rows, each row a list of fields. The stream is read line by line. Fails if the stream cannot be parsed.

Compilation flags:

`static`

Template:

`read_stream_by_line(Stream,Rows)`

Mode and number of proofs:

`read_stream_by_line(+stream_or_alias,-list(list)) - zero_or_one`

Exceptions:

Stream is a variable:

`instantiation_error`

Stream is neither a variable nor a stream-term or alias:

```
domain_error(stream_or_alias,Stream)
Stream is not an open stream:
existence_error(stream,Stream)
Stream is an output stream:
permission_error(input,stream,Stream)
Stream is a binary stream:
permission_error(input,binary_stream,Stream)
```

`write_file/3`

Writes a CSV file with the data represented by the solutions to the specified object predicate.

Compilation flags:

```
static
```

Template:

```
write_file(File,Object,Predicate)
```

Mode and number of proofs:

```
write_file(+atom,+object_identifier,+predicate_indicator) - one
```

Exceptions:

File is a variable:

```
instantiation_error
```

File is neither a variable nor an atom:

```
type_error(atom,File)
```

File is an atom but cannot be opened for writing:

```
permission_error(open,source_sink,File)
```

Object is a variable:

```
instantiation_error
```

Object is neither a variable nor an object identifier:

```
type_error(object_identifier,Object)
```

Object is a valid object identifier but not an existing object:

```
existence_error(object,Object)
```

Predicate is a variable:

```
instantiation_error
```

Predicate is neither a variable nor a predicate indicator:

```
type_error(predicate_indicator,Predicate)
```

Predicate is a valid predicate indicator but not an existing public predicate:

```
existence_error(predicate,Predicate)
```

`write_stream/3`

Writes a CSV stream with the data represented by the solutions to the specified object predicate.

Compilation flags:

`static`

Template:

`write_stream(Stream,Object,Predicate)`

Mode and number of proofs:

`write_stream(+stream_or_alias,+object_identifier,+predicate_indicator) - one`

Exceptions:

Stream is a variable:

`instantiation_error`

Stream is neither a variable nor a stream-term or alias:

`domain_error(stream_or_alias,Stream)`

Stream is not an open stream:

`existence_error(stream,Stream)`

Stream is an input stream:

`permission_error(output,stream,Stream)`

Stream is a binary stream:

`permission_error(output,binary_stream,Stream)`

Object is a variable:

`instantiation_error`

Object is neither a variable nor an object identifier:

`type_error(object_identifier,Object)`

Object is a valid object identifier but not an existing object:

`existence_error(object,Object)`

Predicate is a variable:

`instantiation_error`

Predicate is neither a variable nor a predicate indicator:

`type_error(predicate_indicator,Predicate)`

Predicate is a valid predicate indicator but not an existing public predicate:

`existence_error(predicate,Predicate)`

`guess_separator/2`

Guesses the separator used in a given file, asking the user to confirm.

Compilation flags:

`static`

Template:

`guess_separator(File,Separator)`

Mode and number of proofs:

`guess_separator(+atom,-atom) - one`

Exceptions:

File is a variable:

`instantiation_error`

File is neither a variable nor an atom:

`type_error(atom,File)`

File is an atom but not an existing file:

`existence_error(file,File)`

File is an atom but cannot be opened for writing:

`permission_error(open,source_sink,File)`

`guess_arity/2`

Guesses the arity of records in a given file, asking the user to confirm.

Compilation flags:

`static`

Template:

`guess_arity(File,Arity)`

Mode and number of proofs:

`guess_arity(+atom,-number) - one`

Exceptions:

File is a variable:

`instantiation_error`

File is neither a variable nor an atom:

`type_error(atom,File)`

File is an atom but not an existing file:

```
existence_error(file,File)
File is an atom but cannot be opened for writing:
permission_error(open,source_sink,File)
```

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.10 dates

object

1.10.1 date

Date predicates.

Availability:

```
logtalk_load(dates(loader))
```

Author: Paulo Moura

Version: 1:2:0

Date: 2014-09-27

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public datep
```

Uses:

```
os
```

Remarks:

(none)

Inherited public predicates:

days_in_month/3 leap_year/1 name_of_day/3 name_of_month/3 today/3 valid/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.10.2 datep

Date protocol.

Availability:

logtalk_load(dates(loader))

Author: Paulo Moura

Version: 1:1:0

Date: 2005-03-17

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - today/3
 - leap_year/1
 - name_of_day/3
 - name_of_month/3
 - days_in_month/3
 - valid/3
- Protected predicates
- Private predicates
- Operators

Public predicates

today/3

Returns current date.

Compilation flags:

static

Template:

today(Year,Month,Day)

Mode and number of proofs:

today(-integer,-integer,-integer) - one

leap_year/1

True if the argument is a leap year.

Compilation flags:

static

Template:

leap_year(Year)

Mode and number of proofs:

leap_year(+integer) - zero_or_one

name_of_day/3

Name and short name of day.

Compilation flags:

static

Template:

name_of_day(Index,Name,Short)

Mode and number of proofs:

name_of_day(?integer,?atom,?atom) - zero_or_more

name_of_month/3

Name and short name of month.

Compilation flags:

static

Template:

name_of_month(Index,Name,Short)

Mode and number of proofs:

name_of_month(?integer,?atom,?atom) - zero_or_more

days_in_month/3

Number of days in a month.

Compilation flags:

static

Template:

days_in_month(Month,Year,Days)

Mode and number of proofs:

days_in_month(?integer,+integer,?integer) - zero_or_more

valid/3

True if the arguments represent a valid date.

Compilation flags:

static

Template:

valid(Year,Month,Day)

Mode and number of proofs:

valid(@integer,@integer,@integer) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

 See also

[date](#), [timep](#)

object

1.10.3 time

Time predicates.

Availability:

`logtalk_load(dates(loader))`

Author: Paulo Moura

Version: 1:1:0

Date: 2014-09-27

Compilation flags:

`static, context_switching_calls`

Implements:

`public timep`

Uses:

`os`

Remarks:

(none)

Inherited public predicates:

`cpu_time/1 now/3 valid/3`

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates


(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

datep

protocol

1.10.4 timep

Time protocol.

Availability:

`logtalk__load(dates(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2000-07-24

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - now/3
 - cpu_time/1
 - valid/3
- Protected predicates
- Private predicates
- Operators

Public predicates

now/3

Returns current time.

Compilation flags:

static

Template:

now(Hours,Mins,Secs)

Mode and number of proofs:

now(-integer,-integer,-integer) - one

cpu_time/1

Returns the current cpu time.

Compilation flags:

static

Template:

cpu_time(Time)

Mode and number of proofs:

cpu_time(-number) - one

`valid/3`

True if the arguments represent a valid time value.

Compilation flags:

`static`

Template:

`valid(Hours,Mins,Secs)`

Mode and number of proofs:

`valid(+integer,+integer,+integer) - zero_or_one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

 See also

`time`, `datep`

1.11 dead_code_scanner

object

1.11.1 `dead_code_scanner`

A tool for detecting likely dead code in compiled Logtalk entities and Prolog modules compiled as objects.

Availability:

```
logtalk_load(dead_code_scanner(loader))
```

Author: Barry Evans and Paulo Moura

Version: 0:15:2

Date: 2024-10-21

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public options
```

Uses:

```
list
```

```
logtalk
```

```
os
```

```
type
```

Remarks:

- **Dead code:** A predicate or non-terminal that is not called (directly or indirectly) by any scoped predicate or non-terminal. These predicates and non-terminals are not used, cannot be called without breaking encapsulation, and are thus considered dead code.
- **Known issues:** Use of local meta-calls with goal arguments only known at runtime can result in false positives. Calls from non-standard meta-predicates may be missed if the meta-calls are not optimized.
- **Requirements:** Source files must be compiled with the `source_data` flag turned on. To avoid false positives due to meta-calls, compilation of source files with the `optimized` flag turned on is also advised.

Inherited public predicates:

```
check_option/1 check_options/1 default_option/1 default_options/1 option/2 option/3  
valid_option/1 valid_options/1
```

- **Public predicates**
 - `entity/1`
 - `file/2`
 - `file/1`

- directory/2
- directory/1
- rdirectory/2
- rdirectory/1
- library/2
- library/1
- rlibrary/2
- rlibrary/1
- all/1
- all/0
- predicates/2
- predicate/2
- Protected predicates
- Private predicates
- Operators

Public predicates

entity/1

Scans a loaded entity for dead code. Fails if the entity does not exist.

Compilation flags:

static

Template:

entity(Entity)

Mode and number of proofs:

entity(+entity_identifier) - zero_or_one

file/2

Scans all entities in a loaded source file for dead code using the given options. The file can be given by name, basename, full path, or using library notation. Fails if the file is not loaded.

Compilation flags:

static

Template:

file(File,Options)

Mode and number of proofs:

file(+atom,+list(compound)) - zero_or_one

file/1

Scans all entities in a loaded source file for dead code using default options. The file can be given by name, basename, full path, or using library notation. Fails if the file is not loaded.

Compilation flags:

static

Template:

file(File)

Mode and number of proofs:

file(+atom) - zero_or_one

directory/2

Scans all entities in all loaded files from a given directory for dead code using the given options.

Compilation flags:

static

Template:

directory(Directory,Options)

Mode and number of proofs:

directory(+atom,+list(compound)) - one

directory/1

Scans all entities in all loaded files from a given directory for dead code using default options.

Compilation flags:

static

Template:

directory(Directory)

Mode and number of proofs:

directory(+atom) - one

rdirectory/2

Scans all entities in all loaded files from a given directory and its sub-directories for dead code using the given options.

Compilation flags:

static

Template:

rdirectory(Directory,Options)

Mode and number of proofs:

rdirectory(+atom,+list(compound)) - one

rdirectory/1

Scans all entities in all loaded files from a given directory and its sub-directories for dead code using default options.

Compilation flags:

static

Template:

rdirectory(Directory)

Mode and number of proofs:

rdirectory(+atom) - one

library/2

Scans all entities in all loaded files from a given library for dead code using the given options.

Compilation flags:

static

Template:

library(Library,Options)

Mode and number of proofs:

library(+atom,+list(compound)) - one

library/1

Scans all entities in all loaded files from a given library for dead code using default options.

Compilation flags:

static

Template:

library(Library)

Mode and number of proofs:

library(+atom) - one

rlibrary/2

Scans all entities in all loaded files in a loaded library and its sub-libraries for dead code using the given options.

Compilation flags:

static

Template:

rlibrary(Library,Options)

Mode and number of proofs:

rlibrary(+atom,+list(compound)) - one

rlibrary/1

Scans all entities in all loaded files in a loaded library and its sub-libraries for dead code using default options.

Compilation flags:

static

Template:

rlibrary(Library)

Mode and number of proofs:

rlibrary(+atom) - one

all/1

Scans all entities for dead code using the given options.

Compilation flags:

static

Template:

all(Options)

Mode and number of proofs:

all(+list(compound)) - one

`all/0`

Scans all entities for dead code using default options.

Compilation flags:

`static`

Mode and number of proofs:

`all - one`

`predicates/2`

Returns an ordered set of local predicates (and non-terminals) that are not used, directly or indirectly, by scoped predicates for a loaded entity.

Compilation flags:

`static`

Template:

`predicates(Entity,Predicates)`

Mode and number of proofs:

`predicates(+entity__identifier,-list(predicate__indicator)) - one`

`predicate/2`

Enumerates, by backtracking, local predicates (and non-terminals) that are not used, directly or indirectly, by scoped predicates for a loaded entity.

Compilation flags:

`static`

Template:

`predicate(Entity,Predicate)`

Mode and number of proofs:

predicate(+entity_identifier,?predicate_indicator) - zero_or_more

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.11.2 dead_code_scanner_messages

Logtalk dead_code_scanner tool default message translations.

Availability:

logtalk_load(dead_code_scanner(loader))

Author: Barry Evans and Paulo Moura

Version: 0:8:0

Date: 2024-05-07

Compilation flags:

static

Provides:

logtalk::message_prefix_stream/4

logtalk::message_tokens//2

Remarks:

(none)

Inherited public predicates:

(none)

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.12 debug_messages

object

1.12.1 debug_messages

Supports selective enabling and disabling of debug and debug(Group) messages.

Availability:

```
logtalk_load(debug_messages(loader))
```

Author: Paulo Moura

Version: 1:0:1

Date: 2022-05-05

Compilation flags:

```
static, context_switching_calls
```

Provides:

logtalk::message_hook/4

Uses:

logtalk

Remarks:

- Limitations: Debug messages are suppressed by the compiler when the optimize flag is turned on and thus cannot be enabled in this case.

Inherited public predicates:

(none)

- Public predicates
 - enable/1
 - disable/1
 - enabled/1
 - enable/2
 - disable/2
 - enabled/2
- Protected predicates
- Private predicates
 - enabled_/1
 - enabled_/2
- Operators

Public predicates

enable/1

Enables all debug and debug(Group) messages for the given component.

Compilation flags:

static

Template:

enable(Component)

Mode and number of proofs:

`enable(@term)` - one

`disable/1`

Disables all debug and debug(Group) messages for the given component.

Compilation flags:

`static`

Template:

`disable(Component)`

Mode and number of proofs:

`disable(@term)` - one

`enabled/1`

Enumerates by backtracking the components with enabled debug and debug(Group) messages.

Compilation flags:

`static`

Template:

`enabled(Component)`

Mode and number of proofs:

`enabled(?term)` - zero_or_more

`enable/2`

Enables debug(Group) messages for the given component and group.

Compilation flags:

`static`

Template:

enable(Component,Group)

Mode and number of proofs:

enable(@term,@term) - one

disable/2

Disables debug(Group) messages for the given component and group.

Compilation flags:

static

Template:

disable(Component,Group)

Mode and number of proofs:

disable(@term,@term) - one

enabled/2

Enumerates by backtracking the enabled debug(Group) messages for each component.

Compilation flags:

static

Template:

enabled(Component,Group)

Mode and number of proofs:

enabled(?term,?term) - zero_or_more

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

enabled_/1

Table of components with currently enabled debug and debug(Group) messages.

Compilation flags:

dynamic

Template:

enabled_(Component)

Mode and number of proofs:

enabled_(?term) - zero_or_more

enabled_/2

Table of currently enabled debug(Group) per component.

Compilation flags:

dynamic

Template:

enabled_(Component,Group)

Mode and number of proofs:

enabled_(?term,?term) - zero_or_more

Operators

(none)

1.13 debugger

object

1.13.1 debugger

Command-line debugger based on an extended procedure box model supporting execution tracing and spy points.

Availability:

```
logtalk_load(debugger(loader))
```

Author: Paulo Moura

Version: 7:10:0

Date: 2025-03-18

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public debuggerp
```

Provides:

```
logtalk::debug_handler/1
```

```
logtalk::debug_handler/3
```

Uses:

```
logtalk
```

Remarks:

```
(none)
```

Inherited public predicates:

```
debug/0 debugging/0 debugging/1 leash/1 leashing/1 log/3 logging/3 nodebug/0 nolog/3
nologall/0 nospy/1 nospy/3 nospy/4 nospyall/0 notrace/0 reset/0 set_write_max_depth/1
spy/1 spy/3 spy/4 spying/1 spying/3 spying/4 trace/0 write_max_depth/1
```

- Public predicates
- Protected predicates
- Private predicates
 - debugging_/0

- tracing_/0
 - skipping_/0
 - skipping_unleashed_/1
 - quasi_skipping_/0
 - leaping_/1
 - breakpoint_/2
 - spying_predicate_/3
 - spying_context_/4
 - leashing_/1
 - invocation_number_/1
 - jump_to_invocation_number_/1
 - zap_to_port_/1
 - write_max_depth_/1
 - log_point_/3
 - conditional_breakpoint_/3
 - triggered_breakpoint_/4
 - triggered_breakpoint_enabled_/2
 - file_line_hit_count_/3
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

debugging_/0

True iff debug is on.

Compilation flags:

dynamic

Mode and number of proofs:

debugging_ - zero_or_one

tracing_/0

True iff tracing is on.

Compilation flags:
dynamic

Mode and number of proofs:
tracing_ - zero_or_one

skipping_/0

True iff skipping.

Compilation flags:
dynamic

Mode and number of proofs:
skipping_ - zero_or_one

skipping_unleashed_/1

True iff skipping (a goal with invocation number N) but showing intermediate ports as unleashed.

Compilation flags:
dynamic

Template:
skipping_unleashed_(N)
Mode and number of proofs:
skipping_unleashed_(?integer) - zero_or_one

`quasi_skipping_/0`

True iff quasi-skipping.

Compilation flags:
dynamic

Mode and number of proofs:
`quasi_skipping_ - zero_or_one`

`leaping_/1`

True iff leaping in tracing or debugging mode.

Compilation flags:
dynamic

Template:
leaping_(Mode)
Mode and number of proofs:
leaping_(?atom) - zero_or_one

`breakpoint_/2`

Table of unconditional breakpoints.

Compilation flags:
dynamic

Template:
breakpoint_(Entity,Line)
Mode and number of proofs:
breakpoint_(?object_identifier,?integer) - zero_or_more
breakpoint_(?category_identifier,?integer) - zero_or_more

`spying_predicate_/3`

Table of predicate spy points.

Compilation flags:
dynamic

Template:

`spying_predicate_(Functor,Arity,Original)`

Mode and number of proofs:

`spying_predicate_(?atom,?integer,?predicate_indicator) - zero_or_more`

`spying_predicate_(?atom,?integer,?non_terminal_indicator) - zero_or_more`

`spying_context_/4`

Table of context spy points.

Compilation flags:
dynamic

Template:

`spying_context_(Sender,This,Self,Goal)`

Mode and number of proofs:

`spying_context_(?object_identifier,?object_identifier,?object_identifier,?callable) - zero_or_more`

`leashing_/1`

Table of currently leashed ports.

Compilation flags:
dynamic

Template:

`leashing_(Port)`

Mode and number of proofs:

leashing_(?atom) - zero_or_more

invocation_number_/1

Current call stack invocation number.

Compilation flags:

dynamic

Template:

invocation_number_(N)

Mode and number of proofs:

invocation_number_(?integer) - zero_or_one

jump_to_invocation_number_/1

Invocation number to jump to.

Compilation flags:

dynamic

Template:

jump_to_invocation_number_(N)

Mode and number of proofs:

jump_to_invocation_number_(?integer) - zero_or_one

zap_to_port_/1

Port to zap to.

Compilation flags:

dynamic

Template:

zap_to_port_(Port)

Mode and number of proofs:

zap_to_port_(?integer) - zero_or_one

write_max_depth_/1

Current term write maximum depth.

Compilation flags:

dynamic

Template:

write_max_depth_(MaxDepth)

Mode and number of proofs:

write_max_depth_(?non_negative_integer) - zero_or_one

log_point_/3

Table of log points.

Compilation flags:

dynamic

Template:

log_point_(Entity,Line,Message)

Mode and number of proofs:

log_point_(?object_identifier,?integer,?atom) - zero_or_more

log_point_(?category_identifier,?integer,?atom) - zero_or_more

`conditional_breakpoint_/3`

Table of conditional breakpoints.

Compilation flags:

dynamic

Template:

`conditional_breakpoint_(Entity,Line,Condition)`

Mode and number of proofs:

`conditional_breakpoint_(?object_identifier,?integer,?callable) - zero_or_more`

`conditional_breakpoint_(?category_identifier,?integer,?callable) - zero_or_more`

`triggered_breakpoint_/4`

Table of defined triggered breakpoints.

Compilation flags:

dynamic

Template:

`triggered_breakpoint_(Entity,Line,TriggerEntity,TriggerLine)`

Mode and number of proofs:

`triggered_breakpoint_(?object_identifier,?integer,?object_identifier,?integer) - zero_or_more`

`triggered_breakpoint_(?object_identifier,?integer,?category_identifier,?integer) - zero_or_more`

`triggered_breakpoint_(?category_identifier,?integer,?object_identifier,?integer) - zero_or_more`

`triggered_breakpoint_(?category_identifier,?integer,?category_identifier,?integer) - zero_or_more`

`triggered_breakpoint_enabled_/2`

Table of enabled triggered breakpoints.

Compilation flags:

dynamic

Template:

`triggered_breakpoint_enabled_(Entity,Line)`

Mode and number of proofs:

triggered_breakpoint_enabled_(?object_identifier,?integer) - zero_or_more
triggered_breakpoint_enabled_(?category_identifier,?integer) - zero_or_more

file_line_hit_count_/3

Table of file and line hit counts (successful unifications with clause heads).

Compilation flags:

dynamic

Template:

file_line_hit_count_(File,Line,Count)

Mode and number of proofs:

file_line_hit_count_(?atom,?integer,?integer) - zero_or_one

Operators

(none)

category

1.13.2 debugger_messages

Logtalk debugger tool default message translations.

Availability:

logtalk_load(debugger(loader))

Author: Paulo Moura

Version: 3:7:1

Date: 2024-11-05

Compilation flags:

static

Provides:

```
logtalk::message_prefix_stream/4  
logtalk::question_prompt_stream/4  
logtalk::message_tokens//2
```

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.13.3 debuggerp

Debugger protocol.

Availability:

```
logtalk_load(debugger(loader))
```

Author: Paulo Moura

Version: 3:4:0

Date: 2025-03-18

Compilation flags:

static

Dependencies:

(none)

Remarks:

- Debugger help: Type the character h (condensed help) or the character ? (extended help) at a leashed port.
- Predicate breakpoint: Specified as a ground term Functor/Arity.
- Non-terminal breakpoint: Specified as a ground term Functor//Arity.
- Clause breakpoint: Specified as an Entity-Line term with both Entity and Line bound. Line must be the first source file line of an entity clause.
- Conditional breakpoint: Specified as an Entity-Line term with both Entity and Line bound and a condition. Line must be the first source file line of an entity clause.
- Hit count breakpoint: Specified as an Entity-Line term with both Entity and Line bound and an unification count expression as a condition. Line must be the first source file line of an entity clause.
- Triggered breakpoint: Specified as an Entity-Line term with both Entity and Line bound and another breakpoint as a condition. Line must be the first source file line of an entity clause.
- Context breakpoint: Specified as a (Sender, This, Self, Goal) tuple.
- Log point: Specified as an (Entity, Line, Message) tuple.
- Leash port shorthands: none - [], loose - [fact,rule,call], half - [fact,rule,call,redo], tight - [fact,rule,call,redo,fail,exception], and full - [fact,rule,call,exit,redo,fail,exception].

Inherited public predicates:

(none)

- Public predicates
 - reset/0
 - debug/0
 - nodebug/0
 - debugging/0
 - debugging/1
 - trace/0

- notrace/0
- leash/1
- leashing/1
- spy/1
- spying/1
- nospy/1
- spy/3
- spying/3
- nospy/3
- spy/4
- spying/4
- nospy/4
- nospyall/0
- log/3
- logging/3
- nolog/3
- nologall/0
- write_max_depth/1
- set_write_max_depth/1
- Protected predicates
- Private predicates
- Operators

Public predicates

reset/0

Resets all debugging settings (including breakpoints, log points, and leashed ports) and turns off debugging.

Compilation flags:

static

Mode and number of proofs:

reset - one

See also:

nospyall/0

`debug/0`

Starts debugging for all defined breakpoints.

Compilation flags:

`static`

Mode and number of proofs:

`debug - one`

`nodebug/0`

Stops debugging for all defined breakpoints. Also turns off tracing. Does not remove defined breakpoints.

Compilation flags:

`static`

Mode and number of proofs:

`nodebug - one`

See also:

`reset/0`

`debugging/0`

Reports current debugging settings, including breakpoints and log points.

Compilation flags:

`static`

Mode and number of proofs:

`debugging - one`

debugging/1

Enumerates, by backtracking, all entities compiled in debug mode.

Compilation flags:

static

Template:

debugging(Entity)

Mode and number of proofs:

debugging(?entity__identifier) - zero_or_more

trace/0

Starts tracing all calls compiled in debug mode.

Compilation flags:

static

Mode and number of proofs:

trace - one

notrace/0

Stops tracing of calls compiled in debug mode. Debugger will still stop at defined breakpoints.

Compilation flags:

static

Mode and number of proofs:

notrace - one

leash/1

Sets the debugger leash ports using an abbreviation (none, loose, half, tight, or full) or a list of ports (valid ports are fact, rule, call, exit, redo, fail, and exception).

Compilation flags:

static

Template:

leash(Ports)

Mode and number of proofs:

leash(+atom) - one

leash(+list(atom)) - one

leashing/1

Enumerates, by backtracking, all leashed ports (valid ports are fact, rule, call, exit, redo, fail, and exception).

Compilation flags:

static

Template:

leashing(Port)

Mode and number of proofs:

leashing(?atom) - zero_or_more

spy/1

Sets a predicate or clause breakpoint (removing any existing log point or breakpoint defined for the same location, or a list of breakpoints. Fails if a breakpoint is invalid.

Compilation flags:

static

Template:

spy(Breakpoint)

Mode and number of proofs:

```
spy(@spy__point) - zero_or_one  
spy(@list(spy__point)) - zero_or_one
```

spying/1

Enumerates, by backtracking, all defined predicate and clause breakpoints.

Compilation flags:

static

Template:

spying(Breakpoint)

Mode and number of proofs:

spying(?spy__point) - zero_or_more

nospy/1

Removes all matching predicate and clause breakpoints.

Compilation flags:

static

Template:

nospy(Breakpoint)

Mode and number of proofs:

nospy(@var) - one

nospy(@spy__point) - one

nospy(@list(spy__point)) - one

`spy/3`

Sets a conditional or triggered breakpoint (removing any existing log point or breakpoint defined for the same location). The condition can be a unification count expression, a lambda expression, or another breakpoint. Fails if the breakpoint is invalid.

Compilation flags:

`static`

Template:

`spy(Entity,Line,Condition)`

Mode and number of proofs:

`spy(+atom,+integer,@callable) - zero_or_one`

Remarks:

- Unification count expression conditions: `>(Count)`, `>=(Count)`, `==(Count)`, `=<(Count)`, `<(Count)`, `mod(M)`, and `Count`.
 - Lambda expression conditions: `[Count,N,Goal]>>Condition` and `[Goal]>>Condition` where `Count` is the unification count, `N` is the invocation number, and `Goal` is the goal that unified with the clause head; `Condition` is called in the context of user.
 - Triggered breakpoint conditions: `Entity-Line`.
-

`spying/3`

Enumerates, by backtracking, all conditional and triggered breakpoints.

Compilation flags:

`static`

Template:

`spying(Entity,Line,Condition)`

Mode and number of proofs:

`spying(?atom,?integer,?callable) - zero_or_more`

nospy/3

Removes all matching conditional and triggered breakpoints.

Compilation flags:

static

Template:

nospy(Entity,Line,Condition)

Mode and number of proofs:

nospy(@term,@term,@term) - one

spy/4

Sets a context breakpoint.

Compilation flags:

static

Template:

spy(Sender,This,Self,Goal)

Mode and number of proofs:

spy(@term,@term,@term,@term) - one

spying/4

Enumerates, by backtracking, all defined context breakpoints.

Compilation flags:

static

Template:

spying(Sender,This,Self,Goal)

Mode and number of proofs:

spying(?term,?term,?term,?term) - zero_or_more

[nospy/4](#)

Removes all matching context breakpoints.

Compilation flags:

static

Template:

`nospy(Sender, This, Self, Goal)`

Mode and number of proofs:

`nospy(@term, @term, @term, @term) - one`

[nospyall/0](#)

Removes all breakpoints and log points.

Compilation flags:

static

Mode and number of proofs:

`nospyall - one`

See also:

[reset/0](#)

[log/3](#)

Sets a log point (removing any existing breakpoint defined for the same location). Fails if the log point is invalid.

Compilation flags:

static

Template:

`log(Entity, Line, Message)`

Mode and number of proofs:

`log(@object_identifier,+integer,+atom) - zero_or_one`
`log(@category_identifier,+integer,+atom) - zero_or_one`

`logging/3`

Enumerates, by backtracking, all defined log points.

Compilation flags:

`static`

Template:

`logging(Entity,Line,Message)`

Mode and number of proofs:

`logging(?object_identifier,?integer,?atom) - zero_or_more`
`logging(?category_identifier,?integer,?atom) - zero_or_more`

`nolog/3`

Removes all matching log points.

Compilation flags:

`static`

Template:

`nolog(Entity,Line,Message)`

Mode and number of proofs:

`nolog(@var_or(object_identifier),@var_or(integer),@var_or(atom)) - one`
`nolog(@var_or(category_identifier),@var_or(integer),@var_or(atom)) - one`

`nologall/0`

Removes all log points.

Compilation flags:

`static`

Mode and number of proofs:

`nologall - one`

See also:

`reset/0`

`write_max_depth/1`

Current term write maximum depth. When not defined, the backend default is used.

Compilation flags:

`static`

Template:

`write_max_depth(MaxDepth)`

Mode and number of proofs:

`write_max_depth(?non_negative_integer) - zero_or_one`

`set_write_max_depth/1`

Sets the default term maximum write depth. For most backends, a value of zero means that the whole term is written.

Compilation flags:

`static`

Template:

`set_write_max_depth(MaxDepth)`

Mode and number of proofs:

`set_write_max_depth(+non_negative_integer) - one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

 See also

[debugger](#)

object

1.13.4 dump_trace

Simple solution for redirecting a debugger trace to a file.

Availability:

`logtalk_load(debugger(loader))`

Author: Paulo Moura

Version: 1:0:1

Date: 2021-11-12

Compilation flags:

`static, context_switching_calls`

Uses:

[debugger](#)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - `start_redirect_to_file/2`
 - `stop_redirect_to_file/0`
- Protected predicates
- Private predicates
- Operators

Public predicates

`start_redirect_to_file/2`

Starts redirecting debugger trace messages to a file.

Compilation flags:

static

Template:

`start_redirect_to_file(File,Goal)`

Meta-predicate template:

`start_redirect_to_file(*,0)`

Mode and number of proofs:

`start_redirect_to_file(+atom,+callable) - zero_or_more`

`stop_redirect_to_file/0`

Stops redirecting debugger trace messages to a file.

Compilation flags:

static

Mode and number of proofs:

`stop_redirect_to_file - one`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.14 dependents

category

1.14.1 observer

Smalltalk dependent protocol.

Availability:

logtalk_load(dependents(loader))

Author: Paulo Moura

Version: 1:0:0

Date: 2003-02-09

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - update/1
- Protected predicates
- Private predicates
- Operators

Public predicates

update/1

Called when an observed object is updated.

Compilation flags:

static

Template:

update(Change)

Mode and number of proofs:

update(?nonvar) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

➡ See also

subject

category

1.14.2 subject

Smalltalk dependent handling predicates.

Availability:

`logtalk_load(dependents(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2003-02-09

Compilation flags:

`static`

Dependencies:

`(none)`

Remarks:

`(none)`

Inherited public predicates:

`(none)`

- Public predicates
 - `changed/0`
 - `changed/1`
 - `dependents/1`
 - `addDependent/1`
 - `removeDependent/1`
- Protected predicates
- Private predicates
 - `dependent_/1`
- Operators

Public predicates

changed/0

Receiver changed in some way. Notify all dependents.

Compilation flags:
static

Mode and number of proofs:
changed - one

changed/1

Receiver changed as specified in the argument. Notify all dependents.

Compilation flags:
static

Template:
changed(Change)
Mode and number of proofs:
changed(?nonvar) - one

dependents/1

Returns a list of all dependent objects.

Compilation flags:
static

Template:
dependents(Dependents)
Mode and number of proofs:
dependents(-list) - one

`addDependent/1`

Adds a new dependent object.

Compilation flags:

`static`

Template:

`addDependent(Dependent)`

Mode and number of proofs:

`addDependent(@object) - one`

`removeDependent/1`

Removes a dependent object.

Compilation flags:

`static`

Template:

`removeDependent(Dependent)`

Mode and number of proofs:

`removeDependent(?object) - zero_or_more`

Protected predicates

(none)

Private predicates

`dependent_/1`

Table of dependent objects.

Compilation flags:

`dynamic`

Template:

`dependent__(Dependent)`

Mode and number of proofs:

`dependent__(?object) - zero_or_more`

Operators

(none)

 See also

`observer`

1.15 diagrams

object

1.15.1 d2_graph_language

Predicates for generating graph files in the DOT language (version 2.36.0 or later).

Availability:

`logtalk_load(diagrams(loader))`

Author: Paulo Moura

Version: 1:2:0

Date: 2025-02-04

Compilation flags:

`static, context_switching_calls`

Implements:

`public graph_language_protocol`

Imports:

`public options`

Provides:

`graph_language_registry::language_object/2`

Uses:

`list`

`os`

term_io
user

Remarks:

(none)

Inherited public predicates:

check_option/1 check_options/1 default_option/1 default_options/1 edge/6 file_footer/3
file_header/3 graph_footer/5 graph_header/5 node/7 option/2 option/3 output_file_name/2
valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.15.2 diagram(Format)

- Format - Graph language file format.

Common predicates for generating diagrams.

Availability:

```
logtalk_load(diagrams(loader))
```

Author: Paulo Moura

Version: 3:15:0

Date: 2024-12-04

Compilation flags:

```
static
```

Extends:

```
public options
```

Provides:

```
logtalk::message_prefix_stream/4
```

```
logtalk::message_tokens//2
```

Uses:

```
graph_language_registry
```

```
list
```

```
logtalk
```

```
modules_diagram_support
```

```
os
```

```
pairs
```

```
type
```

```
user
```

Remarks:

```
(none)
```

Inherited public predicates:

```
check_option/1 check_options/1 default_option/1 default_options/1 option/2 option/3
```

```
valid_option/1 valid_options/1
```

- Public predicates
 - libraries/3
 - libraries/2

- libraries/1
- all_libraries/1
- all_libraries/0
- rlibrary/2
- rlibrary/1
- library/2
- library/1
- directories/3
- directories/2
- rdirectory/3
- rdirectory/2
- rdirectory/1
- directory/3
- directory/2
- directory/1
- files/3
- files/2
- files/1
- all_files/1
- all_files/0
- format_object/1
- diagram_description/1
- diagram_name_suffix/1
- Protected predicates
 - diagram_caption/3
 - output_rlibrary/3
 - output_library/3
 - output_rdirectory/3
 - output externals/1
 - output_files/2
 - output_file/4
 - output_sub_diagrams/1
 - reset/0
 - output_node/6
 - node/6

- edge/5
- output_edges/1
- save_edge/5
- output_missing externals/1
- not_excluded_file/4
- output_file_path/4
- locate_library/2
- locate_directory/2
- locate_file/5
- ground_entity_identifier/3
- filter_file_extension/3
- filter_external_file_extension/3
- add_link_options/3
- supported_editor_url_scheme_prefix/1
- omit_path_prefix/3
- add_node_zoom_option/4
- message_diagram_description/1
- Private predicates
 - node_/6
 - node_path_/2
 - edge_/5
- Operators

Public predicates

libraries/3

Creates a diagram for a set of libraries using the specified options. The Project argument is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

libraries(Project,Libraries,Options)

Mode and number of proofs:

libraries(+atom,+list(atom),+list(compound)) - one

libraries/2

Creates a diagram for a set of libraries using the default options. The Project argument is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

libraries(Project,Libraries)

Mode and number of proofs:

libraries(+atom,+list(atom)) - one

libraries/1

Creates a diagram for a set of libraries using the default options. The prefix libraries is used for the diagram file name.

Compilation flags:

static

Template:

libraries(Libraries)

Mode and number of proofs:

libraries(+list(atom)) - one

all_libraries/1

Creates a diagram for all loaded libraries using the specified options.

Compilation flags:

static

Template:

`all_libraries(Options)`

Mode and number of proofs:

`all_libraries(+list(compound)) - one`

`all_libraries/0`

Creates a diagram for all loaded libraries using default options.

Compilation flags:

`static`

Mode and number of proofs:

`all_libraries - one`

`rlibrary/2`

Creates a diagram for a library and its sub-libraries using the specified options.

Compilation flags:

`static`

Template:

`rlibrary(Library,Options)`

Mode and number of proofs:

`rlibrary(+atom,+list(compound)) - one`

`rlibrary/1`

Creates a diagram for a library and its sub-libraries using default options.

Compilation flags:

`static`

Template:

```
rlibrary(Library)
```

Mode and number of proofs:

```
rlibrary(+atom) - one
```

library/2

Creates a diagram for a library using the specified options.

Compilation flags:

```
static
```

Template:

```
library(Library,Options)
```

Mode and number of proofs:

```
library(+atom,+list(compound)) - one
```

library/1

Creates a diagram for a library using default options.

Compilation flags:

```
static
```

Template:

```
library(Library)
```

Mode and number of proofs:

```
library(+atom) - one
```

directories/3

Creates a diagram for a set of directories using the specified options. The Project argument is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

directories(Project,Directories,Options)

Mode and number of proofs:

directories(+atom,+list(atom),+list(compound)) - one

directories/2

Creates a diagram for a set of directories using the default options. The Project argument is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

directories(Project,Directories)

Mode and number of proofs:

directories(+atom,+list(atom)) - one

rdirectory/3

Creates a diagram for a directory and its sub-directories using the specified options. The Project argument is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

rdirectory(Project,Directory,Options)

Mode and number of proofs:

`rdirectory(+atom,+atom,+list(compound)) - one`

`rdirectory/2`

Creates a diagram for a directory and its sub-directories using default options. The Project argument is used as a prefix for the diagram file name.

Compilation flags:

`static`

Template:

`rdirectory(Project,Directory)`

Mode and number of proofs:

`rdirectory(+atom,+atom) - one`

`rdirectory/1`

Creates a diagram for a directory and its sub-directories using default options. The name of the directory is used as a prefix for the diagram file name.

Compilation flags:

`static`

Template:

`rdirectory(Directory)`

Mode and number of proofs:

`rdirectory(+atom) - one`

directory/3

Creates a diagram for a directory using the specified options. The Project argument is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

directory(Project,Directory,Options)

Mode and number of proofs:

directory(+atom,+atom,+list(compound)) - one

directory/2

Creates a diagram for a directory using default options. The Project argument is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

directory(Project,Directory)

Mode and number of proofs:

directory(+atom,+atom) - one

directory/1

Creates a diagram for a directory using default options. The name of the directory is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

directory(Directory)

Mode and number of proofs:

directory(+atom) - one

files/3

Creates a diagram for a set of files using the specified options. The file can be specified by name, basename, full path, or using library notation. The Project argument is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

files(Project,Files,Options)

Mode and number of proofs:

files(+atom,+list(atom),+list(compound)) - one

files/2

Creates a diagram for a set of files using the default options. The file can be specified by name, basename, full path, or using library notation. The Project argument is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

files(Project,Files)

Mode and number of proofs:

files(+atom,+list(atom)) - one

`files/1`

Creates a diagram for a set of files using the default options. The file can be specified by name, basename, full path, or using library notation. The prefix `files` is used for the diagram file name.

Compilation flags:

`static`

Template:

`files(Files)`

Mode and number of proofs:

`files(+list(atom)) - one`

`all_files/1`

Creates a diagram for all loaded files using the specified options.

Compilation flags:

`static`

Template:

`all_files(Options)`

Mode and number of proofs:

`all_files(+list(compound)) - one`

`all_files/0`

Creates a diagram for all loaded files using default options.

Compilation flags:

`static`

Mode and number of proofs:

`all_files - one`

`format_object/1`

Returns the identifier of the object implementing the graph language currently being used. Fails if none is specified.

Compilation flags:

`static`

Template:

`format_object(Object)`

Mode and number of proofs:

`format_object(-object_identifier) - zero_or_one`

`diagram_description/1`

Returns the diagram description.

Compilation flags:

`static`

Template:

`diagram_description(Description)`

Mode and number of proofs:

`diagram_description(-atom) - one`

`diagram_name_suffix/1`

Returns the diagram name suffix.

Compilation flags:

`static`

Template:

`diagram_name_suffix(Suffix)`

Mode and number of proofs:

`diagram_name_suffix(-atom) - one`

Protected predicates

`diagram_caption/3`

Creates a diagram caption from the diagram description and the subject and its kind.

Compilation flags:

`static`

Template:

`diagram_caption(Kind,Subject,Description)`

Mode and number of proofs:

`diagram_caption(+atom,+callable,-atom) - one`

`output_rlibrary/3`

Generates diagram output for a library and its sub-libraries using the specified options.

Compilation flags:

`static`

Template:

`output_rlibrary(Library,Path,Options)`

Mode and number of proofs:

`output_rlibrary(+atom,+atom,+list(compound)) - one`

`output_library/3`

Generates diagram output for a library using the specified options.

Compilation flags:

`static`

Template:

`output_library(Library,Path,Options)`

Mode and number of proofs:

`output_library(+atom,+atom,+list(compound)) - one`

`output_rdirectory/3`

Generates diagram output for a directory and its sub-directories using the specified options.

Compilation flags:

`static`

Template:

`output_rdirectory(Project,Path,Options)`

Mode and number of proofs:

`output_rdirectory(+atom,+atom,+list(compound)) - one`

`output externals/1`

Output external nodes using the specified options depending on the value of the boolean option `externals/1`.

Compilation flags:

`static`

Template:

`output_externals(Options)`

Mode and number of proofs:

`output_externals(+list(compound)) - one`

`output_files/2`

Generates diagram output for a list of files using the specified options.

Compilation flags:

`static`

Template:

`output_files(Files,Options)`

Mode and number of proofs:

`output_files(+list,+list(compound)) - one`

`output_file/4`

Generates diagram output for a file using the specified options.

Compilation flags:

`static`

Template:

`output_file(Path,Basename,Directory,Options)`

Mode and number of proofs:

`output_file(+atom,+atom,+atom,+list(compound)) - one`

`output_sub_diagrams/1`

Outputs sub-diagrams using the specified options.

Compilation flags:

`static`

Template:

`output_sub_diagrams(Options)`

Mode and number of proofs:

`output_sub_diagrams(+list(compound)) - one`

`reset/0`

Resets all temporary information used when generating a diagram.

Compilation flags:

`static`

Mode and number of proofs:

`reset - one`

`output_node/6`

Outputs a graph node.

Compilation flags:

`static`

Template:

`output_node(Identifier,Label,Caption,Contents,Kind,Options)`

Mode and number of proofs:

`output_node(+nonvar,+nonvar,+nonvar,+list(nonvar),+atom,+list(compound)) - one`

`node/6`

Enumerates, by backtracking, all saved nodes.

Compilation flags:

`static`

Template:

`node(Identifier,Label,Caption,Contents,Kind,Options)`

Mode and number of proofs:

`node(?nonvar,?nonvar,?nonvar,?list(compound),?atom,?list(compound)) - zero_or_more`

edge/5

Enumerates, by backtracking, all saved edges.

Compilation flags:

static

Template:

edge(From,To,Labels,Kind,Options)

Mode and number of proofs:

edge(?nonvar,?nonvar,?list(nonvar),?atom,?list(compound)) - zero_or_more

output_edges/1

Outputs all edges.

Compilation flags:

static

Template:

output_edges(Options)

Mode and number of proofs:

output_edges(+list(compound)) - one

save_edge/5

Saves a graph edge.

Compilation flags:

static

Template:

save_edge(From,To,Labels,Kind,Options)

Mode and number of proofs:

save_edge(+nonvar,+nonvar,+list(nonvar),+atom,+list(compound)) - one

`output_missing externals/1`

Outputs missing external nodes (usually due to unloaded resources) that are referenced from edges.

Compilation flags:

`static`

Template:

`output_missing externals(Options)`

Mode and number of proofs:

`output_missing externals(+list(compound)) - one`

`not_excluded_file/4`

True when the given file is not excluded from the generated output. Excluded files may be specified by full path or by basename and with or without extension. Excluded directories may be listed by full or relative path.

Compilation flags:

`static`

Template:

`not_excluded_file(Path,Basename,ExcludedDirectories,ExcludedFiles)`

Mode and number of proofs:

`not_excluded_file(+atom,+atom,+list(atom),+list(atom)) - zero_or_one`

`output_file_path/4`

Returns the output file path.

Compilation flags:

`static`

Template:

`output_file_path(Name,Options,Format,Path)`

Mode and number of proofs:

`output_file_path(+atom,+list(atom),+object_identifier,-atom) - one`

`locate_library/2`

Locates a library given its name.

Compilation flags:

`static`

Template:

`locate_library(Library,Path)`

Mode and number of proofs:

`locate_library(+atom,-atom) - one`

`locate_directory/2`

Locates a directory given its name or full path.

Compilation flags:

`static`

Template:

`locate_directory(Directory,Path)`

Mode and number of proofs:

`locate_directory(+atom,-atom) - one`

`locate_file/5`

Locates a file given its name, basename, full path, or library notation representation.

Compilation flags:

`static`

Template:

`locate_file(File,Basename,Extension,Directory,Path)`

Mode and number of proofs:

`locate_file(+atom,+atom,+atom,+atom,-atom) - one`

`ground_entity_identifier/3`

Converts an entity identifier to a ground term.

Compilation flags:

`static`

Template:

`ground_entity_identifier(Kind,Identifier,GroundIdentifier)`

Mode and number of proofs:

`ground_entity_identifier(+atom,+callable,-callable) - one`

`filter_file_extension/3`

Filters the file name extension depending on the `file_extensions/1` option.

Compilation flags:

`static`

Template:

`filter_file_extension(Basename,Options,Name)`

Mode and number of proofs:

`filter_file_extension(+atom,+list(compound),-atom) - one`

`filter_external_file_extension/3`

Filters the external file name extension depending on the `file_extensions/1` option.

Compilation flags:

`static`

Template:

`filter_external_file_extension(Path,Options,Name)`

Mode and number of proofs:

`filter_external_file_extension(+atom,+list(compound),-atom) - one`

`add_link_options/3`

Adds url/1, urls/2, and tooltip/1 link options (for use by the graph language) based on the specified path to the list of options.

Compilation flags:

`static`

Template:

`add_link_options(Path,Options,LinkingOptions)`

Mode and number of proofs:

`add_link_options(+atom,+list(compound),-list(compound)) - one`

`supported_editor_url_scheme_prefix/1`

Table of prefixes for text editors that supports a URL scheme to open diagram links.

Compilation flags:

`static`

Template:

`supported_editor_url_scheme_prefix(Prefix)`

Mode and number of proofs:

`supported_editor_url_scheme_prefix(?atom) - zero_or_more`

`omit_path_prefix/3`

Removes a prefix from a path, returning the relative path, when using the option `omit_path_prefixes/1`.
Used mainly for constructing directory and file node identifiers and captions.

Compilation flags:

`static`

Template:

`omit_path_prefix(Path,Options,Relative)`

Mode and number of proofs:

`omit_path_prefix(+atom,+list(compound),-atom) - one`

`add_node_zoom_option/4`

Adds node zoom options when using the zoom option.

Compilation flags:

`static`

Template:

`add_node_zoom_option(Identifier,Suffix,Options,NodeOptions)`

Mode and number of proofs:

`add_node_zoom_option(+atom,+atom,+list(compound),-list(compound)) - one`

`message_diagram_description/1`

Diagram description for progress messages.

Compilation flags:

`static`

Template:

`message_diagram_description(Description)`

Mode and number of proofs:

`message_diagram_description(?atom) - one`

Private predicates

`node_/6`

Table of saved nodes.

Compilation flags:
dynamic

Template:
node_(Identifier,Label,Caption,Contents,Kind,Options)

Mode and number of proofs:
node_(?nonvar,?nonvar,?nonvar,?list(compound),?atom,?list(compound)) - zero_or_more

`node_path_/2`

Table of node paths.

Compilation flags:
dynamic

Template:
node_path_(Node,Path)

Mode and number of proofs:
node_path_(?ground,?list(ground)) - zero_or_more

`edge_/5`

Table of saved edges.

Compilation flags:
dynamic

Template:

edge_(From,To,Labels,Kind,Options)
Mode and number of proofs:
edge_(?nonvar,?nonvar,?list(nonvar),?atom,?list(compound)) - zero_or_more

Operators

(none)
object

1.15.3 diagrams

Predicates for generating all supported diagrams for libraries, directories, and files in one step using the DOT format.

Availability:
logtalk_load(diagrams(loader))

Author: Paulo Moura
Version: 2:1:0
Date: 2019-04-07

Compilation flags:
static, context_switching_calls

Extends:
public diagrams(dot)

Remarks:
(none)

Inherited public predicates:
all_files/0 all_files/1 all_libraries/0 all_libraries/1 directories/2 directories/3 directory/1
directory/2 directory/3 files/1 files/2 files/3 libraries/1 libraries/2 libraries/3 library/1
library/2 rdirectory/1 rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2

- Public predicates
- Protected predicates

- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.15.4 diagrams(Format)

- Format - Graph language file format.

Predicates for generating all supported diagrams for libraries, directories, or files in one step using the specified format.

Availability:

```
logtalk_load(diagrams(loader))
```

Author: Paulo Moura

Version: 2:8:0

Date: 2019-06-13

Compilation flags:

```
static, context_switching_calls
```

Uses:

```
list
```

```
os
```

Remarks:

- Common options: `title/1`, `date/1`, `output_directory/1`, `relation_labels/1`, `node_type_captions/1`, `exclude_files/1`, `exclude_libraries/1`, `url_prefixes/1`, `omit_path_prefix/1`, `entity_url_suffix_target/2`, and `layout/1`.
- Limitations: Some of the provided predicates only make sense for some types of diagrams. Also, fine tuning may require generating individual diagrams directly instead of as a batch using this utility object.

Inherited public predicates:

(none)

- Public predicates
 - `libraries/3`
 - `libraries/2`
 - `libraries/1`
 - `all_libraries/1`
 - `all_libraries/0`
 - `rlibrary/2`
 - `rlibrary/1`
 - `library/2`
 - `library/1`
 - `directories/3`
 - `directories/2`
 - `rdirectory/3`
 - `rdirectory/2`
 - `rdirectory/1`
 - `directory/3`
 - `directory/2`
 - `directory/1`
 - `files/3`
 - `files/2`
 - `files/1`
 - `all_files/1`
 - `all_files/0`
- Protected predicates

- Private predicates
- Operators

Public predicates

`libraries/3`

Creates all supported diagrams for a set of libraries using the specified options. The Project argument is used as a prefix for the diagram file names.

Compilation flags:

`static`

Template:

`libraries(Project,Libraries,Options)`

Mode and number of proofs:

`libraries(+atom,+list(atom),+list(compound)) - one`

`libraries/2`

Creates all supported diagrams for a set of libraries using the default options. The Project argument is used as a prefix for the diagram file names.

Compilation flags:

`static`

Template:

`libraries(Project,Libraries)`

Mode and number of proofs:

`libraries(+atom,+list(atom)) - one`

libraries/1

Creates all supported diagrams for a set of libraries using the default options. The prefix libraries is used for the diagram file names.

Compilation flags:

static

Template:

libraries(Libraries)

Mode and number of proofs:

libraries(+list(atom)) - one

all_libraries/1

Creates all supported diagrams for all loaded libraries using the specified options.

Compilation flags:

static

Template:

all_libraries(Options)

Mode and number of proofs:

all_libraries(+list(compound)) - one

all_libraries/0

Creates all supported diagrams for all loaded libraries using default options.

Compilation flags:

static

Mode and number of proofs:

all_libraries - one

rlibrary/2

Creates all supported diagrams for a library and its sub-libraries using the specified options.

Compilation flags:

static

Template:

rlibrary(Library,Options)

Mode and number of proofs:

rlibrary(+atom,+list(compound)) - one

rlibrary/1

Creates all supported diagrams for a library and its sub-libraries using default options.

Compilation flags:

static

Template:

rlibrary(Library)

Mode and number of proofs:

rlibrary(+atom) - one

library/2

Creates all supported diagrams for a library using the specified options.

Compilation flags:

static

Template:

library(Library,Options)

Mode and number of proofs:

library(+atom,+list(compound)) - one

library/1

Creates all supported diagrams for a library using default options.

Compilation flags:

static

Template:

library(Library)

Mode and number of proofs:

library(+atom) - one

directories/3

Creates all supported diagrams for a set of directories using the specified options. The Project argument is used as a prefix for the diagram file names.

Compilation flags:

static

Template:

directories(Project,Directories,Options)

Mode and number of proofs:

directories(+atom,+list(atom),+list(compound)) - one

directories/2

Creates all supported diagrams for a directory using default options. The Project argument is used as a prefix for the diagram file names.

Compilation flags:

static

Template:

directories(Project,Directories)

Mode and number of proofs:

directories(+atom,+list(atom)) - one

rdirectory/3

Creates all supported diagrams for a directory and its sub-directories using the specified options. The Project argument is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

rdirectory(Project,Directory,Options)

Mode and number of proofs:

rdirectory(+atom,+atom,+list(compound)) - one

rdirectory/2

Creates all supported diagrams for a directory and its sub-directories using default options. The Project argument is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

rdirectory(Project,Directory)

Mode and number of proofs:

rdirectory(+atom,+atom) - one

rdirectory/1

Creates all supported diagrams for a directory and its sub-directories using default options. The name of the directory is used as a prefix for the diagram file name.

Compilation flags:

static

Template:

`rdirectory(Directory)`

Mode and number of proofs:

`rdirectory(+atom) - one`

`directory/3`

Creates all supported diagrams for a directory using the specified options. The Project argument is used as a prefix for the diagram file names.

Compilation flags:

`static`

Template:

`directory(Project,Directory,Options)`

Mode and number of proofs:

`directory(+atom,+atom,+list(compound)) - one`

`directory/2`

Creates all supported diagrams for a directory using default options. The Project argument is used as a prefix for the diagram file names.

Compilation flags:

`static`

Template:

`directory(Project,Directory)`

Mode and number of proofs:

`directory(+atom,+atom) - one`

directory/1

Creates all supported diagrams for a directory using default options. The name of the directory is used as a prefix for the diagram file names.

Compilation flags:

static

Template:

directory(Directory)

Mode and number of proofs:

directory(+atom) - one

files/3

Creates all supported diagrams for a set of files using the specified options. The file can be specified by name, basename, full path, or using library notation. The Project argument is used as a prefix for the diagram file names.

Compilation flags:

static

Template:

files(Project,Files,Options)

Mode and number of proofs:

files(+atom,+list(atom),+list(compound)) - one

files/2

Creates all supported diagrams for a set of files using the default options. The file can be specified by name, basename, full path, or using library notation. The Project argument is used as a prefix for the diagram file names.

Compilation flags:

static

Template:

`files(Project,Files)`

Mode and number of proofs:

`files(+atom,+list(atom)) - one`

`files/1`

Creates all supported diagrams for a set of files using the default options. The file can be specified by name, basename, full path, or using library notation. The prefix “files” is used for the diagram file names.

Compilation flags:

`static`

Template:

`files(Files)`

Mode and number of proofs:

`files(+list(atom)) - one`

`all_files/1`

Creates all supported diagrams for all loaded files using the specified options.

Compilation flags:

`static`

Template:

`all_files(Options)`

Mode and number of proofs:

`all_files(+list(compound)) - one`

`all_files/0`

Creates all supported diagrams for all loaded files using default options.

Compilation flags:

`static`

Mode and number of proofs:

`all_files - one`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.15.5 `directory__dependency__diagram`

Predicates for generating directory dependency diagrams in DOT format.

Availability:

`logtalk_load(diagrams(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2019-04-07

Compilation flags:

`static, context__switching__calls`

Extends:

public `directory__dependency__diagram(dot)`

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

directory_load_diagram, file_load_diagram

object

1.15.6 directory_dependency_diagram(Format)

- Format - Graph language file format.

Predicates for generating directory dependency diagrams. A dependency exists when an entity in one directory makes a reference to an entity in another directory.

Availability:

```
logtalk_load(diagrams(loader))
```

Author: Paulo Moura

Version: 3:0:1

Date: 2024-04-01

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public directory_diagram(Format)
```

Uses:

```
file_dependency_diagram(Format)
```

```
list
```

```
logtalk
```

```
modules_diagram_support
```

Remarks:

```
(none)
```

Inherited public predicates:

```
all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1
```

- Public predicates
- Protected predicates
- Private predicates
 - sub_diagram_/2
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

`sub_diagram_/2`

Table of directory sub-diagrams to support their generation.

Compilation flags:

`dynamic`

Template:


`sub_diagram__(Project,Directory)`

Mode and number of proofs:

`sub_diagram__(?atom,?atom) - zero_or_more`

Operators

(none)

 See also

`directory_load_diagram(Format)`, `file_load_diagram(Format)`, `library_load_diagram(Format)`

`category`

1.15.7 `directory_diagram(Format)`

- `Format` - Graph language file format.

Common predicates for generating directory diagrams.

Availability:

`logtalk_load(diagrams(loader))`

Author: Paulo Moura

Version: 1:13:0
Date: 2024-12-04

Compilation flags:
static

Extends:
public diagram(Format)

Uses:
list

Remarks:
(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
 - remember_included_directory/1
 - remember_referenced_logtalk_directory/1
 - remember_referenced_prolog_directory/1
- Private predicates
 - included_directory_/1
 - referenced_logtalk_directory_/1
 - referenced_prolog_directory_/1
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

`remember_included_directory/1`

Remember included Logtalk directory in the diagram.

Compilation flags:

`static`

Template:

`remember_included_directory(Path)`

Mode and number of proofs:

`remember_included_directory(+atom) - one`

`remember_referenced_logtalk_directory/1`

Remember referenced Logtalk directory in the diagram.

Compilation flags:

`static`

Template:

`remember_referenced_logtalk_directory(Path)`

Mode and number of proofs:

`remember_referenced_logtalk_directory(+atom) - one`

`remember_referenced_prolog_directory/1`

Remember referenced Prolog directory in the diagram.

Compilation flags:

`static`

Template:

remember_referenced_prolog_directory(Path)

Mode and number of proofs:

remember_referenced_prolog_directory(+atom) - one

Private predicates

included_directory_/1

Table of Logtalk directories already included in the diagram.

Compilation flags:

dynamic

Template:

included_directory_(Path)

Mode and number of proofs:

included_directory_(?atom) - zero_or_more

referenced_logtalk_directory_/1

Table of referenced Logtalk directories in the diagram.

Compilation flags:

dynamic

Template:

referenced_logtalk_directory_(Path)

Mode and number of proofs:

referenced_logtalk_directory_(?atom) - zero_or_more

referenced_prolog_directory_/1

Table of referenced Prolog directories in the diagram.

Compilation flags:

dynamic

Template:

referenced_prolog_directory_(Path)

Mode and number of proofs:

referenced_prolog_directory_(?atom) - zero_or_more

Operators

(none)

object

1.15.8 directory_load_diagram

Predicates for generating directory loading dependency diagrams in DOT format.

Availability:

logtalk_load(diagrams(loader))

Author: Paulo Moura

Version: 1:0:0

Date: 2019-04-07

Compilation flags:

static, context_switching_calls

Extends:

public directory_load_diagram(dot)

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
 default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
 directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
 libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
 rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

➡ See also

directory_dependency_diagram, file_dependency_diagram

object

1.15.9 directory_load_diagram(Format)

- Format - Graph language file format.

Predicates for generating directory loading dependency diagrams.

Availability:

logtalk_load(diagrams(loader))

Author: Paulo Moura

Version: 3:0:1

Date: 2024-04-01

Compilation flags:

static, context_switching_calls

Imports:

public directory_diagram(Format)

Uses:

file_dependency_diagram(Format)

file_load_diagram(Format)

list

logtalk

modules_diagram_support

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
 - sub_diagram_/2
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

sub_diagram_/2

Table of directory sub-diagrams to support their generation.

Compilation flags:
dynamic

Template:
sub_diagram_(Project,Directory)
Mode and number of proofs:
sub_diagram_(?atom,?atom) - zero_or_more

Operators

(none)

➡ See also

| | | |
|---|----------------------------------|-----|
| directory_dependency_diagram(Format), brary_dependency_diagram(Format) | file_dependency_diagram(Format), | li- |
|---|----------------------------------|-----|

object

1.15.10 dot_graph_language

Predicates for generating graph files in the DOT language (version 2.36.0 or later).

Availability:
logtalk_load(diagrams(loader))

Author: Paulo Moura
Version: 3:11:0
Date: 2024-12-07

Compilation flags:

static, context_switching_calls

Implements:

public graph_language_protocol

Imports:

public options

Provides:

graph_language_registry::language_object/2

Uses:

list

os

term_io

user

Remarks:

(none)

Inherited public predicates:

check_option/1 check_options/1 default_option/1 default_options/1 edge/6 file_footer/3
file_header/3 graph_footer/5 graph_header/5 node/7 option/2 option/3 output_file_name/2
valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.15.11 entity__diagram

Predicates for generating entity diagrams in DOT format with both inheritance and cross-referencing relation edges.

Availability:

```
logtalk__load(diagrams(loader))
```

Author: Paulo Moura

Version: 2:0:0

Date: 2014-01-01

Compilation flags:

```
static, context__switching__calls
```

Extends:

```
public entity__diagram(dot)
```

Remarks:

(none)

Inherited public predicates:

```
all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 file/1 file/2 files/1 files/2 files/3
format_object/1 libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3
rdirectory/1 rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1
```

- Public predicates
- Protected predicates
- Private predicates

- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

[inheritance_diagram](#), [uses_diagram](#), [xref_diagram](#)

object

1.15.12 `entity_diagram`(Format)

- Format - Graph language file format.

Predicates for generating entity diagrams in the specified format with both inheritance and cross-referencing relation edges.

Availability:

`logtalk_load(diagrams(loader))`

Author: Paulo Moura

Version: 2:60:0

Date: 2024-12-04

Compilation flags:

`static`, `context_switching_calls`

Imports:

`public diagram(Format)`

Uses:

```
list
logtalk
modules_diagram_support
user
```

Remarks:

(none)

Inherited public predicates:

```
all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1
```

- Public predicates
 - file/2
 - file/1
- Protected predicates
- Private predicates
 - included_entity_/1
 - included_module_/1
 - referenced_entity_/2
 - referenced_module_/2
- Operators

Public predicates

file/2

Creates a diagram for all entities in a loaded source file using the specified options. The file can be specified by name, basename, full path, or using library notation.

Compilation flags:

static

Template:

file(File,Options)

Mode and number of proofs:

file(+atom,+list(compound)) - one

file/1

Creates a diagram for all entities in a loaded source file using default options. The file can be specified by name, basename, full path, or using library notation.

Compilation flags:

static

Template:

file(File)

Mode and number of proofs:

file(+atom) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

included_entity_/1

Table of Logtalk entities already included in the diagram.

Compilation flags:

dynamic

Template:

included_entity_(Entity)

Mode and number of proofs:

included_entity_(?entity_identifier) - zero_or_more

included__module__/1

Table of Prolog modules already included in the diagram.

Compilation flags:

dynamic

Template:

included__module__(Module)

Mode and number of proofs:

included__module__(?module__identifier) - zero_or_more

referenced__entity__/2

Table of referenced Logtalk entities in the diagram.

Compilation flags:

dynamic

Template:

referenced__entity__(Referencer,Entity)

Mode and number of proofs:

referenced__entity__(?entity__identifier,?entity__identifier) - zero_or_more

referenced__module__/2

Table of referenced Logtalk entities in the diagram.

Compilation flags:

dynamic

Template:

referenced__module__(Referencer,Entity)

Mode and number of proofs:

referenced__module__(?entity__identifier,?module__identifier) - zero_or_more

Operators

(none)

See also

| | | | |
|---|------------------------------------|------------------------------------|------------------|
| <code>inheritance_diagram(Format),</code> | <code>uses_diagram(Format),</code> | <code>xref_diagram(Format),</code> | <code>li-</code> |
| <code>brary_diagram(Format)</code> | | | |

object

1.15.13 `file_dependency_diagram`

Predicates for generating file contents dependency diagrams in DOT format. A dependency exists when an entity in one file makes a reference to an entity in another file.

Availability:

`logtalk_load(diagrams(loader))`

Author: Paulo Moura

Version: 2:1:0

Date: 2019-06-13

Compilation flags:

`static, context_switching_calls`

Extends:

`public file_dependency_diagram(dot)`

Remarks:

(none)

Inherited public predicates:

`all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1`
`default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2`
`directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1`
`libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1`
`rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1`

- Public predicates
- Protected predicates

- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

➡ See also

`file_load_diagram`, `directory_load_diagram`, `library_load_diagram`

object

1.15.14 `file_dependency_diagram`(Format)

- Format - Graph language file format.

Predicates for generating file contents dependency diagrams. A dependency exists when an entity in one file makes a reference to an entity in another file.

Availability:

```
logtalk_load(diagrams(loader))
```

Author: Paulo Moura

Version: 2:28:3

Date: 2024-04-01

Compilation flags:

```
static, context_switching_calls
```

Imports:

public file_diagram(Format)

Uses:

entity_diagram(Format)
list
logtalk
modules_diagram_support
os

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
 - sub_diagram_/1
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

`sub_diagram_/1`

Table of file sub-diagrams to support their generation.

Compilation flags:

`dynamic`

Template:

`sub_diagram_(File)`

Mode and number of proofs:

`sub_diagram_(?atom) - zero_or_more`

Operators

(none)

 See also

`file_load_diagram(Format)`, `directory_load_diagram(Format)`, `library_load_diagram(Format)`

category

1.15.15 `file_diagram(Format)`

- `Format` - Graph language file format.

Common predicates for generating file diagrams.

Availability:

`logtalk_load(diagrams(loader))`

Author: Paulo Moura

Version: 2:14:0

Date: 2024-12-04

Compilation flags:

static

Extends:

public diagram(Format)

Uses:

list

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
 - remember_included_file/1
 - remember_referenced_logtalk_file/1
 - remember_referenced_prolog_file/1
- Private predicates
 - included_file_/1
 - referenced_logtalk_file_/1
 - referenced_prolog_file_/1
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

`remember_included_file/1`

Remember included Logtalk file in the diagram.

Compilation flags:

`static`

Template:

`remember_included_file(Path)`

Mode and number of proofs:

`remember_included_file(+atom) - one`

`remember_referenced_logtalk_file/1`

Remember referenced Logtalk file in the diagram.

Compilation flags:

`static`

Template:

`remember_referenced_logtalk_file(Path)`

Mode and number of proofs:

`remember_referenced_logtalk_file(+atom) - one`

`remember_referenced_prolog_file/1`

Remember referenced Prolog file in the diagram.

Compilation flags:

`static`

Template:

remember_referenced_prolog_file(Path)

Mode and number of proofs:

remember_referenced_prolog_file(+atom) - one

Private predicates

included_file_/1

Table of Logtalk files already included in the diagram.

Compilation flags:

dynamic

Template:

included_file_(Path)

Mode and number of proofs:

included_file_(?atom) - zero_or_more

referenced_logtalk_file_/1

Table of referenced Logtalk files in the diagram.

Compilation flags:

dynamic

Template:

referenced_logtalk_file_(Path)

Mode and number of proofs:

referenced_logtalk_file_(?atom) - zero_or_more

referenced_prolog_file_/1

Table of referenced Prolog files in the diagram.

Compilation flags:

dynamic

Template:

referenced_prolog_file_(Path)

Mode and number of proofs:

referenced_prolog_file_(?atom) - zero_or_more

Operators

(none)

object

1.15.16 file_load_diagram

Predicates for generating file loading dependency diagrams in DOT format. A dependency exists when a file loads or includes another file.

Availability:

logtalk_load(diagrams(loader))

Author: Paulo Moura

Version: 2:1:0

Date: 2019-06-13

Compilation flags:

static, context_switching_calls

Extends:

public file_load_diagram(dot)

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

file_dependency_diagram, directory_dependency_diagram, library_dependency_diagram

object

1.15.17 file_load_diagram(Format)

- Format - Graph language file format.

Predicates for generating file loading dependency diagrams. A dependency exists when a file loads or includes another file.

Availability:

logtalk_load(diagrams(loader))

Author: Paulo Moura

Version: 2:30:3

Date: 2024-12-05

Compilation flags:

static, context_switching_calls

Imports:

public file_diagram(Format)

Uses:

entity_diagram(Format)

list

logtalk

modules_diagram_support

os

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
 - sub_diagram_/1
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

`sub_diagram_/1`

Table of file sub-diagrams to support their generation.

Compilation flags:

`dynamic`

Template:

`sub_diagram_(File)`

Mode and number of proofs:

`sub_diagram_(?atom) - zero_or_more`

Operators

(none)

 See also

`file_dependency_diagram(Format),`
`brary_dependency_diagram(Format)`

`directory_dependency_diagram(Format),`

`li-`

protocol

1.15.18 `graph_language_protocol`

Predicates for generating graph files.

Availability:

`logtalk_load(diagrams(loader))`

Author: Paulo Moura

Version: 2:0:0

Date: 2014-12-30

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - output_file_name/2
 - file_header/3
 - file_footer/3
 - graph_header/5
 - graph_footer/5
 - node/7
 - edge/6
- Protected predicates
- Private predicates
- Operators

Public predicates

output_file_name/2

Constructs the diagram file basename by adding a graph language dependent extension to the given name.

Compilation flags:

static

Template:

output_file_name(Name,Basename)

Mode and number of proofs:

output_file_name(+atom,-atom) - one

`file_header/3`

Writes the output file header using the specified options.

Compilation flags:

`static`

Template:

`file_header(Stream,Identifier,Options)`

Mode and number of proofs:

`file_header(+stream_or_alias,+atom,+list(compound)) - one`

`file_footer/3`

Writes the output file footer using the specified options.

Compilation flags:

`static`

Template:

`file_footer(Stream,Identifier,Options)`

Mode and number of proofs:

`file_footer(+stream_or_alias,+atom,+list(compound)) - one`

`graph_header/5`

Writes a graph header using the specified options.

Compilation flags:

`static`

Template:

`graph_header(Stream,Identifier,Label,Kind,Options)`

Mode and number of proofs:

`graph_header(+stream_or_alias,+atom,+atom,+atom,+list(compound)) - one`

graph_footer/5

Writes a graph footer using the specified options.

Compilation flags:

static

Template:

graph_footer(Stream,Identifier,Label,Kind,Options)

Mode and number of proofs:

graph_footer(+stream_or_alias,+atom,+atom,+atom,+list(compound)) - one

node/7

Writes a node using the specified options.

Compilation flags:

static

Template:

node(Stream,Identifier,Label,Caption,Lines,Kind,Options)

Mode and number of proofs:

node(+stream_or_alias,+nonvar,+nonvar,+nonvar,+list(nonvar),+atom,+list(compound)) - one

edge/6

Writes an edge between two nodes using the specified options.

Compilation flags:

static

Template:

edge(Stream,Start,End,Labels,Kind,Options)

Mode and number of proofs:

edge(+stream_or_alias,+nonvar,+nonvar,+list(nonvar),+atom,+list(compound)) - one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

object

1.15.19 graph_language_registry

Registry of implemented graph languages.

Availability:

`logtalk_load(diagrams(loader))`

Author: Paulo Moura

Version: 1:0:1

Date: 2020-03-25

Compilation flags:

`static, context_switching_calls`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - `language_object/2`
- Protected predicates

- Private predicates
- Operators

Public predicates

language_object/2

Table of defined graph languages and their implementation objects.

Compilation flags:

static, multifile

Template:

language_object(Language, Object)

Mode and number of proofs:

language_object(?atom, ?object_identifier) - zero_or_more

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

object

1.15.20 inheritance_diagram

Predicates for generating entity diagrams in DOT format with inheritance relation edges but no cross-referencing relation edges.

Availability:

logtalk_load(diagrams(loader))

Author: Paulo Moura

Version: 2:0:0

Date: 2014-01-15

Compilation flags:

static, context_switching_calls

Extends:

public inheritance_diagram(dot)

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 file/1 file/2 files/1 files/2 files/3
format_object/1 libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3
rdirectory/1 rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

➡ See also

[entity__diagram](#), [uses__diagram](#), [xref__diagram](#)

object

1.15.21 inheritance__diagram(Format)

- Format - Graph language file format.

Predicates for generating entity diagrams in the specified format with inheritance relation edges but no cross-referencing relation edges.

Availability:

`logtalk__load(diagrams(loader))`

Author: Paulo Moura

Version: 2:20:0

Date: 2024-03-20

Compilation flags:

`static, context__switching__calls`

Extends:

`public entity__diagram(Format)`

Uses:

`logtalk`

Remarks:

(none)

Inherited public predicates:

[all_files/0](#) [all_files/1](#) [all_libraries/0](#) [all_libraries/1](#) [check_option/1](#) [check_options/1](#)
[default_option/1](#) [default_options/1](#) [diagram_description/1](#) [diagram_name_suffix/1](#) [directories/2](#)
[directories/3](#) [directory/1](#) [directory/2](#) [directory/3](#) [file/1](#) [file/2](#) [files/1](#) [files/2](#) [files/3](#)
[format_object/1](#) [libraries/1](#) [libraries/2](#) [libraries/3](#) [library/1](#) [library/2](#) [option/2](#) [option/3](#)
[rdirectory/1](#) [rdirectory/2](#) [rdirectory/3](#) [rlibrary/1](#) [rlibrary/2](#) [valid_option/1](#) [valid_options/1](#)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

`entity_diagram(Format)`, `uses_diagram(Format)`, `xref_diagram(Format)`

object

1.15.22 library__dependency__diagram

Predicates for generating library dependency diagrams in DOT format.

Availability:

`logtalk_load(diagrams(loader))`

Author: Paulo Moura

Version: 2:1:0

Date: 2019-06-13

Compilation flags:

`static`, `context__switching__calls`

Extends:

`public library_dependency_diagram(dot)`

Remarks:

(none)

Inherited public predicates:

`all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

`library_load_diagram, file_load_diagram, entity_diagram`

object

1.15.23 library_dependency_diagram(Format)

- Format - Graph language file format.

Predicates for generating library dependency diagrams. A dependency exists when an entity in one library makes a reference to an entity in another library.

Availability:

```
logtalk_load(diagrams(loader))
```

Author: Paulo Moura

Version: 2:33:1

Date: 2024-04-01

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public library_diagram(Format)
```

Uses:

```
entity_diagram(Format)
list
logtalk
modules_diagram_support
```

Remarks:

(none)

Inherited public predicates:

```
all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1
```

- Public predicates
- Protected predicates
- Private predicates
 - sub_diagram_/1
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

`sub_diagram_/1`

Table of library sub-diagrams to support their generation.

Compilation flags:

`dynamic`

Template:

`sub_diagram_(Library)`

Mode and number of proofs:

`sub_diagram_(?atom) - zero_or_more`

Operators

(none)

See also

`library_load_diagram(Format)`, `directory_load_diagram(Format)`, `file_load_diagram(Format)`, `entity_diagram(Format)`

`category`

1.15.24 `library__diagram(Format)`

- `Format` - Graph language file format.

Common predicates for generating library diagrams.

Availability:

`logtalk_load(diagrams(loader))`

Author: Paulo Moura

Version: 2:17:0

Date: 2024-12-04

Compilation flags:

static

Extends:

public diagram(Format)

Uses:

list

user

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
 - add_library_documentation_url/4
 - remember_included_library/2
 - remember_referenced_logtalk_library/2
 - remember_referenced_prolog_library/2
- Private predicates
 - included_library_/2
 - referenced_logtalk_library_/2
 - referenced_prolog_library_/2
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

`add_library_documentation_url/4`

Adds a documentation URL when using the option `url_prefixes/2`.

Compilation flags:

`static`

Template:

`add_library_documentation_url(Kind,Options,Library,NodeOptions)`

Mode and number of proofs:

`add_library_documentation_url(+atom,+list(compound),+atom,-list(compound)) - one`

`remember_included_library/2`

Remember included Logtalk library in the diagram.

Compilation flags:

`static`

Template:

`remember_included_library(Library,Path)`

Mode and number of proofs:

`remember_included_library(+atom,+atom) - one`

`remember_referenced_logtalk_library/2`

Remember referenced Logtalk library in the diagram.

Compilation flags:

`static`

Template:

remember_referenced_logtalk_library(Library,Path)

Mode and number of proofs:

remember_referenced_logtalk_library(+atom,+atom) - one

remember_referenced_prolog_library/2

Remember referenced Prolog library in the diagram.

Compilation flags:

static

Template:

remember_referenced_prolog_library(Library,Path)

Mode and number of proofs:

remember_referenced_prolog_library(+atom,+atom) - one

Private predicates

included_library_/2

Table of Logtalk libraries already included in the diagram.

Compilation flags:

dynamic

Template:

included_library_(Library,Path)

Mode and number of proofs:

included_library_(?atom,?atom) - zero_or_more

referenced_logtalk_library_/2

Table of referenced Logtalk libraries in the diagram.

Compilation flags:

dynamic

Template:

referenced_logtalk_library_(Library,Path)

Mode and number of proofs:

referenced_logtalk_library_(?atom,?atom) - zero_or_more

referenced_prolog_library_/2

Table of referenced Prolog libraries in the diagram.

Compilation flags:

dynamic

Template:

referenced_prolog_library_(Library,Path)

Mode and number of proofs:

referenced_prolog_library_(?atom,?atom) - zero_or_more

Operators

(none)

 See also

inheritance_diagram(Format), uses_diagram(Format), xref_diagram(Format), entity_diagram(Format)

object

1.15.25 library_load_diagram

Predicates for generating library loading dependency diagrams in DOT format.

Availability:

`logtalk_load(diagrams(loader))`

Author: Paulo Moura

Version: 2:1:0

Date: 2019-06-13

Compilation flags:

`static, context_switching_calls`

Extends:

`public library_load_diagram(dot)`

Remarks:

`(none)`

Inherited public predicates:

`all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

`library__dependency__diagram`, `file__dependency__diagram`, `entity__diagram`

object

1.15.26 `library__load__diagram`(Format)

- Format - Graph language file format.

Predicates for generating library loading dependency diagrams.

Availability:

`logtalk__load`(`diagrams`(`loader`))

Author: Paulo Moura

Version: 2:33:1

Date: 2024-04-01

Compilation flags:

`static`, `context__switching__calls`

Imports:

`public library__diagram`(Format)

Uses:

`entity__diagram`(Format)

`list`

`logtalk`

`modules__diagram__support`

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 files/1 files/2 files/3 format_object/1
libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3 rdirectory/1
rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
 - sub_diagram_/1
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

sub_diagram_/1

Table of library sub-diagrams to support their generation.

Compilation flags:

dynamic

Template:

sub_diagram_(Library)

Mode and number of proofs:

sub_diagram_(?atom) - zero_or_more

Operators

(none)

➡ See also

`library_dependency_diagram(Format),` `directory_dependency_diagram(Format),`
`file_dependency_diagram(Format),` `entity_diagram(Format)`

object

1.15.27 modules_diagram_support

Utility predicates for supporting Prolog modules in diagrams.

Availability:

`logtalk_load(diagrams(loader))`

Author: Paulo Moura

Version: 0:19:5

Date: 2022-07-08

Compilation flags:

`static, context_switching_calls`

Dependencies:

(none)

Remarks:

- Supported backend Prolog systems: ECLiPSe, SICStus Prolog, SWI-Prolog, and YAP.

Inherited public predicates:

(none)

- Public predicates
 - `module_property/2`
 - `loaded_file_property/2`
 - `source_file_extension/1`

- Protected predicates
- Private predicates
- Operators

Public predicates

`module__property/2`

Access to module properties, at least `exports/1`, `file/1`, and `file/2` but also `declares/2`, `defines/2`, `calls/2`, and `provides/3` when possible.

Compilation flags:

`static`

Template:

`module__property(Module,Property)`

Mode and number of proofs:

`module__property(?atom,?callable) - zero_or_more`

`loaded__file__property/2`

Access to loaded source file properties, at least `basename/1`, `directory/1` but also `parent/1` when possible.

Compilation flags:

`static`

Template:

`loaded__file__property(File,Property)`

Mode and number of proofs:

`loaded__file__property(?atom,?callable) - zero_or_more`

source_file_extension/1

Valid source file extension for Prolog source files.

Compilation flags:

static

Template:

source_file_extension(Extension)

Mode and number of proofs:

source_file_extension(?atom) - one_or_more

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

object

1.15.28 uses__diagram

Predicates for generating entity diagrams in DOT format with only uses/2 and use__module/2 relation edges.

Availability:

logtalk_load(diagrams(loader))

Author: Paulo Moura

Version: 2:0:1

Date: 2020-03-27

Compilation flags:

static, context_switching_calls

Extends:

```
public uses__diagram(dot)
```

Remarks:

(none)

Inherited public predicates:

```
all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 file/1 file/2 files/1 files/2 files/3
format_object/1 libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3
rdirectory/1 rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

`entity__diagram`, `inheritance__diagram`, `xref__diagram`

object

1.15.29 `uses__diagram`(Format)

- Format - Graph language file format.

Predicates for generating entity diagrams with only `uses/2` and `use__module/2` relation edges.

Availability:

```
logtalk_load(diagrams(loader))
```

Author: Paulo Moura

Version: 2:21:0

Date: 2024-03-20

Compilation flags:

```
static, context__switching__calls
```

Extends:

```
public entity__diagram(Format)
```

Uses:

```
logtalk
```

Remarks:

```
(none)
```

Inherited public predicates:

```
all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 file/1 file/2 files/1 files/2 files/3
format_object/1 libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3
rdirectory/1 rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

`entity__diagram(Format)`, `inheritance__diagram(Format)`, `xref__diagram(Format)`

object

1.15.30 xref__diagram

Predicates for generating predicate call cross-referencing diagrams in DOT format.

Availability:

`logtalk__load(diagrams(loader))`

Author: Paulo Moura

Version: 2:0:0

Date: 2014-01-01

Compilation flags:

`static`, `context__switching__calls`

Extends:

`public xref__diagram(dot)`

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
 default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
 directories/3 directory/1 directory/2 directory/3 entity/1 entity/2 file/1 file/2 files/1 files/2
 files/3 format_object/1 libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3
 rdirectory/1 rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

➡ See also

entity_diagram, inheritance_diagram, uses_diagram

object

1.15.31 xref_diagram(Format)

- Format - Graph language file format.

Predicates for generating predicate call cross-referencing diagrams.

Availability:

logtalk_load(diagrams(loader))

Author: Paulo Moura

Version: 2:85:0

Date: 2024-12-04

Compilation flags:

static, context_switching_calls

Extends:

public entity_diagram(Format)

Uses:

atom

list

logtalk

modules_diagram_support

os

user

Remarks:

(none)

Inherited public predicates:

all_files/0 all_files/1 all_libraries/0 all_libraries/1 check_option/1 check_options/1
default_option/1 default_options/1 diagram_description/1 diagram_name_suffix/1 directories/2
directories/3 directory/1 directory/2 directory/3 file/1 file/2 files/1 files/2 files/3
format_object/1 libraries/1 libraries/2 libraries/3 library/1 library/2 option/2 option/3
rdirectory/1 rdirectory/2 rdirectory/3 rlibrary/1 rlibrary/2 valid_option/1 valid_options/1

- Public predicates
 - entity/2
 - entity/1
- Protected predicates
- Private predicates
 - included_predicate_/1
 - referenced_predicate_/1
 - external_predicate_/1
- Operators

Public predicates`entity/2`

Creates a diagram for a single entity using the specified options.

Compilation flags:

`static`

Template:

`entity(Entity,Options)`

Mode and number of proofs:

`entity(+entity__identifier,+list(compound)) - one`

`entity/1`

Creates a diagram for a single entity using default options.

Compilation flags:

`static`

Template:

`entity(Entity)`

Mode and number of proofs:

`entity(+entity__identifier) - one`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates`included__predicate__/1`

Table of predicates already included in the diagram for the entity under processing.

Compilation flags:

`dynamic`

Template:

included_predicate_(Predicate)

Mode and number of proofs:

included_predicate_(?predicate_indicator) - zero_or_more

referenced_predicate_/1

Table of referenced predicates for the entity under processing.

Compilation flags:

dynamic

Template:

referenced_predicate_(Predicate)

Mode and number of proofs:

referenced_predicate_(?predicate_indicator) - zero_or_more

external_predicate_/1

Table of external predicate references for all the entities under processing.

Compilation flags:

dynamic

Template:

external_predicate_(Reference)

Mode and number of proofs:

external_predicate_(?compound) - zero_or_more

Operators

(none)

➡ See also

`entity_diagram(Format)`, `inheritance_diagram(Format)`, `uses_diagram(Format)`

1.16 dictionaries

object

1.16.1 avltree

AVL tree implementation of the dictionary protocol. Uses standard order to compare keys.

Availability:

`logtalk_load(dictionaries(loader))`

Author: R.A.O'Keefe, L.Damas, V.S.Costa, Glenn Burgess, Jiri Spitz, and Jan Wielemaker; Logtalk port and additional predicates by Paulo Moura

Version: 1:4:1

Date: 2025-05-28

Compilation flags:

`static`, `context_switching_calls`

Implements:

`public dictionaryp`

Extends:

`public term`

Uses:

`list`

Remarks:

(none)

Inherited public predicates:

`(<)/2` `(=:)/2` `(=<)/2` `(=\=)/2` `(>)/2` `(>=)/2` `apply/4` `as_curly_bracketed/2`
`as_dictionary/2` `as_list/2` `check/1` `clone/3` `clone/4` `delete/4` `delete_max/4` `delete_min/4`
`depth/2` `empty/1` `ground/1` `insert/4` `intersection/2` `intersection/3` `keys/2` `lookup/2` `lookup/3`
`map/2` `map/3` `max/3` `min/3` `new/1` `next/4` `numbervars/1` `numbervars/3` `occurs/2` `previous/4`

singletons/2 size/2 subsumes/2 subterm/2 update/3 update/4 update/5 valid/1 values/2
variables/2 variant/2 varnumbers/2 varnumbers/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

➡ See also

bintree, rbtree

object

1.16.2 bintree

Simple binary tree implementation of the dictionary protocol. Uses standard order to compare keys.

Availability:

logtalk_load(dictionaries(loader))

Author: Paulo Moura and Paul Fodor

Version: 2:11:1

Date: 2022-05-05

Compilation flags:

static, context_switching_calls

Implements:

public dictionaryp

Extends:

public term

Uses:

list

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 apply/4 as_curly_bracketed/2
 as_dictionary/2 as_list/2 check/1 clone/3 clone/4 delete/4 delete_max/4 delete_min/4
 depth/2 empty/1 ground/1 insert/4 intersection/2 intersection/3 keys/2 lookup/2 lookup/3
 map/2 map/3 max/3 min/3 new/1 next/4 numbervars/1 numbervars/3 occurs/2 previous/4
 singletons/2 size/2 subsumes/2 subterm/2 update/3 update/4 update/5 valid/1 values/2
 variables/2 variant/2 varnumbers/2 varnumbers/3

- Public predicates
 - preorder/2
 - inorder/2
 - postorder/2
- Protected predicates
- Private predicates
- Operators

Public predicates

preorder/2

Preorder tree traversal.

Compilation flags:

static

Template:

preorder(Tree,List)

Mode and number of proofs:
preorder(@tree,-list) - one

inorder/2

Inorder tree traversal.

Compilation flags:
static

Template:
inorder(Tree,List)
Mode and number of proofs:
inorder(@tree,-list) - one

postorder/2

Postorder tree traversal.

Compilation flags:
static

Template:
postorder(Tree,List)
Mode and number of proofs:
postorder(@tree,-list) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

[avltree](#), [rbtree](#)

protocol

1.16.3 dictionaryp

Dictionary protocol.

Availability:

`logtalk_load(dictionaries(loader))`

Author: Paulo Moura

Version: 2:4:0

Date: 2024-10-02

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - `as_dictionary/2`
 - `as_list/2`

- as_curly_bracketed/2
 - clone/3
 - clone/4
 - insert/4
 - delete/4
 - update/4
 - update/5
 - update/3
 - empty/1
 - lookup/3
 - lookup/2
 - intersection/2
 - intersection/3
 - previous/4
 - next/4
 - min/3
 - max/3
 - delete_min/4
 - delete_max/4
 - keys/2
 - values/2
 - map/2
 - map/3
 - apply/4
 - size/2
- Protected predicates
 - Private predicates
 - Operators

Public predicates`as_dictionary/2`

Converts a list of key-value pairs to a dictionary.

Compilation flags:

`static`

Template:

`as_dictionary(Pairs,Dictionary)`

Mode and number of proofs:

`as_dictionary(@list(pairs),-dictionary) - one``as_list/2`

Converts a dictionary to an ordered list (as per standard order) of key-value pairs.

Compilation flags:

`static`

Template:

`as_list(Dictionary,Pairs)`

Mode and number of proofs:

`as_list(@dictionary,-list(pairs)) - one``as_curly_bracketed/2`

Creates a curly-bracketed term representation of a dictionary.

Compilation flags:

`static`

Template:

`as_curly_bracketed(Dictionary,Term)`

Mode and number of proofs:

`as_curly_bracketed(+dictionary,--term) - one`

clone/3

Clones a dictionary using the same keys but with all values unbound and returning a list of all the pairs in the new clone.

Compilation flags:

static

Template:

clone(Dictionary,Clone,ClonePairs)

Mode and number of proofs:

clone(+dictionary,-dictionary,-list(pairs)) - one

clone/4

Clones a dictionary using the same keys but with all values unbound and returning the list of all pairs in the dictionary and in the clone.

Compilation flags:

static

Template:

clone(Dictionary,Pairs,Clone,ClonePairs)

Mode and number of proofs:

clone(+dictionary,-list(pairs),-dictionary,-list(pairs)) - one

insert/4

Inserts a key-value pair into a dictionary, returning the updated dictionary. When the key already exists, the associated value is updated.

Compilation flags:

static

Template:

```
insert(OldDictionary,Key,Value,NewDictionary)
```

Mode and number of proofs:

```
insert(+dictionary,+ground,@term,-dictionary) - one
```

`delete/4`

Deletes a matching key-value pair from a dictionary, returning the updated dictionary. Fails if it cannot find the key or if the key exists but the value does not unify.

Compilation flags:

```
static
```

Template:

```
delete(OldDictionary,Key,Value,NewDictionary)
```

Mode and number of proofs:

```
delete(+dictionary,@ground,?term,-dictionary) - zero_or_one
```

`update/4`

Updates the value associated with Key in a dictionary, returning the updated dictionary. Fails if it cannot find the key.

Compilation flags:

```
static
```

Template:

```
update(OldDictionary,Key,NewValue,NewDictionary)
```

Mode and number of proofs:

```
update(+dictionary,@ground,+term,-dictionary) - zero_or_one
```

update/5

Updates the value associated with a key in a dictionary, returning the updated dictionary. Fails if it cannot find the key or if the existing value does not unify.

Compilation flags:

static

Template:

update(OldDictionary,Key,OldValue,NewValue,NewDictionary)

Mode and number of proofs:

update(+dictionary,@ground,?term,+term,-dictionary) - zero_or_one

update/3

Updates the key-value pairs in a dictionary, returning the updated dictionary. Fails if it cannot find one of the keys.

Compilation flags:

static

Template:

update(OldDictionary,Pairs,NewDictionary)

Mode and number of proofs:

update(+dictionary,@list(pair),-dictionary) - zero_or_one

empty/1

True iff the dictionary is empty.

Compilation flags:

static

Template:

empty(Dictionary)

Mode and number of proofs:

empty(@dictionary) - zero_or_one

lookup/3

Lookups a matching key-value pair from a dictionary. Fails if no match is found.

Compilation flags:

static

Template:

lookup(Key,Value,Dictionary)

Mode and number of proofs:

lookup(+ground,?term,@dictionary) - zero_or_one

lookup(-ground,?term,@dictionary) - zero_or_more

lookup/2

Lookups all matching key-value pairs from a dictionary. Fails if it cannot find one of the keys or if a value for a key does not unify.

Compilation flags:

static

Template:

lookup(Pairs,Dictionary)

Mode and number of proofs:

lookup(+list(pair),@dictionary) - zero_or_one

intersection/2

True iff the values of the dictionaries common keys unify. Trivially true when there are no common keys.

Compilation flags:

static

Template:

```
intersection(Dictionary1,Dictionary2)
```

Mode and number of proofs:

```
intersection(+dictionary,+dictionary) - zero_or_one
```

[intersection/3](#)

Returns the (possibly empty) intersection between two dictionaries when the values of their common keys unify.

Compilation flags:

```
static
```

Template:

```
intersection(Dictionary1,Dictionary2,Intersection)
```

Mode and number of proofs:

```
intersection(+dictionary,+dictionary,-dictionary) - zero_or_one
```

[previous/4](#)

Returns the previous pair in a dictionary given a key. Fails if there is no previous pair.

Compilation flags:

```
static
```

Template:

```
previous(Dictionary,Key,Previous,Value)
```

Mode and number of proofs:

```
previous(+dictionary,+key,-key,-value) - zero_or_one
```

next/4

Returns the next pair in a dictionary given a key. Fails if there is no next pair.

Compilation flags:

static

Template:

next(Dictionary,Key,Next,Value)

Mode and number of proofs:

next(+dictionary,+key,-key,-value) - zero_or_one

min/3

Returns the pair with the minimum key (as per standard order) in a dictionary. Fails if the dictionary is empty.

Compilation flags:

static

Template:

min(Dictionary,Key,Value)

Mode and number of proofs:

min(+dictionary,-key,-value) - zero_or_one

max/3

Returns the pair with the maximum key (as per standard order) in a dictionary. Fails if the dictionary is empty.

Compilation flags:

static

Template:

max(Dictionary,Key,Value)

Mode and number of proofs:

max(+dictionary,-key,-value) - zero_or_one

`delete_min/4`

Deletes the pair with the minimum key (as per standard order) from a dictionary, returning the deleted pair and the updated dictionary. Fails if the dictionary is empty.

Compilation flags:

`static`

Template:

`delete_min(OldDictionary,Key,Value,NewDictionary)`

Mode and number of proofs:

`delete_min(+dictionary,-key,-value,-dictionary) - zero_or_one`

`delete_max/4`

Deletes the pair with the maximum key (as per standard order) from a dictionary, returning the deleted pair and the updated dictionary. Fails if the dictionary is empty.

Compilation flags:

`static`

Template:

`delete_max(OldDictionary,Key,Value,NewDictionary)`

Mode and number of proofs:

`delete_max(+dictionary,-key,-value,-dictionary) - zero_or_one`

`keys/2`

Returns a list with all the dictionary keys in ascending order (as per standard order).

Compilation flags:

`static`

Template:

keys(Dictionary,Keys)

Mode and number of proofs:

keys(@dictionary,-list) - one

values/2

Returns a list with all the dictionary values in ascending order of the keys (as per standard order).

Compilation flags:

static

Template:

values(Dictionary,Values)

Mode and number of proofs:

values(@dictionary,-list) - one

map/2

Maps a closure over each dictionary key-value pair. Fails if the mapped closure attempts to modify the keys.

Compilation flags:

static

Template:

map(Closure,Dictionary)

Meta-predicate template:

map(1,*)

Mode and number of proofs:

map(@callable,+dictionary) - zero_or_more

map/3

Maps a closure over each dictionary key-value pair, returning the new dictionary. Fails if the mapped closure attempts to modify the keys.

Compilation flags:

static

Template:

map(Closure,OldDictionary,NewDictionary)

Meta-predicate template:

map(2,*,*)

Mode and number of proofs:

map(@callable,+dictionary,-dictionary) - zero_or_more

apply/4

Applies a closure to a specific key-value pair, returning the new dictionary. Fails if the key cannot be found or if the mapped closure attempts to modify the key.

Compilation flags:

static

Template:

apply(Closure,OldDictionary,Key,NewDictionary)

Meta-predicate template:

apply(2,*,*,*)

Mode and number of proofs:

apply(+callable,+dictionary,+key,-dictionary) - zero_or_one

size/2

Number of dictionary entries.

Compilation flags:

static

Template:

`size(Dictionary,Size)`

Mode and number of proofs:

`size(@dictionary,?integer) - one`

Protected predicates


(none)

Private predicates

(none)

Operators

(none)

 See also

`avltree`, `bintree`, `rbtree`

object

1.16.4 `rbtree`

Red-Black tree implementation of the dictionary protocol. Uses standard order to compare keys.

Availability:

`logtalk_load(dictionaries(loader))`

Author: Vitor Santos Costa; Logtalk port and additional predicates by Paulo Moura.

Version: 1:9:0

Date: 2021-04-12

Compilation flags:

`static`, `context_switching_calls`

Implements:

public `dictionaryp`

Extends:

public `term`

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 apply/4 as_curly_bracketed/2
as_dictionary/2 as_list/2 check/1 clone/3 clone/4 delete/4 delete_max/4 delete_min/4
depth/2 empty/1 ground/1 insert/4 intersection/2 intersection/3 keys/2 lookup/2 lookup/3
map/2 map/3 max/3 min/3 new/1 next/4 numbervars/1 numbervars/3 occurs/2 previous/4
singletons/2 size/2 subsumes/2 subterm/2 update/3 update/4 update/5 valid/1 values/2
variables/2 variant/2 varnumbers/2 varnumbers/3

- Public predicates
 - partial_map/4
- Protected predicates
- Private predicates
- Operators

Public predicates

partial_map/4

Applies a closure to the tree pairs identified by a set of keys.

Compilation flags:

static

Template:

partial_map(Tree,Keys,Closure,NewTree)

Meta-predicate template:

partial_map(*,*,2,*)

Mode and number of proofs:

partial_map(+tree,+list,@closure,-tree) - zero_or_one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

➡ See also

[avltree](#), [bintree](#)

1.17 dif

object

1.17.1 dif

Provides dif/2 and derived predicates.

Availability:

`logtalk__load(dif(loader))`

Author: Paulo Moura

Version: 1:3:0

Date: 2023-10-02

Compilation flags:

`static, context_switching_calls`

Dependencies:

(none)

Remarks:

- Supported backend Prolog systems: B-Prolog, ECLiPSe, SICStus Prolog, SWI-Prolog, Trealla Prolog, and YAP.

Inherited public predicates:
(none)

- Public predicates
 - dif/2
 - dif/1
- Protected predicates
- Private predicates
- Operators

Public predicates

dif/2

Sets a constraint that is true iff the two terms are different.

Compilation flags:
static

Template:
dif(Term1,Term2)
Mode and number of proofs:
dif(+term,+term) - zero_or_one

dif/1

Sets a set of constraints that are true iff all terms in a list are different.

Compilation flags:
static

Template:
dif(Terms)
Mode and number of proofs:
dif(+list(term)) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.18 doclet

object

1.18.1 doclet

Utility object to help automate (re)generating documentation for a project.

Availability:

`logtalk__load(doclet(loader))`

Author: Paulo Moura

Version: 0:5:0

Date: 2017-01-05

Compilation flags:

`static, context_switching_calls`

Provides:

`logtalk::message_tokens//2`

Uses:

`logtalk`

`os`

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - `update/0`
 - `doc_goal/1`
 - `shell_command/1`
- Protected predicates
- Private predicates
- Operators

Public predicates

`update/0`

Updates the project documentation, first by calling a sequence of goals and second by executing a sequence of shell commands. Fails if any goal or shell command fails.

Compilation flags:

`static`

Mode and number of proofs:

`update - zero_or_one`

`doc_goal/1`

Table of goals, typically using the diagrams and the `lgtdoc` tools, used to generate the documentation. Goals are called in the order they are defined and in the context of the user pseudo-object.

Compilation flags:

`static`

Template:

`doc_goal(Goal)`

Mode and number of proofs:

`doc_goal(?callable) - one_or_more`

shell_command/1

Table of shell commands to convert intermediate documentation files into user-friendly documentation. Commands are executed in the order they are defined.

Compilation flags:

static

Template:

shell_command(Command)

Mode and number of proofs:

shell_command(?atom) - one_or_more

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

lgtdocp, diagram(Format)

1.19 edcg

object

1.19.1 edcg

Multiple hidden parameters: an extension to Prolog's DCG notation. Ported to Logtalk as a hook object.

Availability:

```
logtalk_load(edcg(loader))
```

Author: Peter Van Roy; adapted to Logtalk by Paulo Moura.

Version: 1:4:2

Date: 2020-04-08

Copyright: Copyright (C) 1992 Peter Van Roy

License: MIT

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public expanding
```

Provides:

```
logtalk::message_tokens//2
```

Uses:

```
list
```

```
logtalk
```

Remarks:

- Usage: Compile source files with objects (or categories) defining EDCGs using the compiler option `hook(edcg)`.

Inherited public predicates:

```
goal_expansion/2 term_expansion/2
```

- Public predicates
- Protected predicates
- Private predicates
 - `pred_info/3`
 - `acc_info/7`
 - `acc_info/5`

- pass_info/2
- pass_info/1
- Operators
 - op(1200,xfx,-->>)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

pred_info/3

Declares predicates that have the listed hidden parameters.

Compilation flags:

dynamic

Template:

pred_info(Name,Arity,HiddenParameters)

Mode and number of proofs:

pred_info(?atom,?integer,?list(atom)) - zero_or_more

acc_info/7

Long form for declaring accumulators.

Compilation flags:

dynamic

Template:

acc_info(Accumulator,Term,Left,Right,Joiner,LStart,RStart)

Mode and number of proofs:

acc_info(?atom,?term,?term,?term,?callable,?term,?term) - zero_or_more

`acc_info/5`

Short form for declaring accumulators.

Compilation flags:
dynamic

Template:
acc_info(Accumulator,Term,Left,Right,Joiner)
Mode and number of proofs:
acc_info(?atom,?term,?term,?term,?callable) - zero_or_more

`pass_info/2`

Long form for declaring passed arguments. Passed arguments are conceptually the same as accumulators with =/2 as the joiner function.

Compilation flags:
dynamic

Template:
pass_info(Argument,PStart)
Mode and number of proofs:
pass_info(?atom,?term) - zero_or_more

`pass_info/1`

Short form for declaring passed arguments. Passed arguments are conceptually the same as accumulators with =/2 as the joiner function.

Compilation flags:
dynamic

Template:

```
pass_info(Argument)
Mode and number of proofs:
pass_info(?atom) - zero_or_more
```

Operators

```
op(1200,xfx,-->>)
```

Scope:

```
public
```

1.20 events

object

1.20.1 after_event_registry

After events registry predicates.

Availability:

```
logtalk_load(events(loader))
```

Author: Paulo Moura

Version: 1:1:0

Date: 2009-10-08

Compilation flags:

```
static, context_switching_calls, events
```

Implements:

```
public event_registryp
```

Remarks:

```
(none)
```

Inherited public predicates:

```
del_monitors/0 del_monitors/4 monitor/1 monitor/4 monitored/1 monitors/1 set_monitor/4
```

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

[before_event_registry](#), [monitorp](#)

object

1.20.2 [before_event_registry](#)

Before events registry predicates.

Availability:

`logtalk_load(events(loader))`

Author: Paulo Moura

Version: 1:1:0

Date: 2009-10-08

Compilation flags:

`static, context_switching_calls, events`

Implements:

`public event_registryp`

Remarks:

(none)

Inherited public predicates:

`del_monitors/0 del_monitors/4 monitor/1 monitor/4 monitored/1 monitors/1 set_monitor/4`

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

➡ See also

`after_event_registry`, `monitorp`

object

1.20.3 event_registry

Before and after events registry predicates.

Availability:

`logtalk_load(events(loader))`

Author: Paulo Moura

Version: 1:1:0

Date: 2009-10-08

Compilation flags:

`static, context__switching_calls, events`

Implements:

`public event_registry`

Remarks:

`(none)`

Inherited public predicates:

`del_monitors/0 del_monitors/4 monitor/1 monitor/4 monitored/1 monitors/1 set_monitor/4`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.20.4 event_registryp

Event registry protocol.

Availability:

logtalk_load(events(loader))

Author: Paulo Moura

Version: 1:1:0

Date: 2009-10-08

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - monitors/1
 - monitor/1

- monitored/1
- monitor/4
- set_monitor/4
- del_monitors/4
- del_monitors/0
- Protected predicates
- Private predicates
- Operators

Public predicates

monitors/1

Returns a list of all current monitors.

Compilation flags:

static

Template:

monitors(Monitors)

Mode and number of proofs:

monitors(-list(object_identifier)) - one

monitor/1

Monitor is an object playing the role of a monitor.

Compilation flags:

static

Template:

monitor(Monitor)

Mode and number of proofs:

monitor(-object_identifier) - zero_or_more

monitor(+object_identifier) - zero_or_one

monitored/1

Returns a list of all currently monitored objects.

Compilation flags:

static

Template:

monitored(Objects)

Mode and number of proofs:

monitored(-list(object_identifier)) - one

monitor/4

True if the arguments describe a currently defined monitored event.

Compilation flags:

static

Template:

monitor(Object,Message,Sender,Monitor)

Mode and number of proofs:

monitor(?object_identifier,?nonvar,?object_identifier,?object_identifier) - zero_or_more

set_monitor/4

Sets a monitor for the set of matching events.

Compilation flags:

static

Template:

set_monitor(Object,Message,Sender,Monitor)

Mode and number of proofs:

set_monitor(?object_identifier,?nonvar,?object_identifier,+object_identifier) - zero_or_one

`del_monitors/4`

Deletes all matching monitored events.

Compilation flags:

`static`

Template:

`del_monitors(Object,Message,Sender,Monitor)`

Mode and number of proofs:

`del_monitors(?object_identifier,?nonvar,?object_identifier,?object_identifier) - one`

`del_monitors/0`

Deletes all monitored events.

Compilation flags:

`static`

Mode and number of proofs:

`del_monitors - one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

 See also

`event_registry`, `monitorp`

`category`

1.20.5 monitor

Monitor predicates.

Availability:

`logtalk_load(events(loader))`

Author: Paulo Moura

Version: 1:3:0

Date: 2019-03-08

Compilation flags:

`static, events`

Implements:

`public monitorp`

Remarks:

`(none)`

Inherited public predicates:

`activate_monitor/0 del_spy_points/4 monitor_activated/0 reset_monitor/0 set_spy_point/4
spy_point/4 suspend_monitor/0`

- Public predicates
- Protected predicates
- Private predicates
 - `spy_point_/4`
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

`spy__point_/4`

Stores current spy points.

Compilation flags:

`dynamic`

Template:

`spy__point__(Event,Object,Message,Sender)`

Mode and number of proofs:

`spy__point__(?event,?object,?callable,?object) - zero__or__more`

Operators

(none)

protocol

1.20.6 monitorp

Monitor protocol.

Availability:

`logtalk__load(events(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2000-07-24

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - monitor_activated/0
 - activate_monitor/0
 - suspend_monitor/0
 - reset_monitor/0
 - spy_point/4
 - set_spy_point/4
 - del_spy_points/4
- Protected predicates
- Private predicates
- Operators

Public predicates

monitor_activated/0

True if monitor is currently active.

Compilation flags:

static

Mode and number of proofs:

monitor_activated - zero_or_one

`activate_monitor/0`

Activates all spy points and start monitoring.

Compilation flags:

`static`

Mode and number of proofs:

`activate_monitor - one`

`suspend_monitor/0`

Suspends monitoring, deactivating all spy points.

Compilation flags:

`static`

Mode and number of proofs:

`suspend_monitor - one`

`reset_monitor/0`

Resets monitor, deactivating and deleting all spy points.

Compilation flags:

`static`

Mode and number of proofs:

`reset_monitor - one`

`spy_point/4`

Current spy point.

Compilation flags:

`static`

Template:

`spy_point(Event, Object, Message, Sender)`

Mode and number of proofs:

`spy_point(?event, ?object, ?callable, ?object) - zero_or_more`

`set_spy_point/4`

Sets a spy point.

Compilation flags:

`static`

Template:

`set_spy_point(Event, Object, Message, Sender)`

Mode and number of proofs:

`set_spy_point(?event, ?object, ?callable, ?object) - one`

`del_spy_points/4`

Deletes all matching spy points.

Compilation flags:

`static`

Template:

`del_spy_points(Event, Object, Message, Sender)`

Mode and number of proofs:

`del_spy_points(@event, @object, @callable, @object) - one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

 See also

[monitor](#), [event_registry](#)

1.21 `expand_library_alias_paths`

object

1.21.1 `expand_library_alias_paths`

Hook object for expanding library alias paths in `logtalk_library_path/2` facts when compiling a source file.

Availability:

`logtalk_load(expand_library_alias_paths(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2018-04-12

Compilation flags:

`static`, `context_switching_calls`

Implements:

`public` `expanding`

Uses:

`logtalk`

`os`

Remarks:

(none)

Inherited public predicates:

`goal_expansion/2` `term_expansion/2`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.22 expecteds

object

1.22.1 either

Types and predicates for extended type-checking and handling of expected terms.

Availability:

`logtalk_load(expecteds(loader))`

Author: Paulo Moura

Version: 0:7:0

Date: 2021-01-03

Compilation flags:

static, context_switching_calls

Provides:

type::type/1
type::check/2
arbitrary::arbitrary/1
arbitrary::arbitrary/2

Uses:

expected
expected(Expected)
random
type

Remarks:

- Type-checking support: Defines a `either(ValueType, ErrorType)` type for checking expected terms where the value and error terms must be of the given types.
- QuickCheck support: Defines clauses for the `type::arbitrary/1-2` predicates to allow generating random values for the `either(ValueType, ErrorType)` type.

Inherited public predicates:

(none)

- Public predicates
 - `expecteds/2`
 - `unexpecteds/2`
 - `partition/3`
- Protected predicates
- Private predicates
- Operators

Public predicates

`expecteds/2`

Returns the values stored in the expected terms that hold a value.

Compilation flags:

static

Template:

expecteds(Expecteds,Values)

Mode and number of proofs:

expecteds(+list(expected),-list) - one

unexpecteds/2

Returns the errors stored in the expected terms that hold an error.

Compilation flags:

static

Template:

unexpecteds(Expecteds,Errors)

Mode and number of proofs:

unexpecteds(+list(expected),-list) - one

partition/3

Retrieves and partitions the values and errors hold by the expected terms.

Compilation flags:

static

Template:

partition(Expecteds,Values,Errors)

Mode and number of proofs:

partition(+list(expected),-list,-list) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

➡ See also

`expected`, `expected(Expected)`, `type`, `arbitrary`

object

1.22.2 `expected`

Constructors for `expected` terms. An `expected` term contains either a value or an error. Expected terms should be regarded as opaque terms and always used with the `expected/1` object by passing the `expected` term as a parameter.

Availability:

`logtalk_load(expecteds(loader))`

Author: Paulo Moura

Version: 2:1:0

Date: 2021-01-03

Compilation flags:

`static`, `context_switching_calls`

Provides:

`type::type/1`

`type::check/2`

Remarks:

- Type-checking support: This object also defines a type `expected` for use with the type library object.

Inherited public predicates:

(none)

- Public predicates
 - of_unexpected/2
 - of_expected/2
 - from_goal/4
 - from_goal/3
 - from_goal/2
 - from_generator/4
 - from_generator/3
 - from_generator/2
- Protected predicates
- Private predicates
- Operators

Public predicates

of_unexpected/2

Constructs an expected term from an error that represent that the expected value is missing.

Compilation flags:

static

Template:

of_unexpected(Error,Expected)

Mode and number of proofs:

of_unexpected(@term,--nonvar) - one

of_expected/2

Constructs an expected term from an expected value.

Compilation flags:

static

Template:

of_expected(Value,Expected)

Mode and number of proofs:

of_expected(@term,--nonvar) - one

from_goal/4

Constructs an expected term holding a value bound by calling the given goal. Otherwise returns an expected term with the unexpected goal error or failure represented by the Error argument.

Compilation flags:

static

Template:

from_goal(Goal,Value,Error,Expected)

Meta-predicate template:

from_goal(0,*,*,*)

Mode and number of proofs:

from_goal(+callable,--term,@term,--nonvar) - one

from_goal/3

Constructs an expected term holding a value bound by calling the given goal. Otherwise returns an expected term with the unexpected goal error or the atom fail representing the unexpected failure.

Compilation flags:

static

Template:

from_goal(Goal,Value,Expected)

Meta-predicate template:

```
from_goal(0,*,*)
```

Mode and number of proofs:

```
from_goal(+callable,--term,--nonvar) - one
```

from_goal/2

Constructs an expected term holding a value bound by calling the given closure. Otherwise returns an expected term holding the unexpected closure error or the atom fail representing the unexpected failure.

Compilation flags:

```
static
```

Template:

```
from_goal(Closure,Expected)
```

Meta-predicate template:

```
from_goal(1,*)
```

Mode and number of proofs:

```
from_goal(+callable,--nonvar) - one
```

from_generator/4

Constructs expected terms with the values generated by calling the given goal. On goal error or failure, returns an expected term with the unexpected goal error or failure represented by the Error argument.

Compilation flags:

```
static
```

Template:

```
from_generator(Goal,Value,Error,Expected)
```

Meta-predicate template:

```
from_generator(0,*,*,*)
```

Mode and number of proofs:

```
from_generator(+callable,--term,@term,--nonvar) - one_or_more
```

`from_generator/3`

Constructs expected terms with the values generated by calling the given goal. On goal error or failure, returns an expected term with, respectively, the unexpected goal error or the atom fail representing the unexpected goal failure.

Compilation flags:

`static`

Template:

`from_generator(Goal, Value, Expected)`

Meta-predicate template:

`from_generator(0, *, *)`

Mode and number of proofs:

`from_generator(+callable, --term, --nonvar) - one_or_more`

`from_generator/2`

Constructs expected terms with the values generated by calling the given closure. On closure error or failure, returns an expected term with, respectively, the unexpected closure error or the atom fail representing the unexpected closure failure.

Compilation flags:

`static`

Template:

`from_generator(Closure, Expected)`

Meta-predicate template:

`from_generator(1, *)`

Mode and number of proofs:

`from_generator(+callable, --nonvar) - one_or_more`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

`expected(Expected), type`

object

1.22.3 `expected(Expected)`

Expected term predicates. Requires passing an expected term (constructed using the expected object predicates) as a parameter.

Availability:

`logtalk_load(expecteds(loader))`

Author: Paulo Moura

Version: 1:5:0

Date: 2020-01-06

Compilation flags:

`static, context_switching_calls`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - `is_expected/0`
 - `is_unexpected/0`
 - `if_expected/1`
 - `if_unexpected/1`
 - `if_expected_or_else/2`
 - `unexpected/1`
 - `expected/1`
 - `map/2`
 - `flat_map/2`
 - `either/3`
 - `or_else/2`
 - `or_else_get/2`
 - `or_else_call/2`
 - `or_else_throw/1`
 - `or_else_fail/1`
- Protected predicates
- Private predicates
- Operators

Public predicates

`is_expected/0`

True if the `expected` term holds a value. See also the `if_expected/1` predicate.

Compilation flags:

`static`

Mode and number of proofs:

`is_expected - zero_or_one`

`is_unexpected/0`

True if the expected term holds an error. See also the `if_unexpected/1` predicate.

Compilation flags:

`static`

Mode and number of proofs:

`is_unexpected - zero_or_one`

`if_expected/1`

Applies a closure when the expected term holds a value using the value as argument. Succeeds otherwise.

Compilation flags:

`static`

Template:

`if_expected(Closure)`

Meta-predicate template:

`if_expected(1)`

Mode and number of proofs:

`if_expected(+callable) - zero_or_more`

`if_unexpected/1`

Applies a closure when the expected term holds an error using the error as argument. Succeeds otherwise. Can be used to throw the exception hold by the expected term by calling it the `atom throw`.

Compilation flags:

`static`

Template:

`if_unexpected(Closure)`

Meta-predicate template:

`if_unexpected(1)`

Mode and number of proofs:

`if_unexpected(+callable) - zero_or_more`

`if_expected_or_else/2`

Applies either ExpectedClosure or UnexpectedClosure depending on the expected term holding a value or an error.

Compilation flags:

`static`

Template:

`if_expected_or_else(ExpectedClosure,UnexpectedClosure)`

Meta-predicate template:

`if_expected_or_else(1,1)`

Mode and number of proofs:

`if_expected_or_else(+callable,+callable) - zero_or_more`

`unexpected/1`

Returns the error hold by the expected term. Throws an error otherwise.

Compilation flags:

`static`

Template:

`unexpected(Error)`

Mode and number of proofs:

`unexpected(--term) - one_or_error`

Exceptions:

Expected term holds a value:

`existence_error(unexpected_error,Expected)`

`expected/1`

Returns the value hold by the expected term. Throws an error otherwise.

Compilation flags:

`static`

Template:

`expected(Value)`

Mode and number of proofs:

`expected(--term) - one_or_error`

Exceptions:

Expected term holds an error:

`existence_error(expected_value,Expected)`

`map/2`

When the expected term does not hold an error and mapping a closure with the expected value and the new value as additional arguments is successful, returns an expected term with the new value. Otherwise returns the same expected term.

Compilation flags:

`static`

Template:

`map(Closure,NewExpected)`

Meta-predicate template:

`map(2,*)`

Mode and number of proofs:

`map(+callable,--nonvar) - one`

`flat_map/2`

When the expected term does not hold an error and mapping a closure with the expected value and the new expected term as additional arguments is successful, returns the new expected term. Otherwise returns the same expected term.

Compilation flags:

`static`

Template:

`flat_map(Closure,NewExpected)`

Meta-predicate template:

`flat_map(2,*)`

Mode and number of proofs:

`flat_map(+callable,--nonvar) - one`

`either/3`

Applies either `ExpectedClosure` if the expected term holds a value or `UnexpectedClosure` if the expected term holds an error. Returns a new expected term if the applied closure is successful. Otherwise returns the same expected term.

Compilation flags:

`static`

Template:

`either(ExpectedClosure,UnexpectedClosure,NewExpected)`

Meta-predicate template:

`either(2,2,*)`

Mode and number of proofs:

`either(+callable,+callable,--nonvar) - one`

`or_else/2`

Returns the value hold by the expected term if it does not hold an error or the given default term if the expected term holds an error.

Compilation flags:

`static`

Template:

`or_else(Value,Default)`

Mode and number of proofs:

`or_else(--term,@term) - one`

`or_else_get/2`

Returns the value hold by the expected term if it does not hold an error. Otherwise applies a closure to compute the expected value. Throws an error when the expected term holds an error and a value cannot be computed.

Compilation flags:

`static`

Template:

`or_else_get(Value,Closure)`

Meta-predicate template:

`or_else_get(*,1)`

Mode and number of proofs:

`or_else_get(--term,+callable) - one_or_error`

Exceptions:

Expected term holds an unexpected error and an expected value cannot be computed:

`existence_error(expected_value,Expected)`

`or_else_call/2`

Returns the value hold by the expected term if it does not hold an error. Calls a goal deterministically otherwise.

Compilation flags:

`static`

Template:

`or_else_call(Value,Goal)`

Meta-predicate template:

`or_else_call(*,0)`

Mode and number of proofs:

`or_else_call(--term,+callable) - zero_or_one`

`or_else_throw/1`

Returns the value hold by the expected term if present. Throws the error hold by the expected term as an exception otherwise.

Compilation flags:

`static`

Template:

`or_else_throw(Value)`

Mode and number of proofs:

`or_else_throw(--term) - one_or_error`

`or_else_fail/1`

Returns the value hold by the expected term if it does not hold an error. Fails otherwise. Usually called to skip over expected terms holding errors.

Compilation flags:

`static`

Template:

```
or_else_fail(Value)
```

Mode and number of proofs:

```
or_else_fail(--term) - zero_or_one
```

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

 See also

[expected](#)

1.23 fcube

object

1.23.1 fcube

FCube: An Efficient Prover for Intuitionistic Propositional Logic.

Availability:

```
logtalk_load(fcube(loader))
```

Author: Mauro Ferrari, Camillo Fiorentini, Guido Fiorino; ported to Logtalk by Paulo Moura.

Version: 5:0:1

Date: 2024-03-14

Copyright: Copyright 2012 Mauro Ferrari, Camillo Fiorentini, Guido Fiorino; Copyright 2020-2024 Paulo Moura

License: GPL-2.0-or-later

Compilation flags:

static, context_switching_calls

Uses:

integer
list
os
set
user

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - gnu/0
 - fcube/0
 - decide/1
 - decide/2
- Protected predicates
- Private predicates
- Operators
 - op(1200,xfy,<=>)
 - op(1110,xfy,=>)
 - op(1000,xfy,&&)
 - op(500,fy,~)
 - op(1100,xfy,v)

Public predicates

gnu/0

Prints banner with copyright and license information.

Compilation flags:

static

Mode and number of proofs:

gnu - one

fcube/0

Reads a formula and applies the prover to it, printing its counter-model.

Compilation flags:

static

Mode and number of proofs:

fcube - one

decide/1

Applies the prover to the given formula and prints its counter-model.

Compilation flags:

static

Template:

decide(Formula)

Mode and number of proofs:

decide(++compound) - one

decide/2

Applies the prover to the given formula and returns its counter-model.

Compilation flags:

static

Template:

decide(Formula,CounterModel)

Mode and number of proofs:

decide(++compound,--compound) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

op(1200,xfy,<=>)

Scope:

public

op(1110,xfy,=>)

Scope:

public

op(1000,xfy,&&)

Scope:

public

op(500,fy,~)

Scope:

public

`op(1100,xfy,v)`

Scope:

public

1.24 flags

category

1.24.1 flags

Implementation of persistent object flags.

Availability:

`logtalk_load(flags(loader))`

Author: Theofrastos Mantadelis

Version: 1:0:0

Date: 2010-11-27

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - `get_flag_value/2`
 - `set_flag_value/2`
 - `set_flag_value/3`
 - `reset_flags/0`
 - `reset_flags/1`

- flag_groups/1
- flag_group_chk/1
- print_flags/0
- print_flags/1
- defined_flag/6
- built_in_flag/2
- Protected predicates
 - unsafe_set_flag_value/2
 - define_flag/1
 - define_flag/2
- Private predicates
 - defined_flag_/6
 - flag_value_/2
 - validate/3
 - validate_type/1
 - is_validator/1
- Operators

Public predicates

get_flag_value/2

Gets or tests the value of a flag.

Compilation flags:

static

Template:

get_flag_value(Flag,Value)

Mode and number of proofs:

get_flag_value(+atom,?nonvar) - zero_or_one

`set_flag_value/2`

Sets the value of a flag.

Compilation flags:

`static`

Template:

`set_flag_value(Flag,NewValue)`

Mode and number of proofs:

`set_flag_value(+atom,@nonvar) - one`

`set_flag_value/3`

Sets the value of a flag, returning the old value.

Compilation flags:

`static`

Template:

`set_flag_value(Flag,OldValue,NewValue)`

Mode and number of proofs:

`set_flag_value(+atom,?nonvar,@nonvar) - one`

`reset_flags/0`

Resets all flags to their default values.

Compilation flags:

`static`

Mode and number of proofs:

`reset_flags - one`

`reset_flags/1`

Resets all flags in a group to their default values.

Compilation flags:

`static`

Template:

`reset_flags(Group)`

Mode and number of proofs:

`reset_flags(+atom) - one`

`flag_groups/1`

Returns a list of all flag groups.

Compilation flags:

`static`

Template:

`flag_groups(Groups)`

Mode and number of proofs:

`flag_groups(-list(atom)) - one`

`flag_group_chk/1`

Checks if a given atom is a flag group.

Compilation flags:

`static`

Template:

`flag_group_chk(Group)`

Mode and number of proofs:

`flag_group_chk(+atom) - zero_or_one`

`print_flags/0`

Prints a listing of all flags.

Compilation flags:

`static`

Mode and number of proofs:

`print_flags - one`

`print_flags/1`

Prints a listing of all flags in a group.

Compilation flags:

`static`

Template:

`print_flags(Group)`

Mode and number of proofs:

`print_flags(+atom) - one`

`defined_flag/6`

Gets or test the existing (visible) flag definitions.

Compilation flags:

`static`

Template:

`defined_flag(Flag,Group,Type,DefaultValue,Description,Access)`

Mode and number of proofs:

`defined_flag(?atom,?atom,?nonvar,?nonvar,?atom,?atom) - zero_or_more`

`built_in_flag/2`

True if the argument is a built-in flag type with the specified default value.

Compilation flags:

`static`

Template:

`built_in_flag(Type,DefaultValue)`

Mode and number of proofs:

`built_in_flag(?atom,?nonvar) - zero_or_more`

Protected predicates

`unsafe_set_flag_value/2`

Sets the value of a flag without performing any validation checks.

Compilation flags:

`static`

Template:

`unsafe_set_flag_value(Flag,NewValue)`

Mode and number of proofs:

`unsafe_set_flag_value(+atom,@nonvar) - one`

`define_flag/1`

Defines a new flag using default options.

Compilation flags:

`static`

Template:

`define_flag(Flag)`

Mode and number of proofs:

`define_flag(+atom) - one`

`define_flag/2`

Defines a new flag using a given set of options (for example, `[group(general), type(nonvar), default(true), description(Flag), access(read_write)]`).

Compilation flags:

`static`

Template:

`define_flag(Flag,Options)`

Mode and number of proofs:

`define_flag(+atom,@list) - one`

Private predicates

`defined_flag_/6`

Gets or test the existing flag definitions.

Compilation flags:

`dynamic`

Template:

`defined_flag_(Flag,Group,Type,DefaultValue,Description,Access)`

Mode and number of proofs:

`defined_flag_(?atom,?atom,?nonvar,?nonvar,?atom,?atom) - zero_or_more`

`flag_value_/2`

Table of flag values.

Compilation flags:

`dynamic`

Template:

 flag_value_(Flag,Value)

Mode and number of proofs:

 flag_value_(?atom,?nonvar) - zero_or_more

validate/3

Compilation flags:

 static

validate_type/1

Compilation flags:

 static

is_validator/1

Compilation flags:

 static

Operators

(none)

protocol

1.24.2 flags_validator

Flag validation protocol. Must be implemented by validator objects.

Availability:

 logtalk_load(flags(loader))

Author: Theofrastos Mantadelis

Version: 1:0:0
Date: 2010-11-27

Compilation flags:
static

Dependencies:
(none)

Remarks:
(none)

Inherited public predicates:
(none)

- Public predicates
 - print_flags/0
 - validate/1
- Protected predicates
- Private predicates
- Operators

Public predicates

print_flags/0

Validates the validator object itself.

Compilation flags:
static

Mode and number of proofs:
print_flags - zero_or_one

validate/1

Validates a flag value.

Compilation flags:

static

Template:

validate(Value)

Mode and number of proofs:

validate(@term) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.25 format

object

1.25.1 format

Formatted output predicates.

Availability:

logtalk_load(format(loader))

Author: Paulo Moura

Version: 1:2:0

Date: 2023-10-02

Compilation flags:

static, context_switching_calls

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - format/3
 - format/2
- Protected predicates
- Private predicates
- Operators

Public predicates

format/3

Writes a list of arguments after a format specification to the specified output stream.

Compilation flags:

static

Template:

format(Stream,Format,Arguments)

Mode and number of proofs:

format(@stream_or_alias,+atom,@list) - zero_or_one

format(@stream_or_alias,+list(character_code),@list) - zero_or_one

format(@stream_or_alias,+list(character),@list) - zero_or_one

`format/2`

Writes a list of arguments after a format specification to the current output stream.

Compilation flags:

`static`

Template:

`format(Format,Arguments)`

Mode and number of proofs:

`format(+atom,@list) - zero_or_one`

`format(+list(character_code),@list) - zero_or_one`

`format(+list(character),@list) - zero_or_one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.26 genint

object

1.26.1 genint

Global object for generating increasing non-negative integers for named counters. The predicates are declared as synchronized when the library is compiled using a backend supporting threads.

Availability:

`logtalk_load(genint(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2022-07-21

Compilation flags:

static, context_switching_calls

Imports:

public `genint_core`

Remarks:

(none)

Inherited public predicates:

`genint/2` `reset_genint/0` `reset_genint/1`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.26.2 `genint_core`

Predicates for generating increasing non-negative integers. The predicates are declared as synchronized when the library is compiled using a backend supporting threads.

Availability:

```
logtalk_load(genint(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2022-07-26

Compilation flags:

```
static
```

Dependencies:

```
(none)
```

Remarks:

```
(none)
```

Inherited public predicates:

```
(none)
```

- Public predicates
 - `reset__genint/0`
 - `reset__genint/1`
 - `genint/2`
- Protected predicates
- Private predicates
 - `counter_/2`
- Operators

Public predicates

`reset_genint/0`

Resets all counters.

Compilation flags:

static, synchronized

Mode and number of proofs:

`reset_genint - one`

`reset_genint/1`

Resets the given counter.

Compilation flags:

static, synchronized

Template:

`reset_genint(Counter)`

Mode and number of proofs:

`reset_genint(+atom) - one`

`genint/2`

Returns the next integer for a given counter.

Compilation flags:

static, synchronized

Template:

`genint(Counter,Integer)`

Mode and number of proofs:

`genint(+atom,-non_negative_integer) - one`

Protected predicates

(none)

Private predicates

counter_/2

Table of current state of counters.

Compilation flags:

dynamic

Template:

counter_(Counter,Latest)

Mode and number of proofs:

counter_(?atom,?non_negative_integer) - zero_or_more

Operators

(none)

1.27 gensym

object

1.27.1 gensym

Global object for generating unique atoms. The predicates are declared as synchronized when the library is compiled using a backend supporting threads.

Availability:

logtalk_load(gensym(loader))

Author: Paulo Moura

Version: 2:0:0

Date: 2022-07-21

Compilation flags:

static, context_switching_calls

Imports:

public gensym_core

Remarks:

(none)

Inherited public predicates:

gensym/2 reset_gensym/0 reset_gensym/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.27.2 gensym_core

Predicates for generating unique atoms. Protocol based on the gensym module of SWI-Prolog. The predicates are declared as synchronized when the library is compiled using a backend supporting threads.

Availability:

logtalk_load(gensym(loader))

Author: Paulo Moura

Version: 2:1:0

Date: 2022-07-26

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - reset_gensym/0
 - reset_gensym/1
 - gensym/2
- Protected predicates
- Private predicates
 - base_/2
- Operators

Public predicates

reset_gensym/0

Resets the generator counter for all bases.

Compilation flags:

static, synchronized

Mode and number of proofs:

reset_gensym - one

reset_gensym/1

Resets the generator counter for a given base.

Compilation flags:

static, synchronized

Template:

reset_gensym(Base)

Mode and number of proofs:

reset_gensym(+atom) - one

gensym/2

Returns a new unique atom with a given base (prefix).

Compilation flags:

static, synchronized

Template:

gensym(Base,Unique)

Mode and number of proofs:

gensym(+atom,-atom) - one

Protected predicates

(none)

Private predicates

base_/2

Table of generator bases and respective counters.

Compilation flags:

dynamic

Template:

base_(Base,Counter)

Mode and number of proofs:

base_(?atom,?integer) - zero_or_more

Operators

(none)

1.28 git

object

1.28.1 git

Predicates for accessing a git project current branch and latest commit data.

Availability:

logtalk_load([git\(loader\)](#))

Author: Paulo Moura

Version: 2:1:2

Date: 2024-03-11

Compilation flags:

static, context_switching_calls

Implements:

public [git_protocol](#)

Uses:

[os](#)

[user](#)

Remarks:

(none)

Inherited public predicates:

[branch/2](#) [commit_author/2](#) [commit_date/2](#) [commit_hash/2](#) [commit_hash_abbreviated/2](#)
[commit_log/3](#) [commit_message/2](#)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.28.2 git_protocol

Predicates for accessing a git project current branch and latest commit data.

Availability:

`logtalk_load(git(loader))`

Author: Paulo Moura

Version: 1:1:0

Date: 2022-01-21

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - branch/2
 - commit_author/2
 - commit_date/2
 - commit_hash/2
 - commit_hash_abbreviated/2
 - commit_message/2
 - commit_log/3
- Protected predicates
- Private predicates
- Operators

Public predicates

branch/2

Returns the name of the current git branch. Fails if the directory is not a git repo or a sub-directory of a git repo directory.

Compilation flags:

static

Template:

branch(Directory,Branch)

Mode and number of proofs:

branch(+atom,?atom) - zero_or_one

`commit_author/2`

Returns the latest commit author. Fails if the directory is not a git repo or a sub-directory of a git repo directory.

Compilation flags:

`static`

Template:

`commit_author(Directory,Author)`

Mode and number of proofs:

`commit_author(+atom,-atom) - zero_or_one`

`commit_date/2`

Returns the latest commit date (strict ISO 8601 format). Fails if the directory is not a git repo or a sub-directory of a git repo directory.

Compilation flags:

`static`

Template:

`commit_date(Directory,Date)`

Mode and number of proofs:

`commit_date(+atom,-atom) - zero_or_one`

`commit_hash/2`

Returns the latest commit hash. Fails if the directory is not a git repo or a sub-directory of a git repo directory.

Compilation flags:

`static`

Template:

`commit_hash(Directory,Hash)`

Mode and number of proofs:

`commit_hash(+atom,-atom) - zero_or_one`

`commit_hash_abbreviated/2`

Returns the latest commit abbreviated hash. Fails if the directory is not a git repo or a sub-directory of a git repo directory.

Compilation flags:

`static`

Template:

`commit_hash_abbreviated(Directory,Hash)`

Mode and number of proofs:

`commit_hash_abbreviated(+atom,-atom) - zero_or_one`

`commit_message/2`

Returns the latest commit message. Fails if the directory is not a git repo or a sub-directory of a git repo directory.

Compilation flags:

`static`

Template:

`commit_message(Directory,Message)`

Mode and number of proofs:

`commit_message(+atom,-atom) - zero_or_one`

`commit_log/3`

Returns the git latest commit log output for the given format (see e.g. <https://git-scm.com/docs/pretty-formats>). Fails if the directory is not a git repo or a sub-directory of a git repo directory.

Compilation flags:

`static`

Template:

`commit_log(Directory,Format,Output)`

Mode and number of proofs:

`commit_log(+atom,+atom,-atom) - zero_or_one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.29 grammars

object

1.29.1 `blank_grammars(Format)`

Blank grammars.

Availability:

`logtalk_load(grammars(loader))`

Author: Paulo Moura

Version: 0:3:1

Date: 2022-10-08

Compilation flags:

static, context_switching_calls

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - white_space//0
 - white_spaces//0
 - space//0
 - spaces//0
 - tab//0
 - tabs//0
 - new_line//0
 - new_lines//0
 - blank//0
 - blanks//0
 - non_blank//1
 - non_blanks//1
 - control//0
 - controls//0
- Protected predicates
- Private predicates
- Operators

Public predicates

`white_space//0`

Consumes a single space or tab.

Compilation flags:

`static`

Mode and number of proofs:

`white_space - zero_or_one`

`white_spaces//0`

Consumes zero or more spaces and tabs.

Compilation flags:

`static`

Mode and number of proofs:

`white_spaces - one`

`space//0`

Consumes a single space.

Compilation flags:

`static`

Mode and number of proofs:

`space - zero_or_one`

`spaces//0`

Consumes zero or more spaces.

Compilation flags:

`static`

Mode and number of proofs:

`spaces - one`

`tab//0`

Consumes a single tab.

Compilation flags:

`static`

Mode and number of proofs:

`tab - zero_or_one`

`tabs//0`

Consumes zero or more tabs.

Compilation flags:

`static`

Mode and number of proofs:

`tabs - one`

`new_line//0`

Consumes a single new line.

Compilation flags:

`static`

Mode and number of proofs:

`new_line - zero_or_one`

`new_lines//0`

Consumes zero or more new lines.

Compilation flags:

`static`

Mode and number of proofs:

`new_lines - one`

`blank//0`

Consumes a single space, tab, vertical tab, line feed, or new line.

Compilation flags:

`static`

Mode and number of proofs:

`blank - zero_or_one`

`blanks//0`

Consumes zero or more spaces, tabs, vertical tabs, line feeds, or new lines.

Compilation flags:

`static`

Mode and number of proofs:

`blanks - one`

`non_blank//1`

Returns a single non-blank character or character code.

Compilation flags:

`static`

Template:

`non_blank(NonBlank)`

Mode and number of proofs:

`non_blank(-atomic) - zero_or_one`

`non_blanks//1`

Returns a (possibly empty) list of non-blank characters or character codes.

Compilation flags:

`static`

Template:

`non_blanks(NonBlanks)`

Mode and number of proofs:

`non_blanks(-list(atomic)) - one`

`control//0`

Consumes a single control character or character code. Support for the null control character depends on the Prolog backend.

Compilation flags:

`static`

Mode and number of proofs:

`control - zero_or_one`

`controls//0`

Consumes zero or more control characters or character codes. Support for the null control character depends on the Prolog backend.

Compilation flags:

`static`

Mode and number of proofs:

`controls - one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

object

1.29.2 ip_grammars(Format)

IP address grammars.

Availability:

logtalk_load(grammars(loader))

Author: Paulo Moura

Version: 0:1:1

Date: 2022-10-08

Compilation flags:

static, context_switching_calls

Uses:

number_grammars(Format)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - ipv4//1
 - ipv6//1
- Protected predicates
- Private predicates
- Operators

Public predicates

ipv4//1

Parses an IPv4 network address in the format XXX.XXX.XXX.XXX where each XXX is an octet (i.e., an integer between 0 and 255).

Compilation flags:

static

Template:

ipv4(Octets)

Mode and number of proofs:

ipv4(?list(integer)) - zero_or_one

ipv6//1

Parses an IPv6 network address in the format XXXX.XXXX.XXXX.XXXX.XXXX.XXXX.XXXX.XXXX where each X is a hexadecimal digit.

Compilation flags:

static

Template:

ipv6(HexDigits)

Mode and number of proofs:

ipv6(?list(integer)) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.29.3 number_grammars(Format)

Number grammars.

Availability:

logtalk_load(grammars(loader))

Author: Paulo Moura

Version: 0:2:2

Date: 2024-03-14

Compilation flags:

static, context_switching_calls

Uses:

list

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - bit//1
 - bits//1
 - digit//1
 - digits//1
 - hex_digit//1
 - hex_digits//1
 - natural//1
 - integer//1
 - float//1
 - number//1
 - sign//1
 - dot//1
- Protected predicates
- Private predicates
- Operators

Public predicates

`bit//1`

Parses a single bit.

Compilation flags:
static

Template:
bit(Bit)
Mode and number of proofs:
bit(?integer) - zero_or_one

`bits//1`

Parses a sequence of one or more bits.

Compilation flags:
static

Template:
bits(Bits)
Mode and number of proofs:
bits(?list(integer)) - zero_or_one

`digit//1`

Parses a single decimal digit.

Compilation flags:
static

Template:
digit(Digit)
Mode and number of proofs:
digit(?atomic) - zero_or_one

`digits//1`

Parses a sequence of zero or more digits.

Compilation flags:
 `static`

Template:
 `digits(Digits)`
Mode and number of proofs:
 `digits(?list(atomic)) - one`

`hex_digit//1`

Parses a single hexa-decimal digit.

Compilation flags:
 `static`

Template:
 `hex_digit(HexDigit)`
Mode and number of proofs:
 `hex_digit(?atomic) - zero_or_one`

`hex_digits//1`

Parses a sequence of zero or more hexa-decimal digits.

Compilation flags:
 `static`

Template:
 `hex_digits(HexDigits)`
Mode and number of proofs:

`hex_digits(?list(atomic)) - one`

`natural//1`

Parses a natural number (a non signed integer).

Compilation flags:

`static`

Template:

`natural(Natural)`

Mode and number of proofs:

`natural(?non_negative_integer) - zero_or_one`

`integer//1`

Parses an integer.

Compilation flags:

`static`

Template:

`integer(Integer)`

Mode and number of proofs:

`integer(?integer) - zero_or_one`

`float//1`

Parses a float.

Compilation flags:

`static`

Template:

`float(Float)`

Mode and number of proofs:

`float(?float) - zero_or_one`

`number//1`

Parses a number (an integer or a float).

Compilation flags:

`static`

Template:

`number(Number)`

Mode and number of proofs:

`number(?number) - zero_or_one`

`sign//1`

Parses a number sign (plus or minus).

Compilation flags:

`static`

Template:

`sign(Sign)`

Mode and number of proofs:

`sign(?atomic) - zero_or_one`

`dot//1`

Parses a decimal dot.

Compilation flags:

`static`

Template:

`dot(Dot)`

Mode and number of proofs:

`dot(?atomic) - zero_or_one`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.29.4 `sequence_grammars`

Sequence grammars.

Availability:

`logtalk_load(grammars(loader))`

Author: Paulo Moura

Version: 0:3:0

Date: 2023-12-09

Compilation flags:

`static, context_switching_calls`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - zero_or_more//2
 - one_or_more//2
 - zero_or_more//1
 - one_or_more//1
 - zero_or_more//0
 - one_or_more//0
 - without//2
- Protected predicates
- Private predicates
- Operators

Public predicates

zero_or_more//2

Eagerly collect zero or more terminals that satisfy the given closure.

Compilation flags:

static

Template:

zero_or_more(Closure,Terminals)

Meta-predicate template:

zero_or_more(1,*)

Mode and number of proofs:

zero_or_more(+callable,-list(atomic)) - one

`one_or_more//2`

Eagerly collect one or more terminals that satisfy the given closure.

Compilation flags:

`static`

Template:

`one_or_more(Closure,Terminals)`

Meta-predicate template:

`one_or_more(1,*)`

Mode and number of proofs:

`one_or_more(+callable,-list(atomic)) - zero_or_one`

`zero_or_more//1`

Eagerly collect zero or more terminals.

Compilation flags:

`static`

Template:

`zero_or_more(Terminals)`

Mode and number of proofs:

`zero_or_more(-list(atomic)) - one`

`one_or_more//1`

Eagerly collect one or more terminals.

Compilation flags:

`static`

Template:

`one_or_more(Terminals)`

Mode and number of proofs:

`one_or_more(-list(atomic)) - zero_or_one`

`zero_or_more//0`

Eagerly parse zero or more terminals.

Compilation flags:

`static`

Mode and number of proofs:

`zero_or_more - one`

`one_or_more//0`

Eagerly parse one or more terminals.

Compilation flags:

`static`

Mode and number of proofs:

`one_or_more - zero_or_one`

`without//2`

Collects input terminals until one of the stop terminals is found. The stop terminals are excluded from the collected terminals.

Compilation flags:

`static`

Template:

`without(StopTerminals,Terminals)`

Mode and number of proofs:

`without(+list(atomic),-list(atomic)) - one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.30 heaps

object

1.30.1 heap(Order)

Heap implementation, parameterized by the order to be used to compare keys (< or >).

Availability:

logtalk__load(heaps(loader))

Author: Richard O’Keefe; adapted to Logtalk by Paulo Moura and Victor Lagerkvist.

Version: 1:1:0

Date: 2019-05-18

Compilation flags:

static, context__switching__calls

Implements:

public `heapp`

Extends:

public `compound`

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 as_heap/2 as_list/2 check/1 delete/4
depth/2 empty/1 ground/1 insert/4 insert_all/3 merge/3 new/1 numbervars/1 numbervars/3
occurs/2 singletons/2 size/2 subsumes/2 subterm/2 top/3 top_next/5 valid/1 variables/2
variant/2 varnumbers/2 varnumbers/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

minheap, maxheap

protocol

1.30.2 heapp

Heap protocol. Key-value pairs are represented as Key-Value.

Availability:

logtalk_load(heaps(loader))

Author: Richard O'Keefe; adapted to Logtalk by Paulo Moura and Victor Lagerkvist.

Version: 1:0:1

Date: 2010-11-13

Compilation flags:
static

Dependencies:
(none)

Remarks:
(none)

Inherited public predicates:
(none)

- Public predicates
 - insert/4
 - insert_all/3
 - delete/4
 - merge/3
 - empty/1
 - size/2
 - as_list/2
 - as_heap/2
 - top/3
 - top_next/5
- Protected predicates
- Private predicates
- Operators

Public predicates

`insert/4`

Inserts the new pair into a heap, returning the updated heap.

Compilation flags:

`static`

Template:

`insert(Key, Value, Heap, NewHeap)`

Mode and number of proofs:

`insert(+key, +value, +heap, -heap) - one`

`insert_all/3`

Inserts a list of pairs into a heap, returning the updated heap.

Compilation flags:

`static`

Template:

`insert_all(List, Heap, NewHeap)`

Mode and number of proofs:

`insert_all(@list(pairs), +heap, -heap) - one`

`delete/4`

Deletes and returns the top pair in a heap returning the updated heap.

Compilation flags:

`static`

Template:

`delete(Heap, TopKey, TopValue, NewHeap)`

Mode and number of proofs:

`delete(+heap, ?key, ?value, -heap) - zero_or_one`

`merge/3`

Merges two heaps.

Compilation flags:
static

Template:
merge(Heap1,Heap2,NewHeap)
Mode and number of proofs:
merge(+heap,+heap,-heap) - one

`empty/1`

True if the heap is empty.

Compilation flags:
static

Template:
empty(Heap)
Mode and number of proofs:
empty(@heap) - zero_or_one

`size/2`

Returns the number of heap elements.

Compilation flags:
static

Template:
size(Heap,Size)
Mode and number of proofs:

`size(+heap,?integer) - zero_or_one`

`as_list/2`

Returns the current set of pairs in the heap as a list, sorted into ascending order of the keys.

Compilation flags:

`static`

Template:

`as_list(Heap,List)`

Mode and number of proofs:

`as_list(+heap,-list) - one`

`as_heap/2`

Constructs a heap from a list of pairs.

Compilation flags:

`static`

Template:

`as_heap(List,Heap)`

Mode and number of proofs:

`as_heap(+list,-heap) - one`

`top/3`

Returns the top pair in the heap. Fails if the heap is empty.

Compilation flags:

`static`

Template:

```
top(Heap,TopKey,TopValue)
```

Mode and number of proofs:

```
top(+heap,?key,?value) - zero_or_one
```

```
top_next/5
```

Returns the top pair and the next pair in the heap. Fails if the heap does not have at least two elements.

Compilation flags:

```
static
```

Template:

```
top_next(Heap,TopKey,TopValue,NextKey,NextValue)
```

Mode and number of proofs:

```
top_next(+heap,?key,?value,?key,?value) - zero_or_one
```

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

 See also

[heap\(Ord\)](#)

object

1.30.3 maxheap

Max-heap implementation. Uses standard order to compare keys.

Availability:

`logtalk_load(heaps(loader))`

Author: Paulo Moura.

Version: 1:0:0

Date: 2010-02-19

Compilation flags:

`static, context__switching__calls`

Extends:

`public heap(>)`

Remarks:

`(none)`

Inherited public predicates:

`(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 as_heap/2 as_list/2 check/1 delete/4
depth/2 empty/1 ground/1 insert/4 insert_all/3 merge/3 new/1 numbervars/1 numbervars/3
occurs/2 singletons/2 size/2 subsumes/2 subterm/2 top/3 top_next/5 valid/1 variables/2
variant/2 varnumbers/2 varnumbers/3`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.30.4 minheap

Min-heap implementation. Uses standard order to compare keys.

Availability:

`logtalk_load(heaps(loader))`

Author: Paulo Moura.

Version: 1:0:0

Date: 2010-02-19

Compilation flags:

`static, context_switching_calls`

Extends:

`public heap(<)`

Remarks:

(none)

Inherited public predicates:

`(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 as_heap/2 as_list/2 check/1 delete/4
depth/2 empty/1 ground/1 insert/4 insert_all/3 merge/3 new/1 numbervars/1 numbervars/3
occurs/2 singletons/2 size/2 subsumes/2 subterm/2 top/3 top_next/5 valid/1 variables/2
variant/2 varnumbers/2 varnumbers/3`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.31 help

object

1.31.1 help

Command-line help for Logtalk libraries, entities, plus built-in control constructs, predicates, non-terminals, and methods.

Availability:

```
logtalk_load(help(loader))
```

Author: Paulo Moura

Version: 0:37:0

Date: 2025-05-09

Compilation flags:

```
static, context_switching_calls, complements(allow)
```

Implements:

public forwarding

Uses:

atom

os

user

Remarks:

(none)

Inherited public predicates:

apis/0 apis/1 forward/1 handbook/0 handbook/1 man/1

- Public predicates
 - help/0
 - (/)/2
 - (//)/2
 - completion/2
 - completions/2
 - built_in_directive/4
 - built_in_predicate/4
 - built_in_method/4
 - control_construct/4
 - built_in_non_terminal/4
 - library/0
 - library/1
 - entity/1
 - manuals/0
- Protected predicates
- Private predicates
- Operators

Public predicates

`help/0`

Prints instructions on how to use the help tool.

Compilation flags:

`static`

Mode and number of proofs:

`help - one`

`(/)/2`

Provides help on the Functor/Arity built-in control construct, directive, predicate, or method.

Compilation flags:

`static`

Template:

`Functor/Arity`

Mode and number of proofs:

`+atom/ +integer - zero__or__one`

`(//)/2`

Provides help on the Functor//Arity built-in non-terminal.

Compilation flags:

`static`

Template:

`Functor//Arity`

Mode and number of proofs:

`+atom// +integer - zero__or__one`

completion/2

Provides a completion pair, Completion-Page, for a given prefix.

Compilation flags:

static

Template:

completion(Prefix,Completion)

Mode and number of proofs:

completion(+atom,-pair) - zero_or_more

completions/2

Provides a list of completions pairs, Completion-Page, for a given prefix.

Compilation flags:

static

Template:

completions(Prefix,Completions)

Mode and number of proofs:

completions(+atom,-lists(pair)) - zero_or_more

built_in_directive/4

Provides access to the HTML documenting files describing built-in directives.

Compilation flags:

static

Template:

built_in_directive(Functor,Arity,Directory,Basename)

Mode and number of proofs:

built_in_directive(?atom,?integer,-atom,-atom) - zero_or_more

`built_in_predicate/4`

Provides access to the HTML documenting files describing built-in predicates.

Compilation flags:

`static`

Template:

`built_in_predicate(Functor,Arity,Directory,Basename)`

Mode and number of proofs:

`built_in_predicate(?atom,?integer,-atom,-atom) - zero_or_more`

`built_in_method/4`

Provides access to the HTML documenting files describing built-in methods.

Compilation flags:

`static`

Template:

`built_in_method(Functor,Arity,Directory,Basename)`

Mode and number of proofs:

`built_in_method(?atom,?integer,-atom,-atom) - zero_or_more`

`control_construct/4`

Provides access to the HTML documenting files describing built-in control constructs.

Compilation flags:

`static`

Template:

`control_construct(Functor,Arity,Directory,Basename)`

Mode and number of proofs:

`control_construct(?atom,?integer,-atom,-atom) - zero_or_more`

`built_in_non_terminal/4`

Provides access to the HTML documenting files describing built-in DCG non-terminals.

Compilation flags:

`static`

Template:

`built_in_non_terminal(Functor,Arity,Directory,Basename)`

Mode and number of proofs:

`built_in_non_terminal(?atom,?integer,-atom,-atom) - zero_or_more`

`library/0`

Provides help on the standard Logtalk library.

Compilation flags:

`static`

Mode and number of proofs:

`library - one`

`library/1`

Provides help on the standard Logtalk libraries, library predicates, and library non-terminals.

Compilation flags:

`static`

Template:

`library(Topic)`

Mode and number of proofs:

`library(+atom) - zero_or_one`

`library(+predicate_indicator) - zero_or_one`

`library(+non_terminal_indicator) - zero_or_one`

entity/1

Provides help on Logtalk entities (objects, protocols, or categories).

Compilation flags:

static

Template:

entity(Entity)

Mode and number of proofs:

entity(+entity_identifier) - zero_or_one

manuals/0

Provides access to the Logtalk User and Reference manuals.

Compilation flags:

static

Mode and number of proofs:

manuals - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.31.2 `help_info_support`

Experimental help predicates for inline browsing of the Texinfo versions of the Handbook and APIs documentation. Currently requires Ciao Prolog, ECLiPSe, GNU Prolog, XVM, SICStus Prolog, SWI-Prolog, Trealla Prolog, XSB, or YAP as the backend running on a POSIX system.

Availability:

```
logtalk_load(help(loader))
```

Author: Paulo Moura

Version: 0:9:0

Date: 2025-05-02

Compilation flags:

```
static
```

Complements:

```
help
```

Uses:

```
os
```

```
user
```

Remarks:

```
(none)
```

Inherited public predicates:

```
(none)
```

- Public predicates
 - `handbook/0`
 - `handbook/1`
 - `apis/0`
 - `apis/1`
 - `man/1`
- Protected predicates
- Private predicates
- Operators

Public predicates

[handbook/0](#)

Opens inline the Texinfo version of the Handbook.

Compilation flags:
static

Mode and number of proofs:
handbook - one

[handbook/1](#)

Opens inline the Texinfo version of the Handbook at the given topic.

Compilation flags:
static

Template:
handbook(Topic)
Mode and number of proofs:
handbook(+atom) - one
handbook(+predicate_indicator) - one
handbook(+non_terminal_indicator) - one

[apis/0](#)

Opens inline the Texinfo version of the APIs documentation.

Compilation flags:
static

Mode and number of proofs:
apis - one

[apis/1](#)

Opens inline the Texinfo version of the APIs documentation at the given topic.

Compilation flags:

static

Template:

apis(Topic)

Mode and number of proofs:

apis(+atom) - one

apis(+predicate_indicator) - one

apis(+non_terminal_indicator) - one

[man/1](#)

Opens inline the man page of the given script.

Compilation flags:

static

Template:

man(Script)

Mode and number of proofs:

man(+atom) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.32 hierarchies

category

1.32.1 class_hierarchy

Class hierarchy predicates.

Availability:

`logtalk_load(hierarchies(loader))`

Author: Paulo Moura

Version: 1:1:0

Date: 2006-02-20

Compilation flags:

`static`

Implements:

`public class_hierarchy`

Remarks:

(none)

Inherited public predicates:

`ancestor/1 ancestors/1 class/1 classes/1 descendant/1 descendant_class/1 descendant_classes/1
descendant_instance/1 descendant_instances/1 descendants/1 instance/1 instances/1 leaf/1
leaf_class/1 leaf_classes/1 leaf_instance/1 leaf_instances/1 leaves/1 subclass/1 subclasses/1
superclass/1 superclasses/1`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.32.2 class_hierarchy

Class hierarchy protocol.

Availability:

`logtalk_load(hierarchies(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2000-07-24

Compilation flags:

`static`

Extends:

`public hierarchy`

Remarks:

(none)

Inherited public predicates:

`ancestor/1 ancestors/1 descendant/1 descendants/1 leaf/1 leaves/1`

- Public predicates
 - class/1
 - classes/1
 - instance/1
 - instances/1
 - subclass/1
 - subclasses/1
 - superclass/1
 - superclasses/1
 - leaf_instance/1
 - leaf_instances/1
 - leaf_class/1
 - leaf_classes/1
 - descendant_instance/1
 - descendant_instances/1
 - descendant_class/1
 - descendant_classes/1
- Protected predicates
- Private predicates
- Operators

Public predicates

class/1

Returns, by backtracking, all object classes.

Compilation flags:

static

Template:

class(Class)

Mode and number of proofs:

class(?object) - zero_or_more

classes/1

List of all object classes.

Compilation flags:

static

Template:

classes(Classes)

Mode and number of proofs:

classes(-list) - one

instance/1

Returns, by backtracking, all class instances.

Compilation flags:

static

Template:

instance(Instance)

Mode and number of proofs:

instance(?object) - zero_or_more

instances/1

List of all class instances.

Compilation flags:

static

Template:

instances(Instances)

Mode and number of proofs:

instances(-list) - one

subclass/1

Returns, by backtracking, all class subclasses.

Compilation flags:

static

Template:

subclass(Subclass)

Mode and number of proofs:

subclass(?object) - zero_or_more

subclasses/1

List of all class subclasses.

Compilation flags:

static

Template:

subclasses(Subclasses)

Mode and number of proofs:

subclasses(-list) - one

superclass/1

Returns, by backtracking, all class superclasses.

Compilation flags:

static

Template:

superclass(Superclass)

Mode and number of proofs:

superclass(?object) - zero_or_more

`superclasses/1`

List of all class superclasses.

Compilation flags:

`static`

Template:

`superclasses(Superclasses)`

Mode and number of proofs:

`superclasses(-list) - one`

`leaf_instance/1`

Returns, by backtracking, all class leaf instances.

Compilation flags:

`static`

Template:

`leaf_instance(Leaf)`

Mode and number of proofs:

`leaf_instance(?object) - zero_or_more`

`leaf_instances/1`

List of all class leaf instances.

Compilation flags:

`static`

Template:

`leaf_instances(Leaves)`

Mode and number of proofs:

`leaf_instances(-list) - one`

`leaf_class/1`

Returns, by backtracking, all class leaf subclasses.

Compilation flags:

`static`

Template:

`leaf_class(Leaf)`

Mode and number of proofs:

`leaf_class(?object) - zero_or_more`

`leaf_classes/1`

List of all class leaf leaf subclasses.

Compilation flags:

`static`

Template:

`leaf_classes(Leaves)`

Mode and number of proofs:

`leaf_classes(-list) - one`

`descendant_instance/1`

Returns, by backtracking, all class descendant instances.

Compilation flags:

`static`

Template:

`descendant_instance(Descendant)`

Mode and number of proofs:

`descendant_instance(?object) - zero_or_more`

`descendant_instances/1`

List of all class descendant instances.

Compilation flags:

`static`

Template:

`descendant_instances(Descendants)`

Mode and number of proofs:

`descendant_instances(-list) - one`

`descendant_class/1`

Returns, by backtracking, all class descendant subclasses.

Compilation flags:

`static`

Template:

`descendant_class(Descendant)`

Mode and number of proofs:

`descendant_class(?object) - zero_or_more`

`descendant_classes/1`

List of all class descendant subclasses.

Compilation flags:

`static`

Template:

`descendant_classes(Descendants)`

Mode and number of proofs:

`descendant_classes(-list) - one`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

[class_hierarchy](#)

protocol

1.32.3 hierarchy

Common hierarchy protocol for prototype and class hierarchies.

Availability:

`logtalk_load(hierarchies(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2000-07-24

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - ancestor/1
 - ancestors/1
 - leaf/1
 - leaves/1
 - descendant/1
 - descendants/1
- Protected predicates
- Private predicates
- Operators

Public predicates

ancestor/1

Returns, by backtracking, all object ancestors.

Compilation flags:

static

Template:

ancestor(Ancestor)

Mode and number of proofs:

ancestor(?object) - zero_or_more

ancestors/1

List of all object ancestors.

Compilation flags:

static

Template:

ancestors(Ancestors)

Mode and number of proofs:

ancestors(-list) - one

`leaf/1`

Returns, by backtracking, all object leaves.

Compilation flags:

`static`

Template:

`leaf(Leaf)`

Mode and number of proofs:

`leaf(?object) - zero_or_more`

`leaves/1`

List of all object leaves.

Compilation flags:

`static`

Template:

`leaves(Leaves)`

Mode and number of proofs:

`leaves(-list) - one`

`descendant/1`

Returns, by backtracking, all object descendants.

Compilation flags:

`static`

Template:

`descendant(Descendant)`

Mode and number of proofs:

descendant(?object) - zero_or_more

descendants/1

List of all object descendants.

Compilation flags:

static

Template:

descendants(Descendants)

Mode and number of proofs:

descendants(-list) - one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

category

1.32.4 proto_hierarchy

Prototype hierarchy predicates.

Availability:

logtalk_load(hierarchies(loader))

Author: Paulo Moura

Version: 1:1:0

Date: 2006-02-20

Compilation flags:

static

Implements:

public `proto_hierarchyp`

Remarks:

(none)

Inherited public predicates:

`ancestor/1` `ancestors/1` `descendant/1` `descendants/1` `extension/1` `extensions/1` `leaf/1` `leaves/1`
`parent/1` `parents/1`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.32.5 proto_hierarchy

Prototype hierarchy protocol.

Availability:

`logtalk_load(hierarchies(loader))`

Author: Paulo Moura

Version: 1:1:0

Date: 2006-02-20

Compilation flags:

`static`

Extends:

`public hierarchy`

Remarks:

`(none)`

Inherited public predicates:

`ancestor/1 ancestors/1 descendant/1 descendants/1 leaf/1 leaves/1`

- Public predicates
 - `parent/1`
 - `parents/1`
 - `extension/1`
 - `extensions/1`
- Protected predicates
- Private predicates
- Operators

Public predicates

parent/1

Returns, by backtracking, all object parents.

Compilation flags:

static

Template:

parent(Parent)

Mode and number of proofs:

parent(?object) - zero_or_more

parents/1

List of all object parents.

Compilation flags:

static

Template:

parents(Parents)

Mode and number of proofs:

parents(-list) - one

extension/1

Returns, by backtracking, all object direct descendants.

Compilation flags:

static

Template:

extension(Extension)

Mode and number of proofs:

extension(?object) - zero_or_more

`extensions/1`

List of all object direct descendants.

Compilation flags:
`static`

Template:
`extensions(Extensions)`
Mode and number of proofs:
`extensions(-list) - one`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

`proto_hierarchy`

1.33 hook_flows

object

1.33.1 `hook_pipeline(Pipeline)`

- Pipeline - List of hook objects.

Use a pipeline (represented using a list) of hook objects to expand terms and goals. The expansion results from a hook object are passed to the next hook object in the pipeline.

Availability:

```
logtalk_load(hook_flows(loader))
```

Author: Paulo Moura

Version: 2:0:0

Date: 2024-09-27

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public expanding
```

Remarks:

- Usage: Compile source files that should be expanded using the pipeline of hook objects using the compiler option `hook(hook_pipeline(Pipeline))`.

Inherited public predicates:

```
goal_expansion/2 term_expansion/2
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

➡ See also

`hook_set(Set)`

object

1.33.2 `hook_set(Set)`

- Set - Set (list) of hook objects.

Use a set (represented using a list) of hook objects to expand terms and goals. The hook objects are tried in sequence until one of them succeeds in expanding the current term (goal) into a different term (goal).

Availability:

`logtalk_load(hook_flows(loader))`

Author: Paulo Moura

Version: 2:0:0

Date: 2024-09-27

Compilation flags:

`static, context_switching_calls`

Implements:

public `expanding`

Remarks:

- Usage: Compile source files that should be expanded using the set of hook objects using the compiler option `hook(hook_set(Set))`.

Inherited public predicates:

`goal_expansion/2` `term_expansion/2`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

`hook_pipeline(Pipeline)`

1.34 hook_objects

object

1.34.1 backend_adapter_hook

This hook object applies the expansion rules defined in the Prolog backend adapter file.

Availability:

```
logtalk_load(hook_objects(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2020-02-17

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public expanding
```

Remarks:

```
(none)
```

Inherited public predicates:

```
goal_expansion/2 term_expansion/2
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also

`default_workflow_hook`, `identity_hook`, `grammar_rules_hook`, `prolog_module_hook(Module)`, `object_wrapper_hook`, `write_to_stream_hook(Stream,Options)`, `write_to_stream_hook(Stream)`, `print_goal_hook`, `suppress_goal_hook`

object

1.34.2 `default_workflow_hook`

Use this object as the default hook object to restore the default expansion pipeline semantics used by the compiler.

Availability:

`logtalk_load(hook_objects(loader))`

Author: Paulo Moura

Version: 1:0:1

Date: 2020-03-24

Compilation flags:

`static`, `context_switching_calls`

Implements:

public `expanding`

Remarks:

(none)

Inherited public predicates:

`goal_expansion/2` `term_expansion/2`

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also

[backend_adapter_hook](#), [identity_hook](#), [grammar_rules_hook](#), [prolog_module_hook\(Module\)](#), [object_wrapper_hook](#), [write_to_stream_hook\(Stream,Options\)](#), [write_to_stream_hook\(Stream\)](#), [print_goal_hook](#), [suppress_goal_hook](#)

object

1.34.3 `grammar_rules_hook`

This hook object expands grammar rules into clauses.

Availability:

```
logtalk_load(hook_objects(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2020-02-14

Compilation flags:

static, context_switching_calls

Implements:

public expanding

Remarks:

(none)

Inherited public predicates:

goal_expansion/2 term_expansion/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also

backend_adapter_hook, default_workflow_hook, identity_hook, prolog_module_hook(Module),
object_wrapper_hook, write_to_stream_hook(Stream,Options), write_to_stream_hook(Stream),
print_goal_hook, suppress_goal_hook

object

1.34.4 identity_hook

Use this object as a file specific hook object to prevent any (other) user-defined expansion rules to be applied when compiling the file.

Availability:

```
logtalk_load(hook_objects(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2020-02-15

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public expanding
```

Remarks:

```
(none)
```

Inherited public predicates:

```
goal_expansion/2 term_expansion/2
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also

`backend_adapter_hook`, `default_workflow_hook`, `grammar_rules_hook`, `pro-`
`log_module_hook`(Module), `object_wrapper_hook`, `write_to_stream_hook`(Stream,Options),
`write_to_stream_hook`(Stream), `print_goal_hook`, `suppress_goal_hook`

object

1.34.5 `object_wrapper_hook`

Use this object to wrap the contents of a plain Prolog file in an object named after the file. The wrapper sets the `context_switching_calls` flag to allow, enabling calling of the wrapped predicates using the `<</2` control construct.

Availability:

`logtalk_load(hook_objects(loader))`

Author: Paulo Moura

Version: 1:1:0

Date: 2020-10-30

Compilation flags:

`static`, `context_switching_calls`

Implements:

`public` `expanding`

Uses:

`os`

Remarks:

(none)

Inherited public predicates:

`goal_expansion/2` `term_expansion/2`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also

`object_wrapper_hook(Protocol)`, `object_wrapper_hook(Name,Relations)`, `back-end_adapter_hook`, `default_workflow_hook`, `grammar_rules_hook`, `prolog_module_hook(Module)`, `write_to_stream_hook(Stream,Options)`, `write_to_stream_hook(Stream)`, `print_goal_hook`, `suppress_goal_hook`

object

1.34.6 `object_wrapper_hook(Protocol)`

Use this object to wrap the contents of a plain Prolog file in an object named after the file that implements the given protocol.

Availability:

`logtalk_load(hook_objects(loader))`

Author: Paulo Moura

Version: 1:0:0
Date: 2021-11-24

Compilation flags:
static, context_switching_calls

Implements:
public [expanding](#)

Uses:
[os](#)

Remarks:
(none)

Inherited public predicates:
[goal_expansion/2](#) [term_expansion/2](#)

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

➡ See also

```
object_wrapper_hook,      object_wrapper_hook(Name,Relations),      backend_adapter_hook,
default_workflow_hook,   grammar_rules_hook,        prolog_module_hook(Module),
write_to_stream_hook(Stream,Options), write_to_stream_hook(Stream), print_goal_hook, suppress_goal_hook
```

object

1.34.7 object_wrapper_hook(Name,Relations)

Use this object to wrap the contents of a plain Prolog file in an object with the given name and object entity relations (a list).

Availability:

```
logtalk_load(hook_objects(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2022-02-03

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public expanding
```

Remarks:

(none)

Inherited public predicates:

```
goal_expansion/2 term_expansion/2
```

- Public predicates
- Protected predicates
- Private predicates

- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also

`object_wrapper_hook`, `object_wrapper_hook(Protocol)`, `backend_adapter_hook`,
`default_workflow_hook`, `grammar_rules_hook`, `prolog_module_hook(Module)`,
`write_to_stream_hook(Stream,Options)`, `write_to_stream_hook(Stream)`, `print_goal_hook`, `suppress_goal_hook`

object

1.34.8 `print_goal_hook`

Use this object to easily print entity predicate goals before, after, or before and after calling them.

Availability:

`logtalk_load(hook_objects(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2020-03-14

Compilation flags:

`static`, `context_switching_calls`

Implements:

public `expanding`

Remarks:

- Usage: Mark a goal to be printed by prefixing it with an operator. Printing uses a comment message.
- To print goal before calling it: - Goal.
- To print goal after calling it: + Goal.
- To print goal before and after calling it: * Goal.
- Operators: This hook object uses the standard - and + prefix operators and also defines a global * prefix operator with the same type and priority.

Inherited public predicates:

`goal_expansion/2` `term_expansion/2`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also

`backend_adapter_hook`, `default_workflow_hook`, `grammar_rules_hook`, `identity_hook`, `prolog_module_hook(Module)`, `object_wrapper_hook`, `write_to_stream_hook(Stream,Options)`, `write_to_stream_hook(Stream)`, `suppress_goal_hook`

object

1.34.9 `prolog_module_hook(Module)`

This hook object applies the expansion rules defined in a Prolog module (e.g., `user`).

Availability:

`logtalk_load(hook_objects(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2020-02-17

Compilation flags:

`static, context_switching_calls`

Implements:

`public expanding`

Remarks:

`(none)`

Inherited public predicates:

`goal_expansion/2 term_expansion/2`

- `Public predicates`
- `Protected predicates`
- `Private predicates`
- `Operators`

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

➡ See also

`backend_adapter_hook`, `default_workflow_hook`, `identity_hook`, `grammar_rules_hook`, `object_wrapper_hook`, `write_to_stream_hook(Stream,Options)`, `write_to_stream_hook(Stream)`, `print_goal_hook`, `suppress_goal_hook`

object

1.34.10 `suppress_goal_hook`

Use this object to easily suppress a goal in a clause body.

Availability:

`logtalk_load(hook_objects(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2020-05-04

Compilation flags:

`static`, `context_switching_calls`

Implements:

`public expanding`

Remarks:

- Usage: Mark a goal to be suppressed by prefixing it with the `--` operator.
- Operators: This hook object uses the `--` prefix operator declared by Logtalk for use in `mode/2` directives.

Inherited public predicates:

goal_expansion/2 term_expansion/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also

backend_adapter_hook, default_workflow_hook, grammar_rules_hook, identity_hook, prolog_module_hook(Module), object_wrapper_hook, write_to_stream_hook(Stream,Options), write_to_stream_hook(Stream), print_goal_hook

object

1.34.11 write_to_file_hook(File)

This hook object writes term-expansion results to a file in canonical format. The terms are terminated by a period and a new line.

Availability:

logtalk_load(hook_objects(loader))

Author: Paulo Moura

Version: 1:0:0

Date: 2022-07-06

Compilation flags:

static, context_switching_calls

Extends:

public write_to_file_hook(File,[quoted(true),ignore_ops(true)])

Remarks:

(none)

Inherited public predicates:

goal_expansion/2 term_expansion/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also

backend_adapter_hook, default_workflow_hook, identity_hook, grammar_rules_hook,
prolog_module_hook(Module), object_wrapper_hook, write_to_file_hook(File,Options),

```
write_to_stream_hook(Stream,Options), write_to_stream_hook(Stream), print_goal_hook, suppress_goal_hook
```

object

1.34.12 write_to_file_hook(File,Options)

This hook object writes term-expansion results to a file using a list of write_term/3 options. The terms are terminated by a period and a new line.

Availability:

```
logtalk_load(hook_objects(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2022-07-06

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public expanding
```

Remarks:

```
(none)
```

Inherited public predicates:

```
goal_expansion/2 term_expansion/2
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also

backend_adapter_hook, default_workflow_hook, identity_hook, grammar_rules_hook,
prolog_module_hook(Module), object_wrapper_hook, write_to_file_hook(File),
write_to_stream_hook(Stream,Options), write_to_stream_hook(Stream), print_goal_hook, sup-
press_goal_hook

object

1.34.13 write_to_stream_hook(Stream)

This hook object writes term-expansion results to a stream in canonical format. The terms are terminated by a period and a new line.

Availability:

logtalk_load(hook_objects(loader))

Author: Paulo Moura

Version: 1:0:0

Date: 2020-02-16

Compilation flags:

static, context_switching_calls

Extends:

public write_to_stream_hook(Stream,[quoted(true),ignore_ops(true)])

Remarks:

(none)

Inherited public predicates:

`goal_expansion/2` `term_expansion/2`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also

`backend_adapter_hook`, `default_workflow_hook`, `identity_hook`, `grammar_rules_hook`, `prolog_module_hook(Module)`, `object_wrapper_hook`, `write_to_stream_hook(Stream,Options)`, `write_to_file_hook(File,Options)`, `write_to_file_hook(File)`, `print_goal_hook`, `suppress_goal_hook`

object

1.34.14 `write_to_stream_hook(Stream,Options)`

This hook object writes term-expansion results to a stream using a list of `write_term/3` options. The terms are terminated by a period and a new line.

Availability:

```
logtalk_load(hook_objects(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2020-02-16

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public expanding
```

Remarks:

```
(none)
```

Inherited public predicates:

```
goal_expansion/2 term_expansion/2
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

See also

`backend_adapter_hook`, `default_workflow_hook`, `identity_hook`, `grammar_rules_hook`,
`prolog_module_hook(Module)`, `object_wrapper_hook`, `write_to_stream_hook(Stream)`,
`write_to_file_hook(File,Options)`, `write_to_file_hook(File)`, `print_goal_hook`, `suppress_goal_hook`

1.35 html

category

1.35.1 html

HTML generation.

Availability:

`logtalk_load(html(loader))`

Author: Paul Brown and Paulo Moura

Version: 0:3:0

Date: 2021-03-30

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - generate/2
 - void_element/1
 - normal_element/2
- Protected predicates
- Private predicates
 - doctype/1
- Operators

Public predicates

generate/2

Generates HTML content using the representation specified in the first argument (stream(Stream) or file(Path)) for the term in the second argument.

Compilation flags:

static

Template:

generate(Sink,Term)

Mode and number of proofs:

generate(+compound,++term) - one_or_error

void_element/1

Enumerates, by backtracking, all void elements.

Compilation flags:

static

Template:

void_element(Element)

Mode and number of proofs:

`void_element(?atom) - zero_or_more`

`normal_element/2`

Enumerates, by backtracking, all normal elements. The value of the `Display` argument is either `inline` or `block`.

Compilation flags:

`static`

Template:

`normal_element(Element,Display)`

Mode and number of proofs:

`normal_element(?atom,?atom) - zero_or_more`

Protected predicates

(none)

Private predicates

`doctype/1`

Doctype text.

Compilation flags:

`static`

Template:

`doctype(DocType)`

Mode and number of proofs:

`doctype(?atom) - one`

Operators

(none)

object

1.35.2 html5

HTML content generation using the HTML 5 doctype.

Availability:

`logtalk_load(html(loader))`

Author: Paul Brown and Paulo Moura

Version: 1:0:0

Date: 2021-03-29

Compilation flags:

`static, context_switching_calls`

Imports:

`public html`

Remarks:

(none)

Inherited public predicates:

`generate/2 normal_element/2 void_element/1`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.35.3 xhtml11

XHTML content generation using the XHTML 1.1 doctype.

Availability:

`logtalk__load(html(loader))`

Author: Paul Brown and Paulo Moura

Version: 1:0:0

Date: 2021-03-29

Compilation flags:

`static, context_switching_calls`

Imports:

`public html`

Remarks:

(none)

Inherited public predicates:

`generate/2 normal_element/2 void_element/1`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.36 ids

object

1.36.1 ids

Generator of random identifiers with 160 bits (20 bytes) of randomness.

Availability:

```
logtalk_load(ids(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2022-11-23

Compilation flags:

```
static, context_switching_calls
```

Extends:

```
public ids(atom,20)
```

Remarks:

(none)

Inherited public predicates:

generate/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

ids(Representation,Bytes), uuid, ulid

object

1.36.2 ids(Representation,Bytes)

- Representation - Text representation for the identifier. Possible values are atom, chars, and codes.
- Bytes - Number of bytes of randomness.

Generator of random identifiers.

Availability:

```
logtalk_load(ids(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2022-11-23

Compilation flags:

```
static, context_switching_calls
```

Uses:

```
base64
fast_random
list
os
```

Remarks:

```
(none)
```

Inherited public predicates:

```
(none)
```

- Public predicates
 - generate/1
- Protected predicates
- Private predicates
- Operators

Public predicates

`generate/1`

Generate a random identifier.

Compilation flags:

`static`

Template:

`generate(Identifier)`

Mode and number of proofs:

`generate(--textids) - one`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

`ids`, `uuid`, `ulid`

1.37 intervals

object

1.37.1 interval

Basic temporal interval relations. An interval is represented by a compound term, `i/2`, with two ground arguments, the start and end points.

Availability:

```
logtalk_load(intervals(loader))
```

Author: Paulo Moura

Version: 1:2:1

Date: 2022-01-15

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public intervalp
```

Aliases:

```
intervalp before/2 as b/2
intervalp after/2 as bi/2
intervalp meets/2 as m/2
intervalp met_by/2 as mi/2
intervalp overlaps/2 as o/2
intervalp overlapped_by/2 as oi/2
intervalp starts/2 as s/2
intervalp started_by/2 as si/2
intervalp during/2 as d/2
intervalp contains/2 as di/2
intervalp finishes/2 as f/2
intervalp finished_by/2 as fi/2
intervalp equal/2 as eq/2
```

Remarks:

```
(none)
```

Inherited public predicates:

```
after/2 before/2 contains/2 during/2 equal/2 finished_by/2 finishes/2 meets/2 met_by/2
new/3 overlapped_by/2 overlaps/2 started_by/2 starts/2 valid/1
```

- Public predicates
- Protected predicates

- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.37.2 intervalp

Basic temporal interval relations protocol (based on James F. Allen Interval Algebra work).

Availability:

`logtalk_load(intervals(loader))`

Author: Paulo Moura

Version: 1:1:0

Date: 2014-04-26

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - new/3
 - valid/1
 - before/2
 - after/2
 - meets/2
 - met_by/2
 - overlaps/2
 - overlapped_by/2
 - starts/2
 - started_by/2
 - during/2
 - contains/2
 - finishes/2
 - finished_by/2
 - equal/2
- Protected predicates
- Private predicates
- Operators

Public predicates

new/3

Constructs a new interval given start and end points. The start point must strictly precede the end point.

Compilation flags:

static

Template:

new(Start,End,Interval)

Mode and number of proofs:

new(@ground,@ground,-interval) - zero_or_one

[valid/1](#)

True if Interval is a valid interval.

Compilation flags:
static

Template:
valid(Interval)
Mode and number of proofs:
valid(@interval) - zero_or_one

[before/2](#)

True if Interval1 takes place before Interval2.

Compilation flags:
static

Template:
before(Interval1,Interval2)
Mode and number of proofs:
before(@interval,@interval) - zero_or_one

[after/2](#)

True if Interval1 takes place after Interval2.

Compilation flags:
static

Template:
after(Interval1,Interval2)
Mode and number of proofs:

`after(@interval,@interval) - zero_or_one`

`meets/2`

True if Interval1 meets Interval2.

Compilation flags:

`static`

Template:

`meets(Interval1,Interval2)`

Mode and number of proofs:

`meets(@interval,@interval) - zero_or_one`

`met_by/2`

True if Interval1 is met by Interval2.

Compilation flags:

`static`

Template:

`met_by(Interval1,Interval2)`

Mode and number of proofs:

`met_by(@interval,@interval) - zero_or_one`

`overlaps/2`

True if Interval1 overlaps with Interval2.

Compilation flags:

`static`

Template:

`overlaps(Interval1,Interval2)`

Mode and number of proofs:

`overlaps(@interval,@interval) - zero_or_one`

`overlapped_by/2`

True if Interval1 is overlapped by Interval2.

Compilation flags:

`static`

Template:

`overlapped_by(Interval1,Interval2)`

Mode and number of proofs:

`overlapped_by(@interval,@interval) - zero_or_one`

`starts/2`

True if Interval1 starts Interval2.

Compilation flags:

`static`

Template:

`starts(Interval1,Interval2)`

Mode and number of proofs:

`starts(@interval,@interval) - zero_or_one`

`started_by/2`

True if Interval1 is started by Interval2.

Compilation flags:

`static`

Template:

`started_by(Interval1,Interval2)`

Mode and number of proofs:

`started_by(@interval,@interval) - zero_or_one`

`during/2`

True if Interval1 occurs during Interval2.

Compilation flags:

`static`

Template:

`during(Interval1,Interval2)`

Mode and number of proofs:

`during(@interval,@interval) - zero_or_one`

`contains/2`

True if Interval1 contains Interval2.

Compilation flags:

`static`

Template:

`contains(Interval1,Interval2)`

Mode and number of proofs:

`contains(@interval,@interval) - zero_or_one`

`finishes/2`

True if Interval1 finishes Interval2.

Compilation flags:

`static`

Template:

`finishes(Interval1,Interval2)`

Mode and number of proofs:

`finishes(@interval,@interval) - zero_or_one`

`finished_by/2`

True if Interval1 is finished by Interval2.

Compilation flags:

`static`

Template:

`finished_by(Interval1,Interval2)`

Mode and number of proofs:

`finished_by(@interval,@interval) - zero_or_one`

`equal/2`

True if Interval1 is equal to Interval2.

Compilation flags:

`static`

Template:

`equal(Interval1,Interval2)`

Mode and number of proofs:

`equal(@interval,@interval) - zero_or_one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

 See also

[interval](#)

1.38 iso8601

object

1.38.1 iso8601

ISO 8601 (and European civil calendar) compliant library of date predicates.

Availability:

```
logtalk__load(iso8601(loader))
```

Author: Daniel L. Dudley

Version: 1:0:3

Date: 2019-10-09

Compilation flags:

```
static, context_switching_calls
```

Uses:

[os](#)

Remarks:

- Scope: This object currently provides a powerful, versatile and efficient set of date-handling predicates, which—thanks to Logtalk—may be used as is on a wide range of Prolog compilers. Besides taking time to familiarize oneself with each predicate, the user should take note of the following information.

- Validation of dates: Date parts are not validated—that is the caller’s responsibility! However, not being quite heartless yet, we do provide a predicate for this purpose.
- Date arithmetic: Many of the examples illustrate a simplified method of doing date arithmetic. Note, however, that we do not generally recommend this practice—it is all too easy to make mistakes. The safest way of finding the day difference between two dates is to first convert the dates to their Julian day numbers and then subtract one from the other. Similarly, the safe way to add or subtract a day offset to a particular date is to first convert the date to its Julian day number, add or subtract the day offset, and then convert the result to its corresponding date.
- BC years: ISO 8601 specifies that the Gregorian calendar be used, yet requires that years prior to 1 AD be handled arithmetically, i.e., the year we know as 1 BC is year 0, 2 BC is year -1, 3 BC is year -2 and so on. We do not follow ISO 8601 with regard to the handling of BC years. Our date predicates will accept and interpret an input year 0 as 1 BC; however, a negative year, Year, should always be interpreted as `abs(Year) =:= Year BC`. We believe that the average person will find our handling of BC years more user-friendly than the ISO 8601 one, but we encourage feedback from users with a view to a possible change in future versions.
- Week numbers: It is possible for a day (date) to have a week number that belongs to another year. Up to three of the first days of a calendar year may belong to the last week (number) of the prior calendar year, and up to three days of the last days of a calendar year may belong to the first week (number) of the next calendar year. It for this reason that the Week parameter in `date/6-7` is a compound term, namely `week(WeekNo,ActualYear)`.
- Computation of Gregorian Easter Sunday: The algorithm is based upon the “Gaussian rule”. Proleptic use is limited to years > 1582 AD, that is, after the introduction of the Gregorian calendar.
- Some Christian feast day offsets from Easter Sunday: Carnival Monday: -48 days, Mardi Gras (Shrove Tuesday): -47 days, Ash Wednesday: -46 days, Palm Sunday: -7 days, Easter Friday: -2 days, Easter Saturday: -1 day, Easter Monday: +1 day, Ascension of Christ: +39 days, Whitsunday: +49 days, Whitmonday: +50 days, Feast of Corpus Christi: +60 days.

Inherited public predicates:

(none)

- Public predicates
 - `date/4`
 - `date/5`
 - `date/6`
 - `date/7`
 - `date_string/3`
 - `valid_date/3`
 - `leap_year/1`
 - `calendar_month/3`
 - `easter_day/3`
- Protected predicates

- Private predicates
- Operators

Public predicates

date/4

Get the system date and/or its Julian Day # or convert a Julian Day # to/from given date parts.

Compilation flags:

static

Template:

date(JD,Year,Month,Day)

JD - Julian day serial number.

Year - 0 or negative if converted BC year, positive otherwise.

Month - Normally an integer between 1 and 12 inclusive.

Day - Normally an integer between 1 and 31 inclusive depending upon month.

Mode and number of proofs:

date(?integer,?integer,?integer,?integer) - zero_or_one

Examples:

Current date (i.e., today)

date(JD,Year,Month,Day)

JD=2453471,Year=2005,Month=4,Day=10

Convert a date to its Julian day number

date(JD,2000,2,29)

JD=2451604

Convert a Julian day number to its date

date(2451604,Year,Month,Day)

Year=2000,Month=2,Day=29

What is the date of day # 60 in year 2000?

date(JD,2000,1,60)

JD=2451604

What is the Julian of the 1st day prior to 2000-1-1?

date(JD,2000,1,0)

JD=2451544

What is the Julian of the 60th day prior to 2000-1-1?

date(JD,2000,1,-59)

JD=2451485

Illegal date is auto-adjusted (see also next query)

date(JD,1900,2,29)

JD=2415080

This is the correct date!

```
date(2415080,Year,Month,Day)
Year=1900,Month=3,Day=1
```

date/5

Ditto date/4 + get/check its day-of-week #.

Compilation flags:

static

Template:

```
date(JD,Year,Month,Day,DoW)
```

JD - Julian day serial number.

Year - 0 or negative if converted BC year, positive otherwise.

Month - Normally an integer between 1 and 12 inclusive.

Day - Normally an integer between 1 and 31 inclusive depending upon month.

DoW - Day of week, where Monday=1, Tuesday=2, ..., Sunday=7.

Mode and number of proofs:

```
date(?integer,?integer,?integer,?integer,?integer) - zero_or_one
```

Examples:

Get the Julian and the day-of-week # of a date

```
date(JD,2000,2,29,DoW)
```

```
JD=2451604,DoW=2
```

Check the validity of a given date (day-of-week is 2, not 4)

```
date(_,2002,3,5,4)
```

```
no
```

Get the Julian day of a given date if it is a Sunday

```
date(JD,2004,2,29,7)
```

```
JD=2453065
```

Get the date and day-of-week # of a Julian

```
date(2451545,Year,Month,Day,DoW)
```

```
Year=2000,Month=1,Day=1,DoW=6
```

date/6

Ditto date/5 + get/check its week #.

Compilation flags:

static

Template:

date(JD,Year,Month,Day,DoW,Week)

JD - Julian day serial number.

Year - 0 or negative if converted BC year, positive otherwise.

Month - Normally an integer between 1 and 12 inclusive.

Day - Normally an integer between 1 and 31 inclusive depending upon month.

DoW - Day of week, where Monday=1, Tuesday=2, ..., Sunday=7.

Week - Compound term, week(WeekNo,ActualYear), of a day.

Mode and number of proofs:

date(?integer,?integer,?integer,?integer,?integer,?compound) - zero_or_one

Examples:

Get the day-of-week and week number of a date

date(_,2000,1,1,DoW,Week)

DoW=6,Week=week(52,1999)

Get the week number and year of this week

date(_,_,_,_,_,Week)

Week=week(7,2004)

Get the Julian number and the week of a date if it is a Sunday

date(JD,2004,2,29,7,Week)

JD=2453065,Week=week(9,2004)

Get the day-of-week and week of a Julian day number

date(2453066,_,_,_,DoW,Week)

DoW=1,Week=week(10,2004)

Check that given date data matches

date(_,2004,3,1,1,week(10,2004))

yes

What is the date of a day of week (default is 1) in given week # and year?

date(_,Year,Month,Day,DoW,week(26,2004))

Year=2004,Month=6,Day=21,DoW=1

Ditto for Sunday

date(_,Year,Month,Day,7,week(1,2005))

Year=2005,Month=1,Day=9

Ditto for Tuesday in following week

date(_,Year,Month,Day,9,week(1,2005))

Year=2005,Month=1,Day=11

Ditto for Thursday in the prior week

date(_,Year,Month,Day,4,week(0,2005))

```
Year=2004,Month=12,Day=30
Ditto for Tuesday two weeks prior
date(__,Year,Month,Day,2,week(-1,2005))
Year=2004,Month=12,Day=21
Ditto for Saturday
date(__,Year,Month,Day,6,week(53,2004))
Year=2005,Month=1,Day=1
Ditto for Monday (note automatic compensation of nonexistent week number)
date(__,Year,Month,Day,1,week(60,2004))
Year=2005,Month=2,Day=14
```

date/7

Ditto date/6 + get/check its day-of-year #.

Compilation flags:

static

Template:

```
date(JD,Year,Month,Day,DoW,Week,DoY)
JD - Julian day serial number.
Year - 0 or negative if converted BC year, positive otherwise.
Month - Normally an integer between 1 and 12 inclusive.
Day - Normally an integer between 1 and 31 inclusive depending upon month.
DoW - Day of week, where Monday=1, Tuesday=2, ..., Sunday=7.
Week - Compound term, week(WeekNo,ActualYear), of a day.
DoY - Day of year (NB! calendar year, not week # year).
```

Mode and number of proofs:

```
date(?integer,?integer,?integer,?integer,?integer,?compound,?integer) - zero_or_one
```

Examples:

```
Get the date and day-of-year of a Julian number
date(2451649,Year,Month,Day,__,__,DoY)
Year=2000,Month=4,Day=14,DoY=105

Get the Julian number, week number and day-of-year of a date, confirming that it is a Sunday
date(JD,2004,2,29,7,Week,DoY)
JD=2453065,Week=week(9,2004),DoY=60

Confirm that a date is, in fact, a specific day-of-year
date(__,2004,3,1,__,__,61)
yes

Get the Julian number, week day and day-of-year of a date
date(JD,2004,10,18,DoW,__,DoY)
```

```

    JD=2453297,DoW=1,DoY=292
  Get today's day-of-year
    date(__,__,__,__,__,DoY)
    DoY=54
  Get all missing date data (excl. Julian number) for the 60th calendar day of 2004
    date(__,2004,Month,Day,DoW,Week,60)
    Month=2,Day=29,DoW=7,Week=week(9,2004)
  Match given date data and, if true, return the missing data (excl. Julian number)
    date(__,2004,3,Day,DoW,Week,61)
    Day=1,DoW=1,Week=week(10,2004)
  Ditto (the 61st day-of-year cannot be both day 1 and 2 of the month)
    date(__,2004,__,2,__,__,61)
    no

```

date_string/3

Conversion between an ISO 8601 compliant date string and its components (truncated and expanded date representations are currently unsupported). Note that date components are not validated; that is the caller's responsibility!

Compilation flags:

static

Template:

```

date_string(Format,Components,String)
  Format - ISO 8601 format.
  Components - When bound and String is free, either a Julian number or a [Year,Month,Day]
    term; it binds to the system day/date if free When free and String is bound, it binds to an
    integer list representing the numeric elements of String.
  String - ISO 8601 formatted string correspondent to Components.

```

Mode and number of proofs:

```

date_string(+atom,+integer,?atom) - zero_or_one
date_string(+atom,?list,?atom) - zero_or_one

```

Examples:

```

Date, complete, basic (section 5.2.1.1)
  date_string('YYYYMMDD',[2004,2,29],String)
  String='20040229'
Date, complete, basic (section 5.2.1.1)
  date_string('YYYYMMDD',Components,'20040229')
  Components=[2004,2,29]
Date, complete, extended (section 5.2.1.1)
  date_string('YYYY-MM-DD',[2003,12,16],String)

```

```
String='2003-12-16'
Date, complete, extended (section 5.2.1.1)
  date__string('YYYY-MM-DD',Components,'2003-12-16')
  Components=[2003,12,16]
Date, complete, extended (section 5.2.1.1)
  date__string('YYYY-MM-DD',__,String)
  String='2004-02-17'
Date, complete, extended (section 5.2.1.1)
  date__string('YYYY-MM-DD',Components,'2004-02-17')
  Components=[2004,2,17]
Date, reduced, month (section 5.2.1.2 a)
  date__string('YYYY-MM',[2004,9,18],String)
  String='2004-09'
Date, reduced, month (section 5.2.1.2 a)
  date__string('YYYY-MM',Components,'2004-09')
  Components=[2004,9]
Date, reduced, year (section 5.2.1.2 b)
  date__string('YYYY',[1900,7,24],String)
  String='1900'
Date, reduced, year (section 5.2.1.2 b)
  date__string('YYYY',Components,'1900')
  Components=[1900]
Date, reduced, century (section 5.2.1.2 c)
  date__string('YY',2456557,String)
  String='20'
Date, reduced, century (section 5.2.1.2 c)
  date__string('YY',Components,'20')
  Components=[20]
Date, ordinal, complete (section 5.2.2.1)
  date__string('YYYYDDD',[2005,3,25],String)
  String='2005084'
Date, ordinal, complete (section 5.2.2.1)
  date__string('YYYYDDD',Components,'2005084')
  Components=[2005,84]
Date, ordinal, extended (section 5.2.2.1)
  date__string('YYYY-DDD',[1854,12,4],String)
  String='1854-338'
Date, ordinal, extended (section 5.2.2.1)
  date__string('YYYY-DDD',Components,'1854-338')
  Components=[1854,338]
Week, complete, basic (section 5.2.3.1)
  date__string('YYYYWwwD',[2000,1,2],String)
  String='1999W527'
Week, complete, basic (section 5.2.3.1)
  date__string('YYYYWwwD',Components,'1999W527')
  Components=[1999,52,7]
Week, complete, extended (section 5.2.3.1)
```

```

    date_string('YYYY-Www-D',[2003,12,29],String)
    String='2004-W01-1'
Week, complete, extended (section 5.2.3.1)
    date_string('YYYY-Www-D',Components,'2004-W01-1')
    Components=[2004,1,1]
Week, complete, extended (section 5.2.3.1)
    date_string('YYYY-Www-D',2453167,String)
    String='2004-W24-4'
Week, complete, extended (section 5.2.3.1)
    date_string('YYYY-Www-D',Components,'2004-W24-4')
    Components=[2004,24,4]
Week, reduced, basic (section 5.2.3.2)
    date_string('YYYYWww',[2004,2,29],String)
    String='2004W09'
Week, reduced, basic (section 5.2.3.2)
    date_string('YYYYWww',Components,'2004W09')
    Components=[2004,9]
Week, reduced, extended (section 5.2.3.2)
    date_string('YYYY-Www',[2004,2,29],String)
    String='2004-W09'
Week, reduced, extended (section 5.2.3.2)
    date_string('YYYY-Www',Components,'2004-W09')
    Components=[2004,9]

```

`valid_date/3`

Validate a given date in the Gregorian calendar.

Compilation flags:

static

Template:

`valid_date(Year,Month,Day)`

Mode and number of proofs:

`valid_date(+integer,+integer,+integer) - zero_or_one`

Examples:

Yes, the recent millennium was a leap year

`valid_date(2000,2,29)`

yes

2004 was also a leap year

`valid_date(2004,2,29)`

```
yes
Only 30 days in April
  valid_date(2004,4,31)
no
1 BC was a leap year
  valid_date(-1,2,29)
yes
```

`leap_year/1`

Succeed if given year is a leap year in the Gregorian calendar.

Compilation flags:

```
static
```

Template:

```
leap_year(Year)
```

Year - The Gregorian calendar year to investigate. If free, it binds to the system year.

Mode and number of proofs:

```
leap_year(?integer) - zero_or_one
```

Examples:

No, the prior centenary was not a leap year

```
leap_year(1900)
```

```
no
```

The recent millennium

```
leap_year(2000)
```

```
yes
```

This year

```
leap_year(Year)
```

```
Year=2004
```

This year (equivalent to prior query)

```
leap_year(_)
```

```
yes
```

Next centennial

```
leap_year(2100)
```

```
no
```

Year 0, equivalent to 1 BC

```
leap_year(0)
```

```
yes
```

1 BC

```
leap_year(-1)
```

```

    yes
4 BC
    leap__year(-4)
    no
5 BC
    leap__year(-5)
    yes

```

`calendar__month/3`

Compute a calendar month.

Compilation flags:

```
static
```

Template:

```
calendar__month(Year,Month,Calendar)
```

Year - The calendar year.

Month - The calendar month.

Calendar - A compound term, `m/3`, composed of three main arguments specifying year, month, and a list of week and week day numbers (calendar body).

Mode and number of proofs:

```
calendar__month(?integer,?integer,-compound) - zero_or_one
```

Examples:

Compute the calendar of March, 2005

```
calendar__month(2005,3,Calendar)
```

```
Calendar=m(2005,3,[w(9,[0,1,2,3,4,5,6]),w(10,[7,8,9,10,11,12,13]),w(11,[14,15,16,17,18,19,20]),
w(12,[21,22,23,24,25,26,27]),w(13,[28,29,30,31,0,0,0]),w(0,[0,0,0,0,0,0,0])))
```

`easter__day/3`

Compute a Gregorian Easter Sunday.

Compilation flags:

```
static
```

Template:

`easter_day(Year,Month,Day)`

Year - Integer specifying the year to be investigated.

Month - Month in which Easter Sunday falls for given year.

Day - Day of month in which Easter Sunday falls for given year.

Mode and number of proofs:

`easter_day(?integer,-integer,-integer) - zero_or_one`

Examples:

Compute Easter Sunday for a particular year

`easter_day(2006,Month,Day)`

Month=4,Day=16

Compute Easter Sunday for the current year

`easter_day(Year,Month,Day)`

Year=2005,Month=3,Day=27

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.39 issue_creator

object

1.39.1 issue_creator

Support for automatically creating bug report issues for failed tests in GitHub or GitLab servers.

Availability:

`logtalk_load(issue_creator(loader))`

Author: Paulo Moura

Version: 0:12:1

Date: 2025-03-03

Compilation flags:

static, context_switching_calls

Provides:

logtalk::message_hook/4

Uses:

git

os

term_io

user

Remarks:

- Usage: This tool is automatically loaded and used from the logtalk_tester automation script when using its -b option. See the script man page for details.

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.40 java

object

1.40.1 java

Abstract interface to JPL API utility predicates.

Availability:

`logtalk_load(java(loader))`

Author: Paulo Moura

Version: 1:8:0

Date: 2023-03-15

Compilation flags:

`static, context_switching_calls`

Implements:

`public java_utils_protocol`

Uses:

`user`

Remarks:

(none)

Inherited public predicates:

`array_list/2 array_to_list/2 array_to_terms/2 array_to_terms/3 decode_exception/2
decode_exception/3 false/1 is_false/1 is_null/1 is_object/1 is_true/1 is_void/1
iterator_element/2 list_to_array/2 map_element/2 null/1 set_element/2 terms_to_array/2
true/1 value_reference/2 void/1`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

`java(Reference,ReturnValue)`, `java(Reference)`, `java_hook`

object

1.40.2 java(Reference)

- Reference - Either a class name or a Java reference to an object.

Minimal abstraction of the JPL API for calling Java from Logtalk using familiar message-sending syntax and a forward/1 handler to resolve methods.

Availability:

`logtalk_load(java(loader))`

Author: Paulo Moura and Sergio Castro

Version: 1:0:1

Date: 2019-06-13

Compilation flags:

static, context_switching_calls

Extends:

public java(Reference, __)

Remarks:

- Usage: Send to this object any valid message as listed in the JavaDocs for the given reference.

Inherited public predicates:

forward/1 get_field/2 invoke/1 invoke/2 new/1 new/2 set_field/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

java(Reference, ReturnValue), java, java_hook

object

1.40.3 java(Reference,ReturnValue)

- Reference - Either a class name or a Java reference to an object.
- ReturnValue - Value returned by a method call (possibly the Java value void).

Minimal abstraction of the JPL API for calling Java from Logtalk using familiar message-sending syntax and a forward/1 handler to resolve methods.

Availability:

```
logtalk_load(java(loader))
```

Author: Paulo Moura and Sergio Castro

Version: 1:4:0

Date: 2023-03-13

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public forwarding
public java_access_protocol
```

Remarks:

- Usage: Send to this object any valid message as listed in the JavaDocs for the given reference.

Inherited public predicates:

```
forward/1 get_field/2 invoke/1 invoke/2 new/1 new/2 set_field/2
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

java(Reference), java, java_hook

protocol

1.40.4 java_access_protocol

Protocol for a minimal abstraction for calling Java from Logtalk using familiar message-sending syntax.

Availability:

logtalk_load(java(loader))

Author: Paulo Moura and Sergio Castro

Version: 1:2:1

Date: 2023-03-16

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - `get_field/2`
 - `set_field/2`
 - `new/2`
 - `new/1`
 - `invoke/1`
 - `invoke/2`
- Protected predicates
- Private predicates
- Operators

Public predicates

`get_field/2`

Gets the value of a class or object field.

Compilation flags:

`static`

Template:

`get_field(Field,Value)`

Mode and number of proofs:

`get_field(+atom,?nonvar) - zero_or_one`

`set_field/2`

Sets the value of a class or object field.

Compilation flags:

`static`

Template:

`set_field(Field,Value)`

Mode and number of proofs:

`set_field(+atom,+nonvar)` - one

`new/2`

Creates a new instance using the specified parameter values.

Compilation flags:

`static`

Template:

`new(Parameters,Instance)`

Mode and number of proofs:

`new(+list(nonvar),-reference)` - one

`new/1`

Creates a new instance using default parameter values.

Compilation flags:

`static`

Template:

`new(Instance)`

Mode and number of proofs:

`new(-reference)` - one

`invoke/1`

Invokes a method. This is a more efficient compared with relying on the `forward/1` handler to resolve methods.

Compilation flags:

`static`

Template:

 invoke(Method)

Mode and number of proofs:

 invoke(@nonvar) - one

invoke/2

Invokes a method. This is a more efficient compared with relying on the forward/1 handler to resolve methods.

Compilation flags:

 static

Template:

 invoke(Functor,Arguments)

Mode and number of proofs:

 invoke(@nonvar,@list) - one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

object

1.40.5 java_hook

Hook object to optimize messages to the java/1-2 objects that otherwise would trigger the forward/1 handler.

Availability:

 logtalk_load(java(loader))

Author: Paulo Moura

Version: 1:0:1

Date: 2019-06-13

Compilation flags:

`static, context_switching_calls`

Implements:

`public expanding`

Remarks:

- Usage: Compile source files with messages to the java/1-2 objects using the compiler option `hook(java_hook)`.

Inherited public predicates:

`goal_expansion/2 term_expansion/2`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

➡ See also

`java(Reference,ReturnValue), java(Reference)`

protocol

1.40.6 java_utils_protocol

Abstract interface to Java utility predicates.

Availability:

`logtalk_load(java(loader))`

Author: Paulo Moura

Version: 1:6:0

Date: 2023-03-13

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - `value_reference/2`
 - `true/1`
 - `false/1`
 - `void/1`
 - `null/1`

- is_true/1
- is_false/1
- is_void/1
- is_null/1
- is_object/1
- terms_to_array/2
- array_to_terms/3
- array_to_terms/2
- array_to_list/2
- list_to_array/2
- array_list/2
- iterator_element/2
- map_element/2
- set_element/2
- decode_exception/2
- decode_exception/3
- Protected predicates
- Private predicates
- Operators

Public predicates

value_reference/2

Returns an opaque term that represents the Java value with the given name.

Compilation flags:

static

Template:

value_reference(Value,Reference)

Mode and number of proofs:

value_reference(?atom,--ground) - one_or_more

true/1

Returns an opaque term that represents the Java value true.

Compilation flags:

static

Template:

true(Reference)

Mode and number of proofs:

true(--ground) - one

false/1

Returns an opaque term that represents the Java value false.

Compilation flags:

static

Template:

false(Reference)

Mode and number of proofs:

false(--ground) - one

void/1

Returns an opaque term that represents the Java value void.

Compilation flags:

static

Template:

void(Reference)

Mode and number of proofs:

void(--ground) - one

`null/1`

Returns an opaque term that represents the Java value `null`.

Compilation flags:

`static`

Template:

`null(Reference)`

Mode and number of proofs:

`null(--ground) - one`

`is_true/1`

True when the argument is the Java value `true`. Fails if the argument is not instantiated.

Compilation flags:

`static`

Template:

`is_true(Reference)`

Mode and number of proofs:

`is_true(@term) - zero_or_one`

`is_false/1`

True when the argument is the Java value `false`. Fails if the argument is not instantiated.

Compilation flags:

`static`

Template:

`is_false(Reference)`

Mode and number of proofs:

`is_false(@term) - zero_or_one`

`is_void/1`

True when the argument is the Java value `void`. Fails if the argument is not instantiated.

Compilation flags:

`static`

Template:

`is_void(Reference)`

Mode and number of proofs:

`is_void(@term) - zero_or_one`

`is_null/1`

True when the argument is the Java value `null`. Fails if the argument is not instantiated.

Compilation flags:

`static`

Template:

`is_null(Reference)`

Mode and number of proofs:

`is_null(@term) - zero_or_one`

`is_object/1`

True when the argument is a reference to a Java object. Fails if the argument is not instantiated.

Compilation flags:

`static`

Template:

`is_object(Reference)`

Mode and number of proofs:

`is_object(@term) - zero_or_one`

`terms_to_array/2`

Converts a list of ground Prolog terms to an array (a Java reference).

Compilation flags:

`static`

Template:

`terms_to_array(Terms,Array)`

Mode and number of proofs:

`terms_to_array(++list(ground),-array) - one`

`array_to_terms/3`

Converts an array (a Java reference) to a list of ground Prolog terms returning also its length. The array elements must be atoms, integers, floats, or compound terms. Fails otherwise.

Compilation flags:

`static`

Template:

`array_to_terms(Array,Terms,Length)`

Mode and number of proofs:

`array_to_terms(+array,-list(ground),-integer) - one`

`array_to_terms/2`

Converts an array (a Java reference) to a list of ground Prolog terms. The array elements must be atoms, integers, floats, or ground compound terms. Fails otherwise.

Compilation flags:

`static`

Template:

`array_to_terms(Array,Terms)`

Mode and number of proofs:

`array_to_terms(+array,-list(term)) - one`

`array_to_list/2`

Converts an array (a Java reference) to a list of Java references or their values.

Compilation flags:

static

Template:

`array_to_list(Array,List)`

Mode and number of proofs:

`array_to_list(+array,-list) - one`

`list_to_array/2`

Converts a list of Java references or values to an array (a Java reference).

Compilation flags:

static

Template:

`list_to_array(List,Array)`

Mode and number of proofs:

`list_to_array(+list,-array) - one`

`array_list/2`

Converts between an array (a Java reference) and a list of Java references or their values. Deprecated. Use the `array_to_list/2` and `list_to_array/2` predicates instead.

Compilation flags:

static

Template:

`array_list(Array,List)`

Mode and number of proofs:

`array_list(+array,-list)` - one

`array_list(-array,+list)` - one

`iterator_element/2`

Enumerates, by backtracking, all iterator elements.

Compilation flags:

`static`

Template:

`iterator_element(Iterator,Element)`

Mode and number of proofs:

`iterator_element(+iterator,-element)` - zero_or_more

`map_element/2`

Enumerates, by backtracking, all map elements.

Compilation flags:

`static`

Template:

`map_element(Map,Element)`

Mode and number of proofs:

`map_element(+iterator,-element)` - zero_or_more

`set_element/2`

Enumerates, by backtracking, all set elements.

Compilation flags:

`static`

Template:

`set_element(Set,Element)`

Mode and number of proofs:

`set_element(+iterator,-element) - zero_or_more`

`decode_exception/2`

Decodes an exception into its corresponding cause. Fails if the exception is not a Java exception.

Compilation flags:

`static`

Template:

`decode_exception(Exception,Cause)`

Mode and number of proofs:

`decode_exception(+callable,-atom) - zero_or_one`

`decode_exception/3`

Decodes an exception into its corresponding cause and a stack trace. Fails if the exception is not a Java exception.

Compilation flags:

`static`

Template:

`decode_exception(Exception,Cause,StackTrace)`

Mode and number of proofs:

`decode_exception(+callable,-atom,-list(atom)) - zero_or_one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.41 json

object

1.41.1 json

JSON parser and generator. Uses curly terms for parsed JSON objects, dashes for parsed JSON pairs, and atoms for parsed JSON strings.

Availability:

`logtalk_load(json(loader))`

Author: Paulo Moura and Jacinto Dávila

Version: 1:1:0

Date: 2022-11-14

Compilation flags:

`static, context_switching_calls`

Extends:

`public json(curly,dash,atom)`

Remarks:

(none)

Inherited public predicates:

`generate/2 parse/2`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.41.2 json(StringRepresentation)

- StringRepresentation - Text representation to be used when decoding JSON strings. Possible values are atom (default), chars, and codes.

JSON parser and generator. Uses curly terms for parsed JSON objects and dashes for parsed JSON pairs.

Availability:

```
logtalk_load(json(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2022-11-14

Compilation flags:

```
static, context_switching_calls
```

Extends:

```
public json(curly,dash,StringRepresentation)
```

Remarks:

(none)

Inherited public predicates:

`generate/2` `parse/2`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.41.3 `json(ObjectRepresentation,PairRepresentation,StringRepresentation)`

- `ObjectRepresentation` - Object representation to be used when decoding JSON objects. Possible values are curly (default) and list.
- `PairRepresentation` - Pair representation to be used when decoding JSON objects. Possible values are dash (default), equal, and colon.
- `StringRepresentation` - Text representation to be used when decoding JSON strings. Possible values are atom (default), chars, and codes.

JSON parser and generator.

Availability:

`logtalk_load(json(loader))`

Author: Paulo Moura and Jacinto Dávila

Version: 0:13:0

Date: 2024-07-16

Compilation flags:

static, context_switching_calls

Implements:

public json_protocol

Uses:

reader

Remarks:

(none)

Inherited public predicates:

generate/2 parse/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.41.4 json_protocol

JSON parser and generator protocol.

Availability:

logtalk_load(json(loader))

Author: Paulo Moura and Jacinto Dávila

Version: 0:11:0

Date: 2022-11-09

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - parse/2
 - generate/2
- Protected predicates
- Private predicates
- Operators

Public predicates

`parse/2`

Parses the JSON contents read from the given source (`codes(List)`, `stream(Stream)`, `line(Stream)`, `file(Path)`, `chars(List)`, or `atom(Atom)`) into a term. Fails if the JSON contents cannot be parsed.

Compilation flags:

`static`

Template:

`parse(Source,Term)`

Mode and number of proofs:

`parse(++compound,--term) - one_or_error`

`generate/2`

Generates the content using the representation specified in the first argument (`codes(List)`, `stream(Stream)`, `file(Path)`, `chars(List)`, or `atom(Atom)`) for the term in the second argument. Fails if this term cannot be processed.

Compilation flags:

`static`

Template:

`generate(Sink,Term)`

Mode and number of proofs:

`generate(+compound,++term) - one_or_error`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.42 json_lines

object

1.42.1 json_lines

JSON Lines parser and generator. Uses curly terms for parsed JSON objects, dashes for parsed JSON pairs, and atoms for parsed JSON strings.

Availability:

```
logtalk_load(json_lines(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2025-05-27

Compilation flags:

```
static, context_switching_calls
```

Extends:

```
public json_lines(curly,dash,atom)
```

Remarks:

(none)

Inherited public predicates:

```
generate/2 parse/2
```

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)

- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.42.2 json_lines(StringRepresentation)

- StringRepresentation - Text representation to be used when decoding JSON strings. Possible values are atom (default), chars, and codes.

JSON Lines parser and generator. Uses curly terms for parsed JSON objects and dashes for parsed JSON pairs.

Availability:

```
logtalk_load(json_lines(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2025-05-27

Compilation flags:

```
static, context_switching_calls
```

Extends:

```
public json_lines(curly,dash,StringRepresentation)
```

Remarks:

(none)

Inherited public predicates:

`generate/2` `parse/2`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.42.3 `json_lines(ObjectRepresentation,PairRepresentation,StringRepresentation)`

- `ObjectRepresentation` - Object representation to be used when decoding JSON objects. Possible values are curly (default) and list.
- `PairRepresentation` - Pair representation to be used when decoding JSON objects. Possible values are dash (default), equal, and colon.
- `StringRepresentation` - Text representation to be used when decoding JSON strings. Possible values are atom (default), chars, and codes.

JSON Lines parser and generator.

Availability:

`logtalk_load(json_lines(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2025-05-27

Compilation flags:

static, context_switching_calls

Implements:

public json_lines_protocol

Remarks:

(none)

Inherited public predicates:

generate/2 parse/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.42.4 json_lines_protocol

JSON Lines parser and generator protocol.

Availability:

```
logtalk_load(json_lines(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2025-05-27

Compilation flags:

```
static
```

Dependencies:

```
(none)
```

Remarks:

```
(none)
```

Inherited public predicates:

```
(none)
```

- Public predicates
 - parse/2
 - generate/2
- Protected predicates
- Private predicates
- Operators

Public predicates

parse/2

Parses the JSON Lines contents read from the given source (`file(Path)`, `stream(Stream)`, `line(Stream)`, `codes(Codes)`, `chars(Chars)`, or `atom(Atom)`) into a list of ground terms.

Compilation flags:

```
static
```

Template:

parse(Source,Terms)

Mode and number of proofs:

parse(++compound,--list(ground)) - one_or_error

Exceptions:

Source is a variable:

instantiation_error

Source is neither a variable nor a valid source:

domain_error(json_lines_source,Source)

generate/2

Generates the content using the representation specified in the first argument (file(Path), stream(Stream), codes(Codes), chars(Chars), or atom(Atom)) for the list of ground terms in the second argument.

Compilation flags:

static

Template:

generate(Sink,Terms)

Mode and number of proofs:

generate(+compound,++list(ground)) - one_or_error

Exceptions:

Sink is a variable:

instantiation_error

Terms is a variable:

instantiation_error

Terms is neither a variable nor a list:

type_error(list,Terms)

Term is a non-ground element of the list Terms:

instantiation_error

Term is an element of the list Terms but not a valid JSON term:

domain_error(json_term,Term)

Sink cannot be generated:

domain_error(json_lines_sink,Sink)

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.43 lgtdoc

object

1.43.1 lgtdoc

Documenting tool. Generates XML documenting files for loaded entities and for library, directory, entity, and predicate indexes.

Availability:

`logtalk__load(lgtdoc(loader))`

Author: Paulo Moura

Version: 11:1:4

Date: 2025-04-07

Compilation flags:

`static, context_switching_calls`

Implements:

`public lgtdocp`

Imports:

`public options`

Uses:

`date`

`list`

`logtalk`

`os`

`type`

`user`

`varlist`

Remarks:

(none)

Inherited public predicates:

all/0 all/1 check_option/1 check_options/1 default_option/1 default_options/1 directories/1
directories/2 directory/1 directory/2 file/1 file/2 files/1 files/2 fix_option/2 fix_options/2
libraries/1 libraries/2 library/1 library/2 merge_options/2 option/2 option/3 rdirectories/1
rdirectories/2 rdirectory/1 rdirectory/2 rlibraries/1 rlibraries/2 rlibrary/1 rlibrary/2
valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
 - library_entity_/4
 - directory_entity_/4
 - type_entity_/4
 - predicate_entity_/4
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

library_entity_/4

Table of documented entities per library.

Compilation flags:

dynamic

Template:

library_entity_(Library,PrimarySortKey,SecondarySortKey,Entity)

Mode and number of proofs:

library_entity_(?atom,?nonvar,?nonvar,?atom) - zero_or_more

`directory_entity_/4`

Table of documented entities per directory.

Compilation flags:

dynamic

Template:

`directory_entity__(Directory,PrimarySortKey,SecondarySortKey,Entity)`

Mode and number of proofs:

`directory_entity__(?atom,?nonvar,?nonvar,?atom) - zero_or_more`

`type_entity_/4`

Table of documented entities per type.

Compilation flags:

dynamic

Template:

`type_entity__(Type,PrimarySortKey,SecondarySortKey,Entity)`

Mode and number of proofs:

`type_entity__(?atom,?nonvar,?nonvar,?atom) - zero_or_more`

`predicate_entity_/4`

Table of public predicates for all documented entities.

Compilation flags:

dynamic

Template:

`predicate_entity__(Predicate,PrimarySortKey,SecondarySortKey,Entity)`

Mode and number of proofs:

`predicate_entity_(?predicate_indicator,?nonvar,?nonvar,?entity_identifier) - zero_or_more`

Operators

(none)

category

1.43.2 lgtdoc_messages

Logtalk documentation tool default message translations.

Availability:

`logtalk_load(lgtdoc(loader))`

Author: Paulo Moura

Version: 4:0:1

Date: 2024-12-02

Compilation flags:

`static`

Provides:

`logtalk::message_prefix_stream/4`

`logtalk::message_tokens//2`

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.43.3 lgtdocp

Documenting tool protocol.

Availability:

logtalk__load(lgtdoc(loader))

Author: Paulo Moura

Version: 6:0:0

Date: 2024-03-08

Compilation flags:

static

Dependencies:

(none)

Remarks:

- Compiling files for generating XML documentation: All source files must be compiled with the `source_data` flag turned on.
- `xml_spec(Specification)` option: XML documenting files specification format. Possible option values are `dtd` (DTD specification; default) and `xsd` (XML Schema specification).
- `xml_spec_reference(Reference)` option: Reference to the XML specification file in XML documenting files. Possible values are `local` (default; DTD/XSD file in same folder as XML files), `web` (logtalk.org website DTD/XSD file), and `standalone` (no reference to specification files).

- `entity_xsl_file(File)` option: XSLT file to use with generated XML documenting files. Default is `logtalk_entity_to_xml.xsl`, allowing the XML files to be viewed by opening them with a browser supporting XSLT (after running the `lgt2xml.sh` script on the output directory).
- `index_xsl_file(File)` option: XSLT file to use with generated XML documenting files. Default is `logtalk_index_to_xml.xsl`, allowing the XML files to be viewed by opening them with a browser supporting XSLT (after running the `lgt2xml.sh` script on the output directory).
- `xml_docs_directory(Directory)` option: Directory where the XML documenting files will be generated. The default value is `./xml_docs`, a sub-directory of the source files directory.
- `bom(Boolean)` option: Defines if a BOM should be added to the generated XML documenting files.
- `encoding(Encoding)` option: Encoding to be used for the generated XML documenting files.
- `omit_path_prefixes(Prefixes)` option: List of path prefixes (atoms) to omit when writing directory paths. The default value is to omit the home directory.
- `exclude_files(List)` option: List of files to exclude when generating the XML documenting files.
- `exclude_paths(List)` option: List of relative library paths to exclude when generating the XML documenting files (default is []). All sub-directories of the excluded directories are also excluded.
- `exclude_prefixes(List)` option: List of path prefixes to exclude when generating the XML documenting files (default is []).
- `exclude_entities(List)` option: List of entities to exclude when generating the XML documenting files (default is []).
- `sort_predicates(Boolean)` option: Sort entity predicates (default is false).
- Known issues: Some options may depend on the used XSL processor. Most XSL processors support DTDs but only some of them support XML Schemas. Some processors (e.g., `fop2`) reject reference to a DTD.

Inherited public predicates:

(none)

- Public predicates
 - `rlibraries/2`
 - `rlibraries/1`
 - `rlibrary/2`
 - `rlibrary/1`
 - `libraries/2`
 - `libraries/1`
 - `library/2`
 - `library/1`
 - `rdirectories/2`
 - `rdirectories/1`

- rdirectory/2
- rdirectory/1
- directories/2
- directories/1
- directory/2
- directory/1
- files/2
- files/1
- file/2
- file/1
- all/1
- all/0
- Protected predicates
- Private predicates
- Operators

Public predicates

rlibraries/2

Creates XML documenting files for all entities in all given libraries and their sub-libraries using the specified options.

Compilation flags:

static

Template:

rlibraries(Libraries,Options)

Mode and number of proofs:

rlibraries(+list(atom),+list) - one

`rlibraries/1`

Creates XML documenting files for all entities in all given libraries and their sub-libraries using default options.

Compilation flags:

`static`

Template:

`rlibraries(Libraries)`

Mode and number of proofs:

`rlibraries(+list(atom)) - one`

`rlibrary/2`

Creates XML documenting files for all entities in a library and its sub-libraries using the specified options.

Compilation flags:

`static`

Template:

`rlibrary(Library,Options)`

Mode and number of proofs:

`rlibrary(+atom,+list) - one`

Examples:

Generate XML documenting files for all tool entities for later conversion to Markdown files

`rlibrary(tools,[xslfile('lgtmd.xml')])`

`yes`

`rlibrary/1`

Creates XML documenting files for all entities in a library and its sub-libraries using default options.

Compilation flags:

`static`

Template:

`rlibrary(Library)`

Mode and number of proofs:

`rlibrary(+atom) - one`

Examples:

Generate XML documenting files for all tool entities for direct viewing in a browser (after indexing using the `lgt2xml` script)

`rlibrary(tools)`

`yes`

`libraries/2`

Creates XML documenting files for all entities in all given libraries using the specified options.

Compilation flags:

`static`

Template:

`libraries(Libraries,Options)`

Mode and number of proofs:

`libraries(+list(atom),+list) - one`

libraries/1

Creates XML documenting files for all entities in all given libraries using default options.

Compilation flags:

static

Template:

libraries(Libraries)

Mode and number of proofs:

libraries(+list(atom)) - one

library/2

Creates XML documenting files for all entities in a library using the specified options.

Compilation flags:

static

Template:

library(Library,Options)

Mode and number of proofs:

library(+atom,+list) - one

Examples:

Generate XML documenting files for all library entities for later conversion to PDF A4 files

library(library,[xslfile('logtalk_entity_to_pdf_a4.xml')])

yes

library/1

Creates XML documenting files for all entities in a library using default options.

Compilation flags:

static

Template:

library(Library)

Mode and number of proofs:

library(+atom) - one

`rdirectories/2`

Creates XML documenting files for all entities in all given directories and their sub-directories using the specified options.

Compilation flags:

static

Template:

rdirectories(Directories,Options)

Mode and number of proofs:

rdirectories(+list(atom),+list) - one

`rdirectories/1`

Creates XML documenting files for all entities in all given directories and their sub-directories using default options.

Compilation flags:

static

Template:

rdirectories(Directories)

Mode and number of proofs:

rdirectories(+list(atom)) - one

`rdirectory/2`

Creates XML documenting files for all entities in a directory and its sub-directories using the specified options.

Compilation flags:

`static`

Template:

`rdirectory(Directory,Options)`

Mode and number of proofs:

`rdirectory(+atom,+list) - one`

Examples:

Generate XML documenting files for all entities in the tools directory for later conversion to Markdown files

```
rdirectory('./tools',[xslfile('lgtmd.xml')])
yes
```

`rdirectory/1`

Creates XML documenting files for all entities in a directory and its sub-directories using default options.

Compilation flags:

`static`

Template:

`rdirectory(Directory)`

Mode and number of proofs:

`rdirectory(+atom) - one`

Examples:

Generate XML documenting files for all entities in the tools directory for direct viewing in a browser (after indexing using the `lgt2xml` script)

```
rdirectory('./tools')
yes
```

directories/2

Creates XML documenting files for all entities in all given directories using the specified options.

Compilation flags:

static

Template:

directories(Directories,Options)

Mode and number of proofs:

directories(+list(atom),+list) - one

directories/1

Creates XML documenting files for all entities in all given directories using default options.

Compilation flags:

static

Template:

directories(Directories)

Mode and number of proofs:

directories(+list(atom)) - one

directory/2

Creates XML documenting files for all entities in a directory using the specified options.

Compilation flags:

static

Template:

directory(Directory,Options)

Mode and number of proofs:

directory(+atom,+list) - one

Examples:

Generate XML documenting files for all the entities in the current directory for later conversion to PDF A4 files

```
directory('',[xslfile('logtalk_entity_to_pdf_a4.xml')])
yes
```

`directory/1`

Creates XML documenting files for all entities in a directory using default options.

Compilation flags:

static

Template:

directory(Directory)

Mode and number of proofs:

directory(+atom) - one

`files/2`

Creates XML documenting files for all entities in loaded source files using the specified options. The files can be given by name, basename, full path, or using library notation.

Compilation flags:

static

Template:

files(Files,Options)

Mode and number of proofs:

files(+list(atom),+list) - one

files/1

Creates XML documenting files for all entities in loaded source files using default options. The files can be given by name, basename, full path, or using library notation.

Compilation flags:

static

Template:

files(Files)

Mode and number of proofs:

files(+list(atom)) - one

file/2

Creates XML documenting files for all entities in a loaded source file using the specified options. The file can be given by name, basename, full path, or using library notation.

Compilation flags:

static

Template:

file(File,Options)

Mode and number of proofs:

file(+atom,+list) - one

file/1

Creates XML documenting files for all entities in a loaded source file using default options. The file can be given by name, basename, full path, or using library notation.

Compilation flags:

static

Template:

file(File)

Mode and number of proofs:

file(+atom) - one

all/1

Creates XML documenting files for all loaded entities using the specified options.

Compilation flags:

static

Template:

all(Options)

Mode and number of proofs:

all(+list) - one

all/0

Creates XML documenting files for all loaded entities using default options.

Compilation flags:

static

Mode and number of proofs:

all - one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

 See also

lgtdoc

1.44 lgtunit

object

1.44.1 automation_report

Intercepts unit test execution messages and generates a *.totals files for parsing by the logtalk_tester.sh automation shell script.

Availability:

logtalk_load(lgtunit(loader))

Author: Paulo Moura

Version: 6:0:0

Date: 2025-04-07

Compilation flags:

static, context_switching_calls

Provides:

logtalk::message_hook/4

Uses:

user

Remarks:

- Usage: Automatically loaded by the logtalk_tester.sh shell script.

Inherited public predicates:

(none)

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.44.2 `coverage_report`

Intercepts unit test execution messages and generates a `coverage_report.xml` file with a test suite code coverage results.

Availability:

```
logtalk_load(lgtunit(loader))
```

Author: Paulo Moura

Version: 3:2:0

Date: 2023-04-11

Compilation flags:

```
static, context_switching_calls
```

Provides:

```
logtalk::message_hook/4
```

Uses:

logtalk
user

Remarks:

- Usage: Simply load this object before running your tests using the goal `logtalk_load(lgtunit(coverage_report))`.

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
 - `timestamp_/6`
 - `object_file_/2`
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

`timestamp_/6`

Cache of the starting tests timestamp.

Compilation flags:

`dynamic`

Template:

`timestamp_(Year,Month,Day,Hours,Minutes,Seconds)`

Mode and number of proofs:

`timestamp_(-integer,-integer,-integer,-integer,-integer,-integer) - one`

`object__file__`/2

Cache of test object - file pairs.

Compilation flags:
dynamic

Template:
object__file__(Object,File)
Mode and number of proofs:
object__file__(?object__identifier,?atom) - zero_or_more

Operators

(none)
object

1.44.3 lgtunit

A unit test framework supporting predicate clause coverage, determinism testing, input/output testing, property-based testing, and multiple test dialects.

Availability:
logtalk_load(lgtunit(loader))

Author: Paulo Moura
Version: 21:0:0
Date: 2025-04-07

Compilation flags:
static, context_switching_calls

Implements:
public expanding
Provides:
logtalk::trace_event/2
Uses:

fast_random
list
logtalk
os
type
user

Remarks:

- Usage: Define test objects as extensions of the lgtunit object and compile their source files using the compiler option `hook(lgtunit)`.
- Portability: Deterministic unit tests are currently not available when using Quintus Prolog as the backend compiler.
- Known issues: Parameter variables cannot currently be used in the definition of test options.

Inherited public predicates:

`goal_expansion/2` `term_expansion/2`

- Public predicates
 - `cover/1`
 - `run/0`
 - `run/1`
 - `run/2`
 - `run_test_sets/1`
 - `test/1`
 - `number_of_tests/1`
 - `deterministic/1`
 - `deterministic/2`
 - `assertion/1`
 - `assertion/2`
 - `quick_check/3`
 - `quick_check/2`
 - `quick_check/1`
 - `benchmark/2`
 - `benchmark_reified/3`
 - `benchmark/3`
 - `benchmark/4`

- variant/2
- approximately_equal/2
- approximately_equal/3
- essentially_equal/3
- tolerance_equal/4
- ==~/ 2
- epsilon/1
- Protected predicates
 - run_tests/0
 - run_tests/1
 - run_test_set/0
 - run_quick_check_tests/5
 - condition/0
 - setup/0
 - cleanup/0
 - make/1
 - note/1
 - file_path/2
 - suppress_text_output/0
 - suppress_binary_output/0
 - set_text_input/3
 - set_text_input/2
 - set_text_input/1
 - check_text_input/2
 - check_text_input/1
 - text_input_assertion/3
 - text_input_assertion/2
 - clean_text_input/0
 - set_binary_input/3
 - set_binary_input/2
 - set_binary_input/1
 - check_binary_input/2
 - check_binary_input/1
 - binary_input_assertion/3
 - binary_input_assertion/2

- clean__binary__input/0
- set__text__output/3
- set__text__output/2
- set__text__output/1
- check__text__output/3
- check__text__output/2
- check__text__output/1
- text__output__assertion/4
- text__output__assertion/3
- text__output__assertion/2
- text__output__contents/3
- text__output__contents/2
- text__output__contents/1
- clean__text__output/0
- set__binary__output/3
- set__binary__output/2
- set__binary__output/1
- check__binary__output/2
- check__binary__output/1
- binary__output__assertion/3
- binary__output__assertion/2
- binary__output__contents/2
- binary__output__contents/1
- clean__binary__output/0
- create__text__file/3
- create__text__file/2
- create__binary__file/2
- check__text__file/3
- check__text__file/2
- text__file__assertion/4
- text__file__assertion/3
- check__binary__file/2
- binary__file__assertion/3
- clean__file/1
- clean__directory/1

- closed_input_stream/2
- closed_output_stream/2
- stream_position/1
- test/2
- Private predicates
 - running_test_sets_/0
 - test/3
 - auxiliary_predicate_counter_/1
 - test_/2
 - selected_test_/1
 - skipped_/1
 - passed_/3
 - failed_/3
 - flaky_/1
 - fired_/3
 - covered_/4
- Operators
 - op(700,xfx,==~)

Public predicates

cover/1

Declares entities being tested for which code coverage information should be collected.

Compilation flags:

static

Template:

cover(Entity)

Mode and number of proofs:

cover(?entity__identifier) - zero_or_more

run/0

Runs the unit tests, writing the results to the current output stream.

Compilation flags:

static

Mode and number of proofs:

run - one

run/1

Runs a unit test or a list of unit tests, writing the results to the current output stream. Runs the global setup and cleanup steps when defined. Fails when given a partial list of tests or when one of the test identifiers is not valid.

Compilation flags:

static

Template:

run(Tests)

Mode and number of proofs:

run(++callable) - zero_or_one

run(++list(callable)) - zero_or_one

run/2

Runs the unit tests, writing the results to the specified file. Mode can be either write (to create a new file) or append (to add results to an existing file).

Compilation flags:

static

Template:

run(File,Mode)

Mode and number of proofs:

run(+atom,+atom) - one

`run_test_sets/1`

Runs two or more test sets as a unified set generating a single code coverage report if one is requested. When there is a single test set, it is equivalent to sending the message `run/0` to the test set. Trivially succeeds when the argument is an empty list.

Compilation flags:

`static`

Template:

`run_test_sets(TestObjects)`

Mode and number of proofs:

`run_test_sets(+list(object)) - one`

Exceptions:

TestObjects is a partial list or a list with an element which is a variable:

`instantiation_error`

TestObjects is neither a partial list nor a list:

`type_error(list(object),TestObjects)`

An element TestObject of the TestObjects list is not an existing object:

`existence_error(object,TestObject)`

`test/1`

Enumerates, by backtracking, the identifiers of all defined unit tests.

Compilation flags:

`static`

Template:

`test(Identifier)`

Mode and number of proofs:

`test(?callable) - zero_or_more`

`number_of_tests/1`

Number of defined unit tests.

Compilation flags:

`static`

Template:

`number_of_tests(NumerOfTests)`

Mode and number of proofs:

`number_of_tests(?integer) - zero_or_one`

`deterministic/1`

True if the goal succeeds once without leaving choice-points.

Compilation flags:

`static`

Template:

`deterministic(Goal)`

Meta-predicate template:

`deterministic(0)`

Mode and number of proofs:

`deterministic(+callable) - zero_or_one`

`deterministic/2`

Reified version of the `deterministic/1` predicate. True if the goal succeeds. Returns a boolean value (true or false) indicating if the goal succeeded without leaving choice-points.

Compilation flags:

`static`

Template:

`deterministic(Goal,Deterministic)`

Meta-predicate template:

deterministic(0,*)

Mode and number of proofs:

deterministic(+callable,--atom) - zero_or_one

assertion/1

True if the assertion goal succeeds. Throws an error using the assertion goal as argument if the assertion goal throws an error or fails.

Compilation flags:

static

Template:

assertion(Assertion)

Meta-predicate template:

assertion(::)

Mode and number of proofs:

assertion(@callable) - one

Exceptions:

Assertion goal fails:

assertion_failure(Assertion)

Assertion goal throws Error:

assertion_error(Assertion,Error)

assertion/2

True if the assertion goal succeeds. Throws an error using the description as argument if the assertion goal throws an error or fails. The description argument helps to distinguish between different assertions in the same test body.

Compilation flags:

static

Template:

assertion(Description,Assertion)

Meta-predicate template:

assertion(*,0)

Mode and number of proofs:

`assertion(+nonvar,@callable) - one`

Exceptions:

Assertion goal fails:

`assertion_failure(Description)`

Assertion goal throws Error:

`assertion_error(Description,Error)`

`quick_check/3`

Reified version of the `quick_check/2` predicate. Reports `passed(SequenceSeed,Discarded,Labels)`, `failed(Goal,SequenceSeed,TestSeed)`, `error(Error,Goal,SequenceSeed,TestSeed)`, or `broken(Why,Culprit)`. Goal is the failed test.

Compilation flags:

`static`

Template:

`quick_check(Template,Result,Options)`

Meta-predicate template:

`quick_check(:,*,::)`

Mode and number of proofs:

`quick_check(@callable,-callable,++list(compound)) - one`

Remarks:

- `SequenceSeed` argument: Can be used to re-run the same exact sequence of pseudo-random tests by using the `rs/1` option after changes to the code being tested.
 - `TestSeed` argument: Can be used to re-run the test that failed by using the `rs/1` option after changes to the code being tested.
 - `Discarded` argument: Number of generated tests that were discarded for failing to comply a pre-condition specified using the `pc/1` option.
 - `Labels` argument: List of pairs `Label-N` where `N` is the number of generated tests that are classified as `Label` by a closure specified using the `l/1` option.
 - `broken(Why,Culprit)` result: This result signals a broken setup. For example, an invalid template, a broken pre-condition or label goal, or broken test generation.
-

`quick_check/2`

Generates and runs random tests for a predicate given its mode template and a set of options. Fails when a generated test fails printing the test. Also fails on an invalid option, printing the option.

Compilation flags:

`static`

Template:

`quick_check(Template,Options)`

Meta-predicate template:

`quick_check(:,::,::)`

Mode and number of proofs:

`quick_check(@callable,++list(compound)) - zero_or_one`

Remarks:

- Number of tests: Use the `n(NumberOfTests)` option to specify the number of random tests. Default is 100.
- Maximum number of shrink operations: Use the `s(MaxShrinks)` option to specify the number of shrink operations when a counter example is found. Default is 64.
- Type edge cases: Use the `ec(Boolean)` option to specify if type edge cases are tested (before generating random tests). Default is true.
- Starting seed: Use the `rs(Seed)` option to specify the random generator starting seed to be used when generating tests. No default. Seeds should be regarded as opaque terms.
- Test generation filtering: Use the `pc/1` option to specify a pre-condition closure for filtering generated tests (extended with the test arguments; no default).
- Generated tests classification: Use the `l/1` option to specify a label closure for classifying the generated tests (extended with the test arguments plus the labels argument; no default). The labelling predicate can return a single test label or a list of test labels.
- Verbose test generation: Use the `v(Boolean)` option to specify verbose reporting of generated random tests. Default is false.
- Progress bar: Use the `pb(Boolean,Tick)` option to print a progress bar for the executed tests, advancing at every Tick tests. Default is false. Only applies when the verbose option is false.

`quick_check/1`

Generates and runs random tests using default options for a predicate given its mode template. Fails when a generated test fails printing the test.

Compilation flags:

`static`

Template:

`quick_check(Template)`

Mode and number of proofs:

`quick_check(@callable) - zero_or_one`

`benchmark/2`

Benchmarks a goal and returns the total execution time in seconds. Uses CPU clock. Goals that may throw an exception should be wrapped by the `catch/3` control construct.

Compilation flags:

`static`

Template:

`benchmark(Goal,Time)`

Meta-predicate template:

`benchmark(0,*)`

Mode and number of proofs:

`benchmark(+callable,-float) - one`

`benchmark_reified/3`

Benchmarks a goal and returns the total execution time in seconds plus its result (success, failure, or `error(Error)`). Uses CPU clock.

Compilation flags:

`static`

Template:

```
benchmark_reified(Goal,Time,Result)
```

Meta-predicate template:

```
benchmark_reified(0,*,*)
```

Mode and number of proofs:

```
benchmark_reified(+callable,-float,-callable) - one
```

[benchmark/3](#)

Benchmarks a goal by repeating it the specified number of times and returning the total execution time in seconds. Uses CPU clock. Goals that may throw an exception should be wrapped by the catch/3 control construct.

Compilation flags:

```
static
```

Template:

```
benchmark(Goal,Repetitions,Time)
```

Meta-predicate template:

```
benchmark(0,*,*)
```

Mode and number of proofs:

```
benchmark(@callable,+positive_integer,-float) - one
```

[benchmark/4](#)

Benchmarks a goal by repeating it the specified number of times and returning the total execution time in seconds using the given clock (cpu or wall). Goals that may throw an exception should be wrapped by the catch/3 control construct.

Compilation flags:

```
static
```

Template:

```
benchmark(Goal,Repetitions,Clock,Time)
```

Meta-predicate template:

```
benchmark(0,*,*,*)
```

Mode and number of proofs:

```
benchmark(@callable,+positive_integer,+atom,-float) - one
```

variant/2

True when the two arguments are a variant of each other. I.e. if is possible to rename the term variables to make them identical. Useful for checking expected test results that contain variables.

Compilation flags:

static

Template:

variant(Term1,Term2)

Mode and number of proofs:

variant(@term,@term) - zero_or_one

approximately_equal/2

Compares two numbers for approximate equality given the epsilon arithmetic constant value using the de facto standard formula $\text{abs}(\text{Number1} - \text{Number2}) \leq \max(\text{abs}(\text{Number1}), \text{abs}(\text{Number2})) * \text{epsilon}$. Type-checked.

Compilation flags:

static

Template:

approximately_equal(Number1,Number2)

Mode and number of proofs:

approximately_equal(+number,+number) - zero_or_one

approximately_equal/3

Compares two numbers for approximate equality given a user-defined epsilon value using the de facto standard formula $\text{abs}(\text{Number1} - \text{Number2}) \leq \max(\text{abs}(\text{Number1}), \text{abs}(\text{Number2})) * \text{Epsilon}$. Type-checked.

Compilation flags:

static

Template:

approximately_equal(Number1,Number2,Epsilon)

Mode and number of proofs:

`approximately_equal(+number,+number,+number) - zero_or_one`

Remarks:

- Epsilon range: Epsilon should be the epsilon arithmetic constant value or a small multiple of it. Only use a larger value if a greater error is expected.
- Comparison with essential equality: For the same epsilon value, approximate equality is weaker requirement than essential equality.

`essentially_equal/3`

Compares two numbers for essential equality given an epsilon value using the de facto standard formula $\text{abs}(\text{Number1} - \text{Number2}) \leq \min(\text{abs}(\text{Number1}), \text{abs}(\text{Number2})) * \text{Epsilon}$. Type-checked.

Compilation flags:

`static`

Template:

`essentially_equal(Number1,Number2,Epsilon)`

Mode and number of proofs:

`essentially_equal(+number,+number,+number) - zero_or_one`

Remarks:

- Comparison with approximate equality: For the same epsilon value, essential equality is a stronger requirement than approximate equality.

`tolerance_equal/4`

Compares two numbers for close equality given relative and absolute tolerances using the de facto standard formula $\text{abs}(\text{Number1} - \text{Number2}) \leq \max(\text{RelativeTolerance} * \max(\text{abs}(\text{Number1}), \text{abs}(\text{Number2})), \text{AbsoluteTolerance})$. Type-checked.

Compilation flags:

`static`

Template:

`tolerance_equal(Number1,Number2,RelativeTolerance,AbsoluteTolerance)`

Mode and number of proofs:

tolerance_equal(+number,+number,+number,+number) - zero_or_one

`=~= / 2`

Compares two numbers (or lists of numbers) for approximate equality using 100*epsilon for the absolute error and, if that fails, 99.999% accuracy for the relative error. But these precision values may not be adequate for all cases. Type-checked.

Compilation flags:

static

Template:

`=~=(Number1,Number2)`

Mode and number of proofs:

`=~=(+number,+number) - zero_or_one`

`=~=(+list(number),+list(number)) - zero_or_one`

`epsilon/1`

Returns the value of epsilon used in the definition of the `(=~=)/2` predicate.

Compilation flags:

static

Template:

`epsilon(Epsilon)`

Mode and number of proofs:

`epsilon(-float) - one`

Protected predicates

`run_tests/0`

Runs all defined unit tests.

Compilation flags:
static

Mode and number of proofs:
run_tests - one

`run_tests/1`

Runs all the tests defined in the given file.

Compilation flags:
static

Template:
run_tests(File)
Mode and number of proofs:
run_tests(+atom) - one

`run_test_set/0`

Runs a test set as part of running two or more test sets as a unified set.

Compilation flags:
static

Mode and number of proofs:
run_test_set - one

`run_quick_check_tests/5`

Runs a QuickCheck test using the given options. Returns the starting seed used to generate the random tests, the number of discarded tests, and the test label statistics.

Compilation flags:

`static`

Template:

`run_quick_check_tests(Template,Options,Seed,Discarded,Labels)`

Meta-predicate template:

`run_quick_check_tests(:,::,*,*,*)`

Mode and number of proofs:

`run_quick_check_tests(@callable,+list,--nonvar,--number,--list(pair)) - one_or_error`

`condition/0`

Verifies conditions for running the tests. Defaults to the goal true.

Compilation flags:

`static`

Mode and number of proofs:

`condition - zero_or_one`

`setup/0`

Setup environment before running the test set. Defaults to the goal true.

Compilation flags:

`static`

Mode and number of proofs:

`setup - zero_or_one`

cleanup/0

Cleanup environment after running the test set. Defaults to the goal true.

Compilation flags:

static

Mode and number of proofs:

cleanup - zero_or_one

make/1

Make target for automatically running the test set when calling the logtalk_make/1 built-in predicate. No default. Possible values are all and check.

Compilation flags:

static

Template:

make(Target)

Mode and number of proofs:

make(?atom) - zero_or_one

note/1

Note to be printed after the test results. Defaults to the empty atom.

Compilation flags:

static

Template:

note(Note)

Mode and number of proofs:

note(?atom) - zero_or_one

`file_path/2`

Returns the absolute path for a file path that is relative to the tests object path. When the file path is already an absolute path, it is expanded to resolve any remaining relative file path parts.

Compilation flags:

`static`

Template:

`file_path(File,Path)`

Mode and number of proofs:

`file_path(+atom,-atom) - one`

See also:

`clean_file/1`

`clean_directory/1`

`suppress_text_output/0`

Suppresses text output. Useful to avoid irrelevant text output from predicates being tested to clutter the test logs.

Compilation flags:

`static`

Mode and number of proofs:

`suppress_text_output - one`

`suppress_binary_output/0`

Suppresses binary output. Useful to avoid irrelevant binary output from predicates being tested to clutter the test logs.

Compilation flags:

`static`

Mode and number of proofs:

`suppress_binary_output` - one

`set_text_input/3`

Creates a temporary file, in the same directory as the tests object, with the given text contents, and opens it for reading referenced by the given alias and using the additional options. If no `eof_action/1` option is specified, its value will be the default used by the backend compiler.

Compilation flags:

`static`

Template:

`set_text_input(Alias,Contents,Options)`

Mode and number of proofs:

`set_text_input(+atom,+atom,+list(stream_option))` - one

`set_text_input(+atom,+list(atom),+list(stream_option))` - one

See also:

`text_input_assertion/3`

`check_text_input/2`

`clean_text_input/0`

`set_text_input/2`

Creates a temporary file, in the same directory as the tests object, with the given text contents, and opens it for reading referenced by the given alias and using the default end-of-file action for the used backend compiler.

Compilation flags:

`static`

Template:

`set_text_input(Alias,Contents)`

Mode and number of proofs:

`set_text_input(+atom,+atom)` - one

`set_text_input(+atom,+list(atom))` - one

See also:

```
text_input_assertion/3  
check_text_input/2  
clean_text_input/0
```

```
set_text_input/1
```

Creates a temporary file, in the same directory as the tests object, with the given text contents, opens it for reading using the default end-of-file action for the used backend compiler, and sets the current input stream to the file.

Compilation flags:

```
static
```

Template:

```
set_text_input(Contents)
```

Mode and number of proofs:

```
set_text_input(+atom) - one
```

```
set_text_input(+list(atom)) - one
```

See also:

```
text_input_assertion/2  
check_text_input/1  
clean_text_input/0
```

```
check_text_input/2
```

Checks that the temporary file (referenced by the given alias) being read have the expected text contents.

Compilation flags:

```
static
```

Template:

```
check_text_input(Alias,Contents)
```

Mode and number of proofs:

```
check_text_input(+atom,+atom) - zero_or_one
```

See also:

```
set_text_input/2
set_text_input/2
text_input_assertion/3
clean_text_input/0
```

check_text_input/1

Checks that the temporary file being read have the expected text contents.

Compilation flags:

static

Template:

check_text_input(Contents)

Mode and number of proofs:

check_text_input(+atom) - zero_or_one

See also:

```
set_text_input/1
text_input_assertion/2
clean_text_input/0
```

text_input_assertion/3

Returns an assertion for checking that the temporary file (referenced by the given alias) being read have the expected text contents.

Compilation flags:

static

Template:

text_input_assertion(Alias,Contents,Assertion)

Mode and number of proofs:

text_input_assertion(+atom,+atom,--callable) - one

See also:

```
set_text_input/3
```

[check_text_input/2](#)
[clean_text_input/0](#)

[text_input_assertion/2](#)

Returns an assertion for checking that the temporary file being read have the expected text contents.

Compilation flags:

`static`

Template:

`text_input_assertion(Contents,Assertion)`

Mode and number of proofs:

`text_input_assertion(+atom,--callable) - one`

See also:

[set_text_input/1](#)
[check_text_input/1](#)
[clean_text_input/0](#)

[clean_text_input/0](#)

Cleans the temporary file used when testing text input.

Compilation flags:

`static`

Mode and number of proofs:

`clean_text_input - one`

See also:

[set_text_input/3](#)
[set_text_input/2](#)
[set_text_input/1](#)

[set_binary_input/3](#)

Creates a temporary file, in the same directory as the tests object, with the given binary contents, and opens it for reading referenced by the given alias and using the additional options. If no eof_action/1 option is specified, its value will be the default used by the backend compiler.

Compilation flags:

static

Template:

set_binary_input(Alias,Bytes,Options)

Mode and number of proofs:

set_binary_input(+atom,+list(byte),+list(stream_option)) - one

See also:

[binary_input_assertion/3](#)

[check_binary_input/2](#)

[clean_binary_input/0](#)

[set_binary_input/2](#)

Creates a temporary file, in the same directory as the tests object, with the given binary contents, and opens it for reading referenced by the given alias and using the default end-of-file action for the used backend compiler.

Compilation flags:

static

Template:

set_binary_input(Alias,Bytes)

Mode and number of proofs:

set_binary_input(+atom,+list(byte)) - one

See also:

[binary_input_assertion/3](#)

[check_binary_input/2](#)

[clean_binary_input/0](#)

[set_binary_input/1](#)

Creates a temporary file, in the same directory as the tests object, with the given binary contents, and opens it for reading using the default end-of-file action for the used backend compiler, and sets the current input stream to the file.

Compilation flags:

static

Template:

`set_binary_input(Bytes)`

Mode and number of proofs:

`set_binary_input(+list(byte)) - one`

See also:

[binary_input_assertion/2](#)

[check_binary_input/1](#)

[clean_binary_input/0](#)

[check_binary_input/2](#)

Checks that the temporary file (referenced by the given alias) being read have the expected binary contents.

Compilation flags:

static

Template:

`check_binary_input(Alias,Bytes)`

Mode and number of proofs:

`check_binary_input(+atom,+list(byte)) - zero_or_one`

See also:

[set_binary_input/3](#)

[set_binary_input/2](#)

[binary_input_assertion/3](#)

[clean_binary_input/0](#)

[check_binary_input/1](#)

Checks that the temporary file being read have the expected binary contents.

Compilation flags:

static

Template:

`check_binary_input(Bytes)`

Mode and number of proofs:

`check_binary_input(+list(byte)) - zero_or_one`

See also:

[binary_input_assertion/2](#)

[set_binary_input/1](#)

[clean_binary_input/0](#)

[binary_input_assertion/3](#)

Returns an assertion for checking that the temporary file (referenced by the given alias) being read have the expected binary contents.

Compilation flags:

static

Template:

`binary_input_assertion(Alias,Bytes,Assertion)`

Mode and number of proofs:

`binary_input_assertion(+atom,+list(byte),--callable) - one`

See also:

[check_binary_input/2](#)

[set_binary_input/3](#)

[set_binary_input/2](#)

[clean_binary_input/0](#)

[binary_input_assertion/2](#)

Returns an assertion for checking that the temporary file being read have the expected binary contents.

Compilation flags:

static

Template:

`binary_input_assertion(Bytes,Assertion)`

Mode and number of proofs:

`binary_input_assertion(+list(byte),--callable) - one`

See also:

[check_binary_input/1](#)

[set_binary_input/1](#)

[clean_binary_input/0](#)

[clean_binary_input/0](#)

Cleans the temporary file used when testing binary input.

Compilation flags:

static

Mode and number of proofs:

`clean_binary_input - one`

See also:

[set_binary_input/3](#)

[set_binary_input/2](#)

[set_binary_input/1](#)

`set_text_output/3`

Creates a temporary file, in the same directory as the tests object, with the given text contents, and opens it for writing referenced by the given alias and using the additional options.

Compilation flags:

`static`

Template:

`set_text_output(Alias,Contents,Options)`

Mode and number of proofs:

`set_text_output(+atom,+atom,+list(stream_option)) - one`

`set_text_output(+atom,+list(atom),+list(stream_option)) - one`

See also:

`text_output_assertion/4`

`check_text_output/3`

`clean_text_output/0`

`set_text_output/2`

Creates a temporary file, in the same directory as the tests object, with the given text contents, and referenced by the given alias.

Compilation flags:

`static`

Template:

`set_text_output(Alias,Contents)`

Mode and number of proofs:

`set_text_output(+atom,+atom) - one`

`set_text_output(+atom,+list(atom)) - one`

See also:

`text_output_assertion/3`

`check_text_output/2`

`clean_text_output/0`

`set_text_output/1`

Creates a temporary file, in the same directory as the tests object, with the given text contents, and sets the current output stream to the file.

Compilation flags:

`static`

Template:

`set_text_output(Contents)`

Mode and number of proofs:

`set_text_output(+atom) - one`

`set_text_output(+list(atom)) - one`

See also:

`text_output_assertion/2`

`check_text_output/1`

`clean_text_output/0`

`check_text_output/3`

Checks that the temporary file (open with the given options and alias in the same directory as the tests object) being written have the expected text contents.

Compilation flags:

`static`

Template:

`check_text_output(Alias,Contents,Options)`

Mode and number of proofs:

`check_text_output(+atom,+atom,+list(stream_option)) - zero_or_one`

See also:

`set_text_output/3`

`text_output_assertion/4`

`clean_text_output/0`

`check_text_output/2`

Checks that the temporary file (open with default options and alias in the same directory as the tests object) being written have the expected text contents.

Compilation flags:

`static`

Template:

`check_text_output(Alias,Contents)`

Mode and number of proofs:

`check_text_output(+atom,+atom) - zero_or_one`

See also:

`set_text_output/2`

`text_output_assertion/3`

`clean_text_output/0`

`check_text_output/1`

Checks that the temporary file being written have the expected text contents.

Compilation flags:

`static`

Template:

`check_text_output(Contents)`

Mode and number of proofs:

`check_text_output(+atom) - zero_or_one`

See also:

`set_text_output/1`

`text_output_assertion/2`

`clean_text_output/0`

`text_output_assertion/4`

Returns an assertion for checking that the temporary file (open with the given options and alias in the same directory as the tests object) being written have the expected text contents.

Compilation flags:

`static`

Template:

`text_output_assertion(Alias,Contents,Options,Assertion)`

Mode and number of proofs:

`text_output_assertion(+atom,+atom,+list(stream_option),--callable) - one`

See also:

`set_text_output/3`

`check_text_output/3`

`clean_text_output/0`

`text_output_assertion/3`

Returns an assertion for checking that the temporary file (open with default options and alias in the same directory as the tests object) being written have the expected text contents.

Compilation flags:

`static`

Template:

`text_output_assertion(Alias,Contents,Assertion)`

Mode and number of proofs:

`text_output_assertion(+atom,+atom,--callable) - one`

See also:

`set_text_output/2`

`check_text_output/2`

`clean_text_output/0`

`text_output_assertion/2`

Returns an assertion for checking that the temporary file (open with default options in the same directory as the tests object) being written have the expected text contents.

Compilation flags:

`static`

Template:

`text_output_assertion(Contents,Assertion)`

Mode and number of proofs:

`text_output_assertion(+atom,--callable) - one`

See also:

`set_text_output/1`

`check_text_output/1`

`clean_text_output/0`

`text_output_contents/3`

Returns the contents of the temporary file (open with the given options and alias in the same directory as the tests object) being written.

Compilation flags:

`static`

Template:

`text_output_contents(Alias,Contents,Options)`

Mode and number of proofs:

`text_output_contents(+atom,-list(character),+list(stream_option)) - one`

`text_output_contents/2`

Returns the contents of the temporary file (open with default options and alias in the same directory as the tests object) being written.

Compilation flags:

`static`

Template:

`text_output_contents(Alias,Contents)`

Mode and number of proofs:

`text_output_contents(+atom,-list(character)) - one`

`text_output_contents/1`

Returns the contents of the temporary file (open with default options in the same directory as the tests object) being written.

Compilation flags:

`static`

Template:

`text_output_contents(Contents)`

Mode and number of proofs:

`text_output_contents(-list(character)) - one`

`clean_text_output/0`

Cleans the temporary file used when testing text output.

Compilation flags:

`static`

Mode and number of proofs:

`clean_text_output - one`

See also:

```
set_text_output/3  
set_text_output/2  
set_text_output/1
```

`set_binary_output/3`

Creates a temporary file, in the same directory as the tests object, with the given binary contents, and opens it for writing referenced by the given alias and using the additional options.

Compilation flags:

`static`

Template:

`set_binary_output(Alias,Contents,Options)`

Mode and number of proofs:

`set_binary_output(+atom,+list(byte),+list(stream_option))` - one

See also:

```
binary_output_assertion/3  
check_binary_output/2  
clean_binary_output/0
```

`set_binary_output/2`

Creates a temporary file, in the same directory as the tests object, with the given binary contents, and opens it for writing referenced with the given alias.

Compilation flags:

`static`

Template:

`set_binary_output(Alias,Bytes)`

Mode and number of proofs:

`set_binary_output(+atom,+list(byte))` - one

See also:

```
binary_output_assertion/3
```

```
check_binary_output/2  
clean_binary_output/0
```

```
set_binary_output/1
```

Creates a temporary file, in the same directory as the tests object, with the given binary contents, and sets the current output stream to the file.

Compilation flags:

```
static
```

Template:

```
set_binary_output(Bytes)
```

Mode and number of proofs:

```
set_binary_output(+list(byte)) - one
```

See also:

```
binary_output_assertion/2  
check_binary_output/1  
clean_binary_output/0
```

```
check_binary_output/2
```

Checks that the temporary file (referenced by the given alias) have the expected binary contents.

Compilation flags:

```
static
```

Template:

```
check_binary_output(Alias,Bytes)
```

Mode and number of proofs:

```
check_binary_output(+atom,+list(byte)) - zero_or_one
```

See also:

```
set_binary_output/3  
set_binary_output/2  
binary_output_assertion/3
```

`clean_binary_output/0`

`check_binary_output/1`

Checks that the temporary file (open in the same directory as the tests object) have the expected binary contents.

Compilation flags:

`static`

Template:

`check_binary_output(Bytes)`

Mode and number of proofs:

`check_binary_output(+list(byte)) - zero_or_one`

See also:

`set_binary_output/1`

`binary_output_assertion/2`

`clean_binary_output/0`

`binary_output_assertion/3`

Returns an assertion for checking that the temporary file (referenced by the given alias) have the expected binary contents.

Compilation flags:

`static`

Template:

`binary_output_assertion(Alias,Bytes,Assertion)`

Mode and number of proofs:

`binary_output_assertion(+atom,+list(byte),--callable) - one`

See also:

`set_binary_output/2`

`check_binary_output/2`

`clean_binary_output/0`

`binary_output_assertion/2`

Returns an assertion for checking that the temporary file (open in the same directory as the tests object) have the expected binary contents.

Compilation flags:

`static`

Template:

`binary_output_assertion(Bytes,Assertion)`

Mode and number of proofs:

`binary_output_assertion(+list(byte),--callable) - one`

See also:

`set_binary_output/1`

`check_binary_output/1`

`clean_binary_output/0`

`binary_output_contents/2`

Returns the binary contents of the temporary file (referenced by the given alias) being written.

Compilation flags:

`static`

Template:

`binary_output_contents(Alias,Bytes)`

Mode and number of proofs:

`binary_output_contents(+atom,-list(byte)) - one`

`binary_output_contents/1`

Returns the binary contents of the temporary file being written.

Compilation flags:

`static`

Template:

`binary_output_contents(Bytes)`

Mode and number of proofs:

`binary_output_contents(-list(byte)) - one`

`clean_binary_output/0`

Cleans the temporary file used when testing binary output.

Compilation flags:

`static`

Mode and number of proofs:

`clean_binary_output - one`

See also:

`set_binary_output/3`

`set_binary_output/2`

`set_binary_output/1`

`create_text_file/3`

Creates a text file with the given contents. The file is open for writing using the given options. Relative file paths are interpreted as relative to the tests object path.

Compilation flags:

`static`

Template:

```
create_text_file(File,Contents,Options)
```

Mode and number of proofs:

```
create_text_file(+atom,+atom,+list(stream_option)) - one
```

```
create_text_file(+atom,+list(atom),+list(stream_option)) - one
```

`create_text_file/2`

Creates a text file with the given contents. The file is open for writing using default options. Relative file paths are interpreted as relative to the tests object path.

Compilation flags:

```
static
```

Template:

```
create_text_file(File,Contents)
```

Mode and number of proofs:

```
create_text_file(+atom,+atom) - one
```

```
create_text_file(+atom,+list(atom)) - one
```

`create_binary_file/2`

Creates a binary file with the given contents. Relative file paths are interpreted as relative to the tests object path.

Compilation flags:

```
static
```

Template:

```
create_binary_file(File,Bytes)
```

Mode and number of proofs:

```
create_binary_file(+atom,+list(byte)) - one
```

[check_text_file/3](#)

Checks that the contents of a text file match the expected contents. The file is open for reading using the given options. Relative file paths are interpreted as relative to the tests object path.

Compilation flags:

static

Template:

`check_text_file(File,Contents,Options)`

Mode and number of proofs:

`check_text_file(+atom,+atom,+list(stream_option)) - zero_or_one`

See also:

[text_file_assertion/4](#)

[check_text_file/2](#)

Checks that the contents of a text file (open for reading using default options) match the expected contents. Relative file paths are interpreted as relative to the tests object path.

Compilation flags:

static

Template:

`check_text_file(File,Contents)`

Mode and number of proofs:

`check_text_file(+atom,+atom) - zero_or_one`

See also:

[text_file_assertion/3](#)

[text_file_assertion/4](#)

Returns an assertion for checking that the given file have the expected text contents. The file is open for reading using the given options. Relative file paths are interpreted as relative to the tests object path.

Compilation flags:

static

Template:

`text_file_assertion(File,Contents,Options,Assertion)`

Mode and number of proofs:

`text_file_assertion(+atom,+atom,+list(stream_option),--callable) - one`

See also:

[check_text_file/3](#)

[text_file_assertion/3](#)

Returns an assertion for checking that the given file have the expected text contents. The file is open for reading using default options. Relative file paths are interpreted as relative to the tests object path.

Compilation flags:

static

Template:

`text_file_assertion(File,Contents,Assertion)`

Mode and number of proofs:

`text_file_assertion(+atom,+atom,--callable) - one`

See also:

[check_text_file/2](#)

[check_binary_file/2](#)

Checks the contents of a binary file match the expected contents. Relative file paths are interpreted as relative to the tests object path.

Compilation flags:

static

Template:

`check_binary_file(File,Bytes)`

Mode and number of proofs:

`check_binary_file(+atom,+list(byte)) - zero_or_one`

See also:

[binary_file_assertion/3](#)

[binary_file_assertion/3](#)

Returns an assertion for checking that the given file have the expected binary contents. Relative file paths are interpreted as relative to the tests object path.

Compilation flags:

static

Template:

`binary_file_assertion(File,Bytes,Assertion)`

Mode and number of proofs:

`binary_file_assertion(+atom,+list(byte),--callable) - one`

See also:

[check_binary_file/2](#)

[clean_file/1](#)

Closes any existing stream associated with the file and deletes the file if it exists. Relative file paths are interpreted as relative to the tests object path.

Compilation flags:

static

Template:

`clean_file(File)`

Mode and number of proofs:

`clean_file(+atom) - one`

See also:

[clean_directory/1](#)

[file_path/2](#)

[clean_directory/1](#)

Deletes an empty directory if it exists. Relative directory paths are interpreted as relative to the tests object path.

Compilation flags:

static

Template:

`clean_directory(Directory)`

Mode and number of proofs:

`clean_directory(+atom) - one`

See also:

[clean_file/1](#)

[file_path/2](#)

`closed_input_stream/2`

Opens a temporary file in the same directory as the tests object with the given options for reading, closes it, and returns its stream handle.

Compilation flags:

`static`

Template:

`closed_input_stream(Stream,Options)`

Mode and number of proofs:

`closed_input_stream(-stream,+list(stream_option)) - one`

`closed_output_stream/2`

Opens a temporary file in the same directory as the tests object with the given options for writing, closes it, and returns its stream handle.

Compilation flags:

`static`

Template:

`closed_output_stream(Stream,Options)`

Mode and number of proofs:

`closed_output_stream(-stream,+list(stream_option)) - zero_or_one`

`stream_position/1`

Returns a syntactically valid stream position by opening a temporary file in the same directory as the tests object.

Compilation flags:

`static`

Template:

`stream_position(Position)`

Mode and number of proofs:

`stream_position(-stream_position) - one`

`test/2`

Table of defined tests.

Compilation flags:

`static`

Template:

`test(Identifier,Test)`

Mode and number of proofs:

`test(?callable,?compound) - zero_or_more`

Private predicates

`running_test_sets_/0`

Internal flag used when running two or more test sets as a unified set.

Compilation flags:

`dynamic`

Mode and number of proofs:

`running_test_sets_ - zero_or_one`

`test/3`

Compiled unit tests. The list of variables is used to ensure variable sharing between a test with its test options.

Compilation flags:

`static`

Template:

test(Identifier,Variables,Outcome)

Mode and number of proofs:

test(?callable,?list(variable),?nonvar) - zero_or_more

auxiliary_predicate_counter_/1

Counter for generating unique auxiliary predicate names.

Compilation flags:

dynamic

Template:

auxiliary_predicate_counter_(Counter)

Mode and number of proofs:

auxiliary_predicate_counter_(?integer) - one_or_more

test_/2

Table of compiled tests.

Compilation flags:

dynamic

Template:

test_(Identifier,Test)

Mode and number of proofs:

test_(?callable,?compound) - zero_or_more

selected_test_/1

Table of selected tests for execution.

Compilation flags:

dynamic

Template:

selected_test_(Identifier)

Mode and number of proofs:

selected_test_(?callable) - zero_or_more

skipped_/1

Counter for skipped tests.

Compilation flags:

dynamic

Template:

skipped_(Counter)

Mode and number of proofs:

skipped_(?integer) - zero_or_one

passed_/3

Counter and total time for passed tests.

Compilation flags:

dynamic

Template:

passed_(Counter,CPUTime,WallTime)

Mode and number of proofs:

passed_(?integer,-float,-float) - zero_or_one

failed_/3

Counter and total time for failed tests.

Compilation flags:

dynamic

Template:

failed__(Counter,CPUTime,WallTime)

Mode and number of proofs:

failed__(?integer,-float,-float) - zero_or_one

flaky_/1

Counter for failed tests that are marked as flaky.

Compilation flags:

dynamic

Template:

flaky__(Counter)

Mode and number of proofs:

flaky__(?integer) - zero_or_one

fired_/3

Fired clauses when running the unit tests.

Compilation flags:

dynamic

Template:

fired__(Entity,Predicate,Clause)

Mode and number of proofs:

fired__(?entity__identifier,?predicate__indicator,?integer) - zero_or_more

`covered_/4`

Auxiliary predicate for collecting statistics on clause coverage.

Compilation flags:

`dynamic`

Template:

`covered_(Entity,Predicate,Covered>Total)`

Mode and number of proofs:

`covered_(?entity__identifier,?callable,?integer,?integer) - zero_or_more`

Operators

`op(700,xfx,==)`

Scope:

`public`

`category`

1.44.4 lgtunit_messages

Logtalk unit test framework default message translations.

Availability:

`logtalk_load(lgtunit(loader))`

Author: Paulo Moura

Version: 11:0:0

Date: 2025-04-07

Compilation flags:

`static`

Provides:

`logtalk::message_prefix_stream/4`

`logtalk::message_tokens//2`

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.44.5 minimal_output

Intercepts unit test execution messages and outputs a minimal report.

Availability:

logtalk_load(lgtunit(loader))

Author: Paulo Moura

Version: 3:0:0

Date: 2021-05-27

Compilation flags:

static, context_switching_calls

Provides:

`logtalk::message_hook/4`

Remarks:

- Usage: Simply load this object before running your tests using the goal `logtalk_load(lgtunit(minimal_output))`.
- Limitations: Cannot be used when the test objects also intercept lgtunit messages.

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.44.6 tap_output

Intercepts unit test execution messages and outputs a report using the TAP format to the current output stream.

Availability:

```
logtalk_load(lgtunit(loader))
```

Author: Paulo Moura

Version: 5:0:0

Date: 2025-04-07

Compilation flags:

```
static, context_switching_calls
```

Provides:

```
logtalk::message_hook/4
```

Remarks:

- Usage: Simply load this object before running your tests using the goal `logtalk_load(lgtunit(tap_output))`.

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
 - generating_/0
 - partial_/1
 - test_count_/1
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

`generating_/0`

Flag to detect report in progress when processing two or more test sets as a unified set.

Compilation flags:

`dynamic`

Mode and number of proofs:

`generating_ - zero_or_one`

`partial_/1`

Cache of total of tests per test set.

Compilation flags:

`dynamic`

Template:

`partial_(Count)`

Mode and number of proofs:

`partial_(?integer) - zero_or_more`

`test_count_/1`

Test counter.

Compilation flags:

`dynamic`

Template:

`test_count_(Count)`

Mode and number of proofs:

`test_count_(?integer) - zero_or_one`

Operators

(none)

object

1.44.7 `tap_report`

Intercepts unit test execution messages and generates a `tap_report.txt` file using the TAP output format in the same directory as the tests object file.

Availability:

`logtalk_load(lgtunit(loader))`

Author: Paulo Moura

Version: 6:0:0

Date: 2025-04-07

Compilation flags:

`static, context_switching_calls`

Provides:

`logtalk::message_hook/4`

Uses:

`logtalk`

Remarks:

- Usage: Simply load this object before running your tests using the goal `logtalk_load(lgtunit(tap_report))`.

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
 - `partial_/1`
 - `test_count_/1`
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

`partial_/1`

Cache of total of tests per test set.

Compilation flags:

`dynamic`

Template:

`partial_(Count)`

Mode and number of proofs:

`partial_(?integer) - zero_or_more`

`test_count_/1`

Test counter.

Compilation flags:

`dynamic`

Template:

`test_count_(Count)`

Mode and number of proofs:

`test_count_(?integer) - zero_or_one`

Operators

(none)

object

1.44.8 `xunit_net_v2_output`

Intercepts unit test execution messages and outputs a report using the xUnit.net v2 XML format to the current output stream.

Availability:

`logtalk_load(lgtunit(loader))`

Author: Paulo Moura

Version: 5:0:0

Date: 2025-04-07

Compilation flags:

`static, context_switching_calls`

Provides:

`logtalk::message_hook/4`

Uses:

`user`

Remarks:

- Usage: Simply load this object before running your tests using the goal `logtalk_load(lgtunit(xunit_net_v2_output))`.

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
 - `message_cache_/1`
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

`message_cache_/1`

Table of messages emitted by the `lgtunit` tool when running tests.

Compilation flags:

`dynamic`

Template:

`message_cache_(Message)`

Mode and number of proofs:

`message_cache_(?callable) - zero_or_more`

Operators

(none)

object

1.44.9 xunit_net_v2_report

Intercepts unit test execution messages and generates a xunit_report.xml file using the xUnit.net v2 XML format in the same directory as the tests object file.

Availability:

`logtalk_load(lgtunit(loader))`

Author: Paulo Moura

Version: 6:0:0

Date: 2025-04-07

Compilation flags:

`static, context_switching_calls`

Provides:

`logtalk::message_hook/4`

Uses:

`logtalk`

`user`

Remarks:

- Usage: Simply load this object before running your tests using the goal `logtalk_load(lgtunit(xunit_net_v2_report))`.

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
 - `message_cache_/1`
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

`message_cache_/1`

Table of messages emitted by the lgtunit tool when running tests.

Compilation flags:

`dynamic`

Template:

`message_cache_(Message)`

Mode and number of proofs:

`message_cache_(?callable) - zero_or_more`

Operators

(none)

object

1.44.10 xunit_output

Intercepts unit test execution messages and outputs a report using the xUnit XML format to the current output stream.

Availability:

`logtalk_load(lgtunit(loader))`

Author: Paulo Moura

Version: 5:0:1

Date: 2025-04-11

Compilation flags:

static, context_switching_calls

Provides:

logtalk::message_hook/4

Uses:

logtalk

user

Remarks:

- Usage: Simply load this object before running your tests using the goal `logtalk_load(lgtunit(xunit_output))`.

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
 - message_cache_/1
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

message_cache_/1

Table of messages emitted by the lgtunit tool when running tests.

Compilation flags:

dynamic

Template:

```
message_cache_(Message)
```

Mode and number of proofs:

```
message_cache_(?callable) - zero_or_more
```

Operators

(none)

object

1.44.11 xunit_report

Intercepts unit test execution messages and generates a xunit_report.xml file using the xUnit XML format in the same directory as the tests object file.

Availability:

```
logtalk_load(lgtunit(loader))
```

Author: Paulo Moura

Version: 6:0:0

Date: 2025-04-07

Compilation flags:

```
static, context_switching_calls
```

Provides:

```
logtalk::message_hook/4
```

Uses:

```
logtalk
```

```
user
```

Remarks:

- Usage: Simply load this object before running your tests using the goal `logtalk_load(lgtunit(xunit_report))`.

Inherited public predicates:

```
(none)
```

- Public predicates
- Protected predicates
- Private predicates
 - message_cache_/1
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

message_cache_/1

Table of messages emitted by the lgtunit tool when running tests.

Compilation flags:

dynamic

Template:

message_cache_(Message)

Mode and number of proofs:

message_cache_(?callable) - zero_or_more

Operators

(none)

1.45 library

protocol

1.45.1 cloning

Object cloning protocol.

Availability:

`logtalk_load(library(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2010-09-14

Compilation flags:

`static`

Dependencies:

`(none)`

Remarks:

`(none)`

Inherited public predicates:

`(none)`

- Public predicates
 - `clone/1`
- Protected predicates
- Private predicates
- Operators

Public predicates

clone/1

Clones an object, returning the identifier of the new object if none is given.

Compilation flags:

static

Template:

clone(Clone)

Mode and number of proofs:

clone(?object) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

category

1.45.2 counters

Named integer counters. Counter names can be any nonvar term.

Availability:

logtalk_load(library(loader))

Author: Paulo Moura

Version: 1:0:1

Date: 2022-02-11

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - counter/2
 - increment_counter/1
 - decrement_counter/1
 - reset_counter/1
 - reset_counters/0
- Protected predicates
- Private predicates
 - counter_/2
- Operators

Public predicates

counter/2

True if Counter is a counter with value Value.

Compilation flags:

static

Template:

counter(Counter,Value)

Mode and number of proofs:

counter(?nonvar,?integer) - zero_or_more

`increment_counter/1`

Increments the named counter.

Compilation flags:

`static`

Template:

`increment_counter(Counter)`

Mode and number of proofs:

`increment_counter(+nonvar) - one`

`decrement_counter/1`

Decrements the named counter.

Compilation flags:

`static`

Template:

`decrement_counter(Counter)`

Mode and number of proofs:

`decrement_counter(+nonvar) - one`

`reset_counter/1`

Resets the named counter to zero. Creates the counter if it does not exist.

Compilation flags:

`static`

Template:

`reset_counter(Counter)`

Mode and number of proofs:

`reset_counter(+nonvar) - one`

`reset_counters/0`

Resets all existing named counters to zero.

Compilation flags:

`static`

Mode and number of proofs:

`reset_counters - one`

Protected predicates

(none)

Private predicates

`counter_/2`

Table of named counters.

Compilation flags:

`dynamic`

Template:

`counter_(Counter,Value)`

Mode and number of proofs:

`counter_(?nonvar,?integer) - zero_or_more`

Operators

(none)

object

1.45.3 streamvars

Stream variables (supporting logical, backtracable, adding and retrieving of terms).

Availability:

`logtalk_load(library(loader))`

Author: Nobukuni Kino and Paulo Moura

Version: 1:3:0

Date: 2019-06-15

Compilation flags:

`static, context__switching__calls`

Dependencies:

`(none)`

Remarks:

`(none)`

Inherited public predicates:

`(none)`

- Public predicates
 - `new/1`
 - `new/2`
 - `(<=)/2`
 - `(>=)/2`
- Protected predicates
- Private predicates
- Operators
 - `op(100,xfx,<=)`
 - `op(100,xfx,>=)`

Public predicates

new/1

Makes Variable a stream variable. Initial state will be empty.

Compilation flags:

static

Template:

new(Variable)

Mode and number of proofs:

new(--streamvar) - one

Exceptions:

Variable is not a variable:

type__error(variable,Variable)

new/2

Makes Variable a stream variable and sets its initial state to Value.

Compilation flags:

static

Template:

new(Variable,Value)

Mode and number of proofs:

new(--streamvar,@nonvar) - one

Exceptions:

Variable is not a variable:

type__error(variable,Variable)

$(\leq)/2$

Sets the state of the stream variable *Variable* to *Value* (initializing the variable if needed).

Compilation flags:

static

Template:

Variable \leq *Value*

Mode and number of proofs:

$(?streamvar)\leq(@nonvar) - one$

$(\Rightarrow)/2$

Unifies *Value* with the current state of the stream variable *Variable*.

Compilation flags:

static

Template:

Variable \Rightarrow *Value*

Mode and number of proofs:

$+streamvar\Rightarrow ?nonvar - zero_or_one$

Protected predicates

(none)

Private predicates

(none)

Operators

`op(100,xfx,<=)`

Scope:
public

`op(100,xfx,>=)`

Scope:
public

1.46 listing

category

1.46.1 listing

Listing predicates.

Availability:
logtalk__load(listing(loader))

Author: Paulo Moura
Version: 1:0:0
Date: 2024-01-26

Compilation flags:
static

Dependencies:
(none)

Remarks:
(none)

Inherited public predicates:
(none)

- Public predicates
 - listing/0
 - listing/1
 - portray_clause/1
- Protected predicates
- Private predicates
- Operators

Public predicates

listing/0

Lists all clauses of all visible dynamic predicates to the current output stream.

Compilation flags:

static

Mode and number of proofs:

listing - one

listing/1

Lists all clauses of a visible dynamic predicate or non-terminal to the current output stream. When the argument is a clause head, lists all matching clauses.

Compilation flags:

static

Template:

listing(Spec)

Mode and number of proofs:

listing(+predicate_indicator) - one_or_error

listing(+non_terminal_indicator) - one_or_error

listing(+callable) - one_or_error

Exceptions:

Spec is not ground:

instantiation_error
Spec is ground but not a valid predicate indicator:
type_error(predicate_indicator,Spec)
Spec is ground but not a valid non-terminal indicator:
type_error(non_terminal_indicator,Spec)
Spec is a predicate indicator but not a visible predicate:
existence_error(predicate,Spec)
Spec is a non-terminal indicator but not a visible non-terminal:
existence_error(non_terminal,Spec)
Spec is a callable term with a Functor/Arity indicator but not a visible predicate:
existence_error(predicate, Functor/Arity)
Spec is a predicate indicator of a visible predicate but not a dynamic predicate:
permission_error(access, predicate, Spec)
Spec is a non-terminal indicator of a visible non-terminal but not a dynamic non-terminal:
permission_error(access, non_terminal, Spec)
Spec is a callable term for a visible predicate with a Functor/Arity indicator but not a dynamic predicate:
permission_error(access, predicate, Functor/Arity)

portray_clause/1

Pretty prints a clause to the current output stream.

Compilation flags:

static

Template:

portray_clause(Clause)

Mode and number of proofs:

portray_clause(+clause) - one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.47 logging

object

1.47.1 logger

Global logger object for logging events to files.

Availability:

`logtalk_load(logging(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2011-01-06

Compilation flags:

`static, context_switching_calls`

Implements:

`public loggingp`

Remarks:

(none)

Inherited public predicates:

`define_log_file/2 disable_logging/1 enable_logging/1 init_log_file/2 log_event/2 log_file/2 logging/1`

- Public predicates
- Protected predicates
- Private predicates

- log_file_/2
- logging_to_file_/2
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

log_file_/2

Table of log files.

Compilation flags:

dynamic

Template:

log_file_(Alias,File)

Mode and number of proofs:

log_file_(?atom,?nonvar) - zero_or_more

logging_to_file_/2

Table of logging file status for log files.

Compilation flags:

dynamic

Template:

logging_to_file_(Alias,Status)

Mode and number of proofs:

logging_to_file_(?atom,?atom) - zero_or_more

Operators

(none)

category

1.47.2 logging

Logging events to files category.

Availability:

`logtalk_load(logging(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2011-01-06

Compilation flags:

`static`

Implements:

`public loggingp`

Remarks:

(none)

Inherited public predicates:

`define_log_file/2` `disable_logging/1` `enable_logging/1` `init_log_file/2` `log_event/2` `log_file/2`
`logging/1`

- Public predicates
- Protected predicates
- Private predicates
 - `log_file_/2`
 - `logging_to_file_/2`
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

`log_file_/2`

Table of log files.

Compilation flags:
dynamic

Template:

`log_file_(Alias,File)`

Mode and number of proofs:

`log_file_(?atom,?nonvar) - zero_or_more`

`logging_to_file_/2`

Table of logging file status for log files.

Compilation flags:
dynamic

Template:

`logging_to_file_(Alias,Status)`

Mode and number of proofs:

`logging_to_file_(?atom,?atom) - zero_or_more`

Operators

(none)

protocol

1.47.3 loggingp

Logging events to files protocol.

Availability:

logtalk_load(logging(loader))

Author: Paulo Moura

Version: 1:0:0

Date: 2011-01-06

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - log_file/2
 - define_log_file/2
 - init_log_file/2
 - log_event/2
 - logging/1
 - enable_logging/1
 - disable_logging/1
- Protected predicates
- Private predicates

- Operators

Public predicates

`log_file/2`

Access to the table of log files.

Compilation flags:

`static`

Template:

`log_file(Alias,File)`

Mode and number of proofs:

`log_file(?atom,?atom) - zero_or_more`

`define_log_file/2`

Defines a log file with alias `Alias` and file name `File`. If the log file already exists, its contents are kept. Logging is enabled by default.

Compilation flags:

`static`

Template:

`define_log_file(Alias,File)`

Mode and number of proofs:

`define_log_file(+atom,+atom) - one`

`init_log_file/2`

Initializes a new log file with alias `Alias` and file name `File`. If the log file already exists, its contents are erased. Logging is enabled by default.

Compilation flags:

`static`

Template:

`init_log_file(Alias,File)`

Mode and number of proofs:

`init_log_file(+atom,+atom) - one`

`log_event/2`

Logs an event `Event` to a log file with alias `Alias`. Fails if a log file with alias `Alias` is not defined.

Compilation flags:

`static`

Template:

`log_event(Alias,Event)`

Mode and number of proofs:

`log_event(+atom,+nonvar) - zero_or_one`

`logging/1`

True if logging to file with alias `Alias` is enabled.

Compilation flags:

`static`

Template:

`logging(Alias)`

Mode and number of proofs:

`logging(+atom) - zero_or_one`

`enable_logging/1`

Enables logging to file with alias Alias. Fails if a log file with alias Alias is not defined.

Compilation flags:

`static`

Template:

`enable_logging(Alias)`

Mode and number of proofs:

`enable_logging(+atom) - zero_or_one`

`disable_logging/1`

Disables logging to file with alias Alias. Fails if a log file with alias Alias is not defined.

Compilation flags:

`static`

Template:

`disable_logging(Alias)`

Mode and number of proofs:

`disable_logging(+atom) - zero_or_one`

Protected predicates


(none)

Private predicates

(none)

Operators

(none)

 See also

logging

1.48 loops

object

1.48.1 loop

Loop control structures predicates.

Availability:

logtalk_load(loops(loader))

Author: Paulo Moura

Version: 1:4:1

Date: 2020-12-20

Compilation flags:

static, context_switching_calls

Implements:

public `loopp`

Remarks:

(none)

Inherited public predicates:

dowhile/2 fordownto/3 fordownto/4 fordownto/5 foreach/3 foreach/4 forto/3 forto/4 forto/5
whiledo/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.48.2 loopp

Loop control constructs protocol.

Availability:

`logtalk_load(loops(loader))`

Author: Paulo Moura

Version: 1:3:0

Date: 2017-03-20

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - whiledo/2
 - dowhile/2
 - foreach/3
 - foreach/4
 - forto/3
 - forto/4
 - forto/5
 - fordownto/3
 - fordownto/4
 - fordownto/5
- Protected predicates
- Private predicates
- Operators

Public predicates

whiledo/2

While Condition is true do Action.

Compilation flags:

static

Template:

whiledo(Condition,Action)

Meta-predicate template:

whiledo(0,0)

Mode and number of proofs:

whiledo(+callable,@callable) - zero_or_one

dowhile/2

Do Action while Condition is true.

Compilation flags:

static

Template:

dowhile(Action,Condition)

Meta-predicate template:

dowhile(0,0)

Mode and number of proofs:

dowhile(@callable,+callable) - zero_or_one

foreach/3

For each Element in List call Goal.

Compilation flags:

static

Template:

foreach(Element,List,Goal)

Meta-predicate template:

foreach(*,*,0)

Mode and number of proofs:

foreach(@var,+list(term),@callable) - zero_or_one

foreach/4

For each Element in List at position Index call Goal. Index starts at 1.

Compilation flags:

static

Template:

foreach(Element,Index,List,Goal)

Meta-predicate template:

```
foreach(*,*,*,0)
```

Mode and number of proofs:

```
foreach(@var,@var,+list(term),@callable) - zero_or_one
```

forto/3

Calls Goal counting up from First to Last. Increment is 1. For convenience, First and Last can be arithmetic expressions. Fails iff Goal fails.

Compilation flags:

```
static
```

Template:

```
forto(First,Last,Goal)
```

Meta-predicate template:

```
forto(*,*,0)
```

Mode and number of proofs:

```
forto(+number,+number,@callable) - zero_or_one
```

forto/4

Calls Goal counting up from First to Last and binding Count to each successive value. Increment is 1. For convenience, First and Last can be arithmetic expressions. Fails iff Goal fails.

Compilation flags:

```
static
```

Template:

```
forto(Count,First,Last,Goal)
```

Meta-predicate template:

```
forto(*,*,*,0)
```

Mode and number of proofs:

```
forto(@var,+number,+number,@callable) - zero_or_one
```

forto/5

Calls Goal counting up from First to Last and binding Count to each successive value. For convenience, First, Last, and Increment can be arithmetic expressions (uses Increment absolute value). Fails iff Goal fails.

Compilation flags:

static

Template:

forto(Count,First,Last,Increment,Goal)

Meta-predicate template:

forto(*,*,*,*,0)

Mode and number of proofs:

forto(@var,+number,+number,+number,@callable) - zero_or_one

fordownto/3

Calls Goal counting down from First to Last. Decrement is 1. For convenience, First and Last can be arithmetic expressions. Fails iff Goal fails.

Compilation flags:

static

Template:

fordownto(First,Last,Goal)

Meta-predicate template:

fordownto(*,*,0)

Mode and number of proofs:

fordownto(+number,+number,@callable) - zero_or_one

fordownto/4

Calls Goal counting down from First to Last and binding Count to each successive value. Decrement is 1. For convenience, First and Last can be arithmetic expressions. Fails iff Goal fails.

Compilation flags:

static

Template:

```
fordownto(Count,First,Last,Goal)
```

Meta-predicate template:

```
fordownto(*,*,*,0)
```

Mode and number of proofs:

```
fordownto(@var,+number,+number,@callable) - zero_or_one
```

`fordownto/5`

Calls Goal counting down from First to Last and binding Count to each successive value. For convenience, First, Last, and Decrement can be arithmetic expressions (uses Decrement absolute value). Fails iff Goal fails.

Compilation flags:

```
static
```

Template:

```
fordownto(Count,First,Last,Decrement,Goal)
```

Meta-predicate template:

```
fordownto(*,*,*,*,0)
```

Mode and number of proofs:

```
fordownto(@var,+number,+number,+number,@callable) - zero_or_one
```

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

 See also

loop

1.49 meta

object

1.49.1 meta

Some useful meta-predicates.

Availability:

```
logtalk_load(meta(loader))
```

Author: Paulo Moura

Version: 5:2:0

Date: 2016-10-06

Compilation flags:

```
static, context__switching__calls
```

Implements:

```
public metap
```

Aliases:

```
metap map/2 as succeeds/2
metap map/2 as maplist/2
metap map/3 as maplist/3
metap map/4 as maplist/4
metap map/5 as maplist/5
metap map/6 as maplist/6
metap map/7 as maplist/7
metap map/8 as maplist/8
metap include/3 as filter/3
metap fold_left/4 as foldl/4
metap fold_left_1/3 as foldl1/3
metap fold_right/4 as foldr/4
metap fold_right_1/3 as foldr1/3
metap scan_left/4 as scanl/4
metap scan_left_1/3 as scanl1/3
metap scan_right/4 as scanr/4
metap scan_right_1/3 as scanr1/3
```

Remarks:

```
(none)
```

Inherited public predicates:

exclude/3 findall_member/4 findall_member/5 fold_left/4 fold_left_1/3 fold_right/4
 fold_right_1/3 include/3 map/2 map/3 map/4 map/5 map/6 map/7 map/8 map_reduce/5
 partition/4 partition/6 scan_left/4 scan_left_1/3 scan_right/4 scan_right_1/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

➡ See also

[meta_compiler](#)

protocol

1.49.2 metap

Useful meta-predicates protocol.

Availability:

logtalk_load(meta(loader))

Author: Paulo Moura

Version: 6:1:0

Date: 2015-12-23

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - include/3
 - exclude/3
 - findall__member/4
 - findall__member/5
 - partition/4
 - partition/6
 - fold__left/4
 - fold__left__1/3
 - scan__left/4
 - scan__left__1/3
 - fold__right/4
 - fold__right__1/3
 - scan__right/4
 - scan__right__1/3
 - map/2
 - map/3
 - map/4
 - map/5
 - map/6
 - map/7
 - map/8
 - map_reduce/5

- Protected predicates
- Private predicates
- Operators

Public predicates

`include/3`

Returns a list of all list elements that satisfy a predicate.

Compilation flags:

`static`

Template:

`include(Closure,List,Included)`

Meta-predicate template:

`include(1,*,*)`

Mode and number of proofs:

`include(+callable,+list,-list) - one`

`exclude/3`

Returns a list of all list elements that fail to satisfy a predicate.

Compilation flags:

`static`

Template:

`exclude(Closure,List,Excluded)`

Meta-predicate template:

`exclude(1,*,*)`

Mode and number of proofs:

`exclude(+callable,+list,-list) - one`

[findall_member/4](#)

Finds all members of a list that satisfy a given test.

Compilation flags:

static

Template:

findall_member(Member,List,Test,Result)

Meta-predicate template:

findall_member(*,*,0,*)

Mode and number of proofs:

findall_member(@term,+list,@callable,-list) - one

[findall_member/5](#)

Finds all members of a list that satisfy a given test appending the given tail to the result.

Compilation flags:

static

Template:

findall_member(Member,List,Test,Result,Tail)

Meta-predicate template:

findall_member(*,*,0,*,*)

Mode and number of proofs:

findall_member(@term,+list,@callable,-list,+list) - one

[partition/4](#)

Partition a list of elements in two lists using a predicate.

Compilation flags:

static

Template:

partition(Closure,List,Included,Excluded)

Meta-predicate template:

```
partition(1,*,*,*)
```

Mode and number of proofs:

```
partition(+callable,+list,-list,-list) - one
```

[partition/6](#)

Partitions a list in lists with values less, equal, and greater than a given value using a comparison predicate with the same argument order as [compare/3](#).

Compilation flags:

```
static
```

Template:

```
partition(Closure,List,Value,Less,Equal,Greater)
```

Meta-predicate template:

```
partition(3,*,*,*,*,*)
```

Mode and number of proofs:

```
partition(+callable,+list,@term,-list,-list,-list) - one
```

[fold_left/4](#)

List folding (left associative). Closure is extended with three arguments: accumulator, list element, and updated accumulator.

Compilation flags:

```
static
```

Template:

```
fold_left(Closure,Accumulator,List,Result)
```

Meta-predicate template:

```
fold_left(3,*,*,*)
```

Mode and number of proofs:

```
fold_left(+callable,?term,+list,?term) - zero_or_more
```

fold_left_1/3

List folding (left associative). Closure is extended with three arguments: accumulator, list element, and updated accumulator. The initial value of the accumulator is the list first element. Fails for empty lists.

Compilation flags:

static

Template:

fold_left_1(Closure,List,Result)

Meta-predicate template:

fold_left_1(3,*,*)

Mode and number of proofs:

fold_left_1(+callable,+list,?term) - zero_or_more

scan_left/4

List scanning (left associative). Closure is extended with three arguments: accumulator, list element, and updated accumulator.

Compilation flags:

static

Template:

scan_left(Closure,Accumulator,List,Results)

Meta-predicate template:

scan_left(3,*,*,*)

Mode and number of proofs:

scan_left(+callable,?term,+list,?list) - zero_or_more

scan_left_1/3

List scanning (left associative). Closure is extended with three arguments: accumulator, list element, and updated accumulator. The accumulator is initialized with the list first element. Fails for empty lists.

Compilation flags:

static

Template:

```
scan_left_1(Closure,List,Results)
```

Meta-predicate template:

```
scan_left_1(3,*,*)
```

Mode and number of proofs:

```
scan_left_1(+callable,+list,?list) - zero_or_more
```

[fold_right/4](#)

List folding (right associative). Closure is extended with three arguments: list element, accumulator, and updated accumulator.

Compilation flags:

```
static
```

Template:

```
fold_right(Closure,Accumulator,List,Result)
```

Meta-predicate template:

```
fold_right(3,*,*,*)
```

Mode and number of proofs:

```
fold_right(+callable,?term,+list,?term) - zero_or_more
```

[fold_right_1/3](#)

List folding (right associative). Closure is extended with three arguments: list element, accumulator, and updated accumulator. The initial value of the accumulator is the list first element. Fails for empty lists.

Compilation flags:

```
static
```

Template:

```
fold_right_1(Closure,List,Result)
```

Meta-predicate template:

```
fold_right_1(3,*,*)
```

Mode and number of proofs:

```
fold_right_1(+callable,+list,?term) - zero_or_more
```

`scan_right/4`

List scanning (right associative). Closure is extended with three arguments: list element, accumulator, and updated accumulator.

Compilation flags:

`static`

Template:

`scan_right(Closure,Accumulator,List,Results)`

Meta-predicate template:

`scan_right(3,*,*,*)`

Mode and number of proofs:

`scan_right(+callable,?term,+list,?list) - zero_or_more`

`scan_right_1/3`

List scanning (right associative). Closure is extended with three arguments: list element, accumulator, and updated accumulator. The accumulator is initialized with the list first element. Fails for empty lists.

Compilation flags:

`static`

Template:

`scan_right_1(Closure,List,Results)`

Meta-predicate template:

`scan_right_1(3,*,*)`

Mode and number of proofs:

`scan_right_1(+callable,+list,?list) - zero_or_more`

`map/2`

True if the predicate succeeds for each list element.

Compilation flags:

`static`

Template:

`map(Closure,List)`

Meta-predicate template:

`map(1,*)`

Mode and number of proofs:

`map(+callable,?list) - zero_or_more`

`map/3`

List mapping predicate taken arguments from two lists of elements.

Compilation flags:

`static`

Template:

`map(Closure,List1,List2)`

Meta-predicate template:

`map(2,*,*)`

Mode and number of proofs:

`map(+callable,?list,?list) - zero_or_more`

`map/4`

List mapping predicate taken arguments from three lists of elements.

Compilation flags:

`static`

Template:

`map(Closure,List1,List2,List3)`

Meta-predicate template:

`map(3,*,*,*)`

Mode and number of proofs:

`map(+callable,?list,?list,?list) - zero_or_more`

map/5

List mapping predicate taken arguments from four lists of elements.

Compilation flags:

static

Template:

map(Closure,List1,List2,List3,List4)

Meta-predicate template:

map(4,*,*,*,*)

Mode and number of proofs:

map(+callable,?list,?list,?list,?list) - zero_or_more

map/6

List mapping predicate taken arguments from five lists of elements.

Compilation flags:

static

Template:

map(Closure,List1,List2,List3,List4,List5)

Meta-predicate template:

map(5,*,*,*,*,*)

Mode and number of proofs:

map(+callable,?list,?list,?list,?list,?list) - zero_or_more

map/7

List mapping predicate taken arguments from six lists of elements.

Compilation flags:

static

Template:

map(Closure,List1,List2,List3,List4,List5,List6)

Meta-predicate template:

```
map(6,*,*,*,*,*,*)
```

Mode and number of proofs:

```
map(+callable,?list,?list,?list,?list,?list,?list) - zero_or_more
```

map/8

List mapping predicate taken arguments from seven lists of elements.

Compilation flags:

```
static
```

Template:

```
map(Closure,List1,List2,List3,List4,List5,List6,List7)
```

Meta-predicate template:

```
map(7,*,*,*,*,*,*,*)
```

Mode and number of proofs:

```
map(+callable,?list,?list,?list,?list,?list,?list,?list) - zero_or_more
```

map_reduce/5

Map a list and apply a fold left (reduce) to the resulting list.

Compilation flags:

```
static
```

Template:

```
map_reduce(Map,Reduce,Accumulator,List,Result)
```

Meta-predicate template:

```
map_reduce(2,3,*,*,*)
```

Mode and number of proofs:

```
map_reduce(+callable,+callable,+term,?list,?term) - zero_or_more
```

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

 See also

[meta](#)

1.50 meta_compiler

object

1.50.1 meta_compiler

Compiler for the meta object meta-predicates. Generates auxiliary predicates in order to avoid meta-call overheads.

Availability:

`logtalk_load(meta_compiler(loader))`

Author: Paulo Moura

Version: 0:16:0

Date: 2024-10-24

Compilation flags:

`static, context_switching_calls`

Implements:

`public expanding`

Uses:

`gensym`

`list`

`logtalk`

`user`

Remarks:

- Usage: Compile source files with calls to the meta object meta-predicates using the compiler option `hook(meta_compiler)`.

Inherited public predicates:

`goal_expansion/2` `term_expansion/2`

- Public predicates
- Protected predicates
- Private predicates
 - `generated_predicate_/1`
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

`generated_predicate_/1`

Table of generated auxiliary predicates.

Compilation flags:

`dynamic`

Template:

`generated_predicate_(Predicate)`

Mode and number of proofs:

`generated_predicate_(?predicate_indicator) - zero_or_more`

Operators

(none)

 See also

[meta](#)

1.51 metagol

object

1.51.1 metagol

Inductive logic programming (ILP) system based on meta-interpretive learning.

Availability:

```
logtalk_load(metagol(loader))
```

Author: Metagol authors; adapted to Logtalk by Paulo Moura.

Version: 0:24:4

Date: 2024-03-15

Copyright: Copyright 2016 Metagol authors; Copyright 2018-2024 Paulo Moura

License: BSD-3-Clause

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public expanding
```

Provides:

```
logtalk::message\_tokens/2
```

```
logtalk::message\_prefix\_stream/4
```

Uses:

```
coroutining
```

```
integer
```

```
list
```

```
logtalk
```

```
meta
```

```
timeout
```


Remarks:

(none)

Inherited public predicates:

goal_expansion/2 term_expansion/2

- Public predicates
 - learn/3
 - learn/2
 - learn_seq/2
 - learn_with_timeout/4
 - program_to_clauses/2
 - pprint/1
 - metarule/6
 - head_pred/1
 - body_pred/1
 - ibk/3
 - func_test/3
 - functional/0
 - min_clauses/1
 - max_clauses/1
 - max_inv_preds/1
 - metarule_next_id/1
 - timeout/1
- Protected predicates
 - pprint_clause/1
 - pprint_clauses/1
 - compiled_pred_call/2
 - body_pred_call/2
 - type/3
- Private predicates
- Operators

Public predicates

`learn/3`

Learns from a set of positive examples and a set of negative examples and returns the learned program.

Compilation flags:

`static`

Template:

`learn(PositiveExamples,NegativeExamples,Program)`

Mode and number of proofs:

`learn(@list(example),@list(example),-list(term)) - zero_or_more`

`learn/2`

Learns from a set of positive examples and a set of negative examples and pretty prints the learned program.

Compilation flags:

`static`

Template:

`learn(PositiveExamples,NegativeExamples)`

Mode and number of proofs:

`learn(@list(example),@list(example)) - zero_or_more`

`learn_seq/2`

Learns from a sequence of examples represented as a list of PositiveExamples/NegativeExamples elements and returns the learned program.

Compilation flags:

`static`

Template:

`learn_seq(Examples,Program)`

Mode and number of proofs:

```
learn_seq(@list(example),-list(clause)) - zero_or_one
```

`learn_with_timeout/4`

Learns from a set of positive examples and a set of negative examples and returns the learned program constrained by the given timeout or its default value.

Compilation flags:

`static`

Template:

```
learn_with_timeout(PositiveExamples,NegativeExamples,Program,Timeout)
```

Mode and number of proofs:

```
learn_with_timeout(@list(example),@list(example),-list(term),+number) - zero_or_one_or_error
```

```
learn_with_timeout(@list(example),@list(example),-list(term),-number) - zero_or_one_or_error
```

Exceptions:

Learning does not complete in the allowed time:

```
timeout(learn(PositiveExamples,NegativeExamples,Program))
```

`program_to_clauses/2`

Converts a learned program into a list of clauses.

Compilation flags:

`static`

Template:

```
program_to_clauses(Program,Clauses)
```

Mode and number of proofs:

```
program_to_clauses(@list(term),-list(clause)) - one
```

`pprint/1`

Pretty prints a learned program.

Compilation flags:

`static`

Template:

`pprint(Program)`

Mode and number of proofs:

`pprint(@list(term)) - one`

`metarule/6`

Compilation flags:

`static`

`head_pred/1`

Compilation flags:

`static`

`body_pred/1`

Compilation flags:

`dynamic`

ibk/3

Compilation flags:
static

func_test/3

Compilation flags:
static

functional/0

Compilation flags:
dynamic

min_clauses/1

Compilation flags:
dynamic

max_clauses/1

Compilation flags:
dynamic

max_inv_preds/1

Compilation flags:
dynamic

metarule_next_id/1

Compilation flags:
dynamic

timeout/1

Compilation flags:
dynamic

Protected predicates

pprint_clause/1

Compilation flags:
static

pprint_clauses/1

Compilation flags:
static

compiled_pred_call/2

Compilation flags:
dynamic

body_pred_call/2

Compilation flags:
dynamic

type/3

Compilation flags:
dynamic

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)
protocol

1.51.2 metagol_example_protocol

Convenient learning predicates for use in examples and unit tests.

Availability:
logtalk_load(metagol(loader))

Author: Paulo Moura.
Version: 0:1:1
Date: 2024-03-15

License: BSD-3-Clause

Compilation flags:
static

Dependencies:
(none)

Remarks:
(none)

Inherited public predicates:
(none)

- Public predicates
 - learn/1
 - learn/0
- Protected predicates
- Private predicates
- Operators

Public predicates

learn/1

Learns and returns set of clauses.

Compilation flags:
static

Template:
learn(Clauses)

Mode and number of proofs:
learn(-list(clause)) - zero_or_more

learn/0

Learns and prints a set of clauses.

Compilation flags:

static

Mode and number of proofs:

learn - zero_or_more

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.52 mutations

object

1.52.1 default_atom_mutations

Default atom mutations.

Availability:

logtalk_load(mutations(loader))

Author: Paulo Moura

Version: 0:1:0

Date: 2023-11-24

Compilation flags:

static, context_switching_calls

Provides:

`mutations_store::mutation/4`

Uses:

`fast_random`

`list`

`type`

Remarks:

(none)

Inherited public predicates:

(none)

- `Public predicates`
- `Protected predicates`
- `Private predicates`
- `Operators`

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

`type`

object

1.52.2 default_compound_mutations

Default compound mutations.

Availability:

```
logtalk_load(mutations(loader))
```

Author: Paulo Moura

Version: 0:1:0

Date: 2023-11-23

Compilation flags:

```
static, context_switching_calls
```

Provides:

```
mutations_store::mutation/4
```

Uses:

```
mutations_store
```

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

type

object

1.52.3 default_float_mutations

Default float mutations.

Availability:

`logtalk_load(mutations(loader))`

Author: Paulo Moura

Version: 0:1:0

Date: 2023-11-23

Compilation flags:

`static, context_switching_calls`

Provides:

`mutations_store::mutation/4`

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates


(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

type

object

1.52.4 default_integer_mutations

Default integer mutations.

Availability:

`logtalk_load(mutations(loader))`

Author: Paulo Moura

Version: 0:1:0

Date: 2023-11-24

Compilation flags:

`static, context_switching_calls`

Provides:

`mutations_store::mutation/4`

Uses:

`fast_random`

`list`

Remarks:

(none)

Inherited public predicates:

(none)

- `Public predicates`
- `Protected predicates`
- `Private predicates`
- `Operators`

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

`type`

`object`

1.52.5 default_list_mutations

Default list mutations.

Availability:

```
logtalk_load(mutations(loader))
```

Author: Paulo Moura

Version: 0:1:0

Date: 2023-11-24

Compilation flags:

```
static, context_switching_calls
```

Provides:

```
mutations_store::mutation/4
```

Uses:

```
fast_random
```

```
list
```

```
mutations_store
```

Remarks:

```
(none)
```

Inherited public predicates:

```
(none)
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates


(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

[type](#)

category

1.52.6 mutations

Adds mutations support to the library type object.

Availability:

`logtalk_load(mutations(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2023-11-23

Compilation flags:

`static`

Complements:

[type](#)

Uses:

[mutations__store](#)

Remarks:

(none)

Inherited public predicates:
(none)

- Public predicates
 - mutation/3
- Protected predicates
- Private predicates
- Operators

Public predicates

mutation/3

Returns a random mutation of a term into another term of the same type. The input Term is assume to be valid for the given Type.

Compilation flags:
static

Template:
mutation(Type,Term,Mutation)
Mode and number of proofs:
mutation(@callable,@term,-term) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.52.7 mutations_store

Stores mutation definitions for selected types. User extensible by defining objects or categories defining clauses for the mutation/3 predicate and using this object as a hook object for their compilation.

Availability:

`logtalk_load(mutations(loader))`

Author: Paulo Moura

Version: 0:1:0

Date: 2023-11-23

Compilation flags:

`static, context_switching_calls`

Implements:

`public expanding`

Uses:

`fast_random`

Remarks:

(none)

Inherited public predicates:

`goal_expansion/2 term_expansion/2`

- Public predicates
 - `mutation/3`
 - `counter/2`
- Protected predicates
- Private predicates
 - `mutation/4`
 - `counter_/2`

- Operators

Public predicates

`mutation/3`

Returns a random mutation of a term into another term of the same type. The input Term is assumed to be valid for the given Type.

Compilation flags:

`static`

Template:

`mutation(Type,Term,Mutation)`

Mode and number of proofs:

`mutation(@callable,@term,-term) - one`

`counter/2`

Table of the number of mutations available per type.

Compilation flags:

`static`

Template:

`counter(Type,N)`

Mode and number of proofs:

`counter(?callable,?positive_integer) - zero_or_more`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

mutation/4

Returns a random mutation of a term into another term of the same type using mutator N. The input Term is assume to be valid for the given Type.

Compilation flags:
static, multifile

Template:
mutation(Type,N,Term,Mutation)

Mode and number of proofs:
mutation(?callable,?positive_integer,@term,-term) - zero_or_more

counter_/2

Internal counter for the number of mutations available for a given type.

Compilation flags:
dynamic

Template:
counter_(Type,N)

Mode and number of proofs:
counter_(?callable,?positive_integer) - zero_or_more

Operators

(none)

➡ See also

type

1.53 nested_dictionaries

object

1.53.1 navltree

Nested dictionary implementation based on the AVL tree implementation. Uses standard order to compare keys.

Availability:

```
logtalk_load(nested_dictionaries(loader))
```

Author: Paul Brown and Paulo Moura.

Version: 0:1:0

Date: 2021-04-09

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public nested_dictionary_protocol
```

Extends:

```
private avltree
```

Remarks:

(none)

Inherited public predicates:

```
as_curly_bracketed/2 as_nested_dictionary/2 delete_in/4 empty/1 insert_in/4 lookup_in/3
new/1 update_in/4 update_in/5
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

nrbtree, nbintree

object

1.53.2 nbintree

Nested dictionary implementation based on the simple binary tree implementation. Uses standard order to compare keys.

Availability:

`logtalk_load(nested_dictionaries(loader))`

Author: Paul Brown and Paulo Moura.

Version: 0:1:0

Date: 2021-04-09

Compilation flags:

`static, context_switching_calls`

Implements:

public nested_dictionary_protocol

Extends:

private bintree

Remarks:

(none)

Inherited public predicates:

as_curly_bracketed/2 as_nested_dictionary/2 delete_in/4 empty/1 insert_in/4 lookup_in/3
new/1 update_in/4 update_in/5

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

nrbtree, navltree

protocol

1.53.3 nested_dictionary_protocol

Nested dictionary protocol.

Availability:

`logtalk_load(nested_dictionaries(loader))`

Author: Paul Brown and Paulo Moura

Version: 0:1:0

Date: 2021-04-07

Compilation flags:

`static`

Dependencies:

`(none)`

Remarks:

`(none)`

Inherited public predicates:

`(none)`

- Public predicates
 - `new/1`
 - `empty/1`
 - `as_nested_dictionary/2`
 - `as_curly_bracketed/2`
 - `lookup_in/3`
 - `update_in/4`
 - `update_in/5`
 - `insert_in/4`
 - `delete_in/4`
- Protected predicates
- Private predicates
- Operators

Public predicates`new/1`

Create an empty (nested) dictionary.

Compilation flags:

`static`

Template:

`new(Dictionary)`

Mode and number of proofs:

`new(--dictionary) - one``empty/1`

True iff the dictionary is empty.

Compilation flags:

`static`

Template:

`empty(Dictionary)`

Mode and number of proofs:

`empty(@dictionary) - zero_or_one``as_nested_dictionary/2`

Creates a (nested) dictionary term from a curly-bracketed term representation.

Compilation flags:

`static`

Template:

`as_nested_dictionary(Term,Dictionary)`

Mode and number of proofs:

`as_nested_dictionary(++term,--dictionary) - one_or_error`

`as_curly_bracketed/2`

Creates a a curly-bracketed term representation from a (nested) dictionary.

Compilation flags:

`static`

Template:

`as_curly_bracketed(Dictionary,Term)`

Mode and number of proofs:

`as_curly_bracketed(+dictionary,--term) - one_or_error`

`lookup_in/3`

Lookup a chain of keys in a nested dictionary. Unifies Value with Dictionary when Keys is the empty list.

Compilation flags:

`static`

Template:

`lookup_in(Keys,Value,Dictionary)`

Mode and number of proofs:

`lookup_in(++list(ground),?term,+dictionary) - zero_or_more`

`update_in/4`

Updates the value found by traversing through the nested keys.

Compilation flags:

`static`

Template:

`update_in(OldDictionary,Keys,Value,NewDictionary)`

Mode and number of proofs:

```
update_in(+dictionary,++list(ground),++term,--dictionary) - zero_or_one
```

update_in/5

Updates the value found by traversing through the nested keys, only succeeding if the value found after traversal matches the old value.

Compilation flags:

static

Template:

```
update_in(OldDictionary,Keys,OldValue,NewValue,NewDictionary)
```

Mode and number of proofs:

```
update_in(+dictionary,++list(ground),?term,++term,--dictionary) - zero_or_one
```

insert_in/4

Inserts a key-value pair into a dictionary by traversing through the nested keys. When the key already exists, the associated value is updated.

Compilation flags:

static

Template:

```
insert_in(OldDictionary,Keys,Value,NewDictionary)
```

Mode and number of proofs:

```
insert_in(+dictionary,++list(ground),++term,--dictionary) - zero_or_one
```

`delete_in/4`

Deletes a matching key-value pair from a dictionary by traversing through the nested keys, returning the updated dictionary.

Compilation flags:

`static`

Template:

`delete_in(OldDictionary,Keys,Value,NewDictionary)`

Mode and number of proofs:

`delete_in(+dictionary,++list(ground),?term,--dictionary) - zero_or_one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

 See also

`navltree`, `nbintree`, `nrbtree`

object

1.53.4 `nrbtree`

Nested dictionary implementation based on the red-black tree implementation. Uses standard order to compare keys.

Availability:

`logtalk_load(nested_dictionaries(loader))`

Author: Paul Brown and Paulo Moura.

Version: 0:1:0

Date: 2021-04-09

Compilation flags:

static, context_switching_calls

Implements:

public nested_dictionary_protocol

Extends:

private rbtree

Remarks:

(none)

Inherited public predicates:

as_curly_bracketed/2 as_nested_dictionary/2 delete_in/4 empty/1 insert_in/4 lookup_in/3
new/1 update_in/4 update_in/5

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

[navltree](#), [nbintree](#)

1.54 optionals

object

1.54.1 maybe

Types and predicates for type-checking and handling optional terms. Inspired by Haskell.

Availability:

`logtalk_load(optionals(loader))`

Author: Paulo Moura

Version: 0:7:0

Date: 2021-01-03

Compilation flags:

`static, context_switching_calls`

Provides:

`type::type/1`

`type::check/2`

`arbitrary::arbitrary/1`

`arbitrary::arbitrary/2`

Uses:

`optional`

`optional(Optional)`

`random`

`type`

Remarks:

- Type-checking support: Defines type `maybe(Type)` for checking optional terms where the value hold by the optional term must be of the given type.

- QuickCheck support: Defines clauses for the `arbitrary::arbitrary/1-2` predicates to allow generating random values for the `maybe(Type)` type.

Inherited public predicates:

(none)

- Public predicates
 - `cat/2`
- Protected predicates
- Private predicates
- Operators

Public predicates

`cat/2`

Returns the values stored in the non-empty optional terms.

Compilation flags:

`static`

Template:

`cat(Optionals,Values)`

Mode and number of proofs:

`cat(+list(optional),-list) - one`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

`optional`, `optional(Optional)`, `type`, `arbitrary`

object

1.54.2 optional

Constructors for optional terms. An optional term is either empty or holds a value. Optional terms should be regarded as opaque terms and always used with the `optional/1` object by passing the optional term as a parameter.

Availability:

`logtalk_load(optionals(loader))`

Author: Paulo Moura

Version: 2:1:0

Date: 2021-01-03

Compilation flags:

`static`, `context_switching_calls`

Provides:

`type::type/1`

`type::check/2`

Remarks:

- Type-checking support: This object also defines a type optional for use with the type library object.

Inherited public predicates:

(none)

- Public predicates
 - empty/1
 - of/2
 - from_goal/3
 - from_goal/2
 - from_generator/3
 - from_generator/2
- Protected predicates
- Private predicates
- Operators

Public predicates

empty/1

Constructs an empty optional term.

Compilation flags:

static

Template:

empty(Optional)

Mode and number of proofs:

empty(--nonvar) - one

of/2

Constructs an optional term holding the given value.

Compilation flags:

static

Template:

of(Value,Optional)

Mode and number of proofs:

of(@term,--nonvar) - one

`from_goal/3`

Constructs an optional term holding a value bound by calling the given goal. Returns an empty optional term if the goal fails or throws an error.

Compilation flags:

`static`

Template:

`from_goal(Goal,Value,Optional)`

Meta-predicate template:

`from_goal(0,*,*)`

Mode and number of proofs:

`from_goal(+callable,--term,--nonvar) - one`

`from_goal/2`

Constructs an optional term holding a value bound by calling the given closure. Returns an empty optional term if the closure fails or throws an error.

Compilation flags:

`static`

Template:

`from_goal(Closure,Optional)`

Meta-predicate template:

`from_goal(1,*)`

Mode and number of proofs:

`from_goal(+callable,--nonvar) - one`

`from_generator/3`

Constructs optional terms with the values generated by calling the given goal. On goal error or failure, returns an empty optional.

Compilation flags:

`static`

Template:

`from_generator(Goal, Value, Optional)`

Meta-predicate template:

`from_generator(0, *, *)`

Mode and number of proofs:

`from_generator(+callable, --term, --nonvar) - one_or_more`

`from_generator/2`

Constructs optional terms with the values generated by calling the given closure. On closure error or failure, returns an empty optional.

Compilation flags:

`static`

Template:

`from_generator(Closure, Optional)`

Meta-predicate template:

`from_generator(1, *)`

Mode and number of proofs:

`from_generator(+from_generator, --nonvar) - one_or_more`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

`optional(Optional), type`

object

1.54.3 `optional(Optional)`

Optional term handling predicates. Requires passing an optional term (constructed using the optional object predicates) as a parameter.

Availability:

`logtalk_load(optionals(loader))`

Author: Paulo Moura

Version: 1:7:0

Date: 2019-11-26

Compilation flags:

`static, context_switching_calls`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - `is_empty/0`

- is_present/0
 - if_empty/1
 - if_present/1
 - if_present_or_else/2
 - filter/2
 - map/2
 - flat_map/2
 - or/2
 - get/1
 - or_else/2
 - or_else_get/2
 - or_else_call/2
 - or_else_fail/1
 - or_else_throw/2
- Protected predicates
 - Private predicates
 - Operators

Public predicates

is_empty/0

True if the optional term is empty. See also the if_empty/1 predicate.

Compilation flags:

static

Mode and number of proofs:

is_empty - zero_or_one

`is_present/0`

True if the optional term holds a value. See also the `if_present/1` predicate.

Compilation flags:

`static`

Mode and number of proofs:

`is_present - zero_or_one`

`if_empty/1`

Calls a goal if the optional term is empty. Succeeds otherwise.

Compilation flags:

`static`

Template:

`if_empty(Goal)`

Meta-predicate template:

`if_empty(0)`

Mode and number of proofs:

`if_empty(+callable) - zero_or_more`

`if_present/1`

Applies a closure to the value hold by the optional term if not empty. Succeeds otherwise.

Compilation flags:

`static`

Template:

`if_present(Closure)`

Meta-predicate template:

`if_present(1)`

Mode and number of proofs:

`if_present(+callable) - zero_or_more`

`if_present_or_else/2`

Applies a closure to the value hold by the optional term if not empty. Otherwise calls the given goal.

Compilation flags:

`static`

Template:

`if_present_or_else(Closure,Goal)`

Meta-predicate template:

`if_present_or_else(1,0)`

Mode and number of proofs:

`if_present_or_else(+callable,+callable) - zero_or_more`

`filter/2`

Returns the optional term when it is not empty and the value it holds satisfies a closure. Otherwise returns an empty optional term.

Compilation flags:

`static`

Template:

`filter(Closure,NewOptional)`

Meta-predicate template:

`filter(1,*)`

Mode and number of proofs:

`filter(+callable,--nonvar) - one`

`map/2`

When the optional term is not empty and mapping a closure with the value it holds and the new value as additional arguments is successful, returns an optional term with the new value. Otherwise returns an empty optional term.

Compilation flags:

`static`

Template:

`map(Closure,NewOptional)`

Meta-predicate template:

`map(2,*)`

Mode and number of proofs:

`map(+callable,--nonvar) - one`

`flat_map/2`

When the optional term is not empty and mapping a closure with the value it holds and the new optional term as additional arguments is successful, returns the new optional term. Otherwise returns an empty optional term.

Compilation flags:

`static`

Template:

`flat_map(Closure,NewOptional)`

Meta-predicate template:

`flat_map(2,*)`

Mode and number of proofs:

`flat_map(+callable,--nonvar) - one`

or/2

Returns the same optional term if not empty. Otherwise calls closure to generate a new optional term. Fails if optional term is empty and calling the closure fails or throws an error.

Compilation flags:

static

Template:

or(NewOptional,Closure)

Meta-predicate template:

or(*,1)

Mode and number of proofs:

or(--term,@callable) - zero_or_one

get/1

Returns the value hold by the optional term if not empty. Throws an error otherwise.

Compilation flags:

static

Template:

get(Value)

Mode and number of proofs:

get(--term) - one_or_error

Exceptions:

Optional is empty:

existence_error(optional_term,Optional)

`or_else/2`

Returns the value hold by the optional term if not empty or the given default value if the optional term is empty.

Compilation flags:

`static`

Template:

`or_else(Value,Default)`

Mode and number of proofs:

`or_else(--term,@term) - one`

`or_else_get/2`

Returns the value hold by the optional term if not empty. Applies a closure to compute the value otherwise. Throws an error when the optional term is empty and the value cannot be computed.

Compilation flags:

`static`

Template:

`or_else_get(Value,Closure)`

Meta-predicate template:

`or_else_get(*,1)`

Mode and number of proofs:

`or_else_get(--term,+callable) - one_or_error`

Exceptions:

Optional is empty and the term cannot be computed:

`existence_error(optional_term,Optional)`

`or_else_call/2`

Returns the value hold by the optional term if not empty or calls a goal deterministically if the optional term is empty.

Compilation flags:

`static`

Template:

`or_else_call(Value,Goal)`

Meta-predicate template:

`or_else_call(*,0)`

Mode and number of proofs:

`or_else_call(--term,+callable) - zero_or_one`

`or_else_fail/1`

Returns the value hold by the optional term if not empty. Fails otherwise. Usually called to skip over empty optional terms.

Compilation flags:

`static`

Template:

`or_else_fail(Value)`

Mode and number of proofs:

`or_else_fail(--term) - zero_or_one`

`or_else_throw/2`

Returns the value hold by the optional term if not empty. Throws the given error otherwise.

Compilation flags:

`static`

Template:

`or_else_throw(Value,Error)`

Mode and number of proofs:

```
or_else_throw(--term,@nonvar) - one_or_error
```

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

 See also

[optional](#)

1.55 options

category

1.55.1 options

Options processing predicates. Options are represented by compound terms where the functor is the option name.

Availability:

```
logtalk_load(options(loader))
```

Author: Paulo Moura

Version: 1:2:0

Date: 2022-01-03

Compilation flags:

```
static
```

Implements:

```
public options_protocol
```

Uses:

list

Remarks:

(none)

Inherited public predicates:

check_option/1 check_options/1 default_option/1 default_options/1 option/2 option/3
valid_option/1 valid_options/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.55.2 options_protocol

Options protocol.

Availability:

logtalk_load(options(loader))

Author: Paulo Moura

Version: 1:2:0

Date: 2022-01-03

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - check_option/1
 - check_options/1
 - valid_option/1
 - valid_options/1
 - default_option/1
 - default_options/1
 - option/2
 - option/3
- Protected predicates
 - merge_options/2
 - fix_options/2
 - fix_option/2
- Private predicates
- Operators

Public predicates

`check_option/1`

Succeeds if the option is valid. Throws an error otherwise.

Compilation flags:

`static`

Template:

`check_option(Option)`

Mode and number of proofs:

`check_option(@term) - one_or_error`

Exceptions:

Option is a variable:

`instantiation_error`

Option is neither a variable nor a compound term:

`type_error(compound,Option)`

Option is a compound term but not a valid option:

`domain_error(option,Option)`

`check_options/1`

Succeeds if all the options in a list are valid. Throws an error otherwise.

Compilation flags:

`static`

Template:

`check_options(Options)`

Mode and number of proofs:

`check_options(@term) - one_or_error`

Exceptions:

Options is a variable:

`instantiation_error`

Options is neither a variable nor a list:

`type_error(list,Options)`

An element Option of the list Options is a variable:

`instantiation_error`

An element Option of the list Options is neither a variable nor a compound term:

`type_error(compound,Option)`

An element Option of the list Options is a compound term but not a valid option:

`domain_error(option,Option)`

`valid_option/1`

Succeeds if the option is valid.

Compilation flags:

`static`

Template:

`valid_option(Option)`

Mode and number of proofs:

`valid_option(@term) - zero_or_one`

`valid_options/1`

Succeeds if all the options in a list are valid.

Compilation flags:

`static`

Template:

`valid_options(Options)`

Mode and number of proofs:

`valid_options(@term) - one`

`default_option/1`

Enumerates, by backtracking, the default options.

Compilation flags:

`static`

Template:

`default_option(Option)`

Mode and number of proofs:

`default_option(?compound) - zero_or_more`

`default_options/1`

Returns a list of the default options.

Compilation flags:

`static`

Template:

`default_options(Options)`

Mode and number of proofs:

`default_options(-list(compound)) - one`

`option/2`

True iff Option unifies with the first occurrence of the same option in the Options list.

Compilation flags:

`static`

Template:

`option(Option,Options)`

Mode and number of proofs:

`option(+compound,+list(compound)) - zero_or_one`

`option/3`

True iff `Option` unifies with the first occurrence of the same option in the `Options` list or, when that is not the case, if `Option` unifies with `Default`.

Compilation flags:

`static`

Template:

`option(Option,Options,Default)`

Mode and number of proofs:

`option(+compound,+list(compound),+compound) - zero_or_one`

Protected predicates

`merge_options/2`

Merges the user options with the default options, returning the final list of options. Calls the `fix_options/2` predicate to preprocess the options after merging. Callers must ensure, if required, that the user options are valid.

Compilation flags:

`static`

Template:

`merge_options(UserOptions,Options)`

Mode and number of proofs:

`merge_options(+list(compound),-list(compound)) - one`

`fix_options/2`

Fixes a list of options, returning the list of options.

Compilation flags:

`static`

Template:

```
fix_options(Options,FixedOptions)
```

Mode and number of proofs:

```
fix_options(+list(compound),-list(compound)) - one
```

```
fix_option/2
```

Fixes an option.

Compilation flags:

```
static
```

Template:

```
fix_option(Option,FixedOption)
```

Mode and number of proofs:

```
fix_option(+compound,-compound) - zero_or_one
```

Private predicates

(none)

Operators

(none)

 See also

[options](#)

1.56 os

object

1.56.1 `os`

Portable operating-system access predicates.

Availability:

```
logtalk_load(os(loader))
```

Author: Paulo Moura

Version: 1:101:2

Date: 2024-12-01

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public osp
```

Uses:

```
list
```

Aliases:

```
osp absolute_file_name/2 as expand_path/2
```

Remarks:

- File path expansion: To ensure portability, all file paths are expanded before being handed to the backend Prolog system.
- Exception terms: Currently, there is no standardization of the exception terms thrown by the different backend Prolog systems.
- B-Prolog portability: The `wall_time/1` predicate is not supported.
- CxProlog portability: The `date_time/7` predicate returns zeros for all arguments.
- JIProlog portability: The `file_permission/2` and `command_line_arguments/1` predicates are not supported.
- Quintus Prolog: The `pid/1` and `shell/2` predicates are not supported.
- XSB portability: The `command_line_arguments/1` predicate is not supported.

Inherited public predicates:

```
absolute_file_name/2 change_directory/1 command_line_arguments/1 copy_file/2 cpu_time/1  
date_time/7 decompose_file_name/3 decompose_file_name/4 delete_directory/1  
delete_directory_and_contents/1 delete_directory_contents/1 delete_file/1 directory_exists/1  
directory_files/2 directory_files/3 ensure_directory/1 ensure_file/1 environment_variable/2  
file_exists/1 file_modification_time/2 file_permission/2 file_size/2 full_device_path/1  
internal_os_path/2 is_absolute_file_name/1 make_directory/1 make_directory_path/1  
null_device_path/1 operating_system_machine/1 operating_system_name/1  
operating_system_release/1 operating_system_type/1 path_concat/3 pid/1
```

read_only_device_path/1 rename_file/2 shell/1 shell/2 sleep/1 temporary_directory/1
time_stamp/1 wall_time/1 working_directory/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

➡ See also

os_types

category

1.56.2 os_types

A set of operating-system related types.

Availability:

logtalk_load(os(loader))

Author: Paulo Moura

Version: 1:4:0

Date: 2021-02-12

Compilation flags:

static

Provides:

type::type/1
type::check/2

Uses:

list
os

Remarks:

- Provided types: This category adds file, file(Extensions), file(Extensions,Permissions), directory, directory(Permissions), and environment_variable types for type-checking when using the type library object.
- Type file: For checking if a term is an atom and an existing file.
- Type file(Extensions): For checking if a term is an atom and an existing file with one of the listed extensions (specified as '.ext').
- Type file(Extensions,Permissions): For checking if a term is an atom and an existing file with one of the listed extensions (specified as '.ext') and listed permissions ({read, write, execute}).
- Type directory: For checking if a term is an atom and an existing directory.
- Type directory(Permissions): For checking if a term is an atom and an existing directory with the listed permissions ({read, write, execute}).
- Type environment_variable: For checking if a term is an atom and an existing environment variable.

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

osp, os, type

protocol

1.56.3 osp

Portable operating-system access protocol.

Availability:

`logtalk_load(os(loader))`

Author: Paulo Moura

Version: 1:41:0

Date: 2025-05-19

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

- Error handling: Predicates that require a file or directory to exist throw an error when that is not the case. But the exact exception term is currently backend Prolog compiler dependent.

- CPU and wall time accuracy: Depends on the backend and can be different between CPU and wall time (e.g. CPU time can have nanosecond accuracy with wall time only having millisecond accuracy).

Inherited public predicates:

(none)

- Public predicates
 - pid/1
 - shell/2
 - shell/1
 - is_absolute_file_name/1
 - absolute_file_name/2
 - decompose_file_name/3
 - decompose_file_name/4
 - path_concat/3
 - internal_os_path/2
 - make_directory/1
 - make_directory_path/1
 - delete_directory/1
 - delete_directory_contents/1
 - delete_directory_and_contents/1
 - change_directory/1
 - working_directory/1
 - temporary_directory/1
 - null_device_path/1
 - full_device_path/1
 - read_only_device_path/1
 - directory_files/2
 - directory_files/3
 - directory_exists/1
 - ensure_directory/1
 - file_exists/1
 - file_modification_time/2
 - file_size/2
 - file_permission/2

- copy_file/2
- rename_file/2
- delete_file/1
- ensure_file/1
- environment_variable/2
- time_stamp/1
- date_time/7
- cpu_time/1
- wall_time/1
- operating_system_type/1
- operating_system_name/1
- operating_system_machine/1
- operating_system_release/1
- command_line_arguments/1
- sleep/1
- Protected predicates
- Private predicates
- Operators

Public predicates

pid/1

Returns the process identifier of the running process.

Compilation flags:

static

Template:

pid(PID)

Mode and number of proofs:

pid(-integer) - one

shell/2

Runs an operating-system shell command and returns its exit status.

Compilation flags:

static

Template:

shell(Command,Status)

Mode and number of proofs:

shell(+atom,-integer) - one

shell/1

Runs an operating-system shell command.

Compilation flags:

static

Template:

shell(Command)

Mode and number of proofs:

shell(+atom) - zero_or_one

is_absolute_file_name/1

True iff the argument is an absolute file path. On POSIX systems, this predicate is true if File starts with a /. On Windows systems, this predicate is true if File starts with a drive letter. No attempt is made to expand File as a path.

Compilation flags:

static

Template:

is_absolute_file_name(File)

Mode and number of proofs:

is_absolute_file_name(+atom) - zero_or_one

`absolute_file_name/2`

Expands a file name to an absolute file path. An environment variable at the beginning of the file name is also expanded.

Compilation flags:

static

Template:

`absolute_file_name(File,Path)`

Mode and number of proofs:

`absolute_file_name(+atom,-atom) - one`

`decompose_file_name/3`

Decomposes a file name into its directory (which always ends with a slash; `./` is returned if absent) and its basename (which can be the empty atom).

Compilation flags:

static

Template:

`decompose_file_name(File,Directory,Basename)`

Mode and number of proofs:

`decompose_file_name(+atom,?atom,?atom) - one`

`decompose_file_name/4`

Decomposes a file name into its directory (which always ends with a slash; `./` is returned if absent), name (that can be the empty atom), and extension (which starts with a `.` when defined; the empty atom otherwise).

Compilation flags:

static

Template:

```
decompose_file_name(File,Directory,Name,Extension)
```

Mode and number of proofs:

```
decompose_file_name(+atom,?atom,?atom,?atom) - one
```

`path_concat/3`

Concatenates a path prefix and a path suffix, adding a / separator if required. Returns Suffix when it is an absolute path. Returns Prefix with a trailing / appended if missing when Suffix is the empty atom.

Compilation flags:

```
static
```

Template:

```
path_concat(Prefix,Suffix,Path)
```

Mode and number of proofs:

```
path_concat(+atom,+atom,--atom) - one
```

`internal_os_path/2`

Converts between the internal path representation (which is backend dependent) and the operating-system native path representation.

Compilation flags:

```
static
```

Template:

```
internal_os_path(InternalPath,OSPath)
```

Mode and number of proofs:

```
internal_os_path(+atom,-atom) - one
```

```
internal_os_path(-atom,+atom) - one
```

`make_directory/1`

Makes a new directory. Succeeds if the directory already exists.

Compilation flags:

`static`

Template:

`make_directory(Directory)`

Mode and number of proofs:

`make_directory(+atom) - one`

`make_directory_path/1`

Makes a new directory creating all the intermediate directories if necessary. Succeeds if the directory already exists.

Compilation flags:

`static`

Template:

`make_directory_path(Directory)`

Mode and number of proofs:

`make_directory_path(+atom) - one`

`delete_directory/1`

Deletes an empty directory. Throws an error if the directory does not exist.

Compilation flags:

`static`

Template:

`delete_directory(Directory)`

Mode and number of proofs:

`delete_directory(+atom) - one_or_error`

`delete_directory_contents/1`

Deletes directory contents. Throws an error if the directory does not exist.

Compilation flags:

`static`

Template:

`delete_directory_contents(Directory)`

Mode and number of proofs:

`delete_directory_contents(+atom) - one_or_error`

`delete_directory_and_contents/1`

Deletes directory and its contents. Throws an error if the directory does not exist.

Compilation flags:

`static`

Template:

`delete_directory_and_contents(Directory)`

Mode and number of proofs:

`delete_directory_and_contents(+atom) - one_or_error`

`change_directory/1`

Changes current working directory. Throws an error if the directory does not exist.

Compilation flags:

`static`

Template:

`change_directory(Directory)`

Mode and number of proofs:

`change_directory(+atom) - one_or_error`

`working_directory/1`

Current working directory.

Compilation flags:

`static`

Template:

`working_directory(Directory)`

Mode and number of proofs:

`working_directory(?atom) - zero_or_one`

`temporary_directory/1`

Temporary directory. Tries first environment variables: TEMP and TMP on Windows systems; TMPDIR, TMP, TEMP, and TEMPDIR on POSIX systems. When not defined, tries default locations. Returns the working directory as last resort.

Compilation flags:

`static`

Template:

`temporary_directory(Directory)`

Mode and number of proofs:

`temporary_directory(?atom) - one`

`null_device_path/1`

Null device path: nul on Windows systems and /dev/null on POSIX systems.

Compilation flags:

`static`

Template:

`null_device_path(Path)`

Mode and number of proofs:

`null_device_path(?atom) - one`

`full_device_path/1`

Full device path: /dev/full on Linux and BSD systems. Fails on other systems. Experimental.

Compilation flags:

`static`

Template:

`full_device_path(Path)`

Mode and number of proofs:

`full_device_path(?atom) - zero_or_one`

`read_only_device_path/1`

Read-only device path: /dev/urandom on macOS. Fails on other systems. Experimental.

Compilation flags:

`static`

Template:

`read_only_device_path(Path)`

Mode and number of proofs:

`read_only_device_path(?atom) - zero_or_one`

`directory_files/2`

Returns a list of all files (including directories, regular files, and hidden directories and files) in a directory. File paths are relative to the directory. Throws an error if the directory does not exist.

Compilation flags:

`static`

Template:

`directory_files(Directory,Files)`

Mode and number of proofs:

`directory_files(+atom,-list(atom)) - one_or_error`

`directory_files/3`

Returns a list of files filtered using the given list of options. Invalid options are ignored. Default option values are equivalent to `directory_files/2`. Throws an error if the directory does not exist.

Compilation flags:

`static`

Template:

`directory_files(Directory,Files,Options)`

Mode and number of proofs:

`directory_files(+atom,-list(atom),+list(compound)) - one_or_error`

Remarks:

- Option `paths/1`: Possible values are relative and absolute. Default is relative.
 - Option `type/1`: Possible values are all, regular, directory. Default is all.
 - Option `extensions/1`: Argument is a list of required extensions (using the format `'.ext'`). Default is the empty list.
 - Option `prefixes/1`: Argument is a list of required file prefixes (atoms). Default is the empty list.
 - Option `suffixes/1`: Argument is a list of required file suffixes (atoms). Default is the empty list.
 - Option `dot_files/1`: Possible values are true and false. Default is true.
-

`directory_exists/1`

True if the specified directory exists (irrespective of directory permissions).

Compilation flags:

`static`

Template:

`directory_exists(Directory)`

Mode and number of proofs:

`directory_exists(+atom) - zero_or_one`

`ensure_directory/1`

Ensures that a directory exists, creating it if necessary.

Compilation flags:

`static`

Template:

`ensure_directory(Directory)`

Mode and number of proofs:

`ensure_directory(+atom) - one`

`file_exists/1`

True if the specified file exists and is a regular file (irrespective of file permissions).

Compilation flags:

`static`

Template:

`file_exists(File)`

Mode and number of proofs:

`file_exists(+atom) - zero_or_one`

`file_modification_time/2`

File modification time (which can be used for comparison). Throws an error if the file does not exist.

Compilation flags:

`static`

Template:

`file_modification_time(File,Time)`

Mode and number of proofs:

`file_modification_time(+atom,-integer) - one_or_error`

`file_size/2`

File size (in bytes). Throws an error if the file does not exist.

Compilation flags:

`static`

Template:

`file_size(File,Size)`

Mode and number of proofs:

`file_size(+atom,-integer) - one_or_error`

`file_permission/2`

True iff the specified file has the specified permission (read, write, or execute). Throws an error if the file does not exist.

Compilation flags:

`static`

Template:

`file_permission(File,Permission)`

Mode and number of proofs:

`file_permission(+atom,+atom) - zero_or_one_or_error`

`copy_file/2`

Copies a file. Throws an error if the original file does not exist or if the copy cannot be created.

Compilation flags:

`static`

Template:

`copy_file(File,Copy)`

Mode and number of proofs:

`copy_file(+atom,+atom) - one_or_error`

`rename_file/2`

Renames a file or a directory. Throws an error if the file or directory does not exist.

Compilation flags:

`static`

Template:

`rename_file(Old,New)`

Mode and number of proofs:

`rename_file(+atom,+atom) - one_or_error`

`delete_file/1`

Deletes a file. Throws an error if the file does not exist.

Compilation flags:

`static`

Template:

`delete_file(File)`

Mode and number of proofs:

`delete_file(+atom) - one_or_error`

`ensure_file/1`

Ensures that a file exists, creating it if necessary.

Compilation flags:

`static`

Template:

`ensure_file(File)`

Mode and number of proofs:

`ensure_file(+atom) - one`

`environment_variable/2`

Returns an environment variable value. Fails if the variable does not exists.

Compilation flags:

`static`

Template:

`environment_variable(Variable,Value)`

Mode and number of proofs:

`environment_variable(+atom,?atom) - zero_or_one`

`time_stamp/1`

Returns a system-dependent time stamp, which can be used for sorting, but should be regarded otherwise as an opaque term.

Compilation flags:

`static`

Template:

time_stamp(Time)

Mode and number of proofs:

time_stamp(-ground) - one

date_time/7

Returns the current date and time. Note that most backends do not provide sub-second accuracy and in those cases the value of the Milliseconds argument is always zero.

Compilation flags:

static

Template:

date_time(Year,Month,Day,Hours,Minutes,Seconds,Milliseconds)

Mode and number of proofs:

date_time(-integer,-integer,-integer,-integer,-integer,-integer,-integer) - one

cpu_time/1

System cpu time in seconds. Accuracy depends on the backend.

Compilation flags:

static

Template:

cpu_time(Seconds)

Mode and number of proofs:

cpu_time(-number) - one

`wall_time/1`

Wall time in seconds. Accuracy depends on the backend.

Compilation flags:

`static`

Template:

`wall_time(Seconds)`

Mode and number of proofs:

`wall_time(-number) - one`

`operating_system_type/1`

Operating system type. Possible values are `unix`, `windows`, and `unknown`.

Compilation flags:

`static`

Template:

`operating_system_type(Type)`

Mode and number of proofs:

`operating_system_type(?atom) - zero_or_one`

`operating_system_name/1`

Operating system name. On POSIX systems, it returns the value of `uname -s`. On macOS systems, it returns `'Darwin'`. On Windows systems, it returns `'Windows'`.

Compilation flags:

`static`

Template:

`operating_system_name(Name)`

Mode and number of proofs:

`operating_system_name(?atom) - zero_or_one`

`operating_system_machine/1`

Operating system hardware platform. On POSIX systems, it returns the value of `uname -m`. On Windows systems, it returns the value of the `PROCESSOR_ARCHITECTURE` environment variable.

Compilation flags:

`static`

Template:

`operating_system_machine(Machine)`

Mode and number of proofs:

`operating_system_machine(?atom) - zero_or_one`

`operating_system_release/1`

Operating system release. On POSIX systems, it returns the value of `uname -r`. On Windows systems, it uses WMI code.

Compilation flags:

`static`

Template:

`operating_system_release(Release)`

Mode and number of proofs:

`operating_system_release(?atom) - zero_or_one`

`command_line_arguments/1`

Returns a list with the command line arguments that occur after `--`.

Compilation flags:

`static`

Template:

```
command_line_arguments(Arguments)
```

Mode and number of proofs:

```
command_line_arguments(-list(atom)) - one
```

`sleep/1`

Suspends execution the given number of seconds.

Compilation flags:

```
static
```

Template:

```
sleep(Seconds)
```

Mode and number of proofs:

```
sleep(+number) - one
```

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

 See also

`os`, `os_types`

1.57 packs

protocol

1.57.1 pack_protocol

Pack specification protocol. Objects implementing this protocol should be named after the pack with a `_pack` suffix and saved in a file with the same name as the object.

Availability:

`logtalk_load(packs(loader))`

Author: Paulo Moura

Version: 0:18:0

Date: 2025-05-21

Compilation flags:

`static`

Dependencies:

`(none)`

Remarks:

`(none)`

Inherited public predicates:

`(none)`

- Public predicates
 - `name/1`
 - `description/1`
 - `license/1`
 - `home/1`
 - `version/6`
 - `note/3`
- Protected predicates
- Private predicates

- Operators

Public predicates

name/1

Pack name.

Compilation flags:
static

Template:
name(Name)
Mode and number of proofs:
name(?atom) - zero_or_one

description/1

Pack one line description.

Compilation flags:
static

Template:
description(Description)
Mode and number of proofs:
description(?atom) - zero_or_one

license/1

Pack license. Specified using the identifier from the SPDX License List (<https://spdx.org/licenses/>) when possible.

Compilation flags:
static

Template:

license(License)

Mode and number of proofs:

license(?atom) - zero_or_one

home/1

Pack home HTTPS or file URL.

Compilation flags:

static

Template:

home(Home)

Mode and number of proofs:

home(?atom) - zero_or_one

version/6

Table of available versions.

Compilation flags:

static

Template:

version(Version,Status,URL,Checksum,Dependencies,Portability)

Mode and number of proofs:

version(?compound,?atom,-atom,-pair(atom,atom),-list(pair(atom,callable)),?atom) - zero_or_more
version(?compound,?atom,-atom,-pair(atom,atom),-list(pair(atom,callable)),-list(atom)) -
zero_or_more

Remarks:

- Version: This argument uses the same format as entity versions: Major:Minor:Patch. Semantic versioning should be used.
- Status: Version development status: stable, rc, beta, alpha, experimental, or deprecated.

- URL: File URL for a local directory, file URL for a local archive, download HTTPS URL for the pack archive, or download git archive URL for the pack archive.
- Checksum: A pair where the key is the hash algorithm and the value is the checksum. Currently, the hash algorithm must be sha256. For file:// URLs of local directories, use none instead of a pair.
- Dependencies: Pack dependencies list. Each dependency is a Dependency Operator Version term. Operator is a term comparison operator. Valid Dependency values are Registry::Pack, os(Name,Machine), logtalk, and a backend identifier atom.
- Portability: Either the atom all or a list of the supported backend Prolog compilers (using the identifier atoms used by the prolog_dialect flag).
- Clause order: Versions must be listed ordered from newest to oldest.

note/3

Table of notes per action and version.

Compilation flags:

static

Template:

note(Action,Version,Note)

Mode and number of proofs:

note(?atom,?term,-atom) - zero_or_more

Remarks:

- Action: Possible values are install, update, and uninstall. When unbound, the note apply to all actions.
- Version: Version being installed, updated, or uninstalled. When unbound, the note apply to all versions.
- Note: Note to print when performing an action on a pack version.

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

object

1.57.2 packs

Pack handling predicates.

Availability:

logtalk__load(packs(loader))

Author: Paulo Moura

Version: 0:87:0

Date: 2025-05-23

Compilation flags:

static, context_switching_calls

Imports:

public packs__common

public options

Uses:

list

logtalk

os

registries

type

user

Remarks:

(none)

Inherited public predicates:

check_option/1 check_options/1 default_option/1 default_options/1 directory/1 directory/2
help/0 logtalk_packs/0 logtalk_packs/1 option/2 option/3 pin/0 pin/1 pinned/1 prefix/0
prefix/1 readme/1 readme/2 reset/0 setup/0 unpin/0 unpin/1 valid_option/1 valid_options/1
verify_commands_availability/0

- Public predicates

- available/2
- available/1
- available/0
- installed/4
- installed/3
- installed/1
- installed/0
- outdated/5
- outdated/4
- outdated/2
- outdated/1
- outdated/0
- orphaned/2
- orphaned/0
- versions/3
- describe/2
- describe/1
- search/1
- install/4
- install/3
- install/2
- install/1
- update/3
- update/2
- update/1
- update/0
- uninstall/2
- uninstall/1
- uninstall/0
- clean/2
- clean/1
- clean/0
- save/2

- save/1
- restore/2
- restore/1
- dependents/3
- dependents/2
- dependents/1
- lint/2
- lint/1
- lint/0
- Protected predicates
- Private predicates
- Operators

Public predicates

available/2

Enumerates, by backtracking, all available packs.

Compilation flags:

static

Template:

available(Registry,Pack)

Mode and number of proofs:

available(?atom,?atom) - zero_or_more

Exceptions:

Registry is neither a variable nor an atom:

type_error(atom,Registry)

Pack is neither a variable nor an atom:

type_error(atom,Pack)

available/1

Lists all the packs that are available for installation from the given registry.

Compilation flags:

static

Template:

available(Registry)

Mode and number of proofs:

available(+atom) - one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

type_error(atom,Registry)

available/0

Lists all the packs that are available for installation from all defined registries.

Compilation flags:

static

Mode and number of proofs:

available - one

installed/4

Enumerates by backtracking all installed packs.

Compilation flags:

static

Template:

installed(Registry,Pack,Version,Pinned)

Mode and number of proofs:

installed(?atom,?atom,?compound,?boolean) - zero_or_more

Exceptions:

Registry is neither a variable nor an atom:

type__error(atom,Registry)

Pack is neither a variable nor an atom:

type__error(atom,Pack)

Version is neither a variable nor a compound term:

type__error(compound,Version)

Pinned is neither a variable nor a boolean:

type__error(boolean,Pinned)

installed/3

Enumerates by backtracking all installed packs.

Compilation flags:

static

Template:

installed(Registry,Pack,Version)

Mode and number of proofs:

installed(?atom,?atom,?compound) - zero_or_more

Exceptions:

Registry is neither a variable nor an atom:

type__error(atom,Registry)

Pack is neither a variable nor an atom:

type__error(atom,Pack)

Version is neither a variable nor a compound term:

type__error(compound,Version)

installed/1

Lists all the packs that are installed from the given registry. Fails if the registry is unknown.

Compilation flags:

static

Template:

installed(Registry)

Mode and number of proofs:

installed(+atom) - zero_or_one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

type_error(atom,Registry)

installed/0

Lists all the packs that are installed.

Compilation flags:

static

Mode and number of proofs:

installed - one

outdated/5

Enumerates by backtracking all installed but outdated packs (together with the current version installed and the latest version available) using the given options.

Compilation flags:

static

Template:

outdated(Registry,Pack,Version,LatestVersion,Options)

Mode and number of proofs:

outdated(?atom,?atom,?compound,?compound,++list(compound)) - zero_or_more

Exceptions:

Registry is neither a variable nor an atom:

type__error(atom,Registry)

Pack is neither a variable nor an atom:

type__error(atom,Pack)

Version is neither a variable nor a compound term:

type__error(compound,Version)

LatestVersion is neither a variable nor a compound term:

type__error(compound,LatestVersion)

Options is a variable:

instantiation__error

Options is neither a variable nor a list:

type__error(list,Options)

An element Option of the list Options is a variable:

instantiation__error

An element Option of the list Options is neither a variable nor a compound term:

type__error(compound,Option)

An element Option of the list Options is a compound term but not a valid option:

domain__error(option,Option)

Remarks:

- compatible(Boolean) option: Restrict listing to compatible packs. Default is true.
 - status(Status) option: Restrict listing to updates with the given status. Default is [stable,rc,beta,alpha]. Set to all to also list experimental and deprecated updates.
-

outdated/4

Enumerates by backtracking all installed but outdated packs (together with the current version installed and the latest version available) using default options.

Compilation flags:

static

Template:

outdated(Registry,Pack,Version,LatestVersion)

Mode and number of proofs:

outdated(?atom,?atom,?compound,?compound) - zero_or_more

Exceptions:

Registry is neither a variable nor an atom:

```
type__error(atom,Registry)
```

Pack is neither a variable nor an atom:

```
type__error(atom,Pack)
```

Version is neither a variable nor a compound term:

```
type__error(compound,Version)
```

LatestVersion is neither a variable nor a compound term:

```
type__error(compound,LatestVersion)
```

See also:

[outdated/5](#)

[outdated/2](#)

Lists all the packs from the given registry that are installed but outdated using the given options.

Compilation flags:

static

Template:

```
outdated(Registry,Options)
```

Mode and number of proofs:

```
outdated(+atom,++list(compound)) - one
```

Exceptions:

Registry is neither a variable nor an atom:

```
type__error(atom,Registry)
```

Options is a variable:

```
instantiation__error
```

Options is neither a variable nor a list:

```
type__error(list,Options)
```

An element Option of the list Options is a variable:

```
instantiation__error
```

An element Option of the list Options is neither a variable nor a compound term:

```
type__error(compound,Option)
```

An element Option of the list Options is a compound term but not a valid option:

```
domain__error(option,Option)
```

Remarks:

- `compatible(Boolean)` option: Restrict installation to compatible packs. Default is true.
 - `status(Status)` option: Restrict listing to updates with the given status. Default is `[stable,rc,beta,alpha]`. Set to `all` to also list experimental and deprecated updates.
-

`outdated/1`

Lists all the packs from the given registry that are installed but outdated using default options.

Compilation flags:

`static`

Template:

`outdated(Registry)`

Mode and number of proofs:

`outdated(+atom) - one`

Exceptions:

Registry is neither a variable nor an atom:

`type_error(atom,Registry)`

See also:

[`outdated/2`](#)

`outdated/0`

Lists all the packs that are installed but outdated using default options.

Compilation flags:

`static`

Mode and number of proofs:

`outdated - one`

orphaned/2

Lists all the packs that are installed but whose registry is no longer defined.

Compilation flags:

static

Template:

orphaned(Registry,Pack)

Mode and number of proofs:

orphaned(?atom,?atom) - zero_or_more

Exceptions:

Registry is neither a variable nor an atom:

type_error(atom,Registry)

Pack is neither a variable nor an atom:

type_error(atom,Pack)

orphaned/0

Lists all the packs that are installed but whose registry is no longer defined.

Compilation flags:

static

Mode and number of proofs:

orphaned - one

versions/3

Returns a list of all available pack versions. Fails if the pack is unknown.

Compilation flags:

static

Template:

versions(Registry,Pack,Versions)

Mode and number of proofs:

versions(+atom,+atom,-list) - zero_or_one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

type_error(atom,Registry)

Pack is a variable:

instantiation_error

Pack is neither a variable nor an atom:

type_error(atom,Pack)

describe/2

Describes a registered pack, including installed version if applicable. Fails if the pack is unknown.

Compilation flags:

static

Template:

describe(Registry,Pack)

Mode and number of proofs:

describe(+atom,+atom) - zero_or_one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

type_error(atom,Registry)

Pack is a variable:

instantiation_error

Pack is neither a variable nor an atom:

type_error(atom,Pack)

describe/1

Describes a registered pack, including installed version if applicable. Fails if the pack is unknown.

Compilation flags:

static

Template:

describe(Pack)

Mode and number of proofs:

describe(+atom) - zero_or_one

Exceptions:

Pack is a variable:

instantiation_error

Pack is neither a variable nor an atom:

type_error(atom,Pack)

search/1

Searches packs whose name or description includes the search term (case sensitive).

Compilation flags:

static

Template:

search(Term)

Mode and number of proofs:

search(+atom) - one

Exceptions:

Term is a variable:

instantiation_error

Term is neither a variable nor an atom:

type_error(atom,Term)

install/4

Installs a new pack using the specified options. Fails if the pack is unknown or already installed but not using `update(true)` or `force(true)` options. Fails also if the pack version is unknown.

Compilation flags:

`static`

Template:

`install(Registry,Pack,Version,Options)`

Mode and number of proofs:

`install(+atom,+atom,++compound,++list(compound)) - zero_or_one`

Exceptions:

Registry is a variable:

`instantiation_error`

Registry is neither a variable nor an atom:

`type_error(atom,Registry)`

Pack is a variable:

`instantiation_error`

Pack is neither a variable nor an atom:

`type_error(atom,Pack)`

Version is a variable:

`instantiation_error`

Version is neither a variable nor a valid version:

`type_error(pack_version,Version)`

Options is a variable:

`instantiation_error`

Options is neither a variable nor a list:

`type_error(list,Options)`

An element Option of the list Options is a variable:

`instantiation_error`

An element Option of the list Options is neither a variable nor a compound term:

`type_error(compound,Option)`

An element Option of the list Options is a compound term but not a valid option:

`domain_error(option,Option)`

Remarks:

- `update(Boolean)` option: Update pack if already installed. Default is false. Overrides the `force/1` option.
- `force(Boolean)` option: Force pack re-installation if already installed. Default is false.
- `compatible(Boolean)` option: Restrict installation to compatible packs. Default is true.
- `clean(Boolean)` option: Clean pack archive after installation. Default is false.

- `verbose(Boolean)` option: Verbose installing steps. Default is false.
- `checksum(Boolean)` option: Verify pack archive checksum. Default is true.
- `checksig(Boolean)` option: Verify pack archive signature. Default is false.
- `git(Atom)` option: Extra command-line options. Default is ''.
- `downloader(Atom)` option: Downloader utility. Either curl or wget. Default is curl.
- `curl(Atom)` option: Extra command-line options. Default is ''.
- `wget(Atom)` option: Extra command-line options. Default is ''.
- `gpg(Atom)` option: Extra command-line options. Default is ''.
- `tar(Atom)` option: Extra command-line options. Default is ''.

`install/3`

Installs the specified version of a pack from the given registry using default options. Fails if the pack is already installed or unknown. Fails also if the pack version is unknown.

Compilation flags:

`static`

Template:

`install(Registry,Pack,Version)`

Mode and number of proofs:

`install(+atom,+atom,?compound) - zero_or_one`

Exceptions:

Registry is a variable:

`instantiation_error`

Registry is neither a variable nor an atom:

`type_error(atom,Registry)`

Pack is a variable:

`instantiation_error`

Pack is neither a variable nor an atom:

`type_error(atom,Pack)`

Version is a variable:

`instantiation_error`

Version is neither a variable nor a valid version:

`type_error(pack_version,Version)`

install/2

Installs the latest version of a pack from the given registry using default options. Fails if the pack is already installed or unknown.

Compilation flags:

static

Template:

install(Registry,Pack)

Mode and number of proofs:

install(+atom,+atom) - zero_or_one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

type_error(atom,Registry)

Pack is a variable:

instantiation_error

Pack is neither a variable nor an atom:

type_error(atom,Pack)

install/1

Installs a pack (if its name is unique among all registries) using default options. Fails if the pack is already installed or unknown. Fails also if the pack is available from multiple registries.

Compilation flags:

static

Template:

install(Pack)

Mode and number of proofs:

install(+atom) - zero_or_one

Exceptions:

Pack is a variable:

instantiation_error

Pack is not an atom:

```
type__error(atom,Pack)
```

```
update/3
```

Updates an outdated pack to the specified version using the specified options. Fails if the pack or the pack version is unknown or if the pack is not installed. Fails also if the pack is orphaned or pinned and not using a `force(true)` option.

Compilation flags:

```
static
```

Template:

```
update(Pack,Version,Options)
```

Mode and number of proofs:

```
update(+atom,++callable,++list(callable)) - zero_or_one
```

Exceptions:

Pack is a variable:

```
instantiation__error
```

Pack is neither a variable nor an atom:

```
type__error(atom,Pack)
```

Version is a variable:

```
instantiation__error
```

Version is neither a variable nor a valid version:

```
type__error(pack_version,Version)
```

Options is a variable:

```
instantiation__error
```

Options is neither a variable nor a list:

```
type__error(list,Options)
```

An element Option of the list Options is a variable:

```
instantiation__error
```

An element Option of the list Options is neither a variable nor a compound term:

```
type__error(compound,Option)
```

An element Option of the list Options is a compound term but not a valid option:

```
domain__error(option,Option)
```

Remarks:

- `install(Boolean)` option: Install pack latest version if not already installed. Default is false.
- `force(Boolean)` option: Force update if the pack is pinned or breaks installed packs. Default is false.
- `compatible(Boolean)` option: Restrict updating to compatible packs. Default is true.

- `status(Status)` option: Specify allowed pack status. Default is `[stable,rc,beta,alpha]`. Set to `all` to also allow experimental and deprecated.
 - `clean(Boolean)` option: Clean pack archive after updating. Default is `false`.
 - `verbose(Boolean)` option: Verbose updating steps. Default is `false`.
 - `checksum(Boolean)` option: Verify pack archive checksum. Default is `true`.
 - `checksig(Boolean)` option: Verify pack archive signature. Default is `false`.
 - `git(Atom)` option: Extra command-line options. Default is `''`.
 - `downloader(Atom)` option: Downloader utility. Either `curl` or `wget`. Default is `curl`.
 - `curl(Atom)` option: Extra command-line options. Default is `''`.
 - `wget(Atom)` option: Extra command-line options. Default is `''`.
 - `gpg(Atom)` option: Extra command-line options. Default is `''`.
 - `tar(Atom)` option: Extra command-line options. Default is `''`.
-

`update/2`

Updates an outdated pack to its latest version using the specified options. Fails if the pack is orphaned, unknown, or not installed. Fails also if the pack is pinned and not using a `force(true)` option.

Compilation flags:

`static`

Template:

`update(Pack,Options)`

Mode and number of proofs:

`update(+atom,++list(callable)) - zero_or_one`

Exceptions:

Pack is a variable:

`instantiation_error`

Pack is neither a variable nor an atom:

`type_error(atom,Pack)`

Options is a variable:

`instantiation_error`

Options is neither a variable nor a list:

`type_error(list,Options)`

An element Option of the list Options is a variable:

`instantiation_error`

An element Option of the list Options is neither a variable nor a compound term:

`type_error(compound,Option)`

An element Option of the list Options is a compound term but not a valid option:

`domain_error(option,Option)`

Remarks:

- `install(Boolean)` option: Install pack latest version if not already installed. Default is false.
- `force(Boolean)` option: Force update if the pack is pinned or breaks installed packs. Default is false.
- `compatible(Boolean)` option: Restrict updating to compatible packs. Default is true.
- `status(Status)` option: Specify allowed pack update status. Default is [stable,rc,beta,alpha]. Set to all to also allow experimental and deprecated.
- `clean(Boolean)` option: Clean pack archive after updating. Default is false.
- `verbose(Boolean)` option: Verbose updating steps. Default is false.
- `checksum(Boolean)` option: Verify pack archive checksum. Default is true.
- `checksig(Boolean)` option: Verify pack archive signature. Default is false.
- `git(Atom)` option: Extra command-line options. Default is ''.
- `downloader(Atom)` option: Downloader utility. Either curl or wget. Default is curl.
- `curl(Atom)` option: Extra command-line options. Default is ''.
- `wget(Atom)` option: Extra command-line options. Default is ''.
- `gpg(Atom)` option: Extra command-line options. Default is ''.
- `tar(Atom)` option: Extra command-line options. Default is ''.

`update/1`

Updates an outdated pack to its latest version using default options. Fails if the pack is pinned, orphaned, not installed, unknown, or breaks installed packs.

Compilation flags:

`static`

Template:

`update(Pack)`

Mode and number of proofs:

`update(+atom) - zero_or_one`

Exceptions:

Pack is a variable:

`instantiation_error`

Pack is neither a variable nor an atom:

`type_error(atom,Pack)`

See also:

[update/2](#)

[update/3](#)

[update/0](#)

Updates all outdated packs (that are not pinned) using default options.

Compilation flags:

static

Mode and number of proofs:

update - zero_or_one

[uninstall/2](#)

Uninstalls a pack using the specified options. Fails if the pack is unknown or not installed. Fails also if the pack is pinned or have dependents and not using a force(true) option.

Compilation flags:

static

Template:

uninstall(Pack,Options)

Mode and number of proofs:

uninstall(+atom,++list(compound)) - zero_or_one

Exceptions:

Pack is a variable:

instantiation_error

Pack is neither a variable nor an atom:

type_error(atom,Pack)

Options is a variable:

instantiation_error

Options is neither a variable nor a list:

type_error(list,Options)

An element Option of the list Options is a variable:

instantiation_error

An element Option of the list Options is neither a variable nor a compound term:

`type_error(compound,Option)`

An element Option of the list Options is a compound term but not a valid option:

`domain_error(option,Option)`

Remarks:

- `force(Boolean)` option: Force deletion if the pack is pinned. Default is false.
 - `clean(Boolean)` option: Clean pack archive after deleting. Default is false.
 - `verbose(Boolean)` option: Verbose uninstalling steps. Default is false.
-

`uninstall/1`

Uninstalls a pack using default options. Fails if the pack is pinned, have dependents, not installed, or unknown.

Compilation flags:

`static`

Template:

`uninstall(Pack)`

Mode and number of proofs:

`uninstall(+atom) - zero_or_one`

Exceptions:

Pack is a variable:

`instantiation_error`

Pack is neither a variable nor an atom:

`type_error(atom,Pack)`

`uninstall/0`

Uninstalls all packs using the `force(true)` option.

Compilation flags:

`static`

Mode and number of proofs:

uninstall - zero_or_one

clean/2

Cleans all pack archives. Fails if the the pack is unknown.

Compilation flags:

static

Template:

clean(Registry,Pack)

Mode and number of proofs:

clean(+atom,+atom) - zero_or_one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

type_error(atom,Registry)

Pack is a variable:

instantiation_error

Pack is neither a variable nor an atom:

type_error(atom,Pack)

clean/1

Cleans all pack archives. Fails if the pack is unknown.

Compilation flags:

static

Template:

clean(Pack)

Mode and number of proofs:

clean(+atom) - zero_or_one

Exceptions:

Pack is a variable:

instantiation_error

Pack is neither a variable nor an atom:

type_error(atom,Pack)

clean/0

Cleans all archives for all packs.

Compilation flags:

static

Mode and number of proofs:

clean - one

save/2

Saves a list of all installed packs and registries plus pinning status to a file using the given options. Registries without installed packs are saved when using the option save(all) and skipped when using the option save(installed) (default).

Compilation flags:

static

Template:

save(File,Options)

Mode and number of proofs:

save(+atom,++list(compound)) - one_or_error

Exceptions:

File is a variable:

instantiation_error

File is neither a variable nor an atom:

type_error(atom,File)

File is an existing file but cannot be written:

permission_error(open,source_sink,File)

Options is a variable:

instantiation_error

Options is neither a variable nor a list:

`type_error(list,Options)`

An element Option of the list Options is a variable:

`instantiation_error`

An element Option of the list Options is neither a variable nor a compound term:

`type_error(compound,Option)`

An element Option of the list Options is a compound term but not a valid option:

`domain_error(option,Option)`

`save/1`

Saves a list of all installed packs and their registries plus pinning status to a file using default options.

Compilation flags:

`static`

Template:

`save(File)`

Mode and number of proofs:

`save(+atom) - one_or_error`

Exceptions:

File is a variable:

`instantiation_error`

File is neither a variable nor an atom:

`type_error(atom,File)`

File is an existing file but cannot be written:

`permission_error(open,source_sink,File)`

`restore/2`

Restores a list of registries and packs plus their pinning status from a file using the given options. Fails if restoring is not possible.

Compilation flags:

`static`

Template:

```
restore(File,Options)
```

Mode and number of proofs:

```
restore(+atom,++list(compound)) - zero_or_one_or_error
```

Exceptions:

File is a variable:

```
instantiation_error
```

File is neither a variable nor an atom:

```
type_error(atom,File)
```

File is an atom but not an existing file:

```
existence_error(file,File)
```

File is an existing file but cannot be read:

```
permission_error(open,source_sink,File)
```

Options is a variable:

```
instantiation_error
```

Options is neither a variable nor a list:

```
type_error(list,Options)
```

An element Option of the list Options is a variable:

```
instantiation_error
```

An element Option of the list Options is neither a variable nor a compound term:

```
type_error(compound,Option)
```

An element Option of the list Options is a compound term but not a valid option:

```
domain_error(option,Option)
```

Remarks:

- `force(Boolean)` option: Force restoring if a registry is already defined or a pack is already installed. Default is true.
- `compatible(Boolean)` option: Restrict installation to compatible packs. Default is true.
- `clean(Boolean)` option: Clean registry and pack archives after restoring. Default is false.
- `verbose(Boolean)` option: Verbose restoring steps. Default is false.
- `checksum(Boolean)` option: Verify pack archive checksums. Default is true.
- `checksig(Boolean)` option: Verify pack archive signatures. Default is false.
- `git(Atom)` option: Extra command-line options. Default is ''.
- `downloader(Atom)` option: Downloader utility. Either curl or wget. Default is curl.
- `curl(Atom)` option: Extra command-line options. Default is ''.
- `wget(Atom)` option: Extra command-line options. Default is ''.
- `gpg(Atom)` option: Extra command-line options. Default is ''.
- `tar(Atom)` option: Extra command-line options. Default is ''.

restore/1

Restores a list of registries and packs plus their pinning status from a file using default options. Fails if restoring is not possible.

Compilation flags:

static

Template:

restore(File)

Mode and number of proofs:

restore(+atom) - zero_or_one_or_error

Exceptions:

File is a variable:

instantiation_error

File is neither a variable nor an atom:

type_error(atom,File)

File is an atom but not an existing file:

existence_error(file,File)

File is an existing file but cannot be read:

permission_error(open,source_sink,File)

dependents/3

Returns a list of all installed packs that depend on the given pack from the given registry. Fails if the pack is unknown.

Compilation flags:

static

Template:

dependents(Registry,Pack,Dependents)

Mode and number of proofs:

dependents(+atom,+atom,-list(atom)) - zero_or_one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

```

    type_error(atom,Registry)
Pack is a variable:
    instantiation_error
Pack is neither a variable nor an atom:
    type_error(atom,Pack)

```

dependents/2

Prints a list of all installed packs that depend on the given pack from the given registry. Fails if the pack is unknown.

Compilation flags:

```
static
```

Template:

```
dependents(Registry,Pack)
```

Mode and number of proofs:

```
dependents(+atom,+atom) - zero_or_one
```

Exceptions:

Registry is a variable:

```
instantiation_error
```

Registry is neither a variable nor an atom:

```
type_error(atom,Registry)
```

Pack is a variable:

```
instantiation_error
```

Pack is neither a variable nor an atom:

```
type_error(atom,Pack)
```

dependents/1

Prints a list of all installed packs that depend on the given pack if unique from all defined registries. Fails if the pack is unknown or available from multiple registries.

Compilation flags:

```
static
```

Template:

dependents(Pack)

Mode and number of proofs:

dependents(+atom) - zero_or_one

Exceptions:

Pack is a variable:

instantiation_error

Pack is neither a variable nor an atom:

type_error(atom,Pack)

lint/2

Checks the pack specification. Fails if the pack is unknown or if linting detects errors.

Compilation flags:

static

Template:

lint(Registry,Pack)

Mode and number of proofs:

lint(+atom,+atom) - zero_or_one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

type_error(atom,Registry)

Pack is a variable:

instantiation_error

Pack is neither a variable nor an atom:

type_error(atom,Pack)

lint/1

Checks the pack specification. Fails if the pack is unknown, or available from multiple registries, or if linting detects errors.

Compilation flags:

static

Template:

lint(Pack)

Mode and number of proofs:

lint(+atom) - zero_or_one

Exceptions:

Pack is a variable:

instantiation_error

Pack is neither a variable nor an atom:

type_error(atom,Pack)

lint/0

Checks all pack specifications.

Compilation flags:

static

Mode and number of proofs:

lint - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.57.3 packs_common

Common predicates for the packs tool objects.

Availability:

`logtalk__load(packs(loader))`

Author: Paulo Moura

Version: 0:33:0

Date: 2025-01-23

Compilation flags:

`static`

Provides:

`type::type/1`

`type::check/2`

Uses:

`list`

`logtalk`

`os`

`type`

`user`

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - setup/0
 - reset/0
 - verify_commands_availability/0
 - help/0
 - pin/1
 - pin/0
 - unpin/1
 - unpin/0
 - pinned/1
 - directory/2
 - directory/1
 - readme/2
 - readme/1
 - logtalk_packs/1
 - logtalk_packs/0
 - prefix/1
 - prefix/0
- Protected predicates
 - readme_file_path/2
 - print_readme_file_path/1
 - command/2
 - load_registry/1
 - sha256sum_command/1
 - tar_command/1
 - supported_archive/1
 - supported_url_archive/1
 - decode_url_spaces/2
- Private predicates
- Operators

Public predicates

`setup/0`

Ensures that registries and packs directory structure exists. Preserves any defined registries and installed packs.

Compilation flags:

`static`

Mode and number of proofs:

`setup - one`

`reset/0`

Resets registries and packs directory structure. Deletes any defined registries and installed packs.

Compilation flags:

`static`

Mode and number of proofs:

`reset - one`

`verify_commands_availability/0`

Verifies required shell commands availability. Fails printing an error message if a command is missing.

Compilation flags:

`static`

Mode and number of proofs:

`verify_commands_availability - zero_or_one`

help/0

Provides help about the main predicates.

Compilation flags:

static

Mode and number of proofs:

help - one

pin/1

Pins a resource (pack or registry) preventing it from being updated, uninstalled, or deleted. Fails if the resource is not found.

Compilation flags:

static

Template:

pin(Resource)

Mode and number of proofs:

pin(+atom) - zero_or_one

Exceptions:

Resource is a variable:

instantiation_error

Resource is neither a variable nor an atom:

type_error(atom,Resource)

pin/0

Pins all resource (packs or registries) preventing them from being updated, uninstalled, or deleted. Note that resources added after calling this predicate will not be pinned.

Compilation flags:

static

Mode and number of proofs:

pin - one

unpin/1

Unpins a resource (pack or registry), allowing it to be updated, uninstalled, or deleted. Fails if the resource is not found.

Compilation flags:

static

Template:

unpin(Resource)

Mode and number of proofs:

unpin(+atom) - zero_or_one

Exceptions:

Resource is a variable:

instantiation_error

Resource is neither a variable nor an atom:

type_error(atom,Resource)

unpin/0

Unpins all resources (packs or registries), allowing them to be updated, uninstalled, or deleted.

Compilation flags:

static

Mode and number of proofs:

unpin - one

pinned/1

True iff the resource (pack or registry) is defined or installed and if it is pinned.

Compilation flags:

static

Template:

pinned(Resource)

Mode and number of proofs:

pinned(+atom) - zero_or_one

Exceptions:

Resource is a variable:

instantiation_error

Resource is neither a variable nor an atom:

type_error(atom,Resource)

directory/2

Enumerates by backtracking all packs or registries and respective installation or definition directories (using the internal backend format).

Compilation flags:

static

Template:

directory(Resource,Directory)

Mode and number of proofs:

directory(?atom,?atom) - zero_or_more

Exceptions:

Resource is neither a variable nor an atom:

type_error(atom,Resource)

Directory is neither a variable nor an atom:

type_error(atom,Directory)

directory/1

Prints the directory where the registry or the pack is installed (using the native operating-system format).

Compilation flags:

static

Template:

directory(Resource)

Mode and number of proofs:

directory(+atom) - zero_or_one

Exceptions:

Resource is a variable:

instantiation_error

Resource is neither a variable nor an atom:

type_error(atom,Resource)

readme/2

Returns the path to the resource (pack or registry) readme file (using the internal backend format). Fails if the resource is not defined or installed or if no readme file is found for it.

Compilation flags:

static

Template:

readme(Resource,ReadMeFile)

Mode and number of proofs:

readme(+atom,-atom) - zero_or_one

Exceptions:

Resource is a variable:

instantiation_error

Resource is neither a variable nor an atom:

type_error(atom,Resource)

ReadMeFile is neither a variable nor an atom:

type_error(atom,ReadMeFile)

readme/1

Prints the path to the resource (pack or registry) readme file (using the native operating-system format). Fails if the resource is not defined or installed or if no readme file is found for it.

Compilation flags:

static

Template:

readme(Resource)

Mode and number of proofs:

readme(+atom) - zero_or_one

Exceptions:

Resource is a variable:

instantiation_error

Resource is neither a variable nor an atom:

type_error(atom,Resource)

logtalk_packs/1

Returns the directory prefix (using the internal backend format) where the registries, packs, and archives are installed.

Compilation flags:

static

Template:

logtalk_packs(LogtalkPacks)

Mode and number of proofs:

logtalk_packs(-atom) - one

Exceptions:

LogtalkPacks is neither a variable nor an atom:

type_error(atom,LogtalkPacks)

logtalk_packs/0

Prints the directory prefix (using the native operating-system format) where the registries, packs, and archives are installed.

Compilation flags:

static

Mode and number of proofs:

logtalk_packs - one

prefix/1

Returns the directory prefix (using the internal backend format) where the registries or packs are installed.

Compilation flags:

static

Template:

prefix(Prefix)

Mode and number of proofs:

prefix(-atom) - one

Exceptions:

Prefix is neither a variable nor an atom:

type_error(atom,Prefix)

prefix/0

Prints the directory prefix (using the native operating-system format) where the registries or packs are installed.

Compilation flags:

static

Mode and number of proofs:

prefix - one

Protected predicates

readme_file_path/2

Returns the absolute path for the given directory readme file if it exists.

Compilation flags:

static

Template:

readme_file_path(Directory,ReadMeFile)

Mode and number of proofs:

readme_file_path(+atom,-atom) - zero_or_one

Remarks:

- Valid file names: Case variations of README and NOTES with or without a .md or .txt extension. The recommended file name is README.md.
-

print_readme_file_path/1

Prints the absolute path for the given directory readme file if it exists. Succeeds otherwise.

Compilation flags:

static

Template:

print_readme_file_path(Directory)

Mode and number of proofs:

print_readme_file_path(+atom) - one

`command/2`

Executes a shell command. Prints an error message and fails if the command fails.

Compilation flags:

`static`

Template:

`command(Command,FailureMessage)`

Mode and number of proofs:

`command(+atom,@nonvar) - zero_or_one`

`load_registry/1`

Loads all registry files from the given directory.

Compilation flags:

`static`

Template:

`load_registry(Directory)`

Mode and number of proofs:

`load_registry(+atom) - zero_or_one`

`sha256sum_command/1`

Returns the name of the sha256sum command to be used on POSIX systems. Fails if neither gsha256sum or sha256sum commands are found.

Compilation flags:

`static`

Template:

`sha256sum_command(Command)`

Mode and number of proofs:

`sha256sum_command(-atom) - zero_or_one`

`tar_command/1`

Returns the name of the tar command to be used depending on the operating-system.

Compilation flags:

`static`

Template:

`tar_command(Command)`

Mode and number of proofs:

`tar_command(-atom) - one`

`supported_archive/1`

True iff the archive format is supported.

Compilation flags:

`static`

Template:

`supported_archive(Extension)`

Mode and number of proofs:

`supported_archive(+atom) - zero_or_one`

`supported_url_archive/1`

True iff the URL archive is supported.

Compilation flags:

`static`

Template:

`supported_url_archive(URL)`

Mode and number of proofs:

`supported_url_archive(+atom) - zero_or_one`

`decode_url_spaces/2`

Decodes encoded spaces (%20) in URLs to spaces.

Compilation flags:

`static`

Template:

`decode_url_spaces(URL,Decoded)`

Mode and number of proofs:

`decode_url_spaces(+atom,-atom) - one`

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.57.4 `packs_messages`

Packs default message translations.

Availability:

`logtalk_load(packs(loader))`

Author: Paulo Moura

Version: 0:41:0

Date: 2025-05-23

Compilation flags:

`static`

Provides:

logtalk::message_prefix_stream/4
logtalk::message_tokens//2

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.57.5 packs_specs_hook

Hook object for filtering registry and pack specification file contents.

Availability:

logtalk_load(packs(loader))

Author: Paulo Moura

Version: 0:13:0
Date: 2022-06-28

Compilation flags:
static, context_switching_calls

Implements:
public [expanding](#)

Uses:
[character](#)
[logtalk](#)

Remarks:
(none)

Inherited public predicates:
[goal_expansion/2](#) [term_expansion/2](#)

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.57.6 registries

Registry handling predicates.

Availability:

`logtalk_load(packs(loader))`

Author: Paulo Moura

Version: 0:61:0

Date: 2025-05-27

Compilation flags:

`static, context_switching_calls`

Imports:

`public packs_common`

`public options`

Uses:

`list`

`logtalk`

`os`

`type`

`user`

Remarks:

(none)

Inherited public predicates:

`check_option/1 check_options/1 default_option/1 default_options/1 directory/1 directory/2
help/0 logtalk_packs/0 logtalk_packs/1 option/2 option/3 pin/0 pin/1 pinned/1 prefix/0
prefix/1 readme/1 readme/2 reset/0 setup/0 unpin/0 unpin/1 valid_option/1 valid_options/1
verify_commands_availability/0`

- Public predicates
 - `list/0`

- describe/1
- defined/4
- add/3
- add/2
- add/1
- update/2
- update/1
- update/0
- delete/2
- delete/1
- delete/0
- clean/1
- clean/0
- provides/2
- lint/1
- lint/0
- Protected predicates
- Private predicates
- Operators

Public predicates

list/0

Prints a list of all defined registries, including how defined (git, archive, or directory) and if they are pinned.

Compilation flags:
static

Mode and number of proofs:
list - one

describe/1

Prints all registry entries.

Compilation flags:

static

Template:

describe(Registry)

Mode and number of proofs:

describe(+atom) - one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

type_error(atom,Registry)

defined/4

Enumerates by backtracking all defined registries, their definition URL, how they are defined (git, archive, or directory), and if they are pinned.

Compilation flags:

static

Template:

defined(Registry,URL,HowDefined,Pinned)

Mode and number of proofs:

defined(?atom,?atom,?atom,?boolean) - zero_or_more

Exceptions:

Registry is neither a variable nor an atom:

type_error(atom,Registry)

URL is neither a variable nor an atom:

type_error(atom,URL)

HowDefined is neither a variable nor an atom:

type_error(atom,HowDefined)

Pinned is neither a variable nor a boolean:

type_error(boolean,Pinned)

add/3

Adds a new registry using the given options. Fails if the registry cannot be added or if it is already defined but not using `update(true)` or `force(true)` options. A `file://` URL can be used for a local directory or archive.

Compilation flags:

static

Template:

add(Registry,URL,Options)

Mode and number of proofs:

add(+atom,+atom,++list(compound)) - zero_or_one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

type_error(atom,Registry)

URL is a variable:

instantiation_error

URL is neither a variable nor an atom:

type_error(atom,URL)

Options is a variable:

instantiation_error

Options is neither a variable nor a list:

type_error(list,Options)

An element Option of the list Options is a variable:

instantiation_error

An element Option of the list Options is neither a variable nor a compound term:

type_error(compound,Option)

An element Option of the list Options is a compound term but not a valid option:

domain_error(option,Option)

Remarks:

- Registry name: Must be the URL basename when using a git URL or a local directory URL. Must also be the declared registry name in the registry specification object.
- HTTPS URLs: Must end with either a `.git` extension or an archive extension.
- `update(Boolean)` option: Update registry if already defined. Default is false. Overrides the `force/1` option.

- `force(Boolean)` option: Force registry re-installation if already defined by first deleting the previous installation. Default is `false`.
 - `clean(Boolean)` option: Clean registry archive after updating. Default is `false`.
 - `verbose(Boolean)` option: Verbose adding steps. Default is `false`.
 - `downloader(Atom)` option: Downloader utility. Either `curl` or `wget`. Default is `curl`.
 - `curl(Atom)` option: Extra command-line options. Default is `' '`.
 - `wget(Atom)` option: Extra command-line options. Default is `' '`.
 - `gpg(Atom)` option: Extra command-line options. Default is `' '`.
 - `tar(Atom)` option: Extra command-line options. Default is `' '`.
-

`add/2`

Adds a new registry using default options. Fails if the registry cannot be added or if it is already defined. HTTPS URLs must end with either a `.git` extension or an archive extension. A `file://` URL can be used for a local directory or archive.

Compilation flags:

`static`

Template:

`add(Registry,URL)`

Mode and number of proofs:

`add(+atom,+atom) - zero_or_one`

Exceptions:

Registry is a variable:

`instantiation_error`

Registry is neither a variable nor an atom:

`type_error(atom,Registry)`

URL is a variable:

`instantiation_error`

URL is neither a variable nor an atom:

`type_error(atom,URL)`

Remarks:

- Registry name: Must be the URL basename when using a git URL or a local directory URL. Must also be the declared registry name in the registry specification object.
-

add/1

Adds a new registry using default options. Fails if the registry cannot be added or if it is already defined. HTTPS URLs must end with a .git extension or an archive extension. A file:// URL can be used for a local directory or archive.

Compilation flags:

static

Template:

add(URL)

Mode and number of proofs:

add(+atom) - zero_or_one

Exceptions:

URL is a variable:

instantiation_error

URL is neither a variable nor an atom:

type_error(atom,URL)

Remarks:

- Registry name: Taken from the URL basename.
-

update/2

Updates a defined registry using the specified options. Fails if the registry is not defined.

Compilation flags:

static

Template:

update(Registry,Options)

Mode and number of proofs:

update(+atom,++list(compound)) - zero_or_one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

type_error(atom,Registry)

Options is a variable:

`instantiation_error`

Options is neither a variable nor a list:

`type_error(list,Options)`

An element Option of the list Options is a variable:

`instantiation_error`

An element Option of the list Options is neither a variable nor a compound term:

`type_error(compound,Option)`

An element Option of the list Options is a compound term but not a valid option:

`domain_error(option,Option)`

Remarks:

- `force(Boolean)` option: Force update if the registry is pinned. Default is false.
- `clean(Boolean)` option: Clean registry archive after updating. Default is false.
- `verbose(Boolean)` option: Verbose updating steps. Default is false.
- `downloader(Atom)` option: Downloader utility. Either curl or wget. Default is curl.
- `curl(Atom)` option: Extra command-line options. Default is ''.
- `wget(Atom)` option: Extra command-line options. Default is ''.
- `gpg(Atom)` option: Extra command-line options. Default is ''.
- `tar(Atom)` option: Extra command-line options. Default is ''.

[update/1](#)

Updates a defined registry using default options. Fails if the registry is not defined.

Compilation flags:

`static`

Template:

`update(Registry)`

Mode and number of proofs:

`update(+atom) - zero_or_one`

Exceptions:

Registry is a variable:

`instantiation_error`

Registry is neither a variable nor an atom:

`type_error(atom,Registry)`

update/0

Updates all defined registries using default options.

Compilation flags:

static

Mode and number of proofs:

update - zero_or_one

delete/2

Deletes a registry using the specified options (if not pinned).

Compilation flags:

static

Template:

delete(Registry,Options)

Mode and number of proofs:

delete(+atom,++list(compound)) - zero_or_one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

type_error(atom,Registry)

Options is a variable:

instantiation_error

Options is neither a variable nor a list:

type_error(list,Options)

An element Option of the list Options is a variable:

instantiation_error

An element Option of the list Options is neither a variable nor a compound term:

type_error(compound,Option)

An element Option of the list Options is a compound term but not a valid option:

domain_error(option,Option)

Remarks:

- `force(Boolean)` option: Force deletion if the registry is pinned or there are installed registry packs. Default is false.
 - `clean(Boolean)` option: Clean registry archive after deleting. Default is false.
 - `verbose(Boolean)` option: Verbose deleting steps. Default is false.
 - `downloader(Atom)` option: Downloader utility. Either curl or wget. Default is curl.
 - `curl(Atom)` option: Extra command-line options. Default is ''.
 - `wget(Atom)` option: Extra command-line options. Default is ''.
 - `gpg(Atom)` option: Extra command-line options. Default is ''.
 - `tar(Atom)` option: Extra command-line options. Default is ''.
-

`delete/1`

Deletes a registry using default options.

Compilation flags:

`static`

Template:

`delete(Registry)`

Mode and number of proofs:

`delete(+atom) - zero_or_one`

Exceptions:

Registry is a variable:

`instantiation_error`

Registry is neither a variable nor an atom:

`type_error(atom,Registry)`

`delete/0`

Deletes all registries using the `force(true)` option.

Compilation flags:

`static`

Mode and number of proofs:

`delete - zero_or_one`

`clean/1`

Cleans all registry archives. Fails if the registry is not defined.

Compilation flags:

`static`

Template:

`clean(Registry)`

Mode and number of proofs:

`clean(+atom) - zero_or_one`

Exceptions:

Registry is a variable:

`instantiation_error`

Registry is neither a variable nor an atom:

`type_error(atom,Registry)`

`clean/0`

Cleans all archives for all registries.

Compilation flags:

`static`

Mode and number of proofs:

clean - one

provides/2

Enumerates by backtracking all packs provided by a registry.

Compilation flags:

static

Template:

provides(Registry,Pack)

Mode and number of proofs:

provides(?atom,?atom) - zero_or_more

Exceptions:

Registry is neither a variable nor an atom:

type_error(atom,Registry)

Pack is neither a variable nor an atom:

type_error(atom,Pack)

lint/1

Checks the registry specification. Fails if the registry is not defined or if linting detects errors.

Compilation flags:

static

Template:

lint(Registry)

Mode and number of proofs:

lint(+atom) - zero_or_one

Exceptions:

Registry is a variable:

instantiation_error

Registry is neither a variable nor an atom:

type_error(atom,Registry)

lint/0

Checks all registry specifications.

Compilation flags:
static

Mode and number of proofs:
lint - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)
object

1.57.7 registry_loader_hook

Hook object for filtering registry loader file contents.

Availability:
logtalk_load(packs(loader))

Author: Paulo Moura
Version: 0:13:0
Date: 2022-11-20

Compilation flags:
static, context_switching_calls

Implements:

public expanding

Uses:

character

logtalk

Remarks:

(none)

Inherited public predicates:

goal_expansion/2 term_expansion/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.57.8 registry_protocol

Registry specification protocol. Objects implementing this protocol should be named after the pack with a `_registry` suffix and saved in a file with the same name as the object.

Availability:

`logtalk_load(packs(loader))`

Author: Paulo Moura

Version: 0:12:0

Date: 2022-06-28

Compilation flags:

`static`

Dependencies:

`(none)`

Remarks:

`(none)`

Inherited public predicates:

`(none)`

- Public predicates
 - `name/1`
 - `description/1`
 - `home/1`
 - `clone/1`
 - `archive/1`
 - `note/2`
- Protected predicates
- Private predicates
- Operators

Public predicates

name/1

Registry name. Preferably a valid unquoted atom.

Compilation flags:

static

Template:

name(Name)

Mode and number of proofs:

name(?atom) - zero_or_one

description/1

Registry one line description.

Compilation flags:

static

Template:

description(Description)

Mode and number of proofs:

description(?atom) - zero_or_one

home/1

Registry home HTTPS or file URL.

Compilation flags:

static

Template:

home(Home)

Mode and number of proofs:

home(?atom) - zero_or_one

[clone/1](#)

Registry git clone HTTPS URL (must end with the .git extension). Git repos should have the same name as the registry.

Compilation flags:

static

Template:

clone(URL)

Mode and number of proofs:

clone(?atom) - zero_or_one

[archive/1](#)

Registry archive download HTTPS URL.

Compilation flags:

static

Template:

archive(URL)

Mode and number of proofs:

archive(?atom) - zero_or_one

[note/2](#)

Table of notes per action.

Compilation flags:

static

Template:

note(Action,Note)

Mode and number of proofs:

`note(?atom,-atom) - zero_or_more`

Remarks:

- Action: Possible values are add, update, and delete. When unbound, the note apply to all actions.
 - Note: Note to print when performing an action on a registry.
-

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.58 pddl_parser

object

1.58.1 pddl

Simple parser of PDDL 3.0 files.

Availability:

`logtalk_load(pddl_parser(loader))`

Author: Robert Sasak, Charles University in Prague. Adapted to Logtalk by Paulo Moura.

Version: 1:2:2

Date: 2024-03-14

Compilation flags:

`static, context_switching_calls`

Imports:

`public read_file`

Uses:

`user`

Remarks:

(none)

Inherited public predicates:

`read_file/2`

- Public predicates
 - `parse_domain/3`
 - `parse_domain/2`
 - `parse_problem/2`
 - `parse_problem/3`
- Protected predicates
- Private predicates
- Operators

Public predicates

`parse_domain/3`

Parses a PDDL 3.0 domain file, returning a compound term representing its contents and rest of the file. Useful when domain and problem are in one file.

Compilation flags:

`static`

Template:

`parse_domain(File,Output,RestOfFile)`

Mode and number of proofs:

`parse_domain(+atom,-compound,-list(atom)) - one`

`parse_domain/2`

Parses a PDDL 3.0 domain file, returning a compound term representing its contents.

Compilation flags:

`static`

Template:

`parse_domain(File,Output)`

Mode and number of proofs:

`parse_domain(+atom,-compound) - one`

`parse_problem/2`

Parses a PDDL 3.0 problem file, returning a compound term representing its contents.

Compilation flags:

`static`

Template:

`parse_problem(File,Output)`

Mode and number of proofs:

`parse_problem(+atom,-compound) - one`

`parse_problem/3`

Parses a PDDL 3.0 problem file, returning a compound term representing its contents and rest of the file. Useful when domain and problem are in one file.

Compilation flags:

`static`

Template:

`parse_problem(File,Output,RestOfFile)`

Mode and number of proofs:

`parse_problem(+atom,-compound,-list(atom)) - one`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.58.2 read_file

Utility predicates for parsing a file as a list of atoms.

Availability:

logtalk_load(pddl_parser(loader))

Author: Robert Sasak, Charles University in Prague. Adapted to Logtalk by Paulo Moura.

Version: 1:0:0

Date: 2011-08-04

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - `read_file/2`
- Protected predicates
- Private predicates
- Operators

Public predicates

`read_file/2`

Reads a file character by character, parsing it into a list of atoms.

Compilation flags:

`static`

Template:

`read_file(File,List)`

Mode and number of proofs:

`read_file(+atom,-list(atom)) - one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.59 ports_profiler

object

1.59.1 ports_profiler

Predicate execution box model port profiler.

Availability:

```
logtalk_load(ports_profiler(loader))
```

Author: Paulo Moura

Version: 2:0:0

Date: 2024-05-18

Compilation flags:

```
static, context_switching_calls
```

Provides:

```
logtalk::debug_handler/1
```

```
logtalk::debug_handler/3
```

Uses:

```
logtalk
```

```
user
```

Remarks:

```
(none)
```

Inherited public predicates:

```
(none)
```

- Public predicates
 - start/0
 - stop/0
 - data/0
 - data/1
 - data/2
 - reset/0

- reset/1
- port/5
- clause_location/6
- clause/5
- Protected predicates
- Private predicates
 - clause_location_/6
 - port_/5
 - clause_/5
 - entity_defines_/2
- Operators

Public predicates

start/0

Activates the ports profiler for followup goals.

Compilation flags:

static

Mode and number of proofs:

start - one

stop/0

Deactivates the ports profiler.

Compilation flags:

static

Mode and number of proofs:

stop - one

data/0

Prints a table with all port profiling data.

Compilation flags:

static

Mode and number of proofs:

data - one

data/1

Prints a table with all port profiling data for the specified entity.

Compilation flags:

static

Template:

data(Entity)

Mode and number of proofs:

data(+entity__identifier) - one

data/2

Prints a table with all port profiling data for the specified entity predicate (or non-terminal).

Compilation flags:

static

Template:

data(Entity,Predicate)

Mode and number of proofs:

data(+entity__identifier,+predicate__indicator) - one

data(+entity__identifier,+non__terminal__indicator) - one

reset/0

Resets all port profiling data.

Compilation flags:

static

Mode and number of proofs:

reset - one

reset/1

Resets all port profiling data for the specified entity.

Compilation flags:

static

Template:

reset(Entity)

Mode and number of proofs:

reset(+entity__identifier) - one

port/5

Enumerates, by backtracking, all collected port profiling data.

Compilation flags:

static

Template:

port(Port,Entity,Functor,Arity,Count)

Mode and number of proofs:

port(?atom,?entity__identifier,?atom,?integer,?integer) - zero_or_more

`clause_location/6`

Enumerates, by backtracking, all collected profiled clause location data.

Compilation flags:

`static`

Template:

`clause_location(Entity, Functor, Arity, ClauseNumber, File, BeginLine)`

Mode and number of proofs:

`clause_location(?entity__identifier, ?atom, ?integer, ?integer, ?atom, ?integer) - zero__or__more`

`clause/5`

Enumerates, by backtracking, all collected clause profiling data.

Compilation flags:

`dynamic`

Template:

`clause(Entity, Functor, Arity, ClauseNumber, Count)`

Mode and number of proofs:

`clause(?entity__identifier, ?atom, ?integer, ?integer, ?integer) - zero__or__more`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

`clause_location_/6`

Internal table of collected profiled clause location data.

Compilation flags:

`dynamic`

Template:

clause_location_(Entity, Functor, Arity, ClauseNumber, File, BeginLine)

Mode and number of proofs:

clause_location_(?entity__identifier, ?atom, ?integer, ?integer, ?atom, ?integer) - zero_or_more

port_/5

Internal table of collected port profiling data.

Compilation flags:

dynamic

Template:

port_(Port, Entity, Functor, Arity, Count)

Mode and number of proofs:

port_(?atom, ?entity__identifier, ?atom, ?integer, ?integer) - zero_or_more

clause_/5

Internal table of collected clause profiling data.

Compilation flags:

dynamic

Template:

clause_(Entity, Functor, Arity, ClauseNumber, Count)

Mode and number of proofs:

clause_(?entity__identifier, ?atom, ?integer, ?integer, ?integer) - zero_or_more

`entity_defines_/2`

Internal cache for profiled predicates.

Compilation flags:

`dynamic`

Template:

`entity_defines_(Entity,Predicate)`

Mode and number of proofs:

`entity_defines_(?entity_identifier,?predicate_indicator) - zero_or_more`

Operators

`(none)`

1.60 queues

object

1.60.1 queue

Queue predicates implemented using difference lists.

Availability:

`logtalk_load(queues(loader))`

Author: Paulo Moura

Version: 1:3:0

Date: 2020-12-09

Compilation flags:

`static, context_switching_calls`

Implements:

`public queuep`

Extends:

`public compound`

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 append/3 as_list/2 check/1 depth/2
empty/1 ground/1 head/2 join/3 join_all/3 jump/3 jump_all/3 jump_all_block/3 length/2
map/2 map/3 new/1 numbervars/1 numbervars/3 occurs/2 serve/3 singletons/2 subsumes/2
subterm/2 valid/1 variables/2 variant/2 varnumbers/2 varnumbers/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.60.2 queuep

Queue protocol.

Availability:

logtalk_load(queues(loader))

Author: Paulo Moura

Version: 1:3:0

Date: 2020-12-09

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - empty/1
 - head/2
 - join/3
 - join_all/3
 - jump/3
 - jump_all/3
 - jump_all_block/3
 - append/3
 - length/2
 - serve/3
 - as_list/2
 - map/2
 - map/3
- Protected predicates
- Private predicates
- Operators

Public predicates

empty/1

True if the queue is empty.

Compilation flags:

static

Template:

empty(Queue)

Mode and number of proofs:

empty(@queue) - zero_or_one

head/2

Unifies Head with the first element of the queue.

Compilation flags:

static

Template:

head(Queue,Head)

Mode and number of proofs:

head(+queue,?term) - zero_or_one

join/3

Adds the new element at the end of the queue.

Compilation flags:

static

Template:

join(Element,Queue,NewQueue)

Mode and number of proofs:

join(@term,+queue,-queue) - zero_or_one

[join_all/3](#)

Adds the new elements at the end of the queue. The elements are added in the same order that they appear in the list.

Compilation flags:

`static`

Template:

`join_all(List,Queue,NewQueue)`

Mode and number of proofs:

`join_all(+list,+queue,-queue) - zero_or_one`

[jump/3](#)

Adds the new element at the front of the queue.

Compilation flags:

`static`

Template:

`jump(Element,Queue,NewQueue)`

Mode and number of proofs:

`jump(@term,+queue,-queue) - zero_or_one`

[jump_all/3](#)

Adds the new elements at the front of the queue. The last element in the list will be at the front of the queue.

Compilation flags:

`static`

Template:


```
jump_all(Elements,Queue,NewQueue)
```

Mode and number of proofs:

```
jump_all(+list,+queue,-queue) - zero_or_one
```

[jump_all_block/3](#)

Adds the new elements as a block at the front of the queue. The first element in the list will be at the front of the queue.

Compilation flags:

```
static
```

Template:

```
jump_all_block(Elements,Queue,NewQueue)
```

Mode and number of proofs:

```
jump_all_block(+list,+queue,-queue) - zero_or_one
```

[append/3](#)

Appends two queues. The new queue will have the elements of the first queue followed by the elements of the second queue.

Compilation flags:

```
static
```

Template:

```
append(Queue1,Queue2,NewQueue)
```

Mode and number of proofs:

```
append(+queue,+queue,-queue) - one
```

`length/2`

Queue length.

Compilation flags:

`static`

Template:

`length(Queue,Length)`

Mode and number of proofs:

`length(+heap,?integer) - zero_or_one`

`serve/3`

Removes the first element of the queue for service.

Compilation flags:

`static`

Template:

`serve(Queue,Head,NewQueue)`

Mode and number of proofs:

`serve(+queue,?term,-queue) - zero_or_one`

`as_list/2`

Converts a queue to a list.

Compilation flags:

`static`

Template:

`as_list(Queue,List)`

Mode and number of proofs:

`as_list(+queue,-list) - one`

map/2

Applies a closure to all elements of a queue.

Compilation flags:

static

Template:

map(Closure,Queue)

Meta-predicate template:

map(1,*)

Mode and number of proofs:

map(+callable,+queue) - zero_or_one

map/3

Applies a closure to all elements of a queue constructing a new queue.

Compilation flags:

static

Template:

map(Closure,Queue,NewQueue)

Meta-predicate template:

map(2,*,*)

Mode and number of proofs:

map(+callable,+queue,?queue) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

 See also

[queue](#)

1.61 random

object

1.61.1 backend_random

Random number generator predicates using the backend Prolog compiler built-in random generator.

Availability:

`logtalk_load(random(loader))`

Author: Paulo Moura

Version: 1:21:1

Date: 2025-04-07

Compilation flags:

`static, context_switching_calls`

Implements:

`public pseudo_random_protocol`

`public sampling_protocol`

Uses:

`list`

Remarks:

- Implementation: The backend Prolog compiler built-in random generator is only used for the basic `random/1`, `get_seed/1`, and `set_seed/1` predicates.

- Portability: B-Prolog, CxProlog, ECLiPSe, JIProlog, Qu-Prolog, and Quintus Prolog do not provide implementations for the `get_seed/1` and `set_seed/1` predicates and calling these predicates simply succeed without performing any action.

Inherited public predicates:

```
bernoulli/2 beta/3 between/3 binomial/3 chi_squared/2 circular_uniform_cartesian/3
circular_uniform_polar/3 dirichlet/2 enumerate/2 exponential/2 fisher/3 gamma/3 geometric/2
get_seed/1 gumbel/3 hypergeometric/4 logistic/3 lognormal/3 logseries/2 maybe/0 maybe/1
maybe/2 maybe_call/1 maybe_call/2 member/2 normal/3 permutation/2 poisson/2 power/2
random/1 random/3 randseq/4 randset/4 select/3 select/4 sequence/4 set/4 set_seed/1
standard_cauchy/3 standard_exponential/1 standard_gamma/2 standard_normal/1
standard_t/2 swap/2 swap_consecutive/2 triangular/4 uniform/1 uniform/3 von_mises/3
wald/3 weibull/3
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

`random`, `fast_random`

object

1.61.2 fast_random

Fast portable random number generator predicates. Core predicates originally written by Richard O’Keefe. Based on algorithm AS 183 from Applied Statistics.

Availability:

```
logtalk_load(random(loader))
```

Author: Paulo Moura

Version: 2:12:1

Date: 2025-04-07

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public pseudo_random_protocol
```

```
public sampling_protocol
```

Uses:

```
list
```

Remarks:

- Single random number generator: This object provides a faster version of the random library object but does not support being extended to define multiple random number generators.
- Randomness: Loading this object always initializes the random generator seed to the same value, thus providing a pseudo random number generator. The `randomize/1` predicate can be used to initialize the seed with a random value.

Inherited public predicates:

```
bernoulli/2 beta/3 between/3 binomial/3 chi_squared/2 circular_uniform_cartesian/3  
circular_uniform_polar/3 dirichlet/2 enumerate/2 exponential/2 fisher/3 gamma/3 geometric/2  
get_seed/1 gumbel/3 hypergeometric/4 logistic/3 lognormal/3 logseries/2 maybe/0 maybe/1  
maybe/2 maybe_call/1 maybe_call/2 member/2 normal/3 permutation/2 poisson/2 power/2  
random/1 random/3 randseq/4 randset/4 select/3 select/4 sequence/4 set/4 set_seed/1  
standard_cauchy/3 standard_exponential/1 standard_gamma/2 standard_normal/1  
standard_t/2 swap/2 swap_consecutive/2 triangular/4 uniform/1 uniform/3 von_mises/3  
wald/3 weibull/3
```

- Public predicates
 - `reset_seed/0`

- randomize/1
- Protected predicates
- Private predicates
 - seed_/3
- Operators

Public predicates

reset_seed/0

Resets the random generator seed to its default value. Use get_seed/1 and set_seed/1 instead if you need reproducibility.

Compilation flags:

static, synchronized

Mode and number of proofs:

reset_seed - one

randomize/1

Randomizes the random generator using a positive integer to compute a new seed. Use of a large integer is recommended. In alternative, when using a small integer argument, discard the first dozen random values.

Compilation flags:

static, synchronized

Template:

randomize(Seed)

Mode and number of proofs:

randomize(+positive_integer) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

`seed_/3`

Stores the current random generator seed values.

Compilation flags:

`dynamic`

Template:

`seed_(S0,S1,S2)`

Mode and number of proofs:

`seed_(-integer,-integer,-integer) - one`

Operators

(none)

 See also

`random`, `backend_random`

`protocol`

1.61.3 `pseudo_random_protocol`

Pseudo-random number generator protocol for seed handling predicates. These predicates are declared as synchronized when the library is compiled using a backend supporting threads.

Availability:

`logtalk_load(random(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2021-02-21

Compilation flags:

static

Extends:

public random_protocol

Remarks:

(none)

Inherited public predicates:

between/3 enumerate/2 maybe/0 maybe/1 maybe/2 maybe_call/1 maybe_call/2 member/2
 permutation/2 random/1 random/3 randseq/4 randset/4 select/3 select/4 sequence/4 set/4
 swap/2 swap_consecutive/2

- Public predicates
 - get_seed/1
 - set_seed/1
- Protected predicates
- Private predicates
- Operators

Public predicates

get_seed/1

Gets the current random generator seed. Seed should be regarded as an opaque ground term.

Compilation flags:

static, synchronized

Template:

get_seed(Seed)

Mode and number of proofs:

get_seed(-ground) - one

`set_seed/1`

Sets the random generator seed to a given value returned by calling the `get_seed/1` predicate.

Compilation flags:

`static, synchronized`

Template:

`set_seed(Seed)`

Mode and number of proofs:

`set_seed(+ground) - one`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

`random`, `backend_random`, `fast_random`

object

1.61.4 `random`

Portable random number generator predicates. Core predicates originally written by Richard O’Keefe. Based on algorithm AS 183 from Applied Statistics.

Availability:

`logtalk_load(random(loader))`

Author: Paulo Moura

Version: 2:12:1

Date: 2025-04-07

Compilation flags:

static, context_switching_calls

Implements:

public pseudo_random_protocol
public sampling_protocol

Uses:

list

Remarks:

- Multiple random number generators: To define multiple random number generators, simply extend this object. The derived objects must send to self the reset_seed/0 message.
- Randomness: Loading this object always initializes the random generator seed to the same value, thus providing a pseudo random number generator. The randomize/1 predicate can be used to initialize the seed with a random value.

Inherited public predicates:

bernoulli/2 beta/3 between/3 binomial/3 chi_squared/2 circular_uniform_cartesian/3
circular_uniform_polar/3 dirichlet/2 enumerate/2 exponential/2 fisher/3 gamma/3 geometric/2
get_seed/1 gumbel/3 hypergeometric/4 logistic/3 lognormal/3 logseries/2 maybe/0 maybe/1
maybe/2 maybe_call/1 maybe_call/2 member/2 normal/3 permutation/2 poisson/2 power/2
random/1 random/3 randseq/4 randset/4 select/3 select/4 sequence/4 set/4 set_seed/1
standard_cauchy/3 standard_exponential/1 standard_gamma/2 standard_normal/1
standard_t/2 swap/2 swap_consecutive/2 triangular/4 uniform/1 uniform/3 von_mises/3
wald/3 weibull/3

- Public predicates
 - reset_seed/0
 - randomize/1
- Protected predicates
- Private predicates
 - seed_/3
- Operators

Public predicates

`reset_seed/0`

Resets the random generator seed to its default value. Use `get_seed/1` and `set_seed/1` instead if you need reproducibility.

Compilation flags:

`static, synchronized`

Mode and number of proofs:

`reset_seed - one`

`randomize/1`

Randomizes the random generator using a positive integer to compute a new seed. Use of a large integer is recommended. In alternative, when using a small integer argument, discard the first dozen random values.

Compilation flags:

`static, synchronized`

Template:

`randomize(Seed)`

Mode and number of proofs:

`randomize(+positive_integer) - one`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

`seed_/3`

Stores the current random generator seed values.

Compilation flags:

`dynamic`

Template:

```
seed_(S0,S1,S2)
```

Mode and number of proofs:

```
seed_(-integer,-integer,-integer) - one
```

Operators

(none)

➡ See also

[fast_random](#), [backend_random](#)

protocol

1.61.5 random_protocol

Random number generator protocol. The predicates are declared as synchronized when the library is compiled using a backend supporting threads.

Availability:

```
logtalk_load(random(loader))
```

Author: Paulo Moura

Version: 3:3:0

Date: 2023-11-24

Compilation flags:

```
static
```

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - random/1
 - between/3
 - member/2
 - select/3
 - select/4
 - swap/2
 - swap_consecutive/2
 - enumerate/2
 - permutation/2
 - sequence/4
 - set/4
 - random/3
 - randseq/4
 - randset/4
 - maybe/0
 - maybe/1
 - maybe/2
 - maybe_call/1
 - maybe_call/2
- Protected predicates
- Private predicates
- Operators

Public predicates

random/1

Returns a new random float value in the interval $[0.0, 1.0[$.

Compilation flags:

static, synchronized

Template:

random(Random)

Mode and number of proofs:

random(-float) - one

between/3

Returns a new random integer in the interval [Lower, Upper]. Fails if Lower or Upper are not integers or if Lower > Upper.

Compilation flags:

static

Template:

between(Lower,Upper,Random)

Mode and number of proofs:

between(+integer,+integer,-integer) - zero_or_one

member/2

Returns a random member of a list. Fails if the list is empty.

Compilation flags:

static

Template:

member(Random,List)

Mode and number of proofs:

member(-term,+list(term)) - zero_or_one

select/3

Returns a random member of a list and the rest of the list. Fails if the list is empty.

Compilation flags:

static

Template:

select(Random,List,Rest)

Mode and number of proofs:

select(-term,+list(term),-list(term)) - zero_or_one

select/4

Returns a random member of a list, replacing it with a new element and returning the resulting list.

Compilation flags:

static

Template:

select(Random,OldList,New,NewList)

Mode and number of proofs:

select(-term,+list(term),@term,-list(term)) - zero_or_one

swap/2

Swaps two randomly selected elements of a list. Fails if the list is empty or contains a single element.

Compilation flags:

static

Template:

swap(OldList,NewList)

Mode and number of proofs:

swap(-term,+list(term)) - zero_or_one

`swap_consecutive/2`

Swaps two randomly selected consecutive elements of a list. Fails if the list is empty or contains a single element.

Compilation flags:

`static`

Template:

`swap_consecutive(OldList,NewList)`

Mode and number of proofs:

`swap_consecutive(-term,+list(term)) - zero_or_one`

`enumerate/2`

Enumerates the elements of a list in random order. Fails if the list is empty.

Compilation flags:

`static`

Template:

`enumerate(List,Random)`

Mode and number of proofs:

`enumerate(+list(term),--term) - zero_or_more`

`permutation/2`

Returns a random permutation of a list.

Compilation flags:

`static, synchronized`

Template:

`permutation(List,Permutation)`

Mode and number of proofs:

`permutation(+list,-list) - one`

`sequence/4`

Returns list of random integers of given length in random order in interval [Lower, Upper]. Fails if Length, Lower, or Upper are not integers or if Lower > Upper.

Compilation flags:

static, synchronized

Template:

`sequence(Length,Lower,Upper,List)`

Mode and number of proofs:

`sequence(+integer,+integer,+integer,-list(integer)) - zero_or_one`

`set/4`

Returns ordered set of random integers of given size in interval [Lower, Upper]. Fails if Length, Lower, or Upper are not integers, if Lower > Upper, or if Length > Upper - Lower + 1.

Compilation flags:

static, synchronized

Template:

`set(Length,Lower,Upper,Set)`

Mode and number of proofs:

`set(+integer,+integer,+integer,-list(integer)) - zero_or_one`

`random/3`

Returns a new random value in the interval [Lower, Upper]. Fails if Lower > Upper. Deprecated. Use `between/3` for integers.

Compilation flags:

static, synchronized

Template:

```
random(Lower,Upper,Random)
```

Mode and number of proofs:

```
random(+integer,+integer,-integer) - zero_or_one
```

```
random(+float,+float,-float) - zero_or_one
```

`randseq/4`

Returns list of random values of given length in random order in interval [Lower, Upper[. Fails if Lower > Upper or if the arguments are neither integers or floats. Deprecated. Use `sequence/4` for integers.

Compilation flags:

```
static, synchronized
```

Template:

```
randseq(Length,Lower,Upper,List)
```

Mode and number of proofs:

```
randseq(+integer,+integer,+integer,-list(integer)) - zero_or_one
```

```
randseq(+integer,+float,+float,-list(float)) - zero_or_one
```

`randset/4`

Returns ordered set of random values of given size in interval [Lower, Upper[. Fails if the arguments are neither integers or floats, Lower > Upper, or Length > Upper - Lower when arguments are integers. Deprecated. Use `set/4` for integers.

Compilation flags:

```
static, synchronized
```

Template:

```
randset(Length,Lower,Upper,Set)
```

Mode and number of proofs:

```
randset(+integer,+integer,+integer,-list(integer)) - zero_or_one
```

```
randset(+integer,+float,+float,-list(float)) - zero_or_one
```

maybe/0

Succeeds or fails with equal probability.

Compilation flags:

static

Mode and number of proofs:

maybe - zero_or_one

maybe/1

Succeeds with probability Probability or fails with probability 1 - Probability. Fails if Probability is not a float or is outside the interval [0.0, 1.0].

Compilation flags:

static

Template:

maybe(Probability)

Mode and number of proofs:

maybe(+probability) - zero_or_one

maybe/2

Succeeds with probability K/N where K and N are integers satisfying the equation $0 \leq K \leq N$. Fails otherwise.

Compilation flags:

static

Template:

maybe(K,N)

Mode and number of proofs:

maybe(+non_negative_integer,+non_negative_integer) - zero_or_one

`maybe_call/1`

Calls a goal or fails without calling it with equal probability. When the goal is called, it determines if this predicate succeeds once or fails.

Compilation flags:

`static`

Template:

`maybe_call(Goal)`

Meta-predicate template:

`maybe_call(0)`

Mode and number of proofs:

`maybe_call(+callable) - zero_or_one`

`maybe_call/2`

Calls a goal or fails without calling it with probability `Probability`. When the goal is called, it determines if this predicate succeeds once or fails.

Compilation flags:

`static`

Template:

`maybe_call(Probability,Goal)`

Meta-predicate template:

`maybe_call(*,0)`

Mode and number of proofs:

`maybe_call(+probability,+callable) - zero_or_one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

 See also

random, backend_random, fast_random

protocol

1.61.6 sampling_protocol

Predicates for sampling probability distributions.

Availability:

logtalk_load(random(loader))

Author: Paulo Moura

Version: 1:0:0

Date: 2025-02-25

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - normal/3
 - lognormal/3

- wald/3
- chi_squared/2
- fisher/3
- logseries/2
- geometric/2
- hypergeometric/4
- exponential/2
- binomial/3
- bernoulli/2
- beta/3
- gamma/3
- logistic/3
- poisson/2
- power/2
- weibull/3
- uniform/3
- uniform/1
- triangular/4
- von_mises/3
- gumbel/3
- dirichlet/2
- circular_uniform_polar/3
- circular_uniform_cartesian/3
- standard_t/2
- standard_cauchy/3
- standard_exponential/1
- standard_gamma/2
- standard_normal/1
- Protected predicates
- Private predicates
- Operators

Public predicates

normal/3

Returns a scaled normally (Gaussian) distributed random value with the given mean and standard deviation.

Compilation flags:

static

Template:

normal(Mean,Deviation,Value)

Mode and number of proofs:

normal(+float,+non_negative_float,-float) - one

lognormal/3

Returns a scaled log normally distributed random value with the given mean and standard deviation for the normal distribution.

Compilation flags:

static

Template:

lognormal(Mean,Deviation,Value)

Mode and number of proofs:

lognormal(+float,+non_negative_float,-float) - one

wald/3

Returns a scaled Wald (inverse Gaussian) distributed random value with the given mean.

Compilation flags:

static

Template:

wald(Mean,Scale,Value)

Mode and number of proofs:

wald(+positive_float,+positive_float,-float) - one

chi_squared/2

Returns a chi-squared distributed random value given the degrees of freedom.

Compilation flags:

static

Template:

chi_squared(DegreesOfFreedom,Value)

Mode and number of proofs:

chi_squared(+positive_integer,-float) - one

fisher/3

Returns a Fisher distributed random value given the degrees of freedom in the numerator and in the denominator.

Compilation flags:

static

Template:

fisher(DegreesOfFreedomNumerator,DegreesOfFreedomDenominator,Value)

Mode and number of proofs:

fisher(+positive_integer,+positive_integer,-float) - one

logseries/2

Returns a logseries distributed random value. Requires $0.0 < \text{Shape} < 1$ and fails otherwise.

Compilation flags:

static

Template:

logseries(Shape,Value)

Mode and number of proofs:

logseries(+non_negative_integer,-positive_integer) - zero_or_one

geometric/2

Returns a geometric distributed random value (trials until the first success).

Compilation flags:

static

Template:

geometric(Probability,Value)

Mode and number of proofs:

geometric(+probability,-positive_integer) - one

hypergeometric/4

Returns a hypergeometric distributed random value.

Compilation flags:

static

Template:

hypergeometric(Population,Successes,Draws,Value)

Mode and number of proofs:

hypergeometric(+non_negative_integer,+non_negative_integer,+non_negative_integer,
-non_negative_integer) - one

exponential/2

Returns a scaled exponentially distributed random value.

Compilation flags:

static

Template:

exponential(Scale,Value)

Mode and number of proofs:

exponential(+positive_float,-float) - one

binomial/3

Returns a binomial distributed random value.

Compilation flags:

static

Template:

binomial(Trials,Probability,Value)

Mode and number of proofs:

binomial(+positive_integer,+positive_float,-float) - one

bernoulli/2

Returns a Bernoulli distributed random value.

Compilation flags:

static

Template:

bernoulli(Probability,Value)

Mode and number of proofs:

bernoulli(+positive_integer,-float) - one

beta/3

Returns a beta distributed random value.

Compilation flags:

static

Template:

beta(Alpha,Beta,Value)

Mode and number of proofs:

beta(+positive_float,+positive_float,-float) - one

gamma/3

Returns a scaled gamma distributed random value.

Compilation flags:

static

Template:

gamma(Shape,Scale,Value)

Mode and number of proofs:

gamma(+positive_float,+positive_float,-float) - one

logistic/3

Returns a scaled logistic distributed random value.

Compilation flags:

static

Template:

logistic(Location,Scale,Value)

Mode and number of proofs:

logistic(+float,+positive_float,-float) - one

`poisson/2`

Returns a Poisson distributed random value given the expected number of events.

Compilation flags:

`static`

Template:

`poisson(Mean, Value)`

Mode and number of proofs:

`poisson(+non_negative_float, -non_negative_integer) - one`

`power/2`

Returns a power distributed random value.

Compilation flags:

`static`

Template:

`power(Exponent, Value)`

Mode and number of proofs:

`power(+positive_float, -float) - one`

`weibull/3`

Returns a scaled Weibull distributed random value.

Compilation flags:

`static`

Template:

`weibull(Shape, Scale, Value)`

Mode and number of proofs:

`weibull(+float, +positive_float, -float) - one`

uniform/3

Returns a uniform distributed random value in the interval“[Lower, Upper[. Fails if ``Lower or Upper are not integers or if Lower > Upper. Same as random/3.

Compilation flags:

static

Template:

uniform(Lower,Upper,Value)

Mode and number of proofs:

uniform(+float,+float,-float) - zero_or_one

uniform/1

Returns a uniform distributed random value in the interval“[0.0, 1.0[. Same as ``random/1.

Compilation flags:

static

Template:

uniform(Value)

Mode and number of proofs:

uniform(-float) - one

triangular/4

Returns a triangular distributed random value. Fails if the Left =< Mode =< Right condition does not hold.

Compilation flags:

static

Template:

triangular(Left,Mode,Right,Value)

Mode and number of proofs:

triangular(+float,+float,+float,-float) - zero_or_one

`von_mises/3`

Returns a von Mises distributed random value.

Compilation flags:
static

Template:
von_mises(Mode,Concentration,Value)

Mode and number of proofs:
von_mises(+float,+non_negative_float,-float) - zero_or_one

`gumbel/3`

Returns a Gumbel distributed random value.

Compilation flags:
static

Template:
gumbel(Location,Scale,Value)

Mode and number of proofs:
gumbel(+float,+non_negative_float,-float) - zero_or_one

`dirichlet/2`

Returns a Dirichlet distributed list of random values.

Compilation flags:
static

Template:
dirichlet(Alphas,Thetas)

Mode and number of proofs:

`dirichlet(+list(positive_float),-list(positive_float)) - one`

`circular_uniform_polar/3`

Returns a circular uniform distributed random point in polar coordinates given the circle radius.

Compilation flags:

`static`

Template:

`circular_uniform_polar(Radius,Rho,Theta)`

Mode and number of proofs:

`circular_uniform_polar(+float,+float,-float) - one`

`circular_uniform_cartesian/3`

Returns a circular uniform distributed random point in cartesian coordinates given the circle radius.

Compilation flags:

`static`

Template:

`circular_uniform_cartesian(Radius,X,Y)`

Mode and number of proofs:

`circular_uniform_cartesian(+float,+float,-float) - one`

`standard_t/2`

Returns a standard Student's t distributed random value given the degrees of freedom.

Compilation flags:

`static`

Template:


```
standard_t(DegreesOfFreedom,Value)
```

Mode and number of proofs:

```
standard_t(+positive_integer,-float) - one
```

```
standard_cauchy/3
```

Returns a standard Cauchy distributed random value.

Compilation flags:

```
static
```

Template:

```
standard_cauchy(Location,Scale,Value)
```

Mode and number of proofs:

```
standard_cauchy(+float,+float,-float) - one
```

```
standard_exponential/1
```

Returns a standard exponential distributed random value.

Compilation flags:

```
static
```

Template:

```
standard_exponential(Value)
```

Mode and number of proofs:

```
standard_exponential(-float) - one
```

`standard_gamma/2`

Returns a standard gamma distributed random value.

Compilation flags:

`static`

Template:

`standard_gamma(Shape, Value)`

Mode and number of proofs:

`standard_gamma(+positive_float, -float) - one`

`standard_normal/1`

Returns a standard normally (Gaussian) distributed random value (using a default mean of 0.0 and a default deviation of 1.0).

Compilation flags:

`static`

Template:

`standard_normal(Value)`

Mode and number of proofs:

`standard_normal(-float) - one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

➡ See also

`random_protocol`, `pseudo_random_protocol`

1.62 reader

object

1.62.1 reader

Predicates for reading text file and text stream contents to lists of terms, characters, or character codes and for reading binary file and binary stream contents to lists of bytes.

Availability:

`logtalk_load(reader(loader))`

Author: Paulo Moura

Version: 2:2:0

Date: 2023-11-14

Compilation flags:

`static`, `context_switching_calls`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - `file_to_codes/2`
 - `file_to_codes/3`

- file_to_chars/2
 - file_to_chars/3
 - file_to_terms/2
 - file_to_terms/3
 - file_to_bytes/2
 - file_to_bytes/3
 - stream_to_codes/2
 - stream_to_codes/3
 - stream_to_chars/2
 - stream_to_chars/3
 - stream_to_terms/2
 - stream_to_terms/3
 - stream_to_bytes/2
 - stream_to_bytes/3
 - line_to_chars/2
 - line_to_chars/3
 - line_to_codes/2
 - line_to_codes/3
- Protected predicates
 - Private predicates
 - Operators

Public predicates

file_to_codes/2

Reads a text file into a list of character codes.

Compilation flags:

static

Template:

file_to_codes(File,Codes)

Mode and number of proofs:

file_to_codes(+atom,-list(character_code)) - one

`file_to_codes/3`

Reads a text file into a list of character codes. The list is terminated by the given tail.

Compilation flags:

`static`

Template:

`file_to_codes(File,Codes,Tail)`

Mode and number of proofs:

`file_to_codes(+atom,-list(character_code),@term) - one`

`file_to_chars/2`

Reads a text file into a list of characters.

Compilation flags:

`static`

Template:

`file_to_chars(File,Chars)`

Mode and number of proofs:

`file_to_chars(+atom,-list(character)) - one`

`file_to_chars/3`

Reads a text file into a list of characters. The list is terminated by the given tail.

Compilation flags:

`static`

Template:

`file_to_chars(File,Chars,Tail)`

Mode and number of proofs:

`file_to_chars(+atom,-list(character),@term) - one`

`file_to_terms/2`

Reads a text file into a list of terms.

Compilation flags:

`static`

Template:

`file_to_terms(File,Terms)`

Mode and number of proofs:

`file_to_terms(+atom,-list(term)) - one`

`file_to_terms/3`

Reads a text file into a list of terms. The list is terminated by the given tail.

Compilation flags:

`static`

Template:

`file_to_terms(File,Terms,Tail)`

Mode and number of proofs:

`file_to_terms(+atom,-list(term),@term) - one`

`file_to_bytes/2`

Reads a binary file into a list of bytes.

Compilation flags:

`static`

Template:

`file_to_bytes(File,Bytes)`

Mode and number of proofs:

`file_to_bytes(+atom,-list(byte)) - one`

`file_to_bytes/3`

Reads a binary file into a list of bytes. The list is terminated by the given tail.

Compilation flags:

`static`

Template:

`file_to_bytes(File,Bytes,Tail)`

Mode and number of proofs:

`file_to_bytes(+atom,-list(byte),@term) - one`

`stream_to_codes/2`

Reads a text stream into a list of character codes. Does not close the stream.

Compilation flags:

`static`

Template:

`stream_to_codes(Stream,Codes)`

Mode and number of proofs:

`stream_to_codes(+stream_or_alias,-list(character_code)) - one`

`stream_to_codes/3`

Reads a text stream into a list of character codes. Does not close the stream. The list is terminated by the given tail.

Compilation flags:

`static`

Template:

`stream_to_codes(Stream,Codes,Tail)`

Mode and number of proofs:

`stream_to_codes(+stream_or_alias,-list(character_code),@term) - one`

`stream__to__chars/2`

Reads a text stream into a list of characters. Does not close the stream.

Compilation flags:

`static`

Template:

`stream__to__chars(Stream,Chars)`

Mode and number of proofs:

`stream__to__chars(+stream_or_alias,-list(char)) - one`

`stream__to__chars/3`

Reads a text stream into a list of characters. Does not close the stream. The list is terminated by the given tail.

Compilation flags:

`static`

Template:

`stream__to__chars(Stream,Chars,Tail)`

Mode and number of proofs:

`stream__to__chars(+stream_or_alias,-list(char),@term) - one`

`stream__to__terms/2`

Reads a text stream into a list of terms. Does not close the stream.

Compilation flags:

`static`

Template:

`stream__to__terms(Stream,Terms)`

Mode and number of proofs:

`stream_to_terms(+stream_or_alias,-list(term))` - one

`stream_to_terms/3`

Reads a text stream into a list of terms. Does not close the stream. The list is terminated by the given tail.

Compilation flags:

`static`

Template:

`stream_to_terms(Stream,Terms,Tail)`

Mode and number of proofs:

`stream_to_terms(+stream_or_alias,-list(term),@term)` - one

`stream_to_bytes/2`

Reads a binary stream into a list of bytes. Does not close the stream.

Compilation flags:

`static`

Template:

`stream_to_bytes(Stream,Bytes)`

Mode and number of proofs:

`stream_to_bytes(+stream_or_alias,-list(byte))` - one

`stream_to_bytes/3`

Reads a binary stream into a list of bytes. Does not close the stream. The list is terminated by the given tail.

Compilation flags:

`static`

Template:

```
stream_to_bytes(Stream,Bytes,Tail)
```

Mode and number of proofs:

```
stream_to_bytes(+stream_or_alias,-list(byte),@term) - one
```

[line_to_chars/2](#)

Reads a line from a text stream into a list of characters. Discards the end-of-line characters. Unifies Chars with end_of_file at the end of the file.

Compilation flags:

```
static
```

Template:

```
line_to_chars(Stream,Chars)
```

Mode and number of proofs:

```
line_to_chars(+stream_or_alias,-types([atom,list(character)])) - one
```

[line_to_chars/3](#)

Reads a line from a text stream into a list of characters. Keeps the end-of-line marker normalized to the line feed control character. The list is terminated by the given tail, which is unified with the empty list at the end of the file.

Compilation flags:

```
static
```

Template:

```
line_to_chars(Stream,Chars,Tail)
```

Mode and number of proofs:

```
line_to_chars(+stream_or_alias,-list(character),?term) - one
```

`line_to_codes/2`

Reads a line from a text stream into a list of character codes. Discards the end-of-line character codes. Unifies Codes with `end_of_file` at the end of the file.

Compilation flags:

`static`

Template:

`line_to_codes(Stream,Codes)`

Mode and number of proofs:

`line_to_codes(+stream_or_alias,-types([atom,list(character_code)])) - one`

`line_to_codes/3`

Reads a line from a text stream into a list of character codes. Keeps the end-of-line marker normalized to the line feed control character code. The list is terminated by the given tail, which is unified with the empty list at the end of the file.

Compilation flags:

`static`

Template:

`line_to_codes(Stream,Codes,Tail)`

Mode and number of proofs:

`line_to_codes(+stream_or_alias,-list(character_code),?term) - one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.63 recorded_database

object

1.63.1 recorded_database

Legacy recorded database predicates. Provides an application global database.

Availability:

`logtalk_load(recorded_database(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2023-12-17

Compilation flags:

`static, context_switching_calls`

Imports:

`public recorded_database_core`

Remarks:

(none)

Inherited public predicates:

`erase/1 instance/2 recorda/2 recorda/3 recorded/2 recorded/3 recordz/2 recordz/3`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.63.2 recorded_database_core

Legacy recorded database predicates. Can be imported into an object to provide a local database.

Availability:

```
logtalk_load(recorded_database(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2023-12-17

Compilation flags:

```
static
```

Dependencies:

(none)

Remarks:

- References: Opaque ground terms.

Inherited public predicates:

(none)

- Public predicates
 - recorda/3
 - recorda/2
 - recordz/3
 - recordz/2
 - recorded/3
 - recorded/2
 - erase/1
 - instance/2
- Protected predicates
- Private predicates
 - record_/3
 - reference_/1
- Operators

Public predicates

recorda/3

Adds a term as the first term for the given key, returning its reference.

Compilation flags:

static

Template:

recorda(Key,Term,Reference)

Mode and number of proofs:

recorda(+recorded_database_key,+term,--recorded_database_reference) - one_or_error

Exceptions:

Key is a variable:

instantiation_error

Key is neither a variable nor an atomic term or compound term:

type_error(recorded_database_key,Key)

Reference is a not a variable:

uninstantiation_error(Reference)

recorda/2

Adds a term as the first term for the given key.

Compilation flags:

static

Template:

recorda(Key,Term)

Mode and number of proofs:

recorda(+recorded_database_key,+term) - one_or_error

Exceptions:

Key is a variable:

instantiation_error

Key is neither a variable nor an atomic term or compound term:

type_error(recorded_database_key,Key)

recordz/3

Adds a term as the last term for the given key, returning its reference.

Compilation flags:

static

Template:

recordz(Key,Term,Reference)

Mode and number of proofs:

recordz(+recorded_database_key,+term,--recorded_database_reference) - one_or_error

Exceptions:

Key is a variable:

instantiation_error

Key is neither a variable nor an atomic term or compound term:

type_error(recorded_database_key,Key)

Reference is not a variable:

uninstantiation_error(Reference)

`recordz/2`

Adds a term as the last term for the given key.

Compilation flags:

`static`

Template:

`recordz(Key,Term)`

Mode and number of proofs:

`recordz(+recorded_database_key,+term) - one_or_error`

Exceptions:

Key is a variable:

`instantiation_error`

Key is neither a variable nor an atomic term or compound term:

`type_error(recorded_database_key,Key)`

`recorded/3`

Enumerates, by backtracking, all record key-term pairs and their references.

Compilation flags:

`static`

Template:

`recorded(Key,Term,Reference)`

Mode and number of proofs:

`recorded(?recorded_database_key,?term,-recorded_database_reference) - zero_or_more`

`recorded(?recorded_database_key,?term,+recorded_database_reference) - zero_or_one`

recorded/2

Enumerates, by backtracking, all record key-term pairs.

Compilation flags:

static

Template:

recorded(Key,Term)

Mode and number of proofs:

recorded(?recorded_database_key,?term) - zero_or_more

erase/1

Erases the record indexed by the given reference. Fails if there is no record with the given reference.

Compilation flags:

static

Template:

erase(Reference)

Mode and number of proofs:

erase(@recorded_database_reference) - zero_or_one_or_error

Exceptions:

Reference is a variable:

instantiation_error

instance/2

.

Compilation flags:

static

Template:

instance(Reference,Term)

Mode and number of proofs:

instance(@recorded_database_reference,?term) - zero_or_one_or_error

Exceptions:

Reference is a variable:

instantiation_error

Protected predicates

(none)

Private predicates

record_/3

Records table.

Compilation flags:

dynamic

Template:

record_(Key,Term,Reference)

Mode and number of proofs:

record_(?recorded_database_key,?term,?recorded_database_reference) - zero_or_more

reference_/1

Reference count.

Compilation flags:

dynamic

Template:

reference_(Reference)

Mode and number of proofs:

reference_(?non_negative_integer) - zero_or_one

Operators

(none)

1.64 redis

object

1.64.1 redis

Redis client. Inspired by Sean Charles GNU Prolog Redis client.

Availability:

```
logtalk_load(redis(loader))
```

Author: Paulo Moura

Version: 0:5:1

Date: 2021-12-06

Compilation flags:

```
static, context_switching_calls
```

Provides:

```
logtalk::message_tokens//2
```

Uses:

```
list
```

```
logtalk
```

Remarks:

- Command representation: Use the Redis command name as the functor of a compound term where the arguments are the command arguments.
- Valid arguments: Atoms, integers, and floats. Always use atoms instead of double-quoted “strings”. This helps portability by not depending on the value of the double_quotes flag.

Inherited public predicates:

(none)

- Public predicates
 - connect/1
 - connect/3
 - disconnect/1
 - send/3
 - console/1
- Protected predicates
- Private predicates
- Operators

Public predicates

connect/1

Connect to a Redis server running on localhost using the default 6379 port.

Compilation flags:

static

Template:

connect(Connection)

Mode and number of proofs:

connect(--ground) - one

connect/3

Connect to a Redis server running on the given host and port.

Compilation flags:

static

Template:

connect(Host,Port,Connection)

Mode and number of proofs:

connect(+atom,+integer,--ground) - one

`disconnect/1`

Disconnect from a Redis server.

Compilation flags:

`static`

Template:

`disconnect(Connection)`

Mode and number of proofs:

`disconnect(++ground) - one`

`send/3`

Sends a request to the a Redis server and returns its reply.

Compilation flags:

`static`

Template:

`send(Connection,Request,Reply)`

Mode and number of proofs:

`send(++ground,++callable,--callable) - one`

`console/1`

Sends a request to a Redis server running on localhost at the default 6379 port and prints the reply.

Compilation flags:

`static`

Template:

`console(Request)`

Mode and number of proofs:

console(++callable) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.65 sets

object

1.65.1 set

Set predicates implemented using ordered lists. Uses `==/2` for element comparison and standard term ordering.

Availability:

logtalk_load(sets(loader))

Author: Richard O’Keefe (main predicates); adapted to Logtalk by Paulo Moura.

Version: 1:12:0

Date: 2019-05-23

Compilation flags:

static, context_switching_calls

Implements:

public `setp`

Extends:

public `compound`

Aliases:

setp size/2 as length/2

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (= <)/2 (= \=)/2 (>)/2 (>=)/2 as_list/2 as_set/2 check/1 delete/3 depth/2 disjoint/2 empty/1 equal/2 ground/1 insert/3 insert_all/3 intersect/2 intersection/3 intersection/4 member/2 memberchk/2 new/1 numbervars/1 numbervars/3 occurs/2 powerset/2 product/3 select/3 selectchk/3 singletons/2 size/2 subset/2 subsumes/2 subterm/2 subtract/3 symdiff/3 union/3 union/4 valid/1 variables/2 variant/2 varnumbers/2 varnumbers/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

set(Type)

object

1.65.2 set(Type)

Set predicates with elements constrained to a single type and custom comparing rules.

Availability:

`logtalk_load(sets(loader))`

Author: Paulo Moura and Adrian Arroyo

Version: 1:24:0

Date: 2022-02-03

Compilation flags:

`static, context_switching_calls`

Extends:

`public set`

Uses:

`list`

Remarks:

(none)

Inherited public predicates:

`(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 as_list/2 as_set/2 check/1 delete/3 depth/2 disjoint/2 empty/1 equal/2 ground/1 insert/3 insert_all/3 intersect/2 intersection/3 intersection/4 member/2 memberchk/2 new/1 numbervars/1 numbervars/3 occurs/2 powerset/2 product/3 select/3 selectchk/3 singletons/2 size/2 subset/2 subsumes/2 subterm/2 subtract/3 symdiff/3 union/3 union/4 valid/1 variables/2 variant/2 varnumbers/2 varnumbers/3`

- Public predicates
- Protected predicates
- Private predicates
 - `sort/2`
 - `partition/4`
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

sort/2

Sorts a list in ascending order.

Compilation flags:

static

Template:

sort(List,Sorted)

Mode and number of proofs:

sort(+list,-list) - one

partition/4

List partition in two sub-lists using a pivot.

Compilation flags:

static

Template:

partition(List,Pivot,Lowes,Biggers)

Mode and number of proofs:

partition(+list,+nonvar,-list,-list) - one

Operators

(none)

protocol

1.65.3 setp

Set protocol.

Availability:

logtalk_load(sets(loader))

Author: Paulo Moura

Version: 1:6:0

Date: 2019-05-23

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - as_set/2
 - as_list/2
 - delete/3
 - disjoint/2
 - equal/2
 - empty/1
 - insert/3
 - insert_all/3
 - intersect/2

- intersection/3
- intersection/4
- size/2
- member/2
- memberchk/2
- powerset/2
- product/3
- select/3
- selectchk/3
- subset/2
- subtract/3
- symdiff/3
- union/3
- union/4
- Protected predicates
- Private predicates
- Operators

Public predicates

`as_set/2`

Returns a set with all unique elements from the given list.

Compilation flags:

`static`

Template:

`as_set(List,Set)`

Mode and number of proofs:

`as_set(@list,-set) - one`

`as_list/2`

Returns a list with all elements of the given set.

Compilation flags:

`static`

Template:

`as_list(Set,List)`

Mode and number of proofs:

`as_list(@set,-list) - one`

`delete/3`

Deletes an element from a set returning the set of remaining elements.

Compilation flags:

`static`

Template:

`delete(Set,Element,Remaining)`

Mode and number of proofs:

`delete(+set,@term,?set) - one`

`disjoint/2`

True if the two sets have no element in common.

Compilation flags:

`static`

Template:

`disjoint(Set1,Set2)`

Mode and number of proofs:

`disjoint(+set,+set) - zero_or_one`

`equal/2`

True if the two sets are equal.

Compilation flags:

`static`

Template:

`equal(Set1,Set2)`

Mode and number of proofs:

`equal(+set,+set) - zero_or_one`

`empty/1`

True if the set is empty.

Compilation flags:

`static`

Template:

`empty(Set)`

Mode and number of proofs:

`empty(+set) - zero_or_one`

`insert/3`

Inserts an element in a set, returning the resulting set.

Compilation flags:

`static`

Template:

`insert(In,Element,Out)`

Mode and number of proofs:

`insert(+set,+term,?set) - one`

`insert_all/3`

Inserts a list of elements in a set, returning the resulting set.

Compilation flags:

`static`

Template:

`insert_all(List,In,Out)`

Mode and number of proofs:

`insert_all(+list,+set,?set) - one`

`intersect/2`

True if the two sets have at least one element in common.

Compilation flags:

`static`

Template:

`intersect(Set1,Set2)`

Mode and number of proofs:

`intersect(+set,+set) - zero_or_one`

`intersection/3`

Returns the intersection of Set1 and Set2.

Compilation flags:

`static`

Template:

`intersection(Set1,Set2,Intersection)`

Mode and number of proofs:

`intersection(+set,+set,?set) - zero_or_one`

intersection/4

True if Intersection is the intersection of Set1 and Set2 and Difference is the difference between Set2 and Set1.

Compilation flags:

static

Template:

intersection(Set1,Set2,Intersection,Difference)

Mode and number of proofs:

intersection(+set,+set,?set,?set) - zero_or_one

size/2

Number of set elements.

Compilation flags:

static

Template:

size(Set,Size)

Mode and number of proofs:

size(+set,?integer) - zero_or_one

member/2

Element is a member of set Set.

Compilation flags:

static

Template:

member(Element,Set)

Mode and number of proofs:

member(+term,+set) - zero_or_one

member(-term,+set) - zero_or_more

memberchk/2

Checks if a term is a member of a set.

Compilation flags:

static

Template:

memberchk(Element,Set)

Mode and number of proofs:

memberchk(+term,+set) - zero_or_one

powerset/2

Returns the power set of a set, represented as a list of sets.

Compilation flags:

static

Template:

powerset(Set,Powerset)

Mode and number of proofs:

powerset(+set,-list) - one

product/3

Returns the cartesian product of two sets.

Compilation flags:

static

Template:

product(Set1,Set2,Product)

Mode and number of proofs:

`product(+set,+set,-set) - one`

`select/3`

Selects an element from a set, returning the set of remaining elements.

Compilation flags:

`static`

Template:

`select(Element,Set,Remaining)`

Mode and number of proofs:

`select(?term,+set,?set) - zero_or_more`

`selectchk/3`

Checks that an element can be selected from a set, returning the set of remaining elements.

Compilation flags:

`static`

Template:

`selectchk(Element,Set,Remaining)`

Mode and number of proofs:

`selectchk(?term,+set,?set) - zero_or_one`

`subset/2`

True if Subset is a subset of Set.

Compilation flags:

`static`

Template:

subset(Subset,Set)

Mode and number of proofs:

subset(+set,+set) - zero_or_one

subtract/3

True when Difference contains all and only the elements of Set1 which are not also in Set2.

Compilation flags:

static

Template:

subtract(Set1,Set2,Difference)

Mode and number of proofs:

subtract(+set,+set,?set) - zero_or_one

symdiff/3

True if Difference is the symmetric difference of Set1 and Set2, containing all elements that are not in the sets intersection.

Compilation flags:

static

Template:

symdiff(Set1,Set2,Difference)

Mode and number of proofs:

symdiff(+set,+set,?set) - zero_or_one

union/3

True if Union is the union of Set1 and Set2.

Compilation flags:

static

Template:

union(Set1,Set2,Union)

Mode and number of proofs:

union(+set,+set,?set) - zero_or_one

union/4

True if Union is the union of Set1 and Set2 and Difference is the difference between Set2 and Set1.

Compilation flags:

static

Template:

union(Set1,Set2,Union,Difference)

Mode and number of proofs:

union(+set,+set,?set,?set) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

➡ See also

set, set(Type)

1.66 statistics

object

1.66.1 population

Statistical population represented as a list of numbers.

Availability:

logtalk_load(statistics(loader))

Author: Paulo Moura

Version: 1:3:0

Date: 2020-02-02

Compilation flags:

static, context_switching_calls

Imports:

public statistics

Remarks:

(none)

Inherited public predicates:

arithmetic_mean/2 average_deviation/3 coefficient_of_variation/2 fractile/3 geometric_mean/2
harmonic_mean/2 kurtosis/2 max/2 mean_deviation/2 median/2 median_deviation/2 min/2
min_max/3 modes/2 product/2 range/2 relative_standard_deviation/2 skewness/2
standard_deviation/2 sum/2 valid/1 variance/2 weighted_mean/3 z_normalization/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates


(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

sample

object

1.66.2 sample

Statistical sample represented as a list of numbers.

Availability:

`logtalk_load(statistics(loader))`

Author: Paulo Moura

Version: 1:4:0

Date: 2020-02-02

Compilation flags:

`static, context_switching_calls`

Imports:

`public statistics`

Remarks:

(none)

Inherited public predicates:

`arithmetic_mean/2` `average_deviation/3` `coefficient_of_variation/2` `fractile/3` `geometric_mean/2`
`harmonic_mean/2` `kurtosis/2` `max/2` `mean_deviation/2` `median/2` `median_deviation/2` `min/2`
`min_max/3` `modes/2` `product/2` `range/2` `relative_standard_deviation/2` `skewness/2`
`standard_deviation/2` `sum/2` `valid/1` `variance/2` `weighted_mean/3` `z_normalization/2`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

`population`

`category`

1.66.3 statistics

Statistical calculations over a list of numbers.

Availability:

```
logtalk_load(statistics(loader))
```

Author: Paulo Moura

Version: 1:7:1

Date: 2023-05-29

Compilation flags:

```
static
```

Implements:

```
public statisticsp
```

Uses:

```
list
```

```
numberlist
```

Remarks:

```
(none)
```

Inherited public predicates:

```
arithmetic_mean/2 average_deviation/3 coefficient_of_variation/2 fractile/3 geometric_mean/2
harmonic_mean/2 kurtosis/2 max/2 mean_deviation/2 median/2 median_deviation/2 min/2
min_max/3 modes/2 product/2 range/2 relative_standard_deviation/2 skewness/2
standard_deviation/2 sum/2 valid/1 variance/2 weighted_mean/3 z_normalization/2
```

- Public predicates
- Protected predicates
- Private predicates
 - arithmetic_mean/5
 - squares_and_cubes/6
 - squares_and_hypers/6
 - variance/6
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

`arithmetic_mean/5`

Auxiliary predicate for computing the arithmetic mean.

Compilation flags:

`static`

Template:

`arithmetic_mean(List,Length0,Length,Sum,Mean)`

Mode and number of proofs:

`arithmetic_mean(+list(number),+integer,-integer,+number,-float) - one`

`squares_and_cubes/6`

Auxiliary predicate for computing the skewness.

Compilation flags:

`static`

Template:

`squares_and_cubes(List,Mean,Squares0,Squares,Cubes0,Cubes)`

Mode and number of proofs:

`squares_and_cubes(+list(number),+float,+float,-float,+float,-float) - one`

squares_and_hypers/6

Auxiliary predicate for computing the kurtosis.

Compilation flags:

static

Template:

squares_and_hypers(List,Mean,Squares0,Squares,Hypers0,Hypers)

Mode and number of proofs:

squares_and_hypers(+list(number),+float,+float,-float,+float,-float) - one

variance/6

Auxiliary predicate for computing the variance.

Compilation flags:

static

Template:

variance(List,Length0,Length,Mean,M20,M2)

Mode and number of proofs:

variance(+list(number),+integer,-integer,+float,+float,-float) - one

Operators

(none)

protocol

1.66.4 statisticsp

Statistical calculations over a list of numbers protocol.

Availability:

logtalk_load(statistics(loader))

Author: Paulo Moura

Version: 1:3:0

Date: 2022-06-20

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - product/2
 - sum/2
 - min/2
 - max/2
 - min_max/3
 - range/2
 - arithmetic_mean/2
 - geometric_mean/2
 - harmonic_mean/2
 - weighted_mean/3
 - median/2
 - modes/2
 - average_deviation/3
 - mean_deviation/2
 - median_deviation/2
 - standard_deviation/2
 - coefficient_of_variation/2
 - relative_standard_deviation/2
 - skewness/2
 - kurtosis/2

- variance/2
- z_normalization/2
- fractile/3
- valid/1
- Protected predicates
- Private predicates
- Operators

Public predicates

product/2

Calculates the product of all list numbers. Fails if the list is empty.

Compilation flags:

static

Template:

product(List,Product)

Mode and number of proofs:

product(+list(number),-number) - zero_or_one

sum/2

Calculates the sum of all list numbers. Fails if the list is empty.

Compilation flags:

static

Template:

sum(List,Sum)

Mode and number of proofs:

sum(+list(number),-number) - zero_or_one

min/2

Determines the minimum value in a list of numbers. Fails if the list is empty.

Compilation flags:

static

Template:

min(List,Minimum)

Mode and number of proofs:

min(+list,-number) - zero_or_one

max/2

Determines the list maximum value in a list of numbers. Fails if the list is empty.

Compilation flags:

static

Template:

max(List,Maximum)

Mode and number of proofs:

max(+list,-number) - zero_or_one

min_max/3

Determines the minimum and maximum values in a list of numbers. Fails if the list is empty.

Compilation flags:

static

Template:

min_max(List,Minimum,Maximum)

Mode and number of proofs:

min_max(+list(number),-number,-number) - zero_or_one

range/2

Range is the length of the smallest interval which contains all the numbers in List. Fails if the list is empty.

Compilation flags:

static

Template:

range(List,Range)

Mode and number of proofs:

range(+list,-number) - zero_or_one

arithmetic_mean/2

Calculates the arithmetic mean of a list of numbers. Fails if the list is empty.

Compilation flags:

static

Template:

arithmetic_mean(List,Mean)

Mode and number of proofs:

arithmetic_mean(+list(number),-float) - zero_or_one

geometric_mean/2

Calculates the geometric mean of a list of numbers. Fails if the list is empty.

Compilation flags:

static

Template:

geometric_mean(List,Mean)

Mode and number of proofs:

geometric_mean(+list(number),-float) - zero_or_one

harmonic_mean/2

Calculates the harmonic mean of a list of numbers. Fails if the list is empty.

Compilation flags:

static

Template:

harmonic_mean(List,Mean)

Mode and number of proofs:

harmonic_mean(+list(number),-float) - zero_or_one

weighted_mean/3

Calculates the weighted mean of a list of numbers. Fails if the list is empty or if the two lists have different lengths. Wights are assume to be non-negative.

Compilation flags:

static

Template:

weighted_mean(Weights,List,Mean)

Mode and number of proofs:

weighted_mean(+list(number),+list(number),-float) - zero_or_one

median/2

Calculates the median of a list of numbers. Fails if the list is empty.

Compilation flags:

static

Template:

median(List,Median)

Mode and number of proofs:

median(+list(number),-float) - zero_or_one

`modes/2`

Returns the list of modes of a list of numbers in ascending order. Fails if the list is empty.

Compilation flags:

`static`

Template:

`modes(List,Modes)`

Mode and number of proofs:

`modes(+list(number),-list(number)) - zero_or_one`

`average_deviation/3`

Calculates the average absolute deviation of a list of numbers given a central tendency (e.g., mean, median, or mode). Fails if the list is empty.

Compilation flags:

`static`

Template:

`average_deviation(List,CentralTendency,Deviation)`

Mode and number of proofs:

`average_deviation(+list(number),+float,-float) - zero_or_one`

`mean_deviation/2`

Calculates the mean absolute deviation of a list of numbers. Fails if the list is empty.

Compilation flags:

`static`

Template:

`mean_deviation(List,Deviation)`

Mode and number of proofs:

`mean_deviation(+list(number),-float) - zero_or_one`

`median_deviation/2`

Calculates the median absolute deviation of a list of numbers. Fails if the list is empty.

Compilation flags:

`static`

Template:

`median_deviation(List,Deviation)`

Mode and number of proofs:

`median_deviation(+list(number),-float) - zero_or_one`

`standard_deviation/2`

Calculates the standard deviation of a list of numbers. Fails if the list is empty.

Compilation flags:

`static`

Template:

`standard_deviation(List,Deviation)`

Mode and number of proofs:

`standard_deviation(+list(number),-float) - zero_or_one`

`coefficient_of_variation/2`

Calculates the coefficient of variation of a list of numbers. Fails if the list is empty.

Compilation flags:

`static`

Template:

coefficient_of_variation(List,Coefficient)

Mode and number of proofs:

coefficient_of_variation(+list(number),-float) - zero_or_one

relative_standard_deviation/2

Calculates the relative standard deviation of a list of numbers. Fails if the list is empty.

Compilation flags:

static

Template:

relative_standard_deviation(List,Percentage)

Mode and number of proofs:

relative_standard_deviation(+list(number),-float) - zero_or_one

skewness/2

Calculates the (moment) skewness of a list of numbers. Fails if the list is empty.

Compilation flags:

static

Template:

skewness(List,Skewness)

Mode and number of proofs:

skewness(+list(number),-float) - zero_or_one

kurtosis/2

Calculates the (excess) kurtosis of a list of numbers. Fails if the list is empty.

Compilation flags:

static

Template:

kurtosis(List,Kurtosis)

Mode and number of proofs:

kurtosis(+list(number),-float) - zero_or_one

variance/2

Calculates the unbiased variance of a list of numbers. Fails if the list is empty.

Compilation flags:

static

Template:

variance(List,Variance)

Mode and number of proofs:

variance(+list(number),-float) - zero_or_one

z_normalization/2

Normalizes a list of number such that for the resulting list the mean of is close to zero and the standard deviation is close to 1. Fails if the list is empty.

Compilation flags:

static

Template:

z_normalization(List,NormalizedList)

Mode and number of proofs:

z_normalization(+list(number),-list(float)) - zero_or_one

fractile/3

Calculates the smallest value in a list of numbers such that the list elements in its fraction P are less or equal to that value (with P in the open interval (0.0, 1.0)). Fails if the list is empty.

Compilation flags:

static

Template:

fractile(P,List,Fractile)

Mode and number of proofs:

fractile(+float,+list(integer),-integer) - zero_or_one

fractile(+float,+list(float),-float) - zero_or_one

valid/1

Term is a closed list of numbers.

Compilation flags:

static

Template:

valid(Term)

Mode and number of proofs:

valid(@nonvar) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

 See also

statistics, sample, population

1.67 term_io

object

1.67.1 term_io

Term input/output from/to atom, chars, and codes.

Availability:

`logtalk_load(term_io(loader))`

Author: Paulo Moura

Version: 1:3:0

Date: 2023-11-14

Compilation flags:

`static, context_switching_calls`

Implements:

`public term_io_protocol`

Uses:

`os`

Remarks:

(none)

Inherited public predicates:

```

format_to_atom/3 format_to_chars/3 format_to_chars/4 format_to_codes/3
format_to_codes/4 read_from_atom/2 read_from_chars/2 read_from_codes/2
read_term_from_atom/3 read_term_from_chars/3 read_term_from_chars/4
read_term_from_codes/3 read_term_from_codes/4 with_output_to/2 write_term_to_atom/3
write_term_to_chars/3 write_term_to_chars/4 write_term_to_codes/3
write_term_to_codes/4 write_to_atom/2 write_to_chars/2 write_to_codes/2

```

- Public predicates
- Protected predicates
- Private predicates
 - temporary_file_/1
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

temporary_file_/1

Logtalk session and term_io specific temporary file path.

Compilation flags:

dynamic

Template:

temporary_file_(Path)

Mode and number of proofs:

temporary_file_(-atom) - one

Operators

(none)

protocol

1.67.2 term_io_protocol

Predicates for term input/output from/to atom, chars, and codes. The predicates are declared as synchronized when the library is compiled using a backend supporting threads.

Availability:

logtalk_load(term_io(loader))

Author: Paulo Moura

Version: 1:3:0

Date: 2021-10-04

Compilation flags:

static

Dependencies:

(none)

Remarks:

- Portability notes: To keep calls to these library predicates portable, use only standard read/write options and specify output formats using atoms.

Inherited public predicates:

(none)

- Public predicates
 - read_term_from_atom/3
 - read_from_atom/2
 - read_term_from_chars/3
 - read_term_from_chars/4
 - read_from_chars/2
 - read_term_from_codes/3

- read_term_from_codes/4
- read_from_codes/2
- write_term_to_atom/3
- write_to_atom/2
- write_term_to_chars/3
- write_term_to_chars/4
- write_to_chars/2
- write_term_to_codes/3
- write_term_to_codes/4
- write_to_codes/2
- format_to_atom/3
- format_to_chars/3
- format_to_chars/4
- format_to_codes/3
- format_to_codes/4
- with_output_to/2
- Protected predicates
- Private predicates
- Operators

Public predicates

read_term_from_atom/3

Reads a term from an atom using the given read options. A period at the end of the atom is optional. Valid options are those supported by the standard read_term/3 predicate.

Compilation flags:

static, synchronized

Template:

read_term_from_atom(Atom,Term,Options)

Mode and number of proofs:

read_term_from_atom(+atom,-term,+list(read_option)) - one_or_error

`read_from_atom/2`

Reads a term from an atom using default read options. Shorthand for `read_term_from_atom(Atom,Term,[])`. A period at the end of the atom is optional.

Compilation flags:

`static`

Template:

`read_from_atom(Atom,Term)`

Mode and number of proofs:

`read_from_atom(+atom,-term) - one_or_error`

`read_term_from_chars/3`

Reads a term from a list of characters using the given read options. A period at the end of the list is optional. Valid options are those supported by the standard `read_term/3` predicate.

Compilation flags:

`static, synchronized`

Template:

`read_term_from_chars(Chars,Term,Options)`

Mode and number of proofs:

`read_term_from_chars(+list(character),-term,+list(read_option)) - one_or_error`

`read_term_from_chars/4`

Reads a term from a list of characters using the given read options, also returning the remaining characters. A period at the end of the term is required. Valid options are those supported by the standard `read_term/3` predicate.

Compilation flags:

`static`

Template:

`read_term_from_chars(Chars,Term,Tail,Options)`

Mode and number of proofs:

```
read_term_from_chars(+list(character),-term,-list(character),+list(read_option)) - one_or_error
```

`read_from_chars/2`

Reads a term from a list of characters using default read options. Shorthand for `read_term_from_chars(Chars,Term,[])`. A period at the end of the list is optional.

Compilation flags:

```
static
```

Template:

```
read_from_chars(Chars,Term)
```

Mode and number of proofs:

```
read_from_chars(+list(character),-term) - one_or_error
```

`read_term_from_codes/3`

Reads a term from a list of character codes using the given read options. A period at the end of the list is optional. Valid options are those supported by the standard `read_term/3` predicate.

Compilation flags:

```
static, synchronized
```

Template:

```
read_term_from_codes(Codes,Term,Options)
```

Mode and number of proofs:

```
read_term_from_codes(+list(character_code),-term,+list(read_option)) - one_or_error
```

`read_term_from_codes/4`

Reads a term from a list of character codes using the given read options, also returning the remaining character codes. A period at the end of the term is required. Valid options are those supported by the standard `read_term/3` predicate.

Compilation flags:

`static`

Template:

`read_term_from_codes(Codes,Term,Tail,Options)`

Mode and number of proofs:

`read_term_from_codes(+list(character_code),-term,-list(character_code),+list(read_option)) - one_or_error`

`read_from_codes/2`

Reads a term from a list of character codes using default read options. Shorthand for `read_term_from_codes(Codes,Term,[])`. A period at the end of the list is optional.

Compilation flags:

`static`

Template:

`read_from_codes(Codes,Term)`

Mode and number of proofs:

`read_from_codes(+list(character_code),-term) - one_or_error`

`write_term_to_atom/3`

Writes a term to an atom using the given write options. Valid options are those supported by the standard `write_term/3` predicate.

Compilation flags:

`static, synchronized`

Template:

```
write_term_to_atom(Term,Atom,Options)
```

Mode and number of proofs:

```
write_term_to_atom(@term,-atom,+list(write_option)) - one
```

`write_to_atom/2`

Writes a term to an atom using default write options. Shorthand for `write_term_to_atom(Term,Atom,[])`.

Compilation flags:

```
static
```

Template:

```
write_to_atom(Term,Atom)
```

Mode and number of proofs:

```
write_to_atom(@term,-atom) - one
```

`write_term_to_chars/3`

Writes a term to a list of characters using the given write options. Shorthand for `write_term_to_chars(Term,Chars,[],Options)`. Valid options are those supported by the standard `write_term/3` predicate.

Compilation flags:

```
static
```

Template:

```
write_term_to_chars(Term,Chars,Options)
```

Mode and number of proofs:

```
write_term_to_chars(@term,-list(character),+list(write_option)) - one
```

`write_term_to_chars/4`

Writes a term to a list of characters with the given tail using the given write options. Valid options are those supported by the standard `write_term/3` predicate.

Compilation flags:

static, synchronized

Template:

`write_term_to_chars(Term,Chars,Tail,Options)`

Mode and number of proofs:

`write_term_to_chars(@term,-list(character),@term,+list(write_option))` - one

`write_to_chars/2`

Writes a term to a list of characters using default write options. Shorthand for `write_term_to_chars(Term,Chars,[],[])`.

Compilation flags:

static

Template:

`write_to_chars(Term,Chars)`

Mode and number of proofs:

`write_to_chars(@term,-list(character))` - one

`write_term_to_codes/3`

Writes a term to a list of character codes using the given write options. Shorthand for `write_term_to_codes(Term,Codes,[],Options)`. Valid options are those supported by the standard `write_term/3` predicate.

Compilation flags:

static

Template:

`write_term_to_codes(Term,Codes,Options)`

Mode and number of proofs:

```
write_term_to_codes(@term,-list(character_code),+list(write_option)) - one
```

`write_term_to_codes/4`

Writes a term to a list of character codes with the given tail using the given write options. Valid options are those supported by the standard `write_term/3` predicate.

Compilation flags:

```
static, synchronized
```

Template:

```
write_term_to_codes(Term,Codes,Tail,Options)
```

Mode and number of proofs:

```
write_term_to_codes(@term,-list(character_code),@term,+list(write_option)) - one
```

`write_to_codes/2`

Writes a term to a list of character codes using default write options. Shorthand for `write_term_to_chars(Term,Codes,[],[])`.

Compilation flags:

```
static
```

Template:

```
write_to_codes(Term,Codes)
```

Mode and number of proofs:

```
write_to_codes(@term,-list(character_code)) - one
```

`format__to__atom/3`

Writes a list of arguments to an atom using the given format (specified as in the de facto standard `format/2` predicate).

Compilation flags:

static, synchronized

Template:

`format__to__atom(Format,Arguments,Atom)`

Mode and number of proofs:

`format__to__atom(@atom,+list(term),-atom) - one`

`format__to__chars/3`

Writes a list of arguments to a list of characters using the given format (specified as in the de facto standard `format/2` predicate). Shorthand for `format__to__chars(Format,Arguments,Chars,[])`.

Compilation flags:

static

Template:

`format__to__chars(Format,Arguments,Chars)`

Mode and number of proofs:

`format__to__chars(@term,+list(term),-list(character)) - one`

`format__to__chars/4`

Writes a term to a list of characters with the given tail using the given format (specified as in the de facto standard `format/2` predicate).

Compilation flags:

static, synchronized

Template:

`format__to__chars(Format,Arguments,Chars,Tail)`

Mode and number of proofs:

`format__to__chars(@term,+list(term),-list(character),@term) - one`

`format__to__codes/3`

Writes a list of arguments to a list of character codes using the given format (specified as in the de facto standard `format/2` predicate). Shorthand for `format__to__codes(Format,Arguments,Codes,[])`.

Compilation flags:

`static`

Template:

`format__to__codes(Format,Arguments,Codes)`

Mode and number of proofs:

`format__to__codes(@term,+list(term),-list(character_code)) - one`

`format__to__codes/4`

Writes a list of arguments to a list of character codes with the given tail using the given format (specified as in the de facto standard `format/2` predicate).

Compilation flags:

`static, synchronized`

Template:

`format__to__codes(Format,Arguments,Codes,Tail)`

Mode and number of proofs:

`format__to__codes(@term,+list(term),-list(character_code),@term) - one`

`with_output_to/2`

Calls a goal deterministically with output to the given format: `atom(Atom)`, `chars(Chars)`, `chars(Chars,Tail)`, `codes(Codes)`, or `codes(Codes,Tail)`.

Compilation flags:

`static`, `synchronized`

Template:

`with_output_to(Output,Goal)`

Meta-predicate template:

`with_output_to(*,0)`

Mode and number of proofs:

`with_output_to(+compound,+callable) - zero_or_one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.68 timeout

object

1.68.1 timeout

Predicates for calling goal with a time limit.

Availability:

`logtalk_load(timeout(loader))`

Author: Paulo Moura

Version: 0:10:0

Date: 2022-06-15

Compilation flags:

static, context_switching_calls

Dependencies:

(none)

Remarks:

- Supported backend Prolog systems: B-Prolog, ECLiPSe, XVM, SICStus Prolog, SWI-Prolog, Trealla Prolog, XSB, and YAP.

Inherited public predicates:

(none)

- Public predicates
 - call_with_timeout/2
 - call_with_timeout/3
- Protected predicates
- Private predicates
- Operators

Public predicates

call_with_timeout/2

Calls a goal deterministically with the given time limit (expressed in seconds). Note that the goal may fail or throw an error before exhausting the time limit.

Compilation flags:

static

Template:

call_with_timeout(Goal,Timeout)

Meta-predicate template:

call_with_timeout(0,*)

Mode and number of proofs:

call_with_timeout(+callable,+positive_number) - zero_or_one

Exceptions:

Goal does not complete in the allowed time:
 timeout(Goal)

`call_with_timeout/3`

Calls a goal deterministically with the given time limit (expressed in seconds) returning a reified result: true, fail, timeout, or error(Error).

Compilation flags:

 static

Template:

 call_with_timeout(Goal,Timeout,Result)

Meta-predicate template:

 call_with_timeout(0,*,*)

Mode and number of proofs:

 call_with_timeout(+callable,+positive_number,--atom) - one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.69 toychr

object

1.69.1 toychrdb

Simple CHR interpreter/debugger based on the refined operational semantics of CHRs.

Availability:

```
logtalk_load(toychr(loader))
```

Author: Gregory J. Duck; adapted to Logtalk by Paulo Moura.

Version: 0:7:1

Date: 2024-03-15

Copyright: Copyright 2004 Gregory J. Duck; Copyright 2019-2024 Paulo Moura

License: GPL-2.0-or-later

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public expanding
```

Uses:

```
list
```

```
user
```

Remarks:

```
(none)
```

Inherited public predicates:

```
goal_expansion/2 term_expansion/2
```

- Public predicates
 - chr_is/2
 - chr_trace/0
 - chr_notrace/0
 - chr_spy/1
 - chr_nospy/0
 - chr_no_spy/1
 - chr_option/2
- Protected predicates

- `current_prog/1`
- `chr_option_print_trace/0`
- `chr_option_trace_interactive/0`
- `chr_option_optimization_level/1`
- `chr_option_show_stack/0`
- `chr_option_show_store/0`
- `chr_option_show_history/0`
- `chr_option_show_id/0`
- `chr_option_allow_deep_guards/0`
- `chr_next_state/1`
- `chr_spy_point/1`
- Private predicates
 - `chr_rule_/1`
- Operators

Public predicates

`chr_is/2`

Compilation flags:

`static`

`chr_trace/0`

Compilation flags:

`static`

chr_notrace/0

Compilation flags:
static

chr_spy/1

Compilation flags:
static

chr_nospy/0

Compilation flags:
static

chr_no_spy/1

Compilation flags:
static

chr_option/2

Compilation flags:
static

Protected predicates

current_prog/1

Compilation flags:
static

`chr_option_print_trace/0`

Compilation flags:
dynamic

`chr_option_trace_interactive/0`

Compilation flags:
dynamic

`chr_option_optimization_level/1`

Compilation flags:
dynamic

`chr_option_show_stack/0`

Compilation flags:
dynamic

`chr_option_show_store/0`

Compilation flags:
dynamic

`chr_option_show_history/0`

Compilation flags:
dynamic

`chr_option_show_id/0`

Compilation flags:
dynamic

`chr_option_allow_deep_guards/0`

Compilation flags:
dynamic

`chr_next_state/1`

Compilation flags:
dynamic

`chr_spy_point/1`

Compilation flags:
dynamic

Private predicates

`chr_rule_/1`

Compilation flags:
dynamic

Operators

(none)

1.70 tsv

object

1.70.1 tsv

TSV files reading and writing predicates using the option Header-keep.

Availability:
`logtalk_load(tsv(loader))`

Author: Paulo Moura
Version: 1:0:0
Date: 2023-11-15

Compilation flags:
static, context_switching_calls

Extends:
public `tsv(keep)`

Remarks:
(none)

Inherited public predicates:
`read_file/2 read_file/3 read_file_by_line/2 read_file_by_line/3 read_stream/2`
`read_stream/3 read_stream_by_line/2 read_stream_by_line/3 write_file/3 write_stream/3`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.70.2 tsv(Header)

- Header - Header handling option with possible values skip and keep (default).

TSV file and stream reading and writing predicates.

Availability:

```
logtalk_load(tsv(loader))
```

Author: Paulo Moura

Version: 1:0:1

Date: 2024-03-11

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public tsv_protocol
```

Uses:

list
logtalk
reader
type

Remarks:

(none)

Inherited public predicates:

read_file/2 read_file/3 read_file_by_line/2 read_file_by_line/3 read_stream/2
read_stream/3 read_stream_by_line/2 read_stream_by_line/3 write_file/3 write_stream/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.70.3 tsv_protocol

TSV file and stream reading and writing protocol.

Availability:

logtalk_load(tsv(loader))

Author: Paulo Moura

Version: 1:0:1

Date: 2025-05-07

Compilation flags:

static

Dependencies:

(none)

Remarks:

- Type-checking: Some of the predicate file and stream argument type-checking exceptions depend on the Prolog backend compliance with standards.

Inherited public predicates:

(none)

- Public predicates
 - read_file/3
 - read_stream/3
 - read_file/2
 - read_stream/2
 - read_file_by_line/3
 - read_stream_by_line/3
 - read_file_by_line/2
 - read_stream_by_line/2
 - write_file/3
 - write_stream/3
- Protected predicates

- Private predicates
- Operators

Public predicates

`read_file/3`

Reads a TSV file saving the data as clauses for the specified object predicate. Fails if the file cannot be parsed.

Compilation flags:

`static`

Template:

`read_file(File,Object,Predicate)`

Mode and number of proofs:

`read_file(+atom,+object_identifier,+predicate_indicator) - zero_or_one`

Exceptions:

File is a variable:

`instantiation_error`

File is neither a variable nor an atom:

`type_error(atom,File)`

File is an atom but not an existing file:

`existence_error(file,File)`

File is an existing file but cannot be opened for reading:

`permission_error(open,source_sink,File)`

Object is a variable:

`instantiation_error`

Object is neither a variable nor an object identifier:

`type_error(object_identifier,Object)`

Object is a valid object identifier but not an existing object:

`existence_error(object,Object)`

Predicate is a variable:

`instantiation_error`

Predicate is neither a variable nor a predicate indicator:

`type_error(predicate_indicator,Predicate)`

Predicate is a valid predicate indicator but not an existing public predicate:

`existence_error(predicate,Predicate)`

read_stream/3

Reads a TSV stream saving the data as clauses for the specified object predicate. Fails if the stream cannot be parsed.

Compilation flags:

static

Template:

read_stream(Stream, Object, Predicate)

Mode and number of proofs:

read_stream(+stream_or_alias, +object_identifier, +predicate_indicator) - zero_or_one

Exceptions:

Stream is a variable:

instantiation_error

Stream is neither a variable nor a stream-term or alias:

domain_error(stream_or_alias, Stream)

Stream is not an open stream:

existence_error(stream, Stream)

Stream is an output stream:

permission_error(input, stream, Stream)

Stream is a binary stream:

permission_error(input, binary_stream, Stream)

Object is a variable:

instantiation_error

Object is neither a variable nor an object identifier:

type_error(object_identifier, Object)

Object is a valid object identifier but not an existing object:

existence_error(object, Object)

Predicate is a variable:

instantiation_error

Predicate is neither a variable nor a predicate indicator:

type_error(predicate_indicator, Predicate)

Predicate is a valid predicate indicator but not an existing public predicate:

existence_error(predicate, Predicate)

`read_file/2`

Reads a TSV file returning the data as a list of rows, each row a list of fields. Fails if the file cannot be parsed.

Compilation flags:

`static`

Template:

`read_file(File,Rows)`

Mode and number of proofs:

`read_file(+atom,-list(list)) - zero_or_one`

Exceptions:

File is a variable:

`instantiation_error`

File is neither a variable nor an atom:

`type_error(atom,File)`

File is an atom but not an existing file:

`existence_error(file,File)`

File is an existing file but cannot be opened for reading:

`permission_error(open,source_sink,File)`

`read_stream/2`

Reads a TSV stream returning the data as a list of rows, each row a list of fields. Fails if the stream cannot be parsed.

Compilation flags:

`static`

Template:

`read_stream(Stream,Rows)`

Mode and number of proofs:

`read_stream(+stream_or_alias,-list(list)) - zero_or_one`

Exceptions:

Stream is a variable:

`instantiation_error`

Stream is neither a variable nor a stream-term or alias:

```

    domain_error(stream_or_alias,Stream)
Stream is not an open stream:
    existence_error(stream,Stream)
Stream is an output stream:
    permission_error(input,stream,Stream)
Stream is a binary stream:
    permission_error(input,binary_stream,Stream)

```

`read_file_by_line/3`

Reads a TSV file saving the data as clauses for the specified object predicate. The file is read line by line. Fails if the file cannot be parsed.

Compilation flags:
static

Template:

```
read_file_by_line(File,Object,Predicate)
```

Mode and number of proofs:

```
read_file_by_line(+atom,+object_identifier,+predicate_indicator) - zero_or_one
```

Exceptions:

File is a variable:

```
instantiation_error
```

File is neither a variable nor an atom:

```
type_error(atom,File)
```

File is an atom but not an existing file:

```
existence_error(file,File)
```

File is an existing file but cannot be opened for reading:

```
permission_error(open,source_sink,File)
```

Object is a variable:

```
instantiation_error
```

Object is neither a variable nor an object identifier:

```
type_error(object_identifier,Object)
```

Object is a valid object identifier but not an existing object:

```
existence_error(object,Object)
```

Predicate is a variable:

```
instantiation_error
```

Predicate is neither a variable nor a predicate indicator:

```
type_error(predicate_indicator,Predicate)
```

Predicate is a valid predicate indicator but not an existing public predicate:

```
existence_error(predicate,Predicate)
```

`read_stream_by_line/3`

Reads a TSV stream saving the data as clauses for the specified object predicate. The stream is read line by line. Fails if the stream cannot be parsed.

Compilation flags:

`static`

Template:

`read_stream_by_line(Stream,Object,Predicate)`

Mode and number of proofs:

`read_stream_by_line(+stream_or_alias,+object_identifier,+predicate_indicator) - zero_or_one`

Exceptions:

Stream is a variable:

`instantiation_error`

Stream is neither a variable nor a stream-term or alias:

`domain_error(stream_or_alias,Stream)`

Stream is not an open stream:

`existence_error(stream,Stream)`

Stream is an output stream:

`permission_error(input,stream,Stream)`

Stream is a binary stream:

`permission_error(input,binary_stream,Stream)`

Object is a variable:

`instantiation_error`

Object is neither a variable nor an object identifier:

`type_error(object_identifier,Object)`

Object is a valid object identifier but not an existing object:

`existence_error(object,Object)`

Predicate is a variable:

`instantiation_error`

Predicate is neither a variable nor a predicate indicator:

`type_error(predicate_indicator,Predicate)`

Predicate is a valid predicate indicator but not an existing public predicate:

`existence_error(predicate,Predicate)`

`read_file_by_line/2`

Reads a TSV file returning the data as a list of rows, each row a list of fields. The file is read line by line. Fails if the file cannot be parsed.

Compilation flags:

`static`

Template:

`read_file_by_line(File,Rows)`

Mode and number of proofs:

`read_file_by_line(+atom,-list(list)) - zero_or_one`

Exceptions:

File is a variable:

`instantiation_error`

File is neither a variable nor an atom:

`type_error(atom,File)`

File is an atom but not an existing file:

`existence_error(file,File)`

File is an existing file but cannot be opened for reading:

`permission_error(open,source_sink,File)`

`read_stream_by_line/2`

Reads a TSV stream returning the data as a list of rows, each row a list of fields. The stream is read line by line. Fails if the stream cannot be parsed.

Compilation flags:

`static`

Template:

`read_stream_by_line(Stream,Rows)`

Mode and number of proofs:

`read_stream_by_line(+stream_or_alias,-list(list)) - zero_or_one`

Exceptions:

Stream is a variable:

`instantiation_error`

Stream is neither a variable nor a stream-term or alias:

```
domain_error(stream_or_alias,Stream)
Stream is not an open stream:
existence_error(stream,Stream)
Stream is an output stream:
permission_error(input,stream,Stream)
Stream is a binary stream:
permission_error(input,binary_stream,Stream)
```

`write_file/3`

Writes a TSV file with the data represented by the solutions to the specified object predicate.

Compilation flags:

```
static
```

Template:

```
write_file(File,Object,Predicate)
```

Mode and number of proofs:

```
write_file(+atom,+object_identifier,+predicate_indicator) - one
```

Exceptions:

File is a variable:

```
instantiation_error
```

File is neither a variable nor an atom:

```
type_error(atom,File)
```

File is an atom but cannot be opened for writing:

```
permission_error(open,source_sink,File)
```

Object is a variable:

```
instantiation_error
```

Object is neither a variable nor an object identifier:

```
type_error(object_identifier,Object)
```

Object is a valid object identifier but not an existing object:

```
existence_error(object,Object)
```

Predicate is a variable:

```
instantiation_error
```

Predicate is neither a variable nor a predicate indicator:

```
type_error(predicate_indicator,Predicate)
```

Predicate is a valid predicate indicator but not an existing public predicate:

```
existence_error(predicate,Predicate)
```

`write_stream/3`

Writes a TSV stream with the data represented by the solutions to the specified object predicate.

Compilation flags:

`static`

Template:

`write_stream(Stream,Object,Predicate)`

Mode and number of proofs:

`write_stream(+stream_or_alias,+object_identifier,+predicate_indicator) - one`

Exceptions:

Stream is a variable:

`instantiation_error`

Stream is neither a variable nor a stream-term or alias:

`domain_error(stream_or_alias,Stream)`

Stream is not an open stream:

`existence_error(stream,Stream)`

Stream is an input stream:

`permission_error(output,stream,Stream)`

Stream is a binary stream:

`permission_error(output,binary_stream,Stream)`

Object is a variable:

`instantiation_error`

Object is neither a variable nor an object identifier:

`type_error(object_identifier,Object)`

Object is a valid object identifier but not an existing object:

`existence_error(object,Object)`

Predicate is a variable:

`instantiation_error`

Predicate is neither a variable nor a predicate indicator:

`type_error(predicate_indicator,Predicate)`

Predicate is a valid predicate indicator but not an existing public predicate:

`existence_error(predicate,Predicate)`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.71 tutor

object

1.71.1 tutor

This object adds explanations and suggestions to selected compiler warning and error messages.

Availability:

`logtalk__load(tutor(loader))`

Author: Paulo Moura

Version: 0:80:0

Date: 2024-12-13

Compilation flags:

`static, context_switching_calls`

Provides:

`logtalk::message_hook/4`

Uses:

`list`

`logtalk`

Remarks:

- Usage: Simply load this object at startup using the goal `logtalk__load(tutor(loader))`.

Inherited public predicates:

(none)

- Public predicates
 - explain//1
- Protected predicates
- Private predicates
- Operators

Public predicates

explain//1

Generates an explanation for a message.

Compilation flags:

static

Template:

explain(Message)

Mode and number of proofs:

explain(@callable) - zero_or_one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.72 types

object

1.72.1 atom

Atom data type predicates.

Availability:

`logtalk_load(types(loader))`

Author: Paulo Moura

Version: 1:9:0

Date: 2023-04-12

Compilation flags:

`static, context_switching_calls`

Extends:

`public atomic`

Uses:

`user`

Remarks:

`(none)`

Inherited public predicates:

`(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 check/1 depth/2 ground/1 new/1
numbervars/1 numbervars/3 occurs/2 singletons/2 subsumes/2 subterm/2 valid/1 variables/2
variant/2 varnumbers/2 varnumbers/3`

- Public predicates
 - `replace_sub_atom/4`
 - `split/3`
- Protected predicates
- Private predicates
- Operators

Public predicates

`replace_sub_atom/4`

Replaces all occurrences of Old by New in Input returning Output. Returns Input if Old is the empty atom. Fails when Output does not unify with the resulting atom.

Compilation flags:

`static`

Template:

`replace_sub_atom(Old,New,Input,Output)`

Mode and number of proofs:

`replace_sub_atom(+atom,+atom,+atom,?atom) - zero_or_one`

`split/3`

Splits an atom at a given delimiter into a list of sub-atoms.

Compilation flags:

`static`

Template:

`split(Atom,Delimiter,SubAtoms)`

Mode and number of proofs:

`split(+atom,+atom,-list(atom)) - one`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.72.2 atomic

Atomic data type predicates.

Availability:

`logtalk__load(types(loader))`

Author: Paulo Moura

Version: 1:3:0

Date: 2018-07-11

Compilation flags:

`static, context_switching_calls`

Extends:

`public term`

Remarks:

(none)

Inherited public predicates:

`(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 check/1 depth/2 ground/1 new/1
numbervars/1 numbervars/3 occurs/2 singletons/2 subsumes/2 subterm/2 valid/1 variables/2
variant/2 varnumbers/2 varnumbers/3`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.72.3 callable

Callable term type predicates.

Availability:

`logtalk__load(types(loader))`

Author: Paulo Moura

Version: 1:4:0

Date: 2018-07-11

Compilation flags:

`static, context_switching_calls`

Extends:

public `term`

Remarks:

(none)

Inherited public predicates:

`(<)/2 (=:=)/2 (= <)/2 (= \=)/2 (>)/2 (>=)/2 check/1 depth/2 ground/1 new/1
numbervars/1 numbervars/3 occurs/2 singletons/2 subsumes/2 subterm/2 valid/1 variables/2
variant/2 varnumbers/2 varnumbers/3`

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.72.4 [character](#)

Character predicates (most of them assume an ASCII representation).

Availability:

`logtalk_load(types(loader))`

Author: Paulo Moura

Version: 1:9:0

Date: 2019-06-29

Compilation flags:

`static, context_switching_calls`

Implements:

`public characterp`

Extends:

`public atom`

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 check/1 depth/2 ground/1 is_alpha/1
 is_alphanumeric/1 is_ascii/1 is_bin_digit/1 is_control/1 is_dec_digit/1 is_end_of_line/1
 is_hex_digit/1 is_layout/1 is_letter/1 is_lower_case/1 is_newline/1 is_octal_digit/1
 is_period/1 is_punctuation/1 is_quote/1 is_upper_case/1 is_vowel/1 is_white_space/1
 lower_upper/2 new/1 numbervars/1 numbervars/3 occurs/2 parenthesis/2 replace_sub_atom/4
 singletons/2 split/3 subsumes/2 subterm/2 valid/1 variables/2 variant/2 varnumbers/2
 varnumbers/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.72.5 characterp

Character protocol.

Availability:

`logtalk_load(types(loader))`

Author: Paulo Moura

Version: 1:3:0

Date: 2019-06-29

Compilation flags:

`static`

Dependencies:

`(none)`

Remarks:

`(none)`

Inherited public predicates:

`(none)`

- Public predicates
 - `is_ascii/1`
 - `is_alphanumeric/1`
 - `is_alpha/1`
 - `is_letter/1`
 - `is_bin_digit/1`
 - `is_octal_digit/1`
 - `is_dec_digit/1`
 - `is_hex_digit/1`
 - `is_lower_case/1`
 - `is_upper_case/1`
 - `is_vowel/1`
 - `is_white_space/1`
 - `is_layout/1`

- is_quote/1
- is_punctuation/1
- is_period/1
- is_control/1
- is_newline/1
- is_end_of_line/1
- parenthesis/2
- lower_upper/2
- Protected predicates
- Private predicates
- Operators

Public predicates

is_ascii/1

True if the argument is an ASCII character.

Compilation flags:

static

Template:

is_ascii(Char)

Mode and number of proofs:

is_ascii(+char) - zero_or_one

is_alphanumeric/1

True if the argument is an alphanumeric character.

Compilation flags:

static

Template:

is_alphanumeric(Char)

Mode and number of proofs:

`is_alphanumeric(+char) - zero_or_one`

`is_alpha/1`

True if the argument is a letter or an underscore.

Compilation flags:

`static`

Template:

`is_alpha(Char)`

Mode and number of proofs:

`is_alpha(+char) - zero_or_one`

`is_letter/1`

True if the argument is a letter.

Compilation flags:

`static`

Template:

`is_letter(Char)`

Mode and number of proofs:

`is_letter(+char) - zero_or_one`

`is_bin_digit/1`

True if the argument is a binary digit.

Compilation flags:

`static`

Template:

`is_bin_digit(Char)`

Mode and number of proofs:

`is_bin_digit(+char) - zero_or_one`

`is_octal_digit/1`

True if the argument is an octal digit.

Compilation flags:

`static`

Template:

`is_octal_digit(Char)`

Mode and number of proofs:

`is_octal_digit(+char) - zero_or_one`

`is_dec_digit/1`

True if the argument is a decimal digit.

Compilation flags:

`static`

Template:

`is_dec_digit(Char)`

Mode and number of proofs:

`is_dec_digit(+char) - zero_or_one`

`is_hex_digit/1`

True if the argument is an hexadecimal digit.

Compilation flags:

`static`

Template:

`is_hex_digit(Char)`

Mode and number of proofs:

`is_hex_digit(+char) - zero_or_one`

`is_lower_case/1`

True if the argument is a lower case letter.

Compilation flags:

`static`

Template:

`is_lower_case(Char)`

Mode and number of proofs:

`is_lower_case(+char) - zero_or_one`

`is_upper_case/1`

True if the argument is a upper case letter.

Compilation flags:

`static`

Template:

`is_upper_case(Char)`

Mode and number of proofs:

`is_upper_case(+char) - zero_or_one`

`is_vowel/1`

True if the argument is a vowel.

Compilation flags:

`static`

Template:

`is_vowel(Char)`

Mode and number of proofs:

`is_vowel(+char) - zero_or_one`

`is_white_space/1`

True if the argument is a white space character (a space or a tab) inside a line of characters.

Compilation flags:

`static`

Template:

`is_white_space(Char)`

Mode and number of proofs:

`is_white_space(+char) - zero_or_one`

`is_layout/1`

True if the argument is a layout character.

Compilation flags:

`static`

Template:

`is_layout(Char)`

Mode and number of proofs:

`is_layout(+char) - zero_or_one`

is_quote/1

True if the argument is a quote character.

Compilation flags:

static

Template:

is_quote(Char)

Mode and number of proofs:

is_quote(+char) - zero_or_one

is_punctuation/1

True if the argument is a sentence punctuation character.

Compilation flags:

static

Template:

is_punctuation(Char)

Mode and number of proofs:

is_punctuation(+char) - zero_or_one

is_period/1

True if the argument is a character that ends a sentence.

Compilation flags:

static

Template:

is_period(Char)

Mode and number of proofs:

is_period(+char) - zero_or_one

`is_control/1`

True if the argument is an ASCII control character.

Compilation flags:

`static`

Template:

`is_control(Char)`

Mode and number of proofs:

`is_control(+char) - zero_or_one`

`is_newline/1`

True if the argument is the ASCII newline character.

Compilation flags:

`static`

Template:

`is_newline(Char)`

Mode and number of proofs:

`is_newline(+char) - zero_or_one`

`is_end_of_line/1`

True if the argument is the ASCII end-of-line character (either a carriage return or a line feed).

Compilation flags:

`static`

Template:

`is_end_of_line(Char)`

Mode and number of proofs:

`is_end_of_line(+char) - zero_or_one`

parenthesis/2

Recognizes and converts between open and close parenthesis.

Compilation flags:

static

Template:

parenthesis(Char1,Char2)

Mode and number of proofs:

parenthesis(?char,?char) - zero_or_more

parenthesis(+char,?char) - zero_or_one

parenthesis(?char,+char) - zero_or_one

lower_upper/2

Recognizes and converts between lower and upper case letters.

Compilation flags:

static

Template:

lower_upper(Char1,Char2)

Mode and number of proofs:

lower_upper(?char,?char) - zero_or_more

lower_upper(+char,?char) - zero_or_one

lower_upper(?char,+char) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

➡ See also

[character](#)

protocol

1.72.6 comparingp

Comparing protocol using overloading of standard operators.

Availability:

`logtalk_load(types(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2000-07-24

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- [Public predicates](#)
 - [\(<\)/2](#)
 - [\(=<\)/2](#)

- ($>$)/2
- ($>=$)/2
- ($=:=$)/2
- ($=\backslash=$)/2
- Protected predicates
- Private predicates
- Operators

Public predicates

($<$)/2

True if Term1 is less than Term2.

Compilation flags:

static

Template:

Term1<Term2

Mode and number of proofs:

+term< +term - zero_or_one

($=<$)/2

True if Term1 is less or equal than Term2.

Compilation flags:

static

Template:

Term1= $<$ Term2

Mode and number of proofs:

+term= $<$ +term - zero_or_one

(>)/2

True if Term1 is greater than Term2.

Compilation flags:

static

Template:

Term1>Term2

Mode and number of proofs:

+term> +term - zero_or_one

(>=)/2

True if Term1 is equal or grater than Term2.

Compilation flags:

static

Template:

Term1>=Term2

Mode and number of proofs:

+term>= +term - zero_or_one

(=:=)/2

True if Term1 is equal to Term2.

Compilation flags:

static

Template:

Term1=:=Term2

Mode and number of proofs:

+term=:= +term - zero_or_one

$(=\backslash=)/2$

True if Term1 is not equal to Term2.

Compilation flags:

static

Template:

Term1= \backslash =Term2

Mode and number of proofs:

+term= \backslash = +term - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

object

1.72.7 compound

Compound data type.

Availability:

logtalk_load(types(loader))

Author: Paulo Moura

Version: 1:3:0

Date: 2018-07-11

Compilation flags:

static, context_switching_calls

Extends:

public term

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (= <)/2 (= \=)/2 (>)/2 (>=)/2 check/1 depth/2 ground/1 new/1
 numbervars/1 numbervars/3 occurs/2 singletons/2 subsumes/2 subterm/2 valid/1 variables/2
 variant/2 varnumbers/2 varnumbers/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.72.8 difflist

Difference list predicates.

Availability:

logtalk_load(types(loader))

Author: Paulo Moura

Version: 2:0:0

Date: 2020-05-11

Compilation flags:

static, context_switching_calls

Implements:

public [listp](#)

Extends:

public [compound](#)

Uses:

[list](#)

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 append/2 append/3 check/1 delete/3 delete_matches/3 depth/2 drop/3 empty/1 flatten/2 ground/1 hamming_distance/3 keysort/2 last/2 length/2 max/2 member/2 memberchk/2 min/2 msort/2 msort/3 new/1 nextto/3 nth0/3 nth0/4 nth1/3 nth1/4 numbervars/1 numbervars/3 occurrences/2 occurrences/3 occurs/2 partition/5 permutation/2 prefix/2 prefix/3 proper_prefix/2 proper_prefix/3 proper_suffix/2 proper_suffix/3 remove_duplicates/2 reverse/2 same_length/2 same_length/3 select/3 select/4 selectchk/3 selectchk/4 sequential_occurrences/2 sequential_occurrences/3 singletons/2 sort/2 sort/3 sort/4 split/4 sublist/2 subsequence/3 subsequence/4 substitute/4 subsumes/2 subterm/2 subtract/3 suffix/2 suffix/3 take/3 valid/1 variables/2 variant/2 varnumbers/2 varnumbers/3

- Public predicates
 - add/3
 - as_list/2
- Protected predicates
- Private predicates
- Operators

Public predicates

`add/3`

Adds a term to the end of a difference list.

Compilation flags:

`static`

Template:

`add(Term,DiffList,NewDiffList)`

Mode and number of proofs:

`add(@term,+difference_list,-difference_list) - one`

`as_list/2`

Returns a list with the elements of the difference list.

Compilation flags:

`static`

Template:

`as_list(DiffList,List)`

Mode and number of proofs:

`as_list(@difference_list,-list) - one`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

➞ See also

list, list(Type), numberlist, varlist

object

1.72.9 float

Floating point numbers data type predicates.

Availability:

logtalk_load(types(loader))

Author: Paulo Moura

Version: 1:7:0

Date: 2025-02-25

Compilation flags:

static, context_switching_calls

Extends:

public number

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 =~= / 2 (>)/2 (>=)/2 approximately_equal/2
approximately_equal/3 check/1 depth/2 essentially_equal/3 ground/1 new/1 numbervars/1
numbervars/3 occurs/2 singletons/2 subsumes/2 subterm/2 tolerance_equal/4 valid/1
variables/2 variant/2 varnumbers/2 varnumbers/3

- Public predicates
 - between/4
 - sequence/4
 - sequence/5

- Protected predicates
- Private predicates
- Operators

Public predicates

`between/4`

Enumerates by backtracking a sequence of N equally spaced floats in the interval [Lower,Upper]. Assumes $N > 0$ and $\text{Lower} \leq \text{Upper}$; fails otherwise.

Compilation flags:

`static`

Template:

`between(Lower,Upper,N,Float)`

Mode and number of proofs:

`between(+float,+float,+positive_integer,-float) - zero_or_more`

`sequence/4`

Generates a list with the sequence of N equally spaced floats in the interval [Lower,Upper]. Assumes $N > 0$ and $\text{Lower} \leq \text{Upper}$; fails otherwise.

Compilation flags:

`static`

Template:

`sequence(Lower,Upper,N,List)`

Mode and number of proofs:

`sequence(+float,+float,+positive_integer,-list(float)) - zero_or_one`

`sequence/5`

Generates a list with the sequence of Step spaced floats in the interval [Lower,Upper]. Also returns the length of the list. Assumes Lower =< Upper; fails otherwise.

Compilation flags:

`static`

Template:

`sequence(Lower,Upper,Step,List,Length)`

Mode and number of proofs:

`sequence(+float,+float,+float,-list(float),-positive__integer) - zero__or__one`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.72.10 integer

Integer data type predicates.

Availability:

`logtalk_load(types(loader))`

Author: Paulo Moura

Version: 1:56:0

Date: 2025-05-26

Compilation flags:

`static, context_switching_calls`

Extends:

public number

Remarks:

- Portability notes: This object will use the backend Prolog system between/3, plus/3, and succ/2 built-in predicates when available.

Inherited public predicates:

(<)/2 (=:=)/2 (= <)/2 (= \=)/2 =~/2 (>)/2 (>=)/2 approximately_equal/2
 approximately_equal/3 check/1 depth/2 essentially_equal/3 ground/1 new/1 numbervars/1
 numbervars/3 occurs/2 singletons/2 subsumes/2 subterm/2 tolerance_equal/4 valid/1
 variables/2 variant/2 varnumbers/2 varnumbers/3

- Public predicates
 - between/3
 - plus/3
 - succ/2
 - sequence/3
 - sequence/4
 - power_sequence/4
- Protected predicates
- Private predicates
- Operators

Public predicates

between/3

Returns integers in the interval defined by the two first arguments.

Compilation flags:

static

Template:

between(Lower,Upper,Integer)

Mode and number of proofs:

between(+integer,+integer,+integer) - zero_or_one

between(+integer,+integer,-integer) - zero_or_more

plus/3

Reversible integer sum. At least two of the arguments must be instantiated to integers.

Compilation flags:
static

Template:

plus(I,J,Sum)

Mode and number of proofs:

plus(+integer,+integer,?integer) - zero_or_one

plus(+integer,?integer,+integer) - zero_or_one

plus(?integer,+integer,+integer) - zero_or_one

succ/2

Successor of a natural number. At least one of the arguments must be instantiated to a natural number.

Compilation flags:
static

Template:

succ(I,J)

Mode and number of proofs:

succ(+integer,?integer) - zero_or_one

succ(?integer,+integer) - zero_or_one

sequence/3

Generates a list with the sequence of all integers in the interval [Lower,Upper]. Assumes Lower =< Upper and fails otherwise.

Compilation flags:
static

Template:

sequence(Lower,Upper,List)

Mode and number of proofs:

sequence(+integer,+integer,-list(integer)) - zero_or_one

sequence/4

Generates a list with the sequence of integers in the interval [Lower,Upper] by Step. Assumes Lower =< Upper, Step >= 1 and fails otherwise.

Compilation flags:

static

Template:

sequence(Lower,Upper,Step,List)

Mode and number of proofs:

sequence(+integer,+integer,+integer,-list(integer)) - zero_or_one

power_sequence/4

Generates a list of exponentiation results given [Lower,Upper] sequence of exponents and Base. Assumes Lower =< Upper and Base > 1 and fails otherwise.

Compilation flags:

static

Template:

power_sequence(Lower,Upper,Base,List)

Mode and number of proofs:

power_sequence(+integer,+integer,+integer,-list(integer)) - zero_or_one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.72.11 list

List predicates.

Availability:

logtalk_load(types(loader))

Author: Paulo Moura

Version: 4:3:0

Date: 2024-05-24

Compilation flags:

static, context_switching_calls

Implements:

public `listp`

Extends:

public `compound`

Remarks:

- Portability notes: This object will use the backend Prolog system `msort/2` and `sort/4` built-in predicates when available.

Inherited public predicates:

`(<)/2` `(=:)/2` `(=<)/2` `(=\=)/2` `(>)/2` `(>=)/2` `append/2` `append/3` `check/1` `delete/3`
`delete_matches/3` `depth/2` `drop/3` `empty/1` `flatten/2` `ground/1` `hamming_distance/3` `keysort/2`
`last/2` `length/2` `max/2` `member/2` `memberchk/2` `min/2` `msort/2` `msort/3` `new/1` `nextto/3`
`nth0/3` `nth0/4` `nth1/3` `nth1/4` `numbervars/1` `numbervars/3` `occurrences/2` `occurrences/3`
`occurs/2` `partition/5` `permutation/2` `prefix/2` `prefix/3` `proper_prefix/2` `proper_prefix/3`

proper_suffix/2 proper_suffix/3 remove_duplicates/2 reverse/2 same_length/2 same_length/3
 select/3 select/4 selectchk/3 selectchk/4 sequential_occurrences/2 sequential_occurrences/3
 singletons/2 sort/2 sort/3 sort/4 split/4 sublist/2 subsequence/3 subsequence/4 substitute/4
 subsumes/2 subterm/2 subtract/3 suffix/2 suffix/3 take/3 valid/1 variables/2 variant/2
 varnumbers/2 varnumbers/3

- Public predicates
 - as_difflist/2
- Protected predicates
- Private predicates
- Operators

Public predicates

as_difflist/2

Converts a list to a difference list.

Compilation flags:

static

Template:

as_difflist(List,Diffist)

Mode and number of proofs:

as_difflist(+list,-difference_list) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

➡ See also

`list(Type)`, `numberlist`, `varlist`, `difflist`

object

1.72.12 `list(Type)`

List predicates with elements constrained to a single type.

Availability:

`logtalk_load(types(loader))`

Author: Paulo Moura

Version: 1:22:0

Date: 2018-07-11

Compilation flags:

`static`, `context_switching_calls`

Extends:

public `list`

Remarks:

(none)

Inherited public predicates:

`(<)/2` `(=:)/2` `(=<)/2` `(=)/2` `(>)/2` `(>=)/2` `append/2` `append/3` `as_difflist/2` `check/1`
`delete/3` `delete_matches/3` `depth/2` `drop/3` `empty/1` `flatten/2` `ground/1` `hamming_distance/3`
`keysort/2` `last/2` `length/2` `max/2` `member/2` `memberchk/2` `min/2` `msort/2` `msort/3` `new/1`
`nextto/3` `nth0/3` `nth0/4` `nth1/3` `nth1/4` `numbervars/1` `numbervars/3` `occurrences/2`
`occurrences/3` `occurs/2` `partition/5` `permutation/2` `prefix/2` `prefix/3` `proper_prefix/2`
`proper_prefix/3` `proper_suffix/2` `proper_suffix/3` `remove_duplicates/2` `reverse/2` `same_length/2`
`same_length/3` `select/3` `select/4` `selectchk/3` `selectchk/4` `sequential_occurrences/2`
`sequential_occurrences/3` `singletons/2` `sort/2` `sort/3` `sort/4` `split/4` `sublist/2` `subsequence/3`
`subsequence/4` `substitute/4` `subsumes/2` `subterm/2` `subtract/3` `suffix/2` `suffix/3` `take/3` `valid/1`
`variables/2` `variant/2` `varnumbers/2` `varnumbers/3`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates


(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

list, numberlist, varlist, difflist

protocol

1.72.13 listp

List protocol.

Availability:

logtalk_load(types(loader))

Author: Paulo Moura

Version: 1:18:0

Date: 2024-05-24

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - append/2
 - append/3
 - delete/3
 - delete_matches/3
 - empty/1
 - flatten/2
 - hamming_distance/3
 - keysort/2
 - last/2
 - length/2
 - max/2
 - member/2
 - memberchk/2
 - min/2
 - msort/2
 - msort/3
 - nextto/3
 - nth0/3
 - nth0/4
 - nth1/3
 - nth1/4
 - sequential_occurrences/2
 - sequential_occurrences/3
 - occurrences/2
 - occurrences/3

- partition/5
 - permutation/2
 - prefix/2
 - prefix/3
 - proper_prefix/2
 - proper_prefix/3
 - remove_duplicates/2
 - reverse/2
 - same_length/2
 - same_length/3
 - select/3
 - selectchk/3
 - select/4
 - selectchk/4
 - sort/2
 - sort/3
 - sort/4
 - split/4
 - sublist/2
 - subsequence/3
 - subsequence/4
 - substitute/4
 - subtract/3
 - suffix/2
 - suffix/3
 - proper_suffix/2
 - proper_suffix/3
 - take/3
 - drop/3
- Protected predicates
 - Private predicates
 - Operators

Public predicates

append/2

Appends all lists in a list of lists.

Compilation flags:

static

Template:

append(Lists,Concatenation)

Mode and number of proofs:

append(+list(list),?list) - zero_or_one

append/3

Appends two lists.

Compilation flags:

static

Template:

append(List1,List2,List)

Mode and number of proofs:

append(?list,?list,?list) - zero_or_more

delete/3

Deletes from a list all occurrences of an element returning the list of remaining elements. Uses ==/2 for element comparison.

Compilation flags:

static

Template:

delete(List,Element,Remaining)

Mode and number of proofs:

`delete(@list,@term,?list) - one`

`delete_matches/3`

Deletes all matching elements from a list, returning the list of remaining elements. Uses `=/2` for element comparison.

Compilation flags:

`static`

Template:

`delete_matches(List,Element,Remaining)`

Mode and number of proofs:

`delete_matches(@list,@term,?list) - one`

`empty/1`

True if the argument is an empty list.

Compilation flags:

`static`

Template:

`empty(List)`

Mode and number of proofs:

`empty(@list) - zero_or_one`

`flatten/2`

Flattens a list of lists into a list.

Compilation flags:

`static`

Template:

 flatten(List,Flatted)

Mode and number of proofs:

 flatten(+list,-list) - one

hamming_distance/3

Calculates the Hamming distance between two lists (using equality to compare list elements). Fails if the two lists are not of the same length.

Compilation flags:

 static

Template:

 hamming_distance(List1,List2,Distance)

Mode and number of proofs:

 hamming_distance(+list,+list,-integer) - zero_or_one

keysort/2

Sorts a list of key-value pairs in ascending order.

Compilation flags:

 static

Template:

 keysort(List,Sorted)

Mode and number of proofs:

 keysort(+list(pair),-list(pair)) - one

last/2

List last element (if it exists).

Compilation flags:

static

Template:

last(List,Last)

Mode and number of proofs:

last(?list,?term) - zero_or_more

length/2

List length.

Compilation flags:

static

Template:

length(List,Length)

Mode and number of proofs:

length(?list,?integer) - zero_or_more

max/2

Determines the list maximum value using standard order. Fails if the list is empty.

Compilation flags:

static

Template:

max(List,Maximum)

Mode and number of proofs:

max(+list,-term) - zero_or_one

member/2

Element is a list member.

Compilation flags:

static

Template:

member(Element,List)

Mode and number of proofs:

member(?term,?list) - zero_or_more

memberchk/2

Checks if a term is a member of a list.

Compilation flags:

static

Template:

memberchk(Element,List)

Mode and number of proofs:

memberchk(?term,?list) - zero_or_one

min/2

Determines the minimum value in a list using standard order. Fails if the list is empty.

Compilation flags:

static

Template:

min(List,Minimum)

Mode and number of proofs:

min(+list,-term) - zero_or_one

`msort/2`

Sorts a list in ascending order (duplicated elements are not removed).

Compilation flags:

`static`

Template:

`msort(List,Sorted)`

Mode and number of proofs:

`msort(+list,-list) - one`

`msort/3`

Sorts a list using a user-specified comparison predicate modeled on the standard `compare/3` predicate (duplicated elements are not removed).

Compilation flags:

`static`

Template:

`msort(Closure,List,Sorted)`

Meta-predicate template:

`msort(3,*,*)`

Mode and number of proofs:

`msort(+callable,+list,-list) - one`

`nextto/3`

X and Y are consecutive elements in List.

Compilation flags:

`static`

Template:

`nextto(X,Y,List)`

Mode and number of proofs:

`nextto(?term,?term,?list) - zero_or_more`

`nth0/3`

Nth element of a list (counting from zero).

Compilation flags:

`static`

Template:

`nth0(Nth,List,Element)`

Mode and number of proofs:

`nth0(?integer,?list,?term) - zero_or_more`

`nth0/4`

Nth element of a list (counting from zero). Rest is a list of all the other elements. Can be used to either select the nth element of List or to insert an element before the nth element in Rest.

Compilation flags:

`static`

Template:

`nth0(Nth,List,Element,Rest)`

Mode and number of proofs:

`nth0(?integer,?list,?term,?list) - zero_or_more`

`nth1/3`

Nth element of a list (counting from one).

Compilation flags:

`static`

Template:

`nth1(Nth,List,Element)`

Mode and number of proofs:

`nth1(?integer,?list,?term) - zero_or_more`

`nth1/4`

Nth element of a list (counting from one). Rest is a list of all the other elements. Can be used to either select the nth element of List or to insert an element before the nth element in Rest.

Compilation flags:

`static`

Template:

`nth1(Nth,List,Element,Rest)`

Mode and number of proofs:

`nth1(?integer,?list,?term,?list) - zero_or_more`

`sequential_occurrences/2`

Counts the number of sequential occurrences of each List element, unifying Occurrences with a list of Element-Count pairs. Uses term equality for element comparison.

Compilation flags:

`static`

Template:

`sequential_occurrences(List,Occurrences)`

Mode and number of proofs:

`sequential_occurrences(@list,-list(pair(term,positive_integer))) - one`

`sequential_occurrences/3`

Counts the number of sequential occurrences of each List element, unifying Occurrences with a list of Element-Count pairs. Uses Closure for element comparison.

Compilation flags:

`static`

Template:

`sequential_occurrences(List,Closure,Occurrences)`

Mode and number of proofs:

`sequential_occurrences(@list,@callable,-list(pair(term,positive_integer))) - one`

`occurrences/2`

Counts the number of occurrences of each List element, unifying Occurrences with a sorted list of Element-Count pairs. Uses term equality for element comparison.

Compilation flags:

`static`

Template:

`occurrences(List,Occurrences)`

Mode and number of proofs:

`occurrences(@list,-list(pair(term,positive_integer))) - one`

`occurrences/3`

Counts the number of occurrences of each List element, unifying Occurrences with a sorted list of Element-Count pairs. Uses Closure for element comparison.

Compilation flags:

`static`

Template:

`occurrences(List,Closure,Occurrences)`

Meta-predicate template:


```
occurrences(*,2,*)
```

Mode and number of proofs:

```
occurrences(@list,@callable,-list(pair(term,positive_integer))) - one
```

`partition/5`

Partitions a list in lists with values less, equal, and greater than a given value (using standard order).

Compilation flags:

```
static
```

Template:

```
partition(List,Value,Less,Equal,Greater)
```

Mode and number of proofs:

```
partition(+list,+number,-list,-list,-list) - one
```

`permutation/2`

The two lists are a permutation of the same list.

Compilation flags:

```
static
```

Template:

```
permutation(List,Permutation)
```

Mode and number of proofs:

```
permutation(?list,?list) - zero_or_more
```

`prefix/2`

Prefix is a prefix of List.

Compilation flags:

`static`

Template:

`prefix(Prefix,List)`

Mode and number of proofs:

`prefix(?list,+list) - zero_or_more`

`prefix/3`

Prefix is a prefix of length Length of List.

Compilation flags:

`static`

Template:

`prefix(Prefix,Length,List)`

Mode and number of proofs:

`prefix(?list,+integer,+list) - zero_or_one`

`prefix(?list,-integer,+list) - zero_or_more`

`proper_prefix/2`

Prefix is a proper prefix of List.

Compilation flags:

`static`

Template:

`proper_prefix(Prefix,List)`

Mode and number of proofs:

`proper_prefix(?list,+list) - zero_or_more`

`proper_prefix/3`

Prefix is a proper prefix of length Length of List.

Compilation flags:

`static`

Template:

`proper_prefix(Prefix,Length,List)`

Mode and number of proofs:

`proper_prefix(?list,+integer,+list) - zero_or_one`

`proper_prefix(?list,-integer,+list) - zero_or_more`

`remove_duplicates/2`

Removes duplicated list elements using equality (`==/2`) for comparison and keeping the left-most element when repeated.

Compilation flags:

`static`

Template:

`remove_duplicates(List,Set)`

Mode and number of proofs:

`remove_duplicates(+list,-list) - one`

`reverse/2`

Reverses a list.

Compilation flags:

`static`

Template:

```
reverse(List,Reversed)
```

Mode and number of proofs:

```
reverse(+list,?list) - zero_or_one
```

```
reverse(?list,+list) - zero_or_one
```

```
reverse(-list,-list) - one_or_more
```

same_length/2

The two lists have the same length.

Compilation flags:

```
static
```

Template:

```
same_length(List1,List2)
```

Mode and number of proofs:

```
same_length(+list,?list) - zero_or_one
```

```
same_length(?list,+list) - zero_or_one
```

```
same_length(-list,-list) - one_or_more
```

same_length/3

The two lists have the same length.

Compilation flags:

```
static
```

Template:

```
same_length(List1,List2,Length)
```

Mode and number of proofs:

```
same_length(+list,?list,?integer) - zero_or_one
```

```
same_length(?list,+list,?integer) - zero_or_one
```

```
same_length(-list,-list,-integer) - one_or_more
```

`select/3`

Selects an element from a list, returning the list of remaining elements.

Compilation flags:

`static`

Template:

`select(Element,List,Remaining)`

Mode and number of proofs:

`select(?term,?list,?list) - zero_or_more`

`selectchk/3`

Checks that an element can be selected from a list, returning the list of remaining elements.

Compilation flags:

`static`

Template:

`selectchk(Element,List,Remaining)`

Mode and number of proofs:

`selectchk(?term,?list,?list) - zero_or_one`

`select/4`

Selects an element from a list, replacing it by a new element and returning the resulting list.

Compilation flags:

`static`

Template:

`select(Old,OldList,New,NewList)`

Mode and number of proofs:

`select(?term,?list,?term,?list) - zero_or_more`

selectchk/4

Checks that an element from a list can be replaced by a new element, returning the resulting list.

Compilation flags:

static

Template:

selectchk(Old,OldList,New,NewList)

Mode and number of proofs:

selectchk(?term,?list,?term,?list) - zero_or_one

sort/2

Sorts a list in ascending order (duplicated elements are removed).

Compilation flags:

static

Template:

sort(List,Sorted)

Mode and number of proofs:

sort(+list,-list) - one

sort/3

Sorts a list using a user-specified comparison predicate modeled on the standard compare/3 predicate (duplicated elements are removed).

Compilation flags:

static

Template:

sort(Closure,List,Sorted)

Meta-predicate template:

sort(3,*,*)

Mode and number of proofs:

```
sort(+callable,+list,-list) - one
```

```
sort/4
```

Sorts a list using the given key and order. Uses the standard term comparison operators for the order. The key selects the argument in each element in the list to use for comparisons. A key value of zero uses the whole element for comparisons.

Compilation flags:

```
static
```

Template:

```
sort(Key,Order,List,Sorted)
```

Mode and number of proofs:

```
sort(+non_negative_integer,+atom,+list,-list) - one
```

Remarks:

- Removing duplicates: Use one of the @< or @> orders.
 - Keeping duplicates: Use one of the @=< or @>= orders.
 - Sorting in ascending order: Use one of the @< or @=< orders.
 - Sorting in descending order: Use one of the @> or @>= orders.
-

```
split/4
```

Splits a list into sublists of a given length. Also returns a list with the remaining elements. Fails if the length is zero or negative.

Compilation flags:

```
static
```

Template:

```
split(List,Length,Sublists,Remaining)
```

Mode and number of proofs:

```
split(+list,+integer,-list(list),-list) - zero_or_one
```

sublist/2

The first list is a sublist of the second.

Compilation flags:

static

Template:

sublist(Sublist,List)

Mode and number of proofs:

sublist(?list,+list) - zero_or_more

subsequence/3

List is an interleaving of Subsequence and Remaining. Element order is preserved.

Compilation flags:

static

Template:

subsequence(List,Subsequence,Remaining)

Mode and number of proofs:

subsequence(?list,?list,?list) - zero_or_more

subsequence/4

Generates subsequences of a given length from a list. Also returns the remaining elements. Element order is preserved.

Compilation flags:

static

Template:

subsequence(List,Length,Subsequence,Remaining)

Mode and number of proofs:

subsequence(+list,+integer,?list,?list) - zero_or_more

substitute/4

Substitutes all occurrences of Old in List by New, returning NewList. Uses term equality for element comparison.

Compilation flags:

static

Template:

substitute(Old,List,New,NewList)

Mode and number of proofs:

substitute(@term,@list,@term,-list) - one

subtract/3

Removes all elements in the second list from the first list, returning the list of remaining elements.

Compilation flags:

static

Template:

subtract(List,Elements,Remaining)

Mode and number of proofs:

subtract(+list,+list,-list) - one

suffix/2

Suffix is a suffix of List.

Compilation flags:

static

Template:

suffix(Suffix,List)

Mode and number of proofs:

suffix(?list,+list) - zero_or_more

suffix/3

Suffix is a suffix of length Length of List.

Compilation flags:

static

Template:

suffix(Suffix,Length,List)

Mode and number of proofs:

suffix(?list,+integer,+list) - zero_or_one

suffix(?list,-integer,+list) - zero_or_more

proper_suffix/2

Suffix is a proper suffix of List.

Compilation flags:

static

Template:

proper_suffix(Suffix,List)

Mode and number of proofs:

proper_suffix(?list,+list) - zero_or_more

`proper_suffix/3`

Suffix is a proper suffix of length Length of List.

Compilation flags:

`static`

Template:

`proper_suffix(Suffix,Length,List)`

Mode and number of proofs:

`proper_suffix(?list,+integer,+list) - zero_or_one`

`proper_suffix(?list,-integer,+list) - zero_or_more`

`take/3`

Takes the first N elements of a list. Fails if the list have fewer than N elements.

Compilation flags:

`static`

Template:

`take(N,List,Elements)`

Mode and number of proofs:

`take(+integer,+list,-list) - zero_or_one`

`drop/3`

Drops the first N elements of a list. Fails if the list have fewer than N elements.

Compilation flags:

`static`

Template:

`drop(N,List,Remaining)`

Mode and number of proofs:

`drop(+integer,+list,-list) - zero_or_one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

➡ See also

`list`, `list(Type)`, `numberlistp`, `varlistp`

object

1.72.14 `natural`

Natural numbers data type predicates.

Availability:

`logtalk_load(types(loader))`

Author: Paulo Moura

Version: 2:0:0

Date: 2025-01-16

Compilation flags:

`static`, `context_switching_calls`

Extends:

`public integer`

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 =~= / 2 (>)/2 (>=)/2 approximately_equal/2
 approximately_equal/3 between/3 check/1 depth/2 essentially_equal/3 ground/1 new/1
 numbervars/1 numbervars/3 occurs/2 plus/3 power_sequence/4 sequence/3 sequence/4
 singletons/2 subsumes/2 subterm/2 succ/2 tolerance_equal/4 valid/1 variables/2 variant/2
 varnumbers/2 varnumbers/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.72.15 number

Number data type predicates.

Availability:

logtalk_load(types(loader))

Author: Paulo Moura

Version: 1:14:0

Date: 2023-12-07

Compilation flags:

static, context_switching_calls

Extends:

public atomic

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 check/1 depth/2 ground/1 new/1
numbervars/1 numbervars/3 occurs/2 singletons/2 subsumes/2 subterm/2 valid/1 variables/2
variant/2 varnumbers/2 varnumbers/3

- Public predicates
 - approximately_equal/2
 - approximately_equal/3
 - essentially_equal/3
 - tolerance_equal/4
 - ==~ / 2
- Protected predicates
- Private predicates
- Operators
 - op(700,xfx,==~)

Public predicates

approximately_equal/2

Compares two numbers for approximate equality given the epsilon arithmetic constant value using the de facto standard formula $\text{abs}(\text{Number1} - \text{Number2}) \leq \max(\text{abs}(\text{Number1}), \text{abs}(\text{Number2})) * \text{epsilon}$. No type-checking.

Compilation flags:

static

Template:

approximately_equal(Number1,Number2)

Mode and number of proofs:

approximately_equal(+number,+number) - zero_or_one

`approximately_equal/3`

Compares two numbers for approximate equality given a user-defined epsilon value using the de facto standard formula $\text{abs}(\text{Number1} - \text{Number2}) \leq \max(\text{abs}(\text{Number1}), \text{abs}(\text{Number2})) * \text{Epsilon}$. No type-checking.

Compilation flags:

`static`

Template:

`approximately_equal(Number1,Number2,Epsilon)`

Mode and number of proofs:

`approximately_equal(+number,+number,+number) - zero_or_one`

Remarks:

- Epsilon range: Epsilon should be the epsilon arithmetic constant value or a small multiple of it. Only use a larger value if a greater error is expected.
- Comparison with essential equality: For the same epsilon value, approximate equality is weaker requirement than essential equality.

`essentially_equal/3`

Compares two numbers for essential equality given an epsilon value using the de facto standard formula $\text{abs}(\text{Number1} - \text{Number2}) \leq \min(\text{abs}(\text{Number1}), \text{abs}(\text{Number2})) * \text{Epsilon}$. No type-checking.

Compilation flags:

`static`

Template:

`essentially_equal(Number1,Number2,Epsilon)`

Mode and number of proofs:

`essentially_equal(+number,+number,+number) - zero_or_one`

Remarks:

- Comparison with approximate equality: For the same epsilon value, essential equality is a stronger requirement than approximate equality.

tolerance_equal/4

Compares two numbers for close equality given relative and absolute tolerances using the de facto standard formula $\text{abs}(\text{Number1} - \text{Number2}) \leq \max(\text{RelativeTolerance} * \max(\text{abs}(\text{Number1}), \text{abs}(\text{Number2})), \text{AbsoluteTolerance})$. No type-checking.

Compilation flags:

static

Template:

tolerance_equal(Number1,Number2,RelativeTolerance,AbsoluteTolerance)

Mode and number of proofs:

tolerance_equal(+number,+number,+number,+number) - zero_or_one

=~/2

Compares two floats (or lists of floats) for approximate equality using 100*epsilon for the absolute error and, if that fails, 99.999% accuracy for the relative error. Note that these precision values may not be adequate for all cases. No type-checking.

Compilation flags:

static

Template:

=~/2(Float1,Float2)

Mode and number of proofs:

=~/2(+number,+number) - zero_or_one

=~/2(+list(number),+list(number)) - zero_or_one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

op(700,xfx,=~=)

Scope:

public

object

1.72.16 numberlist

List of numbers predicates.

Availability:

logtalk_load(types(loader))

Author: Paulo Moura

Version: 1:16:0

Date: 2025-03-13

Compilation flags:

static, context_switching_calls

Implements:

public numberlistp

Extends:

public list

Uses:

list

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 append/2 append/3 as_difflist/2 average/2
chebyshev_distance/3 chebyshev_norm/2 check/1 delete/3 delete_matches/3 depth/2 drop/3
empty/1 euclidean_distance/3 euclidean_norm/2 flatten/2 ground/1 hamming_distance/3
keysort/2 last/2 least_common_multiple/2 length/2 manhattan_distance/3 manhattan_norm/2
max/2 median/2 member/2 memberchk/2 min/2 min_max/3 modes/2 msort/2 msort/3

new/1 nextto/3 normalize_range/2 normalize_range/4 normalize_scalar/2 normalize_unit/2
nth0/3 nth0/4 nth1/3 nth1/4 numbervars/1 numbervars/3 occurrences/2 occurrences/3
occurs/2 partition/5 permutation/2 prefix/2 prefix/3 product/2 proper_prefix/2
proper_prefix/3 proper_suffix/2 proper_suffix/3 remove_duplicates/2 rescale/3 reverse/2
same_length/2 same_length/3 scalar_product/3 select/3 select/4 selectchk/3 selectchk/4
sequential_occurrences/2 sequential_occurrences/3 singletons/2 softmax/2 softmax/3 sort/2
sort/3 sort/4 split/4 sublist/2 subsequence/3 subsequence/4 substitute/4 subsumes/2
subterm/2 subtract/3 suffix/2 suffix/3 sum/2 take/3 valid/1 variables/2 variant/2
varnumbers/2 varnumbers/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

➡ See also

list, list(Type), varlist, difflist

protocol

1.72.17 numberlistp

List of numbers protocol.

Availability:

`logtalk_load(types(loader))`

Author: Paulo Moura

Version: 1:10:0

Date: 2025-03-13

Compilation flags:

`static`

Dependencies:

`(none)`

Remarks:

`(none)`

Inherited public predicates:

`(none)`

- Public predicates
 - `min/2`
 - `max/2`
 - `min_max/3`
 - `product/2`
 - `sum/2`
 - `average/2`
 - `median/2`
 - `modes/2`
 - `euclidean_norm/2`
 - `chebyshev_norm/2`
 - `manhattan_norm/2`
 - `euclidean_distance/3`
 - `chebyshev_distance/3`

- manhattan_distance/3
- scalar_product/3
- normalize_range/2
- normalize_range/4
- normalize_unit/2
- normalize_scalar/2
- rescale/3
- least_common_multiple/2
- softmax/2
- softmax/3
- Protected predicates
- Private predicates
- Operators

Public predicates

min/2

Determines the minimum value in a list using arithmetic order. Fails if the list is empty.

Compilation flags:

static

Template:

min(List,Minimum)

Mode and number of proofs:

min(+list(number),-number) - zero_or_one

max/2

Determines the list maximum value using arithmetic order. Fails if the list is empty.

Compilation flags:

static

Template:

```
max(List,Maximum)
```

Mode and number of proofs:

```
max(+list(number),-number) - zero_or_one
```

[min_max/3](#)

Determines the minimum and maximum values in a list using arithmetic order. Fails if the list is empty.

Compilation flags:

```
static
```

Template:

```
min_max(List,Minimum,Maximum)
```

Mode and number of proofs:

```
min_max(+list(number),-number,-number) - zero_or_one
```

[product/2](#)

Calculates the product of all list numbers. Fails if the list is empty.

Compilation flags:

```
static
```

Template:

```
product(List,Product)
```

Mode and number of proofs:

```
product(+list(number),-number) - zero_or_one
```

`sum/2`

Calculates the sum of all list numbers. Returns the integer zero if the list is empty.

Compilation flags:

`static`

Template:

`sum(List,Sum)`

Mode and number of proofs:

`sum(+list(number),-number) - one`

`average/2`

Calculates the average (i.e., arithmetic mean) of a list of numbers. Fails if the list is empty.

Compilation flags:

`static`

Template:

`average(List,Average)`

Mode and number of proofs:

`average(+list(number),-float) - zero_or_one`

`median/2`

Calculates the median of a list of numbers. Fails if the list is empty.

Compilation flags:

`static`

Template:

`median(List,Median)`

Mode and number of proofs:

`median(+list(number),-float) - zero_or_one`

`modes/2`

Returns the list of modes of a list of numbers in ascending order. Fails if the list is empty.

Compilation flags:

`static`

Template:

`modes(List,Modes)`

Mode and number of proofs:

`modes(+list(number),-list(number)) - zero_or_one`

`euclidean_norm/2`

Calculates the Euclidean norm of a list of numbers. Fails if the list is empty.

Compilation flags:

`static`

Template:

`euclidean_norm(List,Norm)`

Mode and number of proofs:

`euclidean_norm(+list(number),-float) - zero_or_one`

`chebyshev_norm/2`

Calculates the Chebyshev norm of a list of numbers. Fails if the list is empty.

Compilation flags:

`static`

Template:

`chebyshev_norm(List,Norm)`

Mode and number of proofs:

`chebyshev_norm(+list(integer),-integer) - zero_or_one`

`chebyshev_norm(+list(float),-float) - zero_or_one`

`manhattan_norm/2`

Calculates the Manhattan norm of a list of numbers. Fails if the list is empty.

Compilation flags:

`static`

Template:

`manhattan_norm(List, Norm)`

Mode and number of proofs:

`manhattan_norm(+list(integer), -integer) - zero_or_one`

`manhattan_norm(+list(float), -float) - zero_or_one`

`euclidean_distance/3`

Calculates the Euclidean distance between two lists of numbers. Fails if the two lists are empty or not of the same length.

Compilation flags:

`static`

Template:

`euclidean_distance(List1, List2, Distance)`

Mode and number of proofs:

`euclidean_distance(+list(number), +list(number), -float) - zero_or_one`

`chebyshev_distance/3`

Calculates the Chebyshev distance between two lists of numbers. Fails if the two lists are empty or not of the same length.

Compilation flags:

`static`

Template:

```
chebyshev_distance(List1,List2,Distance)
```

Mode and number of proofs:

```
chebyshev_distance(+list(integer),+list(integer),-integer) - zero_or_one
```

```
chebyshev_distance(+list(float),+list(float),-float) - zero_or_one
```

`manhattan_distance/3`

Calculates the Manhattan distance between two lists of numbers. Fails if the two lists are empty or not of the same length.

Compilation flags:

```
static
```

Template:

```
manhattan_distance(List1,List2,Distance)
```

Mode and number of proofs:

```
manhattan_distance(+list(integer),+list(integer),-integer) - zero_or_one
```

```
manhattan_distance(+list(float),+list(float),-float) - zero_or_one
```

`scalar_product/3`

Calculates the scalar product of two lists of numbers. Fails if the two lists are empty or not of the same length.

Compilation flags:

```
static
```

Template:

```
scalar_product(List1,List2,Product)
```

Mode and number of proofs:

```
scalar_product(+list(integer),+list(integer),-integer) - zero_or_one
```

```
scalar_product(+list(float),+list(float),-float) - zero_or_one
```

`normalize_range/2`

Normalizes a list of numbers into the $[0.0,1.0]$ range. Caller must handle arithmetic exceptions if the input list is not normalizable.

Compilation flags:

`static`

Template:

`normalize_range(List,NormalizedList)`

Mode and number of proofs:

`normalize_range(+list(number),-list(float)) - one`

`normalize_range/4`

Normalizes a list of numbers into the given range. Caller must handle arithmetic exceptions if the input list is not normalizable.

Compilation flags:

`static`

Template:

`normalize_range(List,Minimum,Maximum,NormalizedList)`

Mode and number of proofs:

`normalize_range(+list(number),+number,+number,-list(float)) - one`

`normalize_unit/2`

Normalizes a list of numbers returning its unit vector (i.e., a list with Euclidean norm equal to one). Caller must handle arithmetic exceptions if the input list is not normalizable.

Compilation flags:

`static`

Template:

`normalize_unit(List,NormalizedList)`

Mode and number of proofs:

```
normalize__unit(+list(number),-list(float)) - one
```

```
normalize__scalar/2
```

Normalizes a list of numbers such that the sum of all numbers is equal to one. Caller must handle arithmetic exceptions if the input list is not normalizable.

Compilation flags:

```
static
```

Template:

```
normalize__scalar(List,NormalizedList)
```

Mode and number of proofs:

```
normalize__scalar(+list(number),-list(float)) - one
```

```
rescale/3
```

Rescales all numbers in a list by the given factor.

Compilation flags:

```
static
```

Template:

```
rescale(List,Factor,RescaledList)
```

Mode and number of proofs:

```
rescale(+list(integer),+integer,-list(integer)) - one
```

```
rescale(+list(number),+float,-list(float)) - one
```

`least_common_multiple/2`

Computes the least common multiple of a list of two or more positive integers. Fails if the list is empty or contains a single element. Fails also if any of the elements is zero. May require backend support for unbound integer arithmetic.

Compilation flags:

`static`

Template:

`least_common_multiple(Integers,LeastCommonMultiple)`

Mode and number of proofs:

`least_common_multiple(+list(positive_integer),-positive_integer) - zero_or_one`

`softmax/2`

Computes the softmax of a list of floats, returning a probability distribution.

Compilation flags:

`static`

Template:

`softmax(Floats,Softmax)`

Mode and number of proofs:

`softmax(+list(float),-list(float)) - one`

`softmax/3`

Computes the softmax of a list of floats with the given temperature, returning a probability distribution.

Compilation flags:

`static`

Template:

`softmax(Floats,Temperature,Softmax)`

Mode and number of proofs:

`softmax(+list(float),+positive_float,-list(float)) - one`

Remarks:

- Temperature > 1.0: Makes the distribution more uniform.
- Temperature < 1.0: Makes the distribution more concentrated on the largest values.
- Temperature = 1.0: Standard softmax behavior.

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

 See also

numberlist, listp, varlistp

object

1.72.18 pairs

Useful predicates over lists of pairs (key-value terms).

Availability:

logtalk_load(types(loader))

Author: Paulo Moura

Version: 2:1:1

Date: 2023-11-21

Compilation flags:

static, context_switching_calls

Dependencies:

(none)

Remarks:

- Usage: This object can be loaded independently of other entities in the types library by using the goal `logtalk_load(types(pairs))`.

Inherited public predicates:

(none)

- Public predicates
 - `keys_values/3`
 - `keys/2`
 - `key/2`
 - `values/2`
 - `value/3`
 - `transpose/2`
 - `group_sorted_by_key/2`
 - `group_consecutive_by_key/2`
 - `group_by_key/2`
 - `map/3`
- Protected predicates
- Private predicates
- Operators

Public predicates

`keys_values/3`

Converts between a list of pairs and lists of keys and values. When converting to pairs, this predicate fails if the list of keys and the list of values have different lengths.

Compilation flags:

`static`

Template:

`keys_values(Pairs,Keys,Values)`

Mode and number of proofs:

`keys_values(+list(pair),-list,-list)` - one

`keys_values(-list(pair),+list,+list)` - zero_or_one

[keys/2](#)

Returns a list of keys from a list of pairs.

Compilation flags:

static

Template:

keys(Pairs,Keys)

Mode and number of proofs:

keys(+list(pair),-list) - one

[key/2](#)

Enumerates by backtracking all keys from a list of pairs.

Compilation flags:

static

Template:

key(Pairs,Key)

Mode and number of proofs:

key(+list(pair),-term) - zero_or_more

[values/2](#)

Returns a list of values from a list of pairs.

Compilation flags:

static

Template:

values(Pairs,Values)

Mode and number of proofs:

values(+list(pair),-list) - one

value/3

Returns a value addressed by the given path (a key or a list of keys in the case of nested list of pairs). Fails if path does not exist.

Compilation flags:

static

Template:

value(Pairs,Path,Value)

Mode and number of proofs:

value(+list(pair),+term,-term) - zero_or_one

value(+list(pair),+list,-term) - zero_or_one

transpose/2

Transposes a list of pairs by swapping each pair key and value. The relative order of the list elements is kept.

Compilation flags:

static

Template:

transpose(Pairs,TransposedPairs)

Mode and number of proofs:

transpose(+list(pair),-list(pair)) - one

`group_sorted_by_key/2`

Groups pairs by key by sorting them and then constructing new pairs by grouping all values for a given key in a list. Keys are compared using equality. Relative order of values per key is kept. Resulting list of pairs is sorted by key.

Compilation flags:

static

Template:

`group_sorted_by_key(Pairs,Groups)`

Mode and number of proofs:

`group_sorted_by_key(+list(pair),-list(pair)) - one`

`group_consecutive_by_key/2`

Groups pairs by constructing new pairs by grouping all values for consecutive key in a list. Keys are compared using equality. The relative order of the values for the same key is kept.

Compilation flags:

static

Template:

`group_consecutive_by_key(Pairs,Groups)`

Mode and number of proofs:

`group_consecutive_by_key(+list(pair),-list(pair)) - one`

`group_by_key/2`

Same as the `group_sorted_by_key/2` predicate. Deprecated.

Compilation flags:

static

Template:

`group_by_key(Pairs,Groups)`

Mode and number of proofs:

```
group_by_key(+list(pair),-list(pair)) - one
```

map/3

Maps a list into pairs using a closure that applies to each list element to compute its key.

Compilation flags:

```
static
```

Template:

```
map(Closure,List,Pairs)
```

Meta-predicate template:

```
map(2,*,*)
```

Mode and number of proofs:

```
map(@callable,+list,-list(pair)) - one
```

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

object

1.72.19 term

Term utility predicates.

Availability:

```
logtalk_load(types(loader))
```

Author: Paulo Moura

Version: 1:11:0
Date: 2022-05-13

Compilation flags:
static, context_switching_calls

Implements:
public `term`

Aliases:
term variables/2 as vars/2

Remarks:
(none)

Inherited public predicates:
(<)/2 (=:=)/2 (=<)/2 (=\\=)/2 (>)/2 (>=)/2 check/1 depth/2 ground/1 new/1
numbervars/1 numbervars/3 occurs/2 singletons/2 subsumes/2 subterm/2 valid/1 variables/2
variant/2 varnumbers/2 varnumbers/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.72.20 term_p

Term utility predicates protocol.

Availability:

`logtalk_load(types(loader))`

Author: Paulo Moura

Version: 1:35:0

Date: 2022-05-13

Compilation flags:

`static`

Extends:

`public comparingp`

Remarks:

(none)

Inherited public predicates:

`(<)/2` `(=:=)/2` `(=<)/2` `(=\=)/2` `(>)/2` `(>=)/2`

- Public predicates
 - `depth/2`
 - `ground/1`
 - `new/1`
 - `occurs/2`
 - `subsumes/2`

- subterm/2
- valid/1
- check/1
- variant/2
- variables/2
- singletons/2
- numbervars/3
- numbervars/1
- varnumbers/3
- varnumbers/2
- Protected predicates
- Private predicates
- Operators

Public predicates

depth/2

True if the depth of Term is Depth. The depth of atomic terms is zero; the depth of a compound term is one plus the maximum depth of its sub-terms.

Compilation flags:

static

Template:

depth(Term,Depth)

Mode and number of proofs:

depth(@term,?integer) - zero_or_one

ground/1

True if the argument is ground. Deprecated. Use the ground/1 standard predicate instead.

Compilation flags:

static

Template:

ground(Term)

Mode and number of proofs:

ground(@term) - zero_or_one

new/1

Creates a new term instance (if meaningful).

Compilation flags:

static

Template:

new(Term)

Mode and number of proofs:

new(-nonvar) - zero_or_one

occurs/2

True if the variable occurs in the term.

Compilation flags:

static

Template:

occurs(Variable,Term)

Mode and number of proofs:

occurs(@var,@term) - zero_or_one

subsumes/2

The first term subsumes the second term. Deprecated. Use the subsumes_term/2 standard predicate instead.

Compilation flags:

static

Template:

subsumes(General,Specific)

Mode and number of proofs:

subsumes(@term,@term) - zero_or_one

subterm/2

The first term is a subterm of the second term.

Compilation flags:

static

Template:

subterm(Subterm,Term)

Mode and number of proofs:

subterm(?term,+term) - zero_or_more

valid/1

Term is valid.

Compilation flags:

static

Template:

valid(Term)

Mode and number of proofs:

valid(@nonvar) - zero_or_one

check/1

Checks if a term is valid. Throws an exception if the term is not valid.

Compilation flags:

static

Template:

check(Term)

Mode and number of proofs:

check(@nonvar) - one

variant/2

Each term is a variant of the other (i.e., they are structurally equivalent).

Compilation flags:

static

Template:

variant(Term1,Term2)

Mode and number of proofs:

variant(@term,@term) - zero_or_one

variables/2

Returns a list of all term variables (ordered as found when doing a depth-first, left-to-right traversal of Term). Deprecated. Use the standard term_variables/2 predicate instead.

Compilation flags:

static

Template:

variables(Term,List)

Mode and number of proofs:

variables(@term,-list) - one

singletons/2

Returns a list of all term singleton variables (ordered as found when doing a depth-first, left-to-right traversal of Term).

Compilation flags:

static

Template:

singletons(Term,Singletons)

Mode and number of proofs:

singletons(@term,-list) - one

numbervars/3

Grounds a term by replacing all variables with '\$VAR'(N) terms with N starting at From. The Next argument is unified with the next value for N after binding all variables.

Compilation flags:

static

Template:

numbervars(Term,From,Next)

Mode and number of proofs:

numbervars(?term,+integer,?integer) - zero_or_one

numbervars/1

Grounds a term by replacing all variables with '\$VAR'(N) terms with N starting at 0.

Compilation flags:

static

Template:

numbervars(Term)

Mode and number of proofs:

numbervars(?term) - zero_or_one

varnumbers/3

Replaces all '\$VAR'(N) sub-terms in a term with fresh variables for all values of N grater or equal to From. Variables in Term are shared with Copy.

Compilation flags:

static

Template:

varnumbers(Term,From,Copy)

Mode and number of proofs:

varnumbers(@term,+integer,?term) - zero_or_one

varnumbers/2

Replaces all '\$VAR'(N) sub-terms in a term with fresh variables for all values of N grater or equal to 0. Variables in Term are shared with Copy.

Compilation flags:

static

Template:

varnumbers(Term,Copy)

Mode and number of proofs:

varnumbers(@term,?term) - zero_or_one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

[term](#)

object

1.72.21 type

Type checking predicates. User extensible. New types can be defined by adding clauses for the type/1 and check/2 multifile predicates.

Availability:

```
logtalk_load(types(loader))
```

Author: Paulo Moura

Version: 2:5:1

Date: 2024-09-26

Compilation flags:

```
static, context_switching_calls, complements(restrict)
```

Uses:

[list](#)

Remarks:

- Logtalk specific types: entity, object, protocol, category, entity__identifier, object__identifier, protocol__identifier, category__identifier, event, predicate.
- Prolog module related types (when the backend compiler supports modules): module, module__identifier, qualified_callable.
- Prolog base types: term, var, nonvar, atomic, atom, number, integer, float, compound, callable, ground.

- Atom derived types: `non_quoted_atom`, `non_empty_atom`, `boolean`, `character`, `in_character`, `char`, `operator_specifier`, `hex_char`.
- Atom derived parametric types: `atom(CharSet)`, `atom(CharSet,Length)`, `non_empty_atom(CharSet)`, `character(CharSet)`, `in_character(CharSet)`, `char(CharSet)`.
- Number derived types: `positive_number`, `negative_number`, `non_positive_number`, `non_negative_number`.
- Float derived types: `positive_float`, `negative_float`, `non_positive_float`, `non_negative_float`, `probability`.
- Integer derived types: `positive_integer`, `negative_integer`, `non_positive_integer`, `non_negative_integer`, `byte`, `in_byte`, `character_code`, `in_character_code`, `code`, `operator_priority`, `hex_code`.
- Integer derived parametric types: `character_code(CharSet)`, `in_character_code(CharSet)`, `code(CharSet)`.
- List types (compound derived types): `list`, `non_empty_list`, `partial_list`, `list_or_partial_list`, `list(Type)`, `list(Type,Length)`, `list(Type,Min,Max)`, `list(Type,Length,Min,Max)`, `non_empty_list(Type)`, `codes`, `chars`.
- Difference list types (compound derived types): `difference_list`, `difference_list(Type)`.
- Other compound derived types: `compound(Name,Types)`, `predicate_indicator`, `non_terminal_indicator`, `predicate_or_non_terminal_indicator`, `clause`, `grammar_rule`, `pair`, `pair(KeyType,ValueType)`, `cyclic`, `acyclic`.
- Stream types: `stream`, `stream_or_alias`, `stream(Property)`, `stream_or_alias(Property)`.
- Other types: `Object::Closure`, `between(Type,Lower,Upper)`, `property(Type,LambdaExpression)`, `one_of(Type,Set)`, `var_or(Type)`, `ground(Type)`, `types(Types)`, `constrain(Type,Closure)`, `type`.
- Type predicate notes: This type is used to check for an object public predicate specified as `Object::Functor/Arity`.
- Type boolean notes: The two value of this type are the atoms `true` and `false`.
- Stream types notes: In the case of the `stream(Property)` and `stream_or_alias(Property)` types, `Property` must be a valid stream property.
- Type order notes: The three possible values of this type are the single character atoms `<`, `=`, and `>`.
- Type `character_code` notes: This type takes into account Unicode support by the backend compiler. When Unicode is supported, it distinguishes between BMP and full support. When Unicode is not supported, it assumes a byte representation for characters.
- Type `Object::Closure` notes: Allows calling a public object predicate for type-checking. The predicate should provide valid/2 predicate semantics and assume called with a bound argument. The Closure closure is extended with a single argument, the value to be checked.
- Type `compound(Name,Types)` notes: This type verifies that a compound term have the given `Name` and its arguments conform to `Types`.
- Type `between(Type, Lower, Upper)` notes: The type argument allows distinguishing between numbers and other types. It also allows choosing between mixed integer/float comparisons and strict float or integer comparisons. The term is type-checked before testing for interval membership.
- Type `property(Type, Lambda)` notes: Verifies that `Term` satisfies a property described using a lambda expression of the form `[Parameter]>>Goal`. The lambda expression is applied in the context of `user`. The term is type-checked before calling the goal.

- `one_of(Type, Set)` notes: For checking if a given term is an element of a set. The set is represented using a list. The term is type-checked before testing for set membership.
- `var_or(Type)` notes: Allows checking if a term is either a variable or a valid value of the given type.
- `ground(Type)` notes: Allows checking if a term is ground and a valid value of the given type.
- `types(Types)` notes: Allows checking if a term is a valid value for one of the types in a list of types.
- `constrain(Type, Closure)` notes: Allows checking if a term is a valid value for the given type and satisfies the given closure.
- `type` notes: Allows checking if a term is a valid type.
- `qualified_callable` notes: Allows checking if a term is a possibly module-qualified callable term. When the term is qualified, it also checks that the qualification modules are type correct. When the term is not qualified, its semantics are the same as the callable type.
- Design choices: The main predicates are `valid/2` and `check/3`. These are defined using the predicate `check/2`. Defining clauses for `check/2` instead of `valid/2` gives the user full control of exception terms without requiring an additional predicate.
- Error context: The built-in execution-context method `context/1` can be used to provide the calling context for errors when using the predicate `check/3`.
- Registering new types: New types can be registered by defining clauses for the `type/1` and `check/2` multifile predicates. Clauses for both predicates must have a bound first argument to avoid introducing spurious choice-points when type-checking terms.
- Meta-types: Meta-types are types that have one or more sub-type arguments. E.g. `var_or(Type)`. The sub-types of a meta-type can be enumerated by defining a clause for the `meta_type/3` multifile predicate.
- Character sets: When testing character or character code based terms (e.g., `atom`), it is possible to choose a character set (`ascii_identifier`, `ascii_printable`, `ascii_full`, `byte`, `unicode_bmp`, or `unicode_full`) using the parameterizable types.
- Caveats: The type argument (and any type parameterization) to the predicates is not type-checked (or checked for consistency) for performance reasons.
- Unicode limitations: Currently, correct character/code type-checking is only ensured for XVM and SWI-Prolog as other backends do not provide support for querying a Unicode code point category.

Inherited public predicates:

```
arbitrary/1 arbitrary/2 edge_case/2 get_seed/1 max_size/1 mutation/3 set_seed/1 shrink/3
shrink_sequence/3 shrinker/1
```

- Public predicates
 - `type/1`
 - `meta_type/3`
 - `valid/2`
 - `check/3`

- check/2
- Protected predicates
- Private predicates
- Operators

Public predicates

type/1

Table of defined types. A new type can be registered by defining a clause for this predicate and adding a clause for the check/2 multifile predicate.

Compilation flags:
static, multifile

Template:
type(Type)
Mode and number of proofs:
type(?callable) - zero_or_more

meta_type/3

Table of defined meta-types. A registered type that is a meta-type can be described by defining a clause for this predicate to enumerate its sub-types and optional values in case of a single sub-type.

Compilation flags:
static, multifile

Template:
meta_type(MetaType,SubTypes,Values)
Mode and number of proofs:
meta_type(?callable,-list,-list) - zero_or_more

`valid/2`

True if the given term is of the specified type. Fails otherwise.

Compilation flags:

`static`

Template:

`valid(Type,Term)`

Mode and number of proofs:

`valid(@callable,@term) - zero_or_one`

`check/3`

True if the given term is of the specified type. Throws an error otherwise using the format `error(Error, Context)`. For the possible values of `Error` see the `check/2` predicate.

Compilation flags:

`static`

Template:

`check(Type,Term,Context)`

Mode and number of proofs:

`check(@callable,@term,@term) - one_or_error`

`check/2`

True if the given term is of the specified type. Throws an error otherwise. A new type can be added by defining a clause for this predicate and registering it by adding a clause for the `type/1` multifile predicate.

Compilation flags:

`static, multifile`

Template:

`check(Type,Term)`

Meta-predicate template:

`check(:,*)`

Mode and number of proofs:

`check(@callable,@term) - one_or_error`

Exceptions:

Term is not bound as required:

`instantiation_error`

Term is bound but not of the specified type:

`type_error(Type,Term)`

Term is the of the correct type but not in the specified domain:

`domain_error(Domain,Term)`

Term is the of the correct type and domain but the resource it represents does not exist:

`existence_error(Type,Term)`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

`arbitrary`, `os_types`, `either`, `maybe`

object

1.72.22 varlist

List of variables predicates.

Availability:

`logtalk_load(types(loader))`

Author: Paulo Moura

Version: 2:0:0

Date: 2020-05-11

Compilation flags:

static, context_switching_calls

Implements:

public varlistp

Remarks:

(none)

Inherited public predicates:

append/3 check/1 delete/3 empty/1 flatten/2 last/2 length/2 memberchk/2 nextto/3 nth0/3
nth0/4 nth1/3 nth1/4 permutation/2 prefix/2 remove_duplicates/2 reverse/2 same_length/2
select/3 sublist/2 subtract/3 suffix/2 valid/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

➡ See also

list, list(Type), numberlist, difflist

protocol

1.72.23 varlistp

List of variables protocol.

Availability:

`logtalk_load(types(loader))`

Author: Paulo Moura

Version: 1:3:0

Date: 2022-09-19

Compilation flags:

`static`

Dependencies:

`(none)`

Remarks:

`(none)`

Inherited public predicates:

`(none)`

- Public predicates
 - `append/3`
 - `delete/3`
 - `empty/1`
 - `flatten/2`
 - `last/2`
 - `length/2`
 - `memberchk/2`
 - `nextto/3`
 - `nth0/3`
 - `nth0/4`
 - `nth1/3`
 - `nth1/4`
 - `permutation/2`

- prefix/2
- remove_duplicates/2
- reverse/2
- same_length/2
- select/3
- sublist/2
- subtract/3
- suffix/2
- valid/1
- check/1
- Protected predicates
- Private predicates
- Operators

Public predicates

append/3

Appends two lists.

Compilation flags:

static

Template:

append(List1,List2,List)

Mode and number of proofs:

append(?list,?list,?list) - zero_or_more

delete/3

Deletes from a list all occurrences of an element returning the list of remaining elements.

Compilation flags:

static

Template:

`delete(List,Element,Remaining)`

Mode and number of proofs:

`delete(@list,@term,?list)` - one

`empty/1`

True if the argument is an empty list.

Compilation flags:

`static`

Template:

`empty(List)`

Mode and number of proofs:

`empty(@list)` - zero_or_one

`flatten/2`

Flattens a list of lists into a list.

Compilation flags:

`static`

Template:

`flatten(List,Flatted)`

Mode and number of proofs:

`flatten(@list,-list)` - one

`last/2`

List last element (if it exists).

Compilation flags:

`static`

Template:

`last(List,Last)`

Mode and number of proofs:

`last(@list,@var) - zero_or_one`

`length/2`

List length.

Compilation flags:

`static`

Template:

`length(List,Length)`

Mode and number of proofs:

`length(@list,?integer) - zero_or_one`

`memberchk/2`

Checks if a variable is a member of a list.

Compilation flags:

`static`

Template:

`memberchk(Element,List)`

Mode and number of proofs:

`memberchk(@var,@list) - zero_or_one`

`nextto/3`

X and Y are consecutive elements in List.

Compilation flags:

`static`

Template:

`nextto(X,Y,List)`

Mode and number of proofs:

`nextto(@var,@var,?list) - zero_or_more`

`nth0/3`

Nth element of a list (counting from zero).

Compilation flags:

`static`

Template:

`nth0(Nth,List,Element)`

Mode and number of proofs:

`nth0(?integer,+list,@var) - zero_or_more`

`nth0/4`

Nth element of a list (counting from zero). Rest is a list of all the other elements. Can be used to either select the nth element of List or to insert an element before the nth element in Rest.

Compilation flags:

`static`

Template:

`nth0(Nth,List,Element,Rest)`

Mode and number of proofs:

`nth0(?integer,+list,@var,?list) - zero_or_more`

`nth1/3`

Nth element of a list (counting from one).

Compilation flags:

`static`

Template:

`nth1(Nth,List,Element)`

Mode and number of proofs:

`nth1(?integer,+list,@var) - zero_or_more`

`nth1/4`

Nth element of a list (counting from zero). Rest is a list of all the other elements. Can be used to either select the nth element of List or to insert an element before the nth element in Rest.

Compilation flags:

`static`

Template:

`nth1(Nth,List,Element,Rest)`

Mode and number of proofs:

`nth1(?integer,+list,@var,?list) - zero_or_more`

`permutation/2`

The two lists are a permutation of the same list.

Compilation flags:

`static`

Template:

`permutation(List,Permutation)`

Mode and number of proofs:

permutation(@list,@list) - zero_or_one

prefix/2

Prefix is a prefix of List.

Compilation flags:

static

Template:

prefix(Prefix,List)

Mode and number of proofs:

prefix(?list,@list) - zero_or_more

remove_duplicates/2

Removes duplicated variables and keeping the left-most variable when repeated.

Compilation flags:

static

Template:

remove_duplicates(List,Set)

Mode and number of proofs:

remove_duplicates(+list,-list) - one

reverse/2

Reverses a list.

Compilation flags:

static

Template:

reverse(List,Reversed)

Mode and number of proofs:

reverse(@list,?list) - zero_or_one

reverse(?list,@list) - zero_or_one

reverse(-list,-list) - one_or_more

same_length/2

The two lists have the same length.

Compilation flags:

static

Template:

same_length(List1,List2)

Mode and number of proofs:

same_length(@list,?list) - zero_or_one

same_length(?list,@list) - zero_or_one

same_length(-list,-list) - one_or_more

select/3

Selects an element from a list, returning the list of remaining elements.

Compilation flags:

static

Template:

select(Element,List,Remaining)

Mode and number of proofs:

select(@var,?list,?list) - zero_or_more

sublist/2

The first list is a sublist of the second.

Compilation flags:

static

Template:

sublist(Sublist,List)

Mode and number of proofs:

sublist(?list,@list) - zero_or_more

subtract/3

Removes all elements in the second list from the first list, returning the list of remaining elements.

Compilation flags:

static

Template:

subtract(List,Elements,Remaining)

Mode and number of proofs:

subtract(@list,@list,-list) - one

suffix/2

Suffix is a suffix of List.

Compilation flags:

static

Template:

suffix(Suffix,List)

Mode and number of proofs:

suffix(?list,@list) - zero_or_more

`valid/1`

Term is a valid list of variables.

Compilation flags:

`static`

Template:

`valid(Term)`

Mode and number of proofs:

`valid(@nonvar) - zero_or_one`

`check/1`

Checks if a term is a valid list of variables. Throws an exception if the term is not valid.

Compilation flags:

`static`

Template:

`check(Term)`

Mode and number of proofs:

`check(@nonvar) - one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

 See also

`varlist`, `listp`, `numberlistp`

1.73 ulid

object

1.73.1 ulid

Universally Unique Lexicographically Sortable Identifier (ULID) generator using an atom representation.

Availability:

`logtalk__load(ulid(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2023-05-19

Compilation flags:

`static`, `context_switching_calls`

Extends:

`public ulid(atom)`

Remarks:

(none)

Inherited public predicates:

`generate/1` `generate/2` `generate/8` `timestamp/2` `timestamp/8`

- Public predicates
- Protected predicates
- Private predicates

- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

➡ See also

`ulid(Representation)`, `ulid_types`, `uuid`, `uuid(Representation)`, `ids`, `ids(Representation,Bytes)`

object

1.73.2 `ulid(Representation)`

- Representation - Text representation for the ULID. Possible values are atom, chars, and codes.

Universally Unique Lexicographically Sortable Identifier (ULID) generator.

Availability:

```
logtalk_load(ulid(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2023-05-19

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public ulid_protocol
```

Uses:

`fast_random`
`iso8601`
`list`
`os`

Remarks:

(none)

Inherited public predicates:

`generate/1` `generate/2` `generate/8` `timestamp/2` `timestamp/8`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

➡ See also

`ulid`, `ulid_types`, `uuid(Representation)`, `uuid`, `ids`, `ids(Representation,Bytes)`

protocol

1.73.3 ulid_protocol

Universally Unique Lexicographically Sortable Identifier (ULID) generator protocol.

Availability:

```
logtalk_load(ulid(loader))
```

Author: Paulo Moura

Version: 1:0:0

Date: 2023-05-17

Compilation flags:

```
static
```

Dependencies:

```
(none)
```

Remarks:

```
(none)
```

Inherited public predicates:

```
(none)
```

- Public predicates
 - generate/1
 - generate/2
 - generate/8
 - timestamp/2
 - timestamp/8
- Protected predicates
- Private predicates
- Operators

Public predicates

generate/1

Generates a new ULID.

Compilation flags:
static

Template:
generate(ULID)
Mode and number of proofs:
generate(--ulid) - one

generate/2

Generates a new ULID from a timestamp (number of milliseconds since the Unix epoch: 00:00:00 UTC on January 1, 1970).

Compilation flags:
static

Template:
generate(Milliseconds,ULID)
Mode and number of proofs:
generate(+integer,--ulid) - one

generate/8

Generates a new ULID from a timestamp discrete components.

Compilation flags:
static

Template:
generate(Year,Month,Day,Hours,Minutes,Seconds,Milliseconds,ULID)
Mode and number of proofs:

generate(+integer,+integer,+integer,+integer,+integer,+integer,+integer,--ulid) - one

timestamp/2

Returns the given ULID timestamp (number of milliseconds since the Unix epoch: 00:00:00 UTC on January 1, 1970).

Compilation flags:

static

Template:

timestamp(ULID,Milliseconds)

Mode and number of proofs:

timestamp(++ulid,-integer) - one

timestamp/8

Decodes a ULID into its timestamp discrete components.

Compilation flags:

static

Template:

timestamp(ULID,Year,Month,Day,Hours,Minutes,Seconds,Milliseconds)

Mode and number of proofs:

timestamp(++ulid,-integer,-integer,-integer,-integer,-integer,-integer,-integer) - one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

category

1.73.4 ulid__types

ULID type definition.

Availability:

`logtalk__load(ulid(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2023-05-19

Compilation flags:

`static`

Provides:

`type::type/1`

`type::check/2`

Uses:

`list`

`type`

Remarks:

- **Provided types:** This category adds a `ulid(Representation)` type for type-checking when using the `ulid` library object. Valid representation values are `atom`, `chars`, and `codes`.

Inherited public predicates:

(none)

- Public predicates
- Protected predicates

- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

➡ See also

ulid(Representation), ulid

1.74 union_find

object

1.74.1 union_find

Union find data structure implementation.

Availability:

logtalk_load(union_find(loader))

Author: José Antonio Riaza Valverde; adapted to Logtalk by Paulo Moura

Version: 1:0:0

Date: 2022-02-18

Compilation flags:

static, context_switching_calls

Implements:

public union_find_protocol

Extends:

public compound

Uses:

avltree

Remarks:

(none)

Inherited public predicates:

(<)/2 (=:=)/2 (= <)/2 (= \=)/2 (>)/2 (>=)/2 check/1 depth/2 disjoint_sets/2 find/4
find/5 ground/1 make_set/3 new/1 new/2 numbervars/1 numbervars/3 occurs/2 singletons/2
subsumes/2 subterm/2 union/4 union_all/3 valid/1 variables/2 variant/2 varnumbers/2
varnumbers/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.74.2 union_find_protocol

Union-find data structure protocol.

Availability:

`logtalk_load(union_find(loader))`

Author: José Antonio Riaza Valverde; adapted to Logtalk by Paulo Moura

Version: 1:0:0

Date: 2022-02-17

Compilation flags:

`static`

Dependencies:

`(none)`

Remarks:

`(none)`

Inherited public predicates:

`(none)`

- Public predicates
 - `new/2`
 - `make_set/3`
 - `union/4`
 - `union_all/3`
 - `find/4`
 - `find/5`
 - `disjoint_sets/2`
- Protected predicates
- Private predicates
- Operators

Public predicates

`new/2`

Creates a new union-find data structure with a list of elements as keys.

Compilation flags:

`static`

Template:

`new(Elements,UnionFind)`

Mode and number of proofs:

`new(+list(element),?union_find) - zero_or_one`

`make_set/3`

Makes a new set by creating a new element with a unique key `Element`, a rank of 0, and a parent pointer to itself. The parent pointer to itself indicates that the element is the representative member of its own set.

Compilation flags:

`static`

Template:

`make_set(UnionFind,Element,NewUnionFind)`

Mode and number of proofs:

`make_set(+union_find,+element,?union_find) - zero_or_one`

`union/4`

Merges the two trees, if distinct, that contain the given elements. The trees are joined by attaching the shorter tree (by rank) to the root of the taller tree. Fails if any of the elements is not found.

Compilation flags:

`static`

Template:

`union(UnionFind,Element1,Element2,NewUnionFind)`

Mode and number of proofs:

`union(+union_find,+element,+element,?union_find) - zero_or_one`

`union_all/3`

Merges the distinct trees for all the given elements returning the resulting union-find data structure. Fails if any of the elements is not found.

Compilation flags:

`static`

Template:

`union_all(UnionFind,Elements,NewUnionFind)`

Mode and number of proofs:

`union_all(+union_find,+list(element),?union_find) - zero_or_one`

`find/4`

Finds the root element of a set by following the chain of parent pointers from the given element. Root is the representative member of the set to which the element belongs, and may be element itself. Fails if the element is not found.

Compilation flags:

`static`

Template:

`find(UnionFind,Element,Root,NewUnionFind)`

Mode and number of proofs:

`find(+union_find,+element,?element,?union_find) - zero_or_one`

Remarks:

- Path compression: The structure of the tree containing the element is flattened by making every node point to the root whenever this predicate is used on it.
-

find/5

Same as the find/4 predicate, but returning also the rank of the root. Fails if the element is not found.

Compilation flags:

static

Template:

find(UnionFind,Element,Root,Rank,UnionFindOut)

Mode and number of proofs:

find(+union_find,+element,?element,?rank,?union_find) - zero_or_one

Remarks:

- Path compression: The structure of the tree containing the element is flattened by making every node point to the root whenever this predicate is used on it.

disjoint_sets/2

Returns the list of disjoint sets in the given union-find data structure.

Compilation flags:

static

Template:

disjoint_sets(UnionFind,Sets)

Mode and number of proofs:

disjoint_sets(+union_find,?sets) - zero_or_one

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

➡ See also

[union_find](#)

1.75 uuid

object

1.75.1 uuid

Universally unique identifier (UUID) generator using an atom representation.

Availability:

`logtalk_load(uuid(loader))`

Author: Paulo Moura

Version: 0:2:0

Date: 2022-11-23

Compilation flags:

`static, context_switching_calls`

Extends:

`public uuid(atom)`

Remarks:

(none)

Inherited public predicates:

`random_node/1 uuid_null/1 uuid_v1/2 uuid_v4/1`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

 See also

`uuid(Representation)`, `ulid`, `ulid(Representation)`, `ids`, `ids(Representation,Bytes)`

object

1.75.2 `uuid(Representation)`

- Representation - Text representation for the UUID. Possible values are atom, chars, and codes.

Universally unique identifier (UUID) generator.

Availability:

`logtalk_load(uuid(loader))`

Author: Paulo Moura

Version: 0:5:0

Date: 2022-11-23

Compilation flags:

`static`, `context_switching_calls`

Implements:

public uuid_protocol

Uses:

fast_random

iso8601

list

os

Remarks:

(none)

Inherited public predicates:

random_node/1 uuid_null/1 uuid_v1/2 uuid_v4/1

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

➡ See also

uuid, ulid, ulid(Representation), ids, ids(Representation,Bytes)

protocol

1.75.3 uuid_protocol

Universally unique identifier (UUID) generator protocol.

Availability:

`logtalk_load(uuid(loader))`

Author: Paulo Moura

Version: 0:3:0

Date: 2021-03-13

Compilation flags:

`static`

Dependencies:

`(none)`

Remarks:

`(none)`

Inherited public predicates:

`(none)`

- Public predicates
 - `uuid_v1/2`
 - `uuid_v4/1`
 - `uuid_null/1`
 - `random_node/1`
- Protected predicates
- Private predicates
- Operators

Public predicates

`uuid_v1/2`

Returns a version 1 UUID for the given MAC address (a list of six bytes). The MAC address can be replaced by a random 6 bytes node identifier as per RFC 4122 when the MAC address is not available or should not be disclosed.

Compilation flags:

`static`

Template:

`uuid_v1(MAC,UUID)`

Mode and number of proofs:

`uuid_v1(+list(byte),--ground) - one`

`uuid_v4/1`

Returns a version 4 UUID.

Compilation flags:

`static`

Template:

`uuid_v4(UUID)`

Mode and number of proofs:

`uuid_v4(--ground) - one`

`uuid_null/1`

Returns the null UUID.

Compilation flags:

`static`

Template:

`uuid_null(UUID)`

Mode and number of proofs:

`uuid_null(--ground) - one`

`random_node/1`

Generates a list with six random bytes that can be used in alternative to a MAC address when generating version 1 UUIDs.

Compilation flags:

`static`

Template:

`random_node(Node)`

Mode and number of proofs:

`random_node(--list(byte)) - one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

1.76 verdi_neruda

object

1.76.1 `a_star_interpreter(W)`

A* interpreter for general logic programs. The parameter `W` is used to fine tune the behavior. `W = 0` gives us a breadth-first search and `W = 1` gives us a greedy best-first search. The default value for `W` is 0.5.

Availability:

```
logtalk_load(verdi_neruda(loader))
```

Author: Victor Lagerkvist

Version: 1:0:0

Date: 2010-06-13

Compilation flags:

```
static, context_switching_calls
```

Imports:

```
public best_first
```

Remarks:

```
(none)
```

Inherited public predicates:

```
prove/2 prove/3
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.76.2 benchmark_generators

Generates random data structures for use in benchmarks.

Availability:

`logtalk_load(verdi_neruda(loader))`

Author: Victor Lagerkvist

Version: 1:0:0

Date: 2010-06-13

Compilation flags:

`static, context_switching_calls`

Uses:

`random`

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - `random_tree/1`
- Protected predicates

- Private predicates
- Operators

Public predicates

`random_tree/1`

Generates a random tree.

Compilation flags:

`static`

Template:

`random_tree(Tree)`

Mode and number of proofs:

`random_tree(-tree) - one`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

`category`

1.76.3 `best_first`

Best-first framework for general logic programs.

Availability:

`logtalk_load(verdi_neruda(loader))`

Author: Victor Lagerkvist

Version: 1:1:0
Date: 2019-03-08

Compilation flags:
static

Implements:
public [interpreterp](#)

Uses:
[counter](#)
[minheap](#)

Remarks:
(none)

Inherited public predicates:
[prove/2](#) [prove/3](#)

- Public predicates
- Protected predicates
 - [f/4](#)
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

[f/4](#)

.

Compilation flags:
static

Template:
[f](#)(Length1,Length2,Depth,Cost)

Mode and number of proofs:

`f(+float,+float,+float,-float) - zero_or_more`

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.76.4 bfs_interpreter

Breadth-first interpreter for general logic programs.

Availability:

`logtalk_load(verdi_neruda(loader))`

Author: Victor Lagerkvist

Version: 1:0:0

Date: 2010-06-13

Compilation flags:

`static, context_switching_calls`

Implements:

`public interpreterp`

Uses:

`counter`

`queue`

Remarks:

(none)

Inherited public predicates:

`prove/2 prove/3`

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.76.5 `bup_interpreter`

Semi-naive bottom-up interpreter for general (stratified) logic programs. Magic transformation is realized through an expansion hook.

Availability:

```
logtalk_load(verdi_neruda(loader))
```

Author: Ulf Nilsson. Ported to Logtalk and augmented with negation by Victor Lagerkvist.

Version: 1:1:3

Date: 2023-11-30

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public interpreterp
```

Uses:

```
counter
```

list
magic
term

Remarks:

(none)

Inherited public predicates:

prove/2 prove/3

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.76.6 counter

Counter implemented with asserta/retract.

Availability:

logtalk_load(verdi_neruda(loader))

Author: Victor Lagerkvist

Version: 1:0:1

Date: 2022-10-08

Compilation flags:

static, context_switching_calls

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - increment/0
 - increase/1
 - set/1
 - value/1
 - reset/0
- Protected predicates
- Private predicates
 - c/1
- Operators

Public predicates

increment/0

Increment the counter by 1.

Compilation flags:

static

Mode and number of proofs:

increment - one

increase/1

Increments the counter by the specified amount.

Compilation flags:
static

Template:
increase(I)

Mode and number of proofs:
increase(+number) - one

set/1

Sets the counter to the specified amount.

Compilation flags:
static

Template:
set(N)

Mode and number of proofs:
set(+number) - one

value/1

Gets the current value of the counter.

Compilation flags:
static

Template:
value(N)

Mode and number of proofs:

value(?number) - one

reset/0

Resets the counter to zero.

Compilation flags:

static

Mode and number of proofs:

reset - one

Protected predicates

(none)

Private predicates

c/1

Stores the current value of the counter.

Compilation flags:

dynamic

Template:

c(N)

Mode and number of proofs:

c(?number) - zero_or_one

Operators

(none)

protocol

1.76.7 databasep

Database protocol.

Availability:

logtalk_load(verdi_neruda(loader))

Author: Victor Lagerkvist

Version: 1:0:0

Date: 2010-06-13

Compilation flags:

static

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - rule/4
 - rule/3
 - rule/2
 - bench_goal/1
- Protected predicates
- Private predicates
- Operators

Public predicates

rule/4

Clauses for this predicate are automatically generated using term-expansion. The third argument contains the length of Body.

Compilation flags:

static

Template:

rule(Head,Body,Length,Tail)

Mode and number of proofs:

rule(?callable,?callable,-,-) - zero_or_more

rule/3

Clauses for this predicate are automatically generated using term-expansion. The third argument denotes the tail of the Body.

Compilation flags:

static

Template:

rule(Head,Body,Tail)

Mode and number of proofs:

rule(?callable,?callable,-) - zero_or_more

rule/2

Clauses for this predicate are automatically generated using term-expansion.

Compilation flags:

static

Template:

rule(Head,Body)

Mode and number of proofs:

`rule(?callable,-list(callable)) - zero_or_more`

`bench_goal/1`

Table of benchmark goals. They are used from `shell.lgt` to make benchmarking easier.

Compilation flags:

`static`

Template:

`bench_goal(Goal)`

Mode and number of proofs:

`bench_goal(?callable) - zero_or_more`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

object

1.76.8 `debug_expansion`(Mode)

Expands `debug/1` calls. The parameter `Mode` can be either the atom “debug” or “production”.

Availability:

`logtalk_load(verdi_neruda(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2010-04-15

Compilation flags:

static, context_switching_calls

Implements:

public `expanding`

Remarks:

(none)

Inherited public predicates:

`goal_expansion/2` `term_expansion/2`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.76.9 demodb

Availability:

`logtalk_load(verdi_neruda(loader))`

Compilation flags:

`static, context_switching_calls`

Implements:

public `databasep`

Remarks:

(none)

Inherited public predicates:

`bench_goal/1 rule/2 rule/3 rule/4`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.76.10 dfs_interpreter

Depth-first interpreter for general logic programs.

Availability:

`logtalk_load(verdi_neruda(loader))`

Author: Victor Lagerkvist

Version: 1:0:0

Date: 2010-06-13

Compilation flags:

`static, context_switching_calls`

Implements:

`public interpreterp`

Uses:

`counter`

Remarks:

(none)

Inherited public predicates:

`prove/2 prove/3`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

category

1.76.11 flattening

Flattens conjunction of goals with the form `f and g` into a list `[f,g]`.

Availability:

`logtalk__load(verdi__neruda(loader))`

Author: Victor Lagerkvist

Version: 1:0:0

Date: 2010-06-13

Compilation flags:

`static`

source: Based on source code from The Craft of Prolog, by Richard O’Keefe.

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
- Protected predicates
 - `flatten_goals//1`
- Private predicates
- Operators

Public predicates

(none)

Protected predicates

`flatten_goals//1`

Flattens a conjunction of goals.

Compilation flags:

`static`

Template:

`flatten_goals(Conjunction)`

Mode and number of proofs:

`flatten_goals(+callable) - one`

Private predicates

(none)

Operators

(none)

object

1.76.12 `heuristic_expansion`(Mode)

Expands rules of the form `p if f and g` to `rule(p, [f,g|Tail], Length, Tail)`.

Availability:

```
logtalk_load(verdi_neruda(loader))
```

Author: Victor Lagerkvist

Version: 1:0:2

Date: 2022-10-08

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public expanding
```

Extends:

```
public rule_expansion(Mode)
```

Uses:

```
list
```

Remarks:

```
(none)
```

Inherited public predicates:

```
goal_expansion/2 term_expansion/2
```

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.76.13 iddfs_interpreter(Increment)

Iterative deepening depth-first interpreter for general logic programs. Based on source code from The Craft of Prolog, by Richard O’Keefe. The default value for the increment is 1.

Availability:

`logtalk_load(verdi_neruda(loader))`

Author: Victor Lagerkvist

Version: 1:0:0

Date: 2010-06-13

Compilation flags:

`static, context_switching_calls`

Implements:

`public interpreterp`

Uses:

`counter`

`dfs_interpreter`

Remarks:

(none)

Inherited public predicates:

`prove/2 prove/3`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

protocol

1.76.14 interpreterp

Protocol for an interpreter.

Availability:

```
logtalk_load(verdi_neruda(loader))
```

Author: Victor Lagerkvist

Version: 1:0:0

Date: 2010-06-13

Compilation flags:

```
static
```

Dependencies:

```
(none)
```

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - prove/2
 - prove/3
- Protected predicates
- Private predicates
- Operators

Public predicates

prove/2

True if goal is provable in the specified database.

Compilation flags:

static

Template:

prove(Goal,DB)

Mode and number of proofs:

prove(+goal,+database) - zero_or_more

prove/3

True if goal is provable within the given depth-limit in the specified database.

Compilation flags:

static

Template:

prove(Goal,Limit,DB)

Mode and number of proofs:

prove(+goal,+limit,+database) - zero_or_more

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

object

1.76.15 magic

Object encapsulating magic methods.

Availability:

logtalk_load(verdi_neruda(loader))

Author: Ulf Nilsson. Ported to Logtalk and augmented with stratified negation by Victor Lagerkvist.

Version: 1:0:0

Date: 2010-06-13

Compilation flags:

static, context_switching_calls

Uses:

[list](#)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - `magicise/4`
 - `magic/2`
- Protected predicates
- Private predicates
- Operators

Public predicates

`magicise/4`

Transform `(Head :- Body)` into a magic clause `(NewHead :- NewBody)`.

Compilation flags:

`static`

Template:

`magicise(Head,Body,NewHead,NewBody)`

Mode and number of proofs:

`magicise(+term,+list,-term,-list) - zero_or_one`

`magic/2`

Prefix the predicate symbol of `Old` with `magic`.

Compilation flags:

`static`

Template:

`magic(Old,New)`

Mode and number of proofs:

`magic(+callable,-callable) - zero_or_one`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.76.16 `magic_expansion`(Mode)

Expands rules of the form `p if f and g` to the more manageable rule(`p`, `[f,g]`) and performs magic transformation of clauses.

Availability:

`logtalk_load(verdi_neruda(loader))`

Author: Victor Lagerkvist

Version: 1:0:2

Date: 2022-10-08

Compilation flags:

`static, context_switching_calls`

Implements:

`public expanding`

Imports:

`public flatting`

Extends:

`public debug_expansion`(Mode)

Uses:

`list`

`magic`

Remarks:

(none)

Inherited public predicates:

`goal_expansion/2 term_expansion/2`

- [Public predicates](#)
- [Protected predicates](#)
- [Private predicates](#)
- [Operators](#)

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.76.17 [rule_expansion](#)(Mode)

Expands rules of the form `p if f and g` to the more manageable rule(`p`, `[f,g]`).

Availability:

`logtalk_load(verdi_neruda(loader))`

Author: Victor Lagerkvist

Version: 1:0:2

Date: 2022-10-08

Compilation flags:

`static, context_switching_calls`

Implements:

`public expanding`

Imports:

`public flattening`

Extends:

`public debug_expansion(Mode)`

Remarks:

(none)

Inherited public predicates:

`goal_expansion/2 term_expansion/2`

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.76.18 shell

User frontend to start the application.

Availability:

`logtalk_load(verdi_neruda(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2019-03-20

Compilation flags:

static, context_switching_calls

Uses:

shell(Interpreters)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - welcome/0
 - start/0
- Protected predicates
- Private predicates
- Operators

Public predicates

welcome/0

Compilation flags:

static

start/0

Compilation flags:

static

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.76.19 shell(Interpreters)

Prolog shell for the interpreters.

Availability:

logtalk_load(verdi_neruda(loader))

Author: Victor Lagerkvist and Paulo Moura

Version: 1:1:3

Date: 2024-03-15

Compilation flags:

static, context_switching_calls

Uses:

counter

list

meta

pairs

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - init/0
- Protected predicates
- Private predicates
- Operators

Public predicates

init/0

Compilation flags:
static

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

object

1.76.20 shell_expansion(Mode)

Expansion object for the shell.

Availability:
logtalk_load(verdi_neruda(loader))

Author: Victor Lagerkvist

Version: 1:0:1

Date: 2022-10-08

Compilation flags:

static, context_switching_calls

Implements:

public expanding

Extends:

public rule_expansion(Mode)

Remarks:

(none)

Inherited public predicates:

goal_expansion/2 term_expansion/2

- Public predicates
- Protected predicates
- Private predicates
- Operators

Public predicates

(no local declarations; see entity ancestors if any)

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

1.77 wrapper

object

1.77.1 wrapper

Adviser tool for porting and wrapping plain Prolog applications.

Availability:

```
logtalk_load(wrapper(loader))
```

Author: Paulo Moura

Version: 0:12:2

Date: 2024-05-10

Compilation flags:

```
static, context_switching_calls
```

Implements:

```
public expanding
```

Provides:

```
logtalk::message_hook/4
```

```
logtalk::message_prefix_stream/4
```

```
logtalk::message_tokens//2
```

Uses:

```
logtalk
```

```
os
```

Remarks:

- `prolog_extensions(Extensions)` option: List of file name extensions used to recognize Prolog source files (default is `['.pl', '.pro', '.prolog']`).
- `logtalk_extension(Extension)` option: Logtalk file name extension to be used for the generated wrapper files (default is `'.lgt'`).
- `exclude_files(Files)` option: List of Prolog source files names to exclude (default is `[]`).
- `exclude_directories(Files)` option: List of sub-directory names to exclude (default is `[]`).
- `include_wrapped_files(Boolean)`: Generate include/1 directives for the wrapped Prolog source files (default is `true`).

Inherited public predicates:

```
goal_expansion/2 term_expansion/2
```

- Public predicates
 - rdirectory/2
 - rdirectory/1
 - directory/2
 - directory/1
 - directories/2
 - directories/1
 - files/2
 - files/1
 - file/2
 - file/1
 - save/1
 - save/0
 - default_option/1
 - default_options/1
- Protected predicates
- Private predicates
 - merge_options/2
 - predicate_called_but_not_defined_/2
 - object_predicate_called_/3
 - module_predicate_called_/3
 - unknown_predicate_called_/2
 - missing_predicate_directive_/3
 - non_standard_predicate_call_/2
 - dynamic_directive_/3
 - multifile_directive_/3
 - add_directive_before_entity_/2
 - add_directive_/2
 - add_directive_/3
 - remove_directive_/2
 - file_being_advised_/4
- Operators

Public predicates

`rdirectory/2`

Advises the user on missing directives for converting all plain Prolog files in a directory and its sub-directories to Logtalk objects using the specified options.

Compilation flags:

`static`

Template:

`rdirectory(Directory,Options)`

Mode and number of proofs:

`rdirectory(+atom,+list(compound)) - one`

`rdirectory/1`

Advises the user on missing directives for converting all plain Prolog files in a directory and its sub-directories to Logtalk objects using default options.

Compilation flags:

`static`

Template:

`rdirectory(Directory)`

Mode and number of proofs:

`rdirectory(+atom) - one`

`directory/2`

Advises the user on missing directives for converting all plain Prolog files in a directory to Logtalk objects using the specified options.

Compilation flags:

`static`

Template:

directory(Directory,Options)

Mode and number of proofs:

directory(+atom,+list(compound)) - one

directory/1

Advises the user on missing directives for converting all plain Prolog files in a directory to Logtalk objects using default options.

Compilation flags:

static

Template:

directory(Directory)

Mode and number of proofs:

directory(+atom) - one

directories/2

Advises the user on missing directives for converting all Prolog files in a set of directories to Logtalk objects using the specified options.

Compilation flags:

static

Template:

directories(Directories,Options)

Mode and number of proofs:

directories(+list(atom),+list(compound)) - one

directories/1

Advises the user on missing directives for converting all Prolog files in a set of directories to Logtalk objects using default options.

Compilation flags:

static

Template:

directories(Directories)

Mode and number of proofs:

directories(+list(atom)) - one

files/2

Advises the user on missing directives for converting a list of plain Prolog files to Logtalk objects using the specified options.

Compilation flags:

static

Template:

files(Files,Options)

Mode and number of proofs:

files(+list(atom),+list(compound)) - one

files/1

Advises the user on missing directives for converting a list of plain Prolog files to Logtalk objects using default options.

Compilation flags:

static

Template:

files(Files)

Mode and number of proofs:

`files(+list(atom)) - one`

`file/2`

Advises the user on missing directives for converting a plain Prolog file to Logtalk objects using the specified options.

Compilation flags:

`static`

Template:

`file(File,Options)`

Mode and number of proofs:

`file(+atom,+list(compound)) - one`

`file/1`

Advises the user on missing directives for converting a plain Prolog file to Logtalk objects using default options.

Compilation flags:

`static`

Template:

`file(File)`

Mode and number of proofs:

`file(+atom) - one`

save/1

Saves the generated wrapper objects (plus a loader file per directory) for all advised files using the specified options. The wrapper objects are saved to the same directories that contain the wrapped Prolog files.

Compilation flags:

static

Template:

save(Options)

Mode and number of proofs:

save(+list(compound)) - one

save/0

Saves the generated wrapper objects (plus a loader file per directory) for all advised files using default options. The wrapper objects are saved to the same directories that contain the wrapped Prolog files.

Compilation flags:

static

Mode and number of proofs:

save - one

default_option/1

Enumerates by backtracking the default options used when generating the wrapper objects.

Compilation flags:

static

Template:

default_option(DefaultOption)

Mode and number of proofs:

default_option(?compound) - zero_or_more

default_options/1

Returns a list of the default options used when generating the wrapper objects.

Compilation flags:

static

Template:

default_options(DefaultOptions)

Mode and number of proofs:

default_options(-list(compound)) - one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

merge_options/2

Merges the user options with the default options, returning the list of options used when generating the wrapper objects.

Compilation flags:

static

Template:

merge_options(UserOptions,Options)

Mode and number of proofs:

merge_options(+list(compound),-list(compound)) - one

`predicate_called_but_not_defined_/2`

Table of called object predicates that are not locally defined.

Compilation flags:

dynamic

Template:

`predicate_called_but_not_defined_(Object,Predicate)`

Mode and number of proofs:

`predicate_called_but_not_defined_(?atom,?predicate_indicator) - zero_or_more`

`object_predicate_called_/3`

Table of called object predicates.

Compilation flags:

dynamic

Template:

`object_predicate_called_(Object,Other,Predicate)`

Mode and number of proofs:

`object_predicate_called_(?atom,?atom,?predicate_indicator) - zero_or_more`

`module_predicate_called_/3`

Table of called module predicates.

Compilation flags:

dynamic

Template:

`module_predicate_called_(Object,Module,Predicate)`

Mode and number of proofs:

`module_predicate_called_(?atom,?atom,?predicate_indicator) - zero_or_more`

unknown_predicate_called_/2

Table of predicates called but not defined.

Compilation flags:

dynamic

Template:

unknown_predicate_called_(Object,Predicate)

Mode and number of proofs:

unknown_predicate_called_(?atom,?predicate_indicator) - zero_or_more

missing_predicate_directive_/3

Table of missing predicate directives.

Compilation flags:

dynamic

Template:

missing_predicate_directive_(Object,Directive,Predicate)

Mode and number of proofs:

missing_predicate_directive_(?atom,?predicate_indicator,?predicate_indicator) - zero_or_more

non_standard_predicate_call_/2

Table of called non-standard predicates.

Compilation flags:

dynamic

Template:

non_standard_predicate_call_(Object,Predicate)

Mode and number of proofs:

non_standard_predicate_call_(?atom,?predicate_indicator) - zero_or_more

`dynamic_directive_/3`

Table of declared dynamic predicates.

Compilation flags:

`dynamic`

Template:

`dynamic_directive_(Object,Line,Predicate)`

Mode and number of proofs:

`dynamic_directive_(?atom,?integer,?predicate_indicator) - zero_or_more`

`multifile_directive_/3`

Table of declared multifile predicates.

Compilation flags:

`dynamic`

Template:

`multifile_directive_(Object,Line,Predicate)`

Mode and number of proofs:

`multifile_directive_(?atom,?integer,?predicate_indicator) - zero_or_more`

`add_directive_before_entity_/2`

Table of directives to be added before the entity opening directive.

Compilation flags:

`dynamic`

Template:

`add_directive_before_entity_(Object,Directive)`

Mode and number of proofs:

`add_directive_before_entity_(?atom,?predicate_indicator) - zero_or_more`

`add_directive_/2`

Table of directives to be added.

Compilation flags:

`dynamic`

Template:

`add_directive_(Object,Directive)`

Mode and number of proofs:

`add_directive_(?atom,?predicate_indicator) - zero_or_more`

`add_directive_/3`

Table of directives to be added to complement existing directives.

Compilation flags:

`dynamic`

Template:

`add_directive_(Object,Directive,NewDirective)`

Mode and number of proofs:

`add_directive_(?atom,?predicate_indicator,?predicate_indicator) - zero_or_more`

`remove_directive_/2`

Table of directives to be removed.

Compilation flags:

`dynamic`

Template:

`remove_directive_(Object,Directive)`

Mode and number of proofs:

`remove_directive_(?atom,?predicate_indicator) - zero_or_more`

file_being_advised_/4

Table of files being advised are respective directories and names (basename without extension).

Compilation flags:

dynamic

Template:

file_being_advised__(File,Path,Directory,Name)

Mode and number of proofs:

file_being_advised__((?atom,?atom,?atom,?atom) - zero_or_more

Operators

(none)

1.78 xml_parser

object

1.78.1 xml

Bi-directional XML parser.

Availability:

logtalk_load(xml_parser(loader))

Author: John Fletcher; adapted to Logtalk by Paulo Moura.

Version: 3:8:4

Date: 2024-03-14

Copyright: Copyright (C) 2001-2005 Binding Time Limited, Copyright (C) 2005-2013 John Fletcher

License: This program is offered free of charge, as unsupported source code. You may use it, copy it, distribute it, modify it or sell it without restriction, but entirely at your own risk.

Compilation flags:

static, context_switching_calls

Uses:

list
term

Remarks:

- On-line documentation: https://binding-time.co.uk/index.php/Parsing_XML_with_Prolog
- Compliance: This XML parser supports a subset of XML suitable for XML Data and Worldwide Web applications. It is neither as strict nor as comprehensive as the XML 1.0 Specification mandates.
- Compliance-strictness: It is not as strict, because, while the specification must eliminate ambiguities, not all errors need to be regarded as faults, and some reasonable examples of real XML usage would have to be rejected if they were.
- Compliance-comprehensive: It is not as comprehensive, because, where the XML specification makes provision for more or less complete DTDs to be provided as part of a document, xml.pl actions the local definition of ENTITIES only. Other DTD extensions are treated as commentary.
- Bi-directional conversions: Conversions are not fully symmetrical as weaker XML is accepted than can be generated. Notably, in-bound (Codes -> Document) parsing does not require strictly well-formed XML. If Codes does not represent well-formed XML, Document is instantiated to the term malformed(<attributes>,<content>).

Inherited public predicates:

(none)

- Public predicates
 - parse/2
 - parse/3
 - subterm/2
 - pp/1
- Protected predicates
- Private predicates
 - xml_to_document/3
 - empty_map/1
 - map_member/3
 - map_store/4
 - pp_string/1
 - fault/5
 - exception/4
 - document_generation//2
 - pcddata_7bit//1

- character_data_format/3
- cdata_generation//1
- Operators

Public predicates

parse/2

Parses a list of character codes to/from a data structure of the form `xml(<atts>,<content>)`.

Compilation flags:

static

Template:

parse(Codes,Document)

Mode and number of proofs:

parse(+list(character_code),?nonvar) - zero_or_one

parse(?list(character_code),+nonvar) - zero_or_one

parse/3

Parses a list of character codes to/from a data structure of the form `xml(<atts>,<content>)` using the given list of options.

Compilation flags:

static

Template:

parse(Options,Codes,Document)

Mode and number of proofs:

parse(++list(compound),+list(character_code),?nonvar) - zero_or_one

parse(++list(compound),?list(character_code),+nonvar) - zero_or_one

Remarks:

- extended_characters(Boolean) option: Use the extended character entities for XHTML (default true).
- format(Boolean) option: For parsing, strip layouts when no character data appears between elements (default true). For generating, indent the element content (default true).

- `remove_attribute_prefixes(Boolean)` option: Remove namespace prefixes from attributes when it's the same as the prefix of the parent element (default false).
 - `allow_ampersand(Boolean)` option: Allow unescaped ampersand characters (&) to occur in PCDATA (default false).
-

`subterm/2`

Unifies Subterm with a sub-term of XMLTerm. Note that XMLTerm is a sub-term of itself.

Compilation flags:

`static`

Template:

`subterm(XMLTerm,Subterm)`

Mode and number of proofs:

`subterm(+nonvar,?nonvar) - zero_or_one`

`pp/1`

Pretty prints a XML document on the current output stream.

Compilation flags:

`static`

Template:

`pp(XMLDocument)`

Mode and number of proofs:

`pp(+nonvar) - zero_or_one`

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

`xml_to_document/3`

Translates the list of character codes XML into the Prolog term Document. Options is a list of terms controlling the treatment of layout characters and character entities.

Compilation flags:

static

Template:

`xml_to_document(Options,XML,Document)`

Mode and number of proofs:

`xml_to_document(+nonvar,+nonvar,?nonvar) - zero_or_one`

`empty_map/1`

True if Map is a null map.

Compilation flags:

static

Template:

`empty_map(Map)`

Mode and number of proofs:

`empty_map(?nonvar) - zero_or_one`

map_member/3

True if Map is a ordered map structure which records the pair Key-Data. Key must be ground.

Compilation flags:

static

Template:

map_member(Key,Map,Data)

Mode and number of proofs:

map_member(+nonvar,+nonvar,?nonvar) - zero_or_one

map_store/4

True if Map0 is an ordered map structure, Key must be ground, and Map1 is identical to Map0 except that the pair Key-Data is recorded by Map1.

Compilation flags:

static

Template:

map_store(Map0,Key,Data,Map1)

Mode and number of proofs:

map_store(+nonvar,+nonvar,+nonvar,?nonvar) - zero_or_one

pp_string/1

Prints String onto the current output stream. If String contains only 7-bit chars it is printed in shorthand quoted format, otherwise it is written as a list.

Compilation flags:

static

Template:

pp_string(String)

Mode and number of proofs:

pp_string(+nonvar) - zero_or_one

`fault/5`

Identifies SubTerm as a sub-term of Term which cannot be serialized after Indentation. Message is an atom naming the type of error; Path is a string encoding a list of SubTerm's ancestor elements in the form `<tag>{(id)}*` where `<tag>` is the element tag and `<id>` is the value of any attribute `__named__ id`.

Compilation flags:

`static`

Template:

`fault(Term,Indentation,SubTerm,Path,Message)`

Mode and number of proofs:

`fault(+nonvar,+nonvar,?nonvar,?nonvar,?nonvar) - zero_or_one`

`exception/4`

Hook to raise an exception to be raised in respect of a fault in the XML Term Document.

Compilation flags:

`static`

Template:

`exception(Message,Document,Culprit,Path)`

Mode and number of proofs:

`exception(+atom,+nonvar,+nonvar,+nonvar) - one`

`document_generation//2`

DCG generating Document as a list of character codes. Format is `true|false` defining whether layouts, to provide indentation, should be added between the element content of the resultant "string". Note that formatting is disabled for elements that are interspersed with `pcdata/1` terms, such as XHTML's 'inline' elements. Also, Format is over-ridden, for an individual element, by an explicit `'xml:space'="preserve"` attribute.

Compilation flags:

static

Template:

document_generation(Format,Document)

Mode and number of proofs:

document_generation(+nonvar,+nonvar) - zero_or_one

pcdata_7bit//1

Represents the ASCII character set in its simplest format, using the character entities &, ", <, and > which are common to both XML and HTML. The numeric entity ' is used in place of ' because browsers don't recognize it in HTML.

Compilation flags:

static

Template:

pcdata_7bit(Code)

Mode and number of proofs:

pcdata_7bit(?nonvar) - zero_or_one

character_data_format/3

Holds when Format0 and Format1 are the statuses of XML formatting before and after Codes - which may be null.

Compilation flags:

static

Template:

character_data_format(Codes,Format0,Format1)

Mode and number of proofs:

character_data_format(+nonvar,+nonvar,?nonvar) - zero_or_one

`cdata_generation//1`

Holds when `Format0` and `Format1` are the statuses of XML formatting before and after `Codes` - which may be null.

Compilation flags:

`static`

Template:

`cdata_generation(Codes)`

Mode and number of proofs:

`cdata_generation(+list) - zero_or_one`

Operators

(none)

1.79 zippers

protocol

1.79.1 zipperp

Zipper protocol.

Availability:

`logtalk_load(zippers(loader))`

Author: Paulo Moura

Version: 1:0:0

Date: 2019-01-20

Compilation flags:

`static`

Dependencies:

(none)

Remarks:

(none)

Inherited public predicates:

(none)

- Public predicates
 - zip/2
 - zip/3
 - unzip/2
 - current/2
 - next/2
 - next/3
 - previous/2
 - previous/3
 - rewind/2
 - rewind/3
 - forward/2
 - forward/3
 - apply/2
 - insert_before/3
 - insert_after/3
 - replace/3
 - delete_and_previous/2
 - delete_and_next/2
 - delete_and_unzip/2
 - delete_all_before/2
 - delete_all_before_and_unzip/2
 - delete_all_after/2
 - delete_all_after_and_unzip/2
- Protected predicates
- Private predicates
- Operators

Public predicates

zip/2

Adds a zipper to a compound term holding a sequence of elements. Fails if the sequence is empty.

Compilation flags:

static

Template:

zip(Sequence,Zipper)

Mode and number of proofs:

zip(+sequence,--zipper) - zero_or_one

zip/3

Adds a zipper to a compound term holding a sequence of elements. Also returns the first element. Fails if the sequence is empty.

Compilation flags:

static

Template:

zip(Sequence,Zipper,First)

Mode and number of proofs:

zip(+sequence,--zipper,--term) - zero_or_one

unzip/2

Removes a zipper from a sequence.

Compilation flags:

static

Template:

unzip(Zipper,Sequence)

Mode and number of proofs:

`unzip(@zipper,--sequence) - one`

`current/2`

Current element.

Compilation flags:
static

Template:
current(Zipper,Current)
Mode and number of proofs:
current(+zipper,?term) - zero_or_one

`next/2`

Moves to the next element. Fails if already at the last elements.

Compilation flags:
static

Template:
next(Zipper,NewZipper)
Mode and number of proofs:
next(+zipper,--zipper) - zero_or_one

`next/3`

Moves to and returns the next element. Fails if already at the last elements.

Compilation flags:
static

Template:

```
next(Zipper,NewZipper,Next)
```

Mode and number of proofs:

```
next(+zipper,--zipper,-term) - zero_or_one
```

[previous/2](#)

Moves to the previous element. Fails if already at the first elements.

Compilation flags:

```
static
```

Template:

```
previous(Zipper,NewZipper)
```

Mode and number of proofs:

```
previous(+zipper,--zipper) - zero_or_one
```

[previous/3](#)

Moves to and returns the previous element. Fails if already at the first element.

Compilation flags:

```
static
```

Template:

```
previous(Zipper,NewZipper,Previous)
```

Mode and number of proofs:

```
previous(+zipper,--zipper,-term) - zero_or_one
```

rewind/2

Rewinds the zipper so that the first element becomes the current element.

Compilation flags:

static

Template:

rewind(Zipper,NewZipper)

Mode and number of proofs:

rewind(+zipper,--zipper) - one

rewind/3

Rewinds the zipper so that the first element becomes the current element. Also returns the first element.

Compilation flags:

static

Template:

rewind(Zipper,NewZipper,First)

Mode and number of proofs:

rewind(+zipper,--zipper,?term) - zero_or_one

forward/2

Forward the zipper so that the last element becomes the current element.

Compilation flags:

static

Template:

forward(Zipper,NewZipper)

Mode and number of proofs:

forward(+zipper,--zipper) - one

forward/3

Forward the zipper so that the last element becomes the current element. Also returns the last element.

Compilation flags:

static

Template:

forward(Zipper,NewZipper,Last)

Mode and number of proofs:

forward(+zipper,--zipper,?term) - zero_or_one

apply/2

Applies a closure to the current element.

Compilation flags:

static

Template:

apply(Closure,Zipper)

Meta-predicate template:

apply(1,*)

Mode and number of proofs:

apply(+callable,+zipper) - zero_or_more

insert_before/3

Inserts an element before the current one.

Compilation flags:

static

Template:

insert_before(Zipper,Element,NewZipper)

Mode and number of proofs:

insert_before(+zipper,?term,--zipper) - zero_or_one

`insert_after/3`

Inserts an element after the current one.

Compilation flags:

`static`

Template:

`insert_after(Zipper,Element,NewZipper)`

Mode and number of proofs:

`insert_after(+zipper,?term,--zipper) - zero_or_one`

`replace/3`

Replaces the current element with a new element.

Compilation flags:

`static`

Template:

`replace(Zipper,NewCurrent,NewZipper)`

Mode and number of proofs:

`replace(+zipper,?term,--zipper) - one`

`delete_and_previous/2`

Deletes the current element and moves to the previous element. Fails if no previous element exists.

Compilation flags:

`static`

Template:

`delete_and_previous(Zipper,NewZipper)`

Mode and number of proofs:

`delete_and_previous(+zipper,--zipper) - zero_or_one`

`delete_and_next/2`

Deletes the current element and moves to the next element. Fails if no next element exists.

Compilation flags:

`static`

Template:

`delete_and_next(Zipper,NewZipper)`

Mode and number of proofs:

`delete_and_next(+zipper,--zipper) - zero_or_one`

`delete_and_unzip/2`

Deletes the current element and removes the zipper returning the resulting sequence.

Compilation flags:

`static`

Template:

`delete_and_unzip(Zipper,Sequence)`

Mode and number of proofs:

`delete_and_unzip(+zipper,--sequence) - one`

`delete_all_before/2`

Deletes all elements before the current element.

Compilation flags:

`static`

Template:

```
delete_all_before(Zipper,NewZipper)
```

Mode and number of proofs:

```
delete_all_before(+zipper,--zipper) - one
```

```
delete_all_before_and_unzip/2
```

Deletes all elements before the current element and removes the zipper returning the resulting sequence.

Compilation flags:

```
static
```

Template:

```
delete_all_before_and_unzip(Zipper,NewZipper)
```

Mode and number of proofs:

```
delete_all_before_and_unzip(+zipper,--sequence) - one
```

```
delete_all_after/2
```

Deletes all elements after the current element.

Compilation flags:

```
static
```

Template:

```
delete_all_after(Zipper,NewZipper)
```

Mode and number of proofs:

```
delete_all_after(+zipper,--zipper) - one
```

`delete_all_after_and_unzip/2`

Deletes all elements after the current element and removes the zipper returning the resulting sequence.

Compilation flags:

`static`

Template:

`delete_all_after_and_unzip(Zipper,NewZipper)`

Mode and number of proofs:

`delete_all_after_and_unzip(+zipper,--sequence) - one`

Protected predicates

(none)

Private predicates

(none)

Operators

(none)

 See also

[zlist](#)

object

1.79.2 zlist

Zipper list predicates. Zippers should be regarded as opaque terms.

Availability:

`logtalk_load(zippers(loader))`

Author: Paulo Moura

Version: 1:0:1

Date: 2019-03-12

Compilation flags:

static, context_switching_calls

Implements:

public zipperp

Remarks:

(none)

Inherited public predicates:

apply/2 current/2 delete_all_after/2 delete_all_after_and_unzip/2 delete_all_before/2
 delete_all_before_and_unzip/2 delete_and_next/2 delete_and_previous/2 delete_and_unzip/2
 forward/2 forward/3 insert_after/3 insert_before/3 next/2 next/3 previous/2 previous/3
 replace/3 rewind/2 rewind/3 unzip/2 zip/2 zip/3

- Public predicates
 - zip_at_index/4
- Protected predicates
- Private predicates
- Operators

Public predicates

zip_at_index/4

Adds a zipper to a list opened at the given index and also returns the element at the index. Fails if the list is empty or the index (starting at 1) does not exist.

Compilation flags:

static

Template:

zip_at_index(Index,List,Zipper,Element)

Mode and number of proofs:

zip_at_index(+natural,+list,--zipper,--term) - zero_or_one

Protected predicates

(no local declarations; see entity ancestors if any)

Private predicates

(no local declarations; see entity ancestors if any)

Operators

(none)

DIRECTORIES

To load an entity, always load the library that includes it using the goal `logtalk__load(library__name(loader))` instead of using its path. The library loader file ensures that all the required dependencies are also loaded and that any required flags are used. The loading goal can be found in the entity documentation.

- 2.1** [contributions/flags/](#)
- 2.2** [contributions/iso8601/](#)
- 2.3** [contributions/pddl_parser/](#)
- 2.4** [contributions/verdi_neruda/](#)
- 2.5** [contributions/xml_parser/](#)
- 2.6** [core/](#)
- 2.7** [library/](#)
- 2.8** [library/arbitrary/](#)
- 2.9** [library/assignvars/](#)
- 2.10** [library/base64/](#)
- 2.11** [library/cbor/](#)
- 2.12** [library/coroutining/](#)
- 2.13** [library/csv/](#)
- 2.14** [library/dates/](#)
- 2.15** [library/dependents/](#)
- 2.16** [library/dictionaries/](#)
- 2.17** [library/dif/](#)
- 2.18** [library/edcg/](#)
- 2.19** [library/events/](#)
- 2.20** [library/expand_library_alias_paths/](#)
- 2.1.** [contributions/flags/](#)
- 2.21** [library/expecteds/](#)

ENTITIES

To load an entity, always load the library that includes it using the goal `logtalk__load(library__name(loader))` instead of loading just the entity. The library loader file ensures that all the required dependencies are also loaded and that any required flags are used. The loading goal can be found in the entity documentation.

3.1 Categories

3.2 Objects

3.3 Protocols

PREDICATES

This index lists all entities declaring a given predicate. To load an entity providing the predicate that you want to call, always load the library that includes it using the goal `logtalk_load(library_name(loader))` instead of loading just the entity. The library loader file ensures that all the required dependencies are also loaded and that any required flags are used. The loading goal can be found in the entity documentation.

4.1 `(/)/2`

- `help`

4.2 `(//)/2`

- `help`

4.3 `(<)/2`

- `comparingp`

4.4 `(<=)/2`

- `assignvarsp`
- `streamvars`

4.5 `(:=)/2`

- `comparingp`

4.6 $(= <)/2$

- `comparingp`

4.7 $(= >)/2$

- `assignvarsp`
- `streamvars`

4.8 $(= \backslash =)/2$

- `comparingp`

4.9 $= \sim = / 2$

- `lgtunit`
- `number`

4.10 $(>)/2$

- `comparingp`

4.11 $(> =)/2$

- `comparingp`

4.12 `absolute_file_name/2`

- `osp`

4.13 `activate_debug_handler/1`

- `logtalk`

4.14 activate_monitor/0

- monitorp

4.15 active_debug_handler/1

- logtalk

4.16 add/1

- registries

4.17 add/2

- registries

4.18 add/3

- difflist
- registries

4.19 addDependent/1

- subject

4.20 after/2

- intervalp

4.21 after/3

- monitoring

4.22 all/0

- `code_metric`
- `dead_code_scanner`
- `lgtdocp`

4.23 all/1

- `code_metric`
- `dead_code_scanner`
- `lgtdocp`

4.24 all_files/0

- `diagram(Format)`
- `diagrams(Format)`

4.25 all_files/1

- `diagram(Format)`
- `diagrams(Format)`

4.26 all_libraries/0

- `diagram(Format)`
- `diagrams(Format)`

4.27 all_libraries/1

- `diagram(Format)`
- `diagrams(Format)`

4.28 all_score/1

- code_metric

4.29 ancestor/1

- hierarchyp

4.30 ancestors/1

- hierarchyp

4.31 apis/0

- help_info_support

4.32 apis/1

- help_info_support

4.33 append/2

- listp

4.34 append/3

- listp
- queuep
- varlistp

4.35 apply/2

- zipperp

4.36 apply/4

- dictionaryp

4.37 approximately_equal/2

- lgtunit
- number

4.38 approximately_equal/3

- lgtunit
- number

4.39 arbitrary/1

- arbitrary

4.40 arbitrary/2

- arbitrary

4.41 archive/1

- registry_protocol

4.42 arithmetic_mean/2

- statisticsp

4.43 array_list/2

- java_utils_protocol

4.44 array__to__list/2

- java__utils__protocol

4.45 array__to__terms/2

- java__utils__protocol

4.46 array__to__terms/3

- java__utils__protocol

4.47 as__curly__bracketed/2

- dictionaryp
- nested_dictionary_protocol

4.48 as__dictionary/2

- dictionaryp

4.49 as__difflist/2

- list

4.50 as__heap/2

- heapp

4.51 as__list/2

- dictionaryp
- difflist
- heapp
- queuep
- setp

4.52 as__nested__dictionary/2

- nested_dictionary_protocol

4.53 as__set/2

- setp

4.54 ask__question/5

- logtalk

4.55 assertion/1

- assertions(Mode)
- lgtunit

4.56 assertion/2

- assertions(Mode)
- lgtunit

4.57 assignable/1

- assignvarsp

4.58 assignable/2

- assignvarsp

4.59 available/0

- packs

4.60 available/1

- packs

4.61 available/2

- packs

4.62 average/2

- numberlistp

4.63 average_deviation/3

- statisticsp

4.64 before/2

- intervalp

4.65 before/3

- monitoring

4.66 bench_goal/1

- databasep

4.67 benchmark/2

- lgtunit

4.68 benchmark/3

- lgtunit

4.69 benchmark/4

- lgtunit

4.70 benchmark_reified/3

- lgtunit

4.71 bernoulli/2

- sampling_protocol

4.72 beta/3

- sampling_protocol

4.73 between/3

- integer
- random_protocol

4.74 between/4

- float

4.75 binomial/3

- sampling_protocol

4.76 bit//1

- `number__grammars(Format)`

4.77 bits//1

- `number__grammars(Format)`

4.78 blank//0

- `blank__grammars(Format)`

4.79 blanks//0

- `blank__grammars(Format)`

4.80 body__pred/1

- `metagol`

4.81 branch/2

- `git__protocol`

4.82 built__in__directive/4

- `help`

4.83 built__in__flag/2

- `flags`

4.84 built_in_method/4

- help

4.85 built_in_non_terminal/4

- help

4.86 built_in_predicate/4

- help

4.87 calendar_month/3

- iso8601

4.88 call_with_timeout/2

- timeout

4.89 call_with_timeout/3

- timeout

4.90 cat/2

- maybe

4.91 change_directory/1

- osp

4.92 changed/0

- subject

4.93 changed/1

- subject

4.94 chebyshev_distance/3

- numberlistp

4.95 chebyshev_norm/2

- numberlistp

4.96 check/1

- term p
- varlistp

4.97 check/2

- type

4.98 check/3

- type

4.99 check_option/1

- options_protocol

4.100 check_options/1

- options_protocol

4.101 chi_squared/2

- sampling_protocol

4.102 chr_is/2

- toychrdb

4.103 chr_no_spy/1

- toychrdb

4.104 chr_nospy/0

- toychrdb

4.105 chr_notrace/0

- toychrdb

4.106 chr_option/2

- toychrdb

4.107 chr_spy/1

- toychrdb

4.108 chr_trace/0

- toychrdb

4.109 circular_uniform_cartesian/3

- sampling_protocol

4.110 circular_uniform_polar/3

- sampling_protocol

4.111 class/1

- class_hierarchy

4.112 classes/1

- class_hierarchy

4.113 clause/5

- ports_profiler

4.114 clause_location/6

- ports_profiler

4.115 clean/0

- packs
- registries

4.116 clean/1

- packs
- registries

4.117 clean/2

- packs

4.118 clone/1

- cloning
- registry_protocol

4.119 clone/3

- dictionaryp

4.120 clone/4

- dictionaryp

4.121 coefficient_of_variation/2

- statisticsp

4.122 command_line_arguments/1

- osp

4.123 commit_author/2

- git_protocol

4.124 `commit_date/2`

- `git_protocol`

4.125 `commit_hash/2`

- `git_protocol`

4.126 `commit_hash_abbreviated/2`

- `git_protocol`

4.127 `commit_log/3`

- `git_protocol`

4.128 `commit_message/2`

- `git_protocol`

4.129 `compile_aux_clauses/1`

- `logtalk`

4.130 `compile_predicate_heads/4`

- `logtalk`

4.131 `compile_predicate_indicators/3`

- `logtalk`

4.132 completion/2

- help

4.133 completions/2

- help

4.134 connect/1

- redis

4.135 connect/3

- redis

4.136 console/1

- redis

4.137 contains/2

- intervalp

4.138 control//0

- blank_grammars(Format)

4.139 control_construct/4

- help

4.140 controls//0

- blank_grammars(Format)

4.141 copy_file/2

- osp

4.142 counter/2

- counters
- mutations_store

4.143 cover/1

- lgtunit

4.144 cpu_time/1

- osp
- timep

4.145 current/2

- zipperp

4.146 data/0

- ports_profiler

4.147 data/1

- ports_profiler

4.148 data/2

- ports_profiler

4.149 date/4

- iso8601

4.150 date/5

- iso8601

4.151 date/6

- iso8601

4.152 date/7

- iso8601

4.153 date_string/3

- iso8601

4.154 date_time/7

- osp

4.155 days_in_month/3

- datep

4.156 deactivate_debug_handler/0

- logtalk

4.157 debug/0

- debuggerp

4.158 debug_handler/1

- logtalk

4.159 debug_handler/3

- logtalk

4.160 debugging/0

- debuggerp

4.161 debugging/1

- debuggerp

4.162 decide/1

- fcube

4.163 decide/2

- fcube

4.164 `decode__exception/2`

- `java__utils__protocol`

4.165 `decode__exception/3`

- `java__utils__protocol`

4.166 `decompile__predicate__heads/4`

- `logtalk`

4.167 `decompile__predicate__indicators/4`

- `logtalk`

4.168 `decompose__file__name/3`

- `osp`

4.169 `decompose__file__name/4`

- `osp`

4.170 `decrement__counter/1`

- `counters`

4.171 `default__option/1`

- `options__protocol`
- `wrapper`

4.172 default_options/1

- options_protocol
- wrapper

4.173 define_log_file/2

- loggingp

4.174 defined/4

- registries

4.175 defined_flag/6

- flags

4.176 del_monitors/0

- event_registryp

4.177 del_monitors/4

- event_registryp

4.178 del_spy_points/4

- monitorp

4.179 delete/0

- registries

4.180 delete/1

- registries

4.181 delete/2

- registries

4.182 delete/3

- listp
- setp
- varlistp

4.183 delete/4

- dictionaryp
- heapp

4.184 delete__all__after/2

- zipperp

4.185 delete__all__after__and__unzip/2

- zipperp

4.186 delete__all__before/2

- zipperp

4.187 delete__all__before__and__unzip/2

- zipperp

4.188 delete__and__next/2

- zipperp

4.189 delete__and__previous/2

- zipperp

4.190 delete__and__unzip/2

- zipperp

4.191 delete__directory/1

- osp

4.192 delete__directory__and__contents/1

- osp

4.193 delete__directory__contents/1

- osp

4.194 delete__file/1

- osp

4.195 delete__in/4

- nested_dictionary_protocol

4.196 delete_matches/3

- listp

4.197 delete_max/4

- dictionaryp

4.198 delete_min/4

- dictionaryp

4.199 depends/1

- packs
- subject

4.200 depends/2

- packs

4.201 depends/3

- packs

4.202 depth/2

- term p

4.203 descendant/1

- hierarchyp

4.204 descendant_class/1

- class_hierarchy

4.205 descendant_classes/1

- class_hierarchy

4.206 descendant_instance/1

- class_hierarchy

4.207 descendant_instances/1

- class_hierarchy

4.208 descendants/1

- hierarchy

4.209 describe/1

- packs
- registries

4.210 describe/2

- packs

4.211 description/1

- pack_protocol
- registry_protocol

4.212 deterministic/1

- lgtunit

4.213 deterministic/2

- lgtunit

4.214 diagram_description/1

- diagram(Format)

4.215 diagram_name_suffix/1

- diagram(Format)

4.216 dif/1

- coroutining
- dif

4.217 dif/2

- coroutining
- dif

4.218 digit//1

- number_grammars(Format)

4.219 digits//1

- number_grammars(Format)

4.220 directories/1

- lgtdocp
- wrapper

4.221 directories/2

- diagram(Format)
- diagrams(Format)
- lgtdocp
- wrapper

4.222 directories/3

- diagram(Format)
- diagrams(Format)

4.223 directory/1

- code__metric
- dead__code__scanner
- diagram(Format)
- diagrams(Format)
- lgtdocp
- packs__common
- wrapper

4.224 directory/2

- code__metric
- dead__code__scanner
- diagram(Format)
- diagrams(Format)
- lgtdocp
- packs__common
- wrapper

4.225 directory/3

- `directory(Format)`
- `directories(Format)`

4.226 directory_exists/1

- `directory_exists`

4.227 directory_files/2

- `directory_files`

4.228 directory_files/3

- `directory_files`

4.229 directory_score/2

- `directory_score`

4.230 dirichlet/2

- `dirichlet_protocol`

4.231 disable/1

- `debug_messages`

4.232 disable/2

- `debug_messages`

4.233 `disable_logging/1`

- `loggingp`

4.234 `disconnect/1`

- `redis`

4.235 `disjoint/2`

- `setp`

4.236 `disjoint_sets/2`

- `union_find_protocol`

4.237 `doc_goal/1`

- `doclet`

4.238 `dot//1`

- `number_grammars(Format)`

4.239 `dowhile/2`

- `loopp`

4.240 `drop/3`

- `listp`

4.241 during/2

- intervalp

4.242 easter_day/3

- iso8601

4.243 edge/6

- graph_language_protocol

4.244 edge_case/2

- arbitrary

4.245 either/3

- expected(Expected)

4.246 empty/1

- dictionaryp
- heapp
- listp
- nested_dictionary_protocol
- optional
- queuep
- setp
- varlistp

4.247 enable/1

- debug_messages

4.248 enable/2

- debug_messages

4.249 enable_logging/1

- loggingp

4.250 enabled/1

- debug_messages

4.251 enabled/2

- debug_messages

4.252 ensure_directory/1

- osp

4.253 ensure_file/1

- osp

4.254 entity/1

- code_metric
- dead_code_scanner
- help
- xref_diagram(Format)

4.255 entity/2

- xref_diagram(Format)

4.256 entity_info_pair_score_hook/3

- doc_metric

4.257 entity_info_score_hook/2

- doc_metric

4.258 entity_predicates_weights_hook/2

- doc_metric

4.259 entity_prefix/2

- logtalk

4.260 entity_score/2

- code_metric

4.261 enumerate/2

- random_protocol

4.262 environment_variable/2

- osp

4.263 epsilon/1

- lgtunit

4.264 equal/2

- intervalp
- setp

4.265 erase/1

- recorded__database__core

4.266 essentially_equal/3

- lgtunit
- number

4.267 euclidean_distance/3

- numberlistp

4.268 euclidean_norm/2

- numberlistp

4.269 exclude/3

- metap

4.270 execution_context/7

- logtalk

4.271 `expand_library_path/2`

- `logtalk`

4.272 `expected/1`

- `expected(Expected)`

4.273 `expecteds/2`

- `either`

4.274 `explain//1`

- `tutor`

4.275 `exponential/2`

- `sampling_protocol`

4.276 `extension/1`

- `proto_hierarchy`

4.277 `extensions/1`

- `proto_hierarchy`

4.278 `false/1`

- `java_utils_protocol`

4.279 fcube/0

- fcube

4.280 file/1

- code__metric
- dead__code__scanner
- entity__diagram(Format)
- lgtdocp
- wrapper

4.281 file/2

- code__metric
- dead__code__scanner
- entity__diagram(Format)
- lgtdocp
- wrapper

4.282 file_exists/1

- osp

4.283 file_footer/3

- graph_language_protocol

4.284 file_header/3

- graph_language_protocol

4.285 file_modification_time/2

- osp

4.286 file_permission/2

- osp

4.287 file_score/2

- code_metric

4.288 file_size/2

- osp

4.289 file_to_bytes/2

- reader

4.290 file_to_bytes/3

- reader

4.291 file_to_chars/2

- reader

4.292 file_to_chars/3

- reader

4.293 file_to_codes/2

- reader

4.294 file_to_codes/3

- reader

4.295 file_to_terms/2

- reader

4.296 file_to_terms/3

- reader

4.297 file_type_extension/2

- logtalk

4.298 files/1

- diagram(Format)
- diagrams(Format)
- lgtdocp
- wrapper

4.299 files/2

- diagram(Format)
- diagrams(Format)
- lgtdocp
- wrapper

4.300 files/3

- `diagram(Format)`
- `diagrams(Format)`

4.301 filter/2

- `optional(Optional)`

4.302 find/4

- `union_find_protocol`

4.303 find/5

- `union_find_protocol`

4.304 findall_member/4

- `metap`

4.305 findall_member/5

- `metap`

4.306 finished_by/2

- `intervalp`

4.307 finishes/2

- `intervalp`

4.308 fisher/3

- sampling_protocol

4.309 flag_group_chk/1

- flags

4.310 flag_groups/1

- flags

4.311 flat_map/2

- expected(Expected)
- optional(Optional)

4.312 flatten/2

- listp
- varlistp

4.313 float//1

- number_grammars(Format)

4.314 fold_left/4

- metap

4.315 fold_left_1/3

- metap

4.316 fold_right/4

- metap

4.317 fold_right_1/3

- metap

4.318 fordownto/3

- looppp

4.319 fordownto/4

- looppp

4.320 fordownto/5

- looppp

4.321 foreach/3

- looppp

4.322 foreach/4

- looppp

4.323 format/2

- format

4.324 `format/3`

- `format`

4.325 `format_entity_score//2`

- `code_metric`

4.326 `format_object/1`

- `diagram(Format)`

4.327 `format_to_atom/3`

- `term_io_protocol`

4.328 `format_to_chars/3`

- `term_io_protocol`

4.329 `format_to_chars/4`

- `term_io_protocol`

4.330 `format_to_codes/3`

- `term_io_protocol`

4.331 `format_to_codes/4`

- `term_io_protocol`

4.332 forto/3

- loopp

4.333 forto/4

- loopp

4.334 forto/5

- loopp

4.335 forward/1

- forwarding

4.336 forward/2

- zipperp

4.337 forward/3

- zipperp

4.338 fractile/3

- statisticsp

4.339 freeze/2

- coroutining

4.340 from_generator/2

- expected
- optional

4.341 from_generator/3

- expected
- optional

4.342 from_generator/4

- expected

4.343 from_goal/2

- expected
- optional

4.344 from_goal/3

- expected
- optional

4.345 from_goal/4

- expected

4.346 frozen/2

- coroutining

4.347 full_device_path/1

- osp

4.348 func_test/3

- metagol

4.349 functional/0

- metagol

4.350 gamma/3

- sampling_protocol

4.351 generate/1

- ids(Representation,Bytes)
- ulid_protocol

4.352 generate/2

- base64
- base64url
- cbor(StringRepresentation)
- html
- json_lines_protocol
- json_protocol
- ulid_protocol

4.353 generate/8

- ulid_protocol

4.354 genint/2

- genint_core

4.355 gensym/2

- gensym_core

4.356 geometric/2

- sampling_protocol

4.357 geometric_mean/2

- statisticsp

4.358 get/1

- optional(Optional)

4.359 get_field/2

- java_access_protocol

4.360 get_flag_value/2

- flags

4.361 get_seed/1

- arbitrary
- pseudo_random_protocol

4.362 gnu/0

- fcube

4.363 goal_expansion/2

- expanding

4.364 graph_footer/5

- graph_language_protocol

4.365 graph_header/5

- graph_language_protocol

4.366 ground/1

- term

4.367 group_by_key/2

- pairs

4.368 group_consecutive_by_key/2

- pairs

4.369 group_sorted_by_key/2

- pairs

4.370 guess_arity/2

- csv_protocol

4.371 guess_separator/2

- csv_protocol

4.372 gumbel/3

- sampling_protocol

4.373 hamming_distance/3

- listp

4.374 handbook/0

- help_info_support

4.375 handbook/1

- help_info_support

4.376 harmonic_mean/2

- statisticsp

4.377 head/2

- `queuep`

4.378 head__pred/1

- `metagol`

4.379 help/0

- `help`
- `packs__common`

4.380 hex__digit//1

- `number__grammars(Format)`

4.381 hex__digits//1

- `number__grammars(Format)`

4.382 home/1

- `pack__protocol`
- `registry__protocol`

4.383 hypergeometric/4

- `sampling__protocol`

4.384 ibk/3

- `metagol`

4.385 if_empty/1

- optional(Optional)

4.386 if_expected/1

- expected(Expected)

4.387 if_expected_or_else/2

- expected(Expected)

4.388 if_present/1

- optional(Optional)

4.389 if_present_or_else/2

- optional(Optional)

4.390 if_unexpected/1

- expected(Expected)

4.391 include/3

- metap

4.392 increase/1

- counter

4.393 increment/0

- counter

4.394 increment_counter/1

- counters

4.395 init/0

- shell(Interpreters)

4.396 init_log_file/2

- loggingp

4.397 inorder/2

- bintree

4.398 insert/3

- setp

4.399 insert/4

- dictionaryp
- heapp

4.400 insert_after/3

- zipperp

4.401 insert_all/3

- heapp
- setp

4.402 insert_before/3

- zipperp

4.403 insert_in/4

- nested_dictionary_protocol

4.404 install/1

- packs

4.405 install/2

- packs

4.406 install/3

- packs

4.407 install/4

- packs

4.408 installed/0

- packs

4.409 installed/1

- packs

4.410 installed/3

- packs

4.411 installed/4

- packs

4.412 instance/1

- class_hierarchy

4.413 instance/2

- recorded_database_core

4.414 instances/1

- class_hierarchy

4.415 integer//1

- number_grammars(Format)

4.416 internal_os_path/2

- osp

4.417 intersect/2

- setp

4.418 intersection/2

- dictionaryp

4.419 intersection/3

- dictionaryp
- setp

4.420 intersection/4

- setp

4.421 invoke/1

- java__access__protocol

4.422 invoke/2

- java__access__protocol

4.423 ipv4//1

- ip_grammars(Format)

4.424 ipv6//1

- ip_grammars(Format)

4.425 `is__absolute__file__name/1`

- `osp`

4.426 `is__alpha/1`

- `characterp`

4.427 `is__alphanumeric/1`

- `characterp`

4.428 `is__ascii/1`

- `characterp`

4.429 `is__bin__digit/1`

- `characterp`

4.430 `is__control/1`

- `characterp`

4.431 `is__dec__digit/1`

- `characterp`

4.432 `is__empty/0`

- `optional(Optional)`

4.433 is_end_of_line/1

- characterp

4.434 is_expected/0

- expected(Expected)

4.435 is_false/1

- java_utils_protocol

4.436 is_hex_digit/1

- characterp

4.437 is_layout/1

- characterp

4.438 is_letter/1

- characterp

4.439 is_lower_case/1

- characterp

4.440 is_newline/1

- characterp

4.441 is__null/1

- java_utils_protocol

4.442 is__object/1

- java_utils_protocol

4.443 is__octal__digit/1

- characterp

4.444 is__period/1

- characterp

4.445 is__present/0

- optional(Optional)

4.446 is__punctuation/1

- characterp

4.447 is__quote/1

- characterp

4.448 is__true/1

- java_utils_protocol

4.449 is__unexpected/0

- expected(Expected)

4.450 is__upper__case/1

- characterp

4.451 is__void/1

- java_utils_protocol

4.452 is__vowel/1

- characterp

4.453 is__white__space/1

- characterp

4.454 iterator__element/2

- java_utils_protocol

4.455 join/3

- queuep

4.456 join__all/3

- queuep

4.457 jump/3

- queuep

4.458 jump_all/3

- queuep

4.459 jump_all_block/3

- queuep

4.460 key/2

- pairs

4.461 keys/2

- dictionaryp
- pairs

4.462 keys_values/3

- pairs

4.463 keysort/2

- listp

4.464 kurtosis/2

- statisticsp

4.465 language_object/2

- graph_language_registry

4.466 last/2

- listp
- varlistp

4.467 leaf/1

- hierarchyp

4.468 leaf_class/1

- class_hierarchyp

4.469 leaf_classes/1

- class_hierarchyp

4.470 leaf_instance/1

- class_hierarchyp

4.471 leaf_instances/1

- class_hierarchyp

4.472 leap_year/1

- datep
- iso8601

4.473 learn/0

- metagol_example_protocol

4.474 learn/1

- metagol_example_protocol

4.475 learn/2

- metagol

4.476 learn/3

- metagol

4.477 learn_seq/2

- metagol

4.478 learn_with_timeout/4

- metagol

4.479 leash/1

- debuggerp

4.480 leashing/1

- debuggerp

4.481 least_common_multiple/2

- numberlistp

4.482 leaves/1

- hierarchyp

4.483 length/2

- listp
- queuep
- varlistp

4.484 libraries/1

- diagram(Format)
- diagrams(Format)
- lgtdocp

4.485 libraries/2

- diagram(Format)
- diagrams(Format)
- lgtdocp

4.486 libraries/3

- diagram(Format)
- diagrams(Format)

4.487 library/0

- help

4.488 library/1

- code__metric
- dead__code__scanner
- diagram(Format)
- diagrams(Format)
- help
- lgtdocp

4.489 library/2

- code__metric
- dead__code__scanner
- diagram(Format)
- diagrams(Format)
- lgtdocp

4.490 library__score/2

- code__metric

4.491 license/1

- pack__protocol

4.492 line__to__chars/2

- reader

4.493 line_to_chars/3

- reader

4.494 line_to_codes/2

- reader

4.495 line_to_codes/3

- reader

4.496 lint/0

- packs
- registries

4.497 lint/1

- packs
- registries

4.498 lint/2

- packs

4.499 list/0

- registries

4.500 list_to_array/2

- java_utils_protocol

4.501 listing/0

- listing

4.502 listing/1

- listing

4.503 loaded_file/1

- logtalk

4.504 loaded_file_property/2

- logtalk
- modules_diagram_support

4.505 log/3

- debuggerp

4.506 log_event/2

- loggingp

4.507 log_file/2

- loggingp

4.508 logging/1

- loggingp

4.509 logging/3

- debuggerp

4.510 logistic/3

- sampling_protocol

4.511 lognormal/3

- sampling_protocol

4.512 logseries/2

- sampling_protocol

4.513 logtalk_packs/0

- packs_common

4.514 logtalk_packs/1

- packs_common

4.515 lookup/2

- dictionaryp

4.516 lookup/3

- dictionaryp

4.517 lookup_in/3

- nested_dictionary_protocol

4.518 lower_upper/2

- characterp

4.519 magic/2

- magic

4.520 magicise/4

- magic

4.521 make_directory/1

- osp

4.522 make_directory_path/1

- osp

4.523 make_set/3

- union_find_protocol

4.524 man/1

- help_info_support

4.525 manhattan_distance/3

- numberlistp

4.526 manhattan_norm/2

- numberlistp

4.527 manuals/0

- help

4.528 map/2

- dictionaryp
- expected(Expected)
- metap
- optional(Optional)
- queuep

4.529 map/3

- dictionaryp
- metap
- pairs
- queuep

4.530 map/4

- metap

4.531 map/5

- metap

4.532 map/6

- metap

4.533 map/7

- metap

4.534 map/8

- metap

4.535 map_element/2

- java_utils_protocol

4.536 map_reduce/5

- metap

4.537 max/2

- listp
- numberlistp
- statisticsp

4.538 max/3

- dictionaryp

4.539 max_clauses/1

- metagol

4.540 max_inv_preds/1

- metagol

4.541 max_size/1

- arbitrary

4.542 maybe/0

- random_protocol

4.543 maybe/1

- random_protocol

4.544 maybe/2

- random_protocol

4.545 maybe_call/1

- random_protocol

4.546 maybe_call/2

- random_protocol

4.547 mean_deviation/2

- statisticsp

4.548 median/2

- numberlistp
- statisticsp

4.549 median_deviation/2

- statisticsp

4.550 meets/2

- intervalp

4.551 member/2

- listp
- random_protocol
- setp

4.552 memberchk/2

- listp
- setp
- varlistp

4.553 merge/3

- heapp

4.554 message_hook/4

- logtalk

4.555 message_prefix_file/6

- logtalk

4.556 message_prefix_stream/4

- logtalk

4.557 message_tokens//2

- logtalk

4.558 met_by/2

- intervalp

4.559 meta_type/3

- type

4.560 metarule/6

- metagol

4.561 metarule_next_id/1

- metagol

4.562 min/2

- listp
- numberlistp
- statisticsp

4.563 min/3

- dictionaryp

4.564 min_clauses/1

- metagol

4.565 min_max/3

- numberlistp
- statisticsp

4.566 modes/2

- numberlistp
- statisticsp

4.567 module_property/2

- modules_diagram_support

4.568 monitor/1

- event_registryp

4.569 monitor/4

- event_registry

4.570 monitor_activated/0

- monitorp

4.571 monitored/1

- event_registry

4.572 monitors/1

- event_registry

4.573 msort/2

- listp

4.574 msort/3

- listp

4.575 mutation/3

- mutations
- mutations_store

4.576 name/1

- pack_protocol
- registry_protocol

4.577 name_of_day/3

- datep

4.578 name_of_month/3

- datep

4.579 natural//1

- number_grammars(Format)

4.580 new/1

- java_access_protocol
- nested_dictionary_protocol
- streamvars
- term_p

4.581 new/2

- java_access_protocol
- streamvars
- union_find_protocol

4.582 new/3

- intervalp

4.583 new_line//0

- blank_grammars(Format)

4.584 new_lines//0

- blank_grammars(Format)

4.585 next/2

- zipperp

4.586 next/3

- zipperp

4.587 next/4

- dictionaryp

4.588 nextto/3

- listp
- varlistp

4.589 node/7

- graph_language_protocol

4.590 nodebug/0

- debuggerp

4.591 nolog/3

- debuggerp

4.592 nologall/0

- debuggerp

4.593 non_blank//1

- blank_grammars(Format)

4.594 non_blanks//1

- blank_grammars(Format)

4.595 normal/3

- sampling_protocol

4.596 normal_element/2

- html

4.597 normalize_range/2

- numberlistp

4.598 normalize_range/4

- numberlistp

4.599 normalize_scalar/2

- numberlistp

4.600 normalize__unit/2

- numberlistp

4.601 nospy/1

- debuggerp

4.602 nospy/3

- debuggerp

4.603 nospy/4

- debuggerp

4.604 nospyall/0

- debuggerp

4.605 note/2

- registry__protocol

4.606 note/3

- pack__protocol

4.607 notrace/0

- debuggerp

4.608 now/3

- timep

4.609 nth0/3

- listp
- varlistp

4.610 nth0/4

- listp
- varlistp

4.611 nth1/3

- listp
- varlistp

4.612 nth1/4

- listp
- varlistp

4.613 null/1

- java_utils_protocol

4.614 null_device_path/1

- osp

4.615 number//1

- number__grammars(Format)

4.616 number_of_tests/1

- lgtunit

4.617 numbervars/1

- term_p

4.618 numbervars/3

- term_p

4.619 occurrences/2

- list_p

4.620 occurrences/3

- list_p

4.621 occurs/2

- term_p

4.622 of/2

- optional

4.623 of_expected/2

- expected

4.624 of_unexpected/2

- expected

4.625 one_or_more//0

- sequence_grammars

4.626 one_or_more//1

- sequence_grammars

4.627 one_or_more//2

- sequence_grammars

4.628 operating_system_machine/1

- osp

4.629 operating_system_name/1

- osp

4.630 operating_system_release/1

- osp

4.631 `operating_system_type/1`

- `osp`

4.632 `option/2`

- `options_protocol`

4.633 `option/3`

- `options_protocol`

4.634 `or/2`

- `optional(Optional)`

4.635 `or_else/2`

- `expected(Expected)`
- `optional(Optional)`

4.636 `or_else_call/2`

- `expected(Expected)`
- `optional(Optional)`

4.637 `or_else_fail/1`

- `expected(Expected)`
- `optional(Optional)`

4.638 or_else_get/2

- expected(Expected)
- optional(Optional)

4.639 or_else_throw/1

- expected(Expected)

4.640 or_else_throw/2

- optional(Optional)

4.641 orphaned/0

- packs

4.642 orphaned/2

- packs

4.643 outdated/0

- packs

4.644 outdated/1

- packs

4.645 outdated/2

- packs

4.646 outdated/4

- packs

4.647 outdated/5

- packs

4.648 output_file_name/2

- graph_language_protocol

4.649 overlapped_by/2

- intervalp

4.650 overlaps/2

- intervalp

4.651 parent/1

- proto_hierarchy

4.652 parenthesis/2

- characterp

4.653 parents/1

- proto_hierarchy

4.654 parse/2

- base64
- base64url
- cbor(StringRepresentation)
- json_lines_protocol
- json_protocol
- xml

4.655 parse/3

- xml

4.656 parse_domain/2

- pddl

4.657 parse_domain/3

- pddl

4.658 parse_problem/2

- pddl

4.659 parse_problem/3

- pddl

4.660 partial_map/4

- rbtrees

4.661 partition/3

- either

4.662 partition/4

- metap

4.663 partition/5

- listp

4.664 partition/6

- metap

4.665 path_concat/3

- osp

4.666 permutation/2

- listp
- random_protocol
- varlistp

4.667 pid/1

- osp

4.668 pin/0

- packs_common

4.669 pin/1

- packs_common

4.670 pinned/1

- packs_common

4.671 plus/3

- integer

4.672 poisson/2

- sampling_protocol

4.673 port/5

- ports_profiler

4.674 portray_clause/1

- listing

4.675 postorder/2

- bintree

4.676 power/2

- sampling_protocol

4.677 power_sequence/4

- integer

4.678 powerset/2

- setp

4.679 pp/1

- xml

4.680 pprint/1

- metagol

4.681 predicate/2

- dead_code_scanner

4.682 predicate_info_pair_score_hook/4

- doc_metric

4.683 predicate_info_score_hook/3

- doc_metric

4.684 predicate_mode_score_hook/3

- doc_metric

4.685 predicate_mode_score_hook/5

- doc_metric

4.686 predicates/2

- dead_code_scanner

4.687 prefix/0

- packs_common

4.688 prefix/1

- packs_common

4.689 prefix/2

- listp
- varlistp

4.690 prefix/3

- listp

4.691 preorder/2

- bintree

4.692 previous/2

- zipperp

4.693 previous/3

- zipperp

4.694 previous/4

- dictionaryp

4.695 print__flags/0

- flags
- flags_validator

4.696 print__flags/1

- flags

4.697 print__message/3

- logtalk

4.698 print__message_token/4

- logtalk

4.699 print__message_tokens/3

- logtalk

4.700 product/2

- numberlistp
- statisticsp

4.701 product/3

- setp

4.702 program_to_clauses/2

- metagol

4.703 proper_prefix/2

- listp

4.704 proper_prefix/3

- listp

4.705 proper_suffix/2

- listp

4.706 proper_suffix/3

- listp

4.707 prove/2

- interpreterp

4.708 prove/3

- interpreterp

4.709 provides/2

- registries

4.710 question_hook/6

- logtalk

4.711 question_prompt_stream/4

- logtalk

4.712 quick_check/1

- lgtunit

4.713 quick_check/2

- lgtunit

4.714 quick_check/3

- lgtunit

4.715 random/1

- random_protocol

4.716 random/3

- random_protocol

4.717 random_node/1

- uuid_protocol

4.718 random_tree/1

- benchmark_generators

4.719 randomize/1

- fast_random
- random

4.720 randseq/4

- random_protocol

4.721 randset/4

- random_protocol

4.722 range/2

- statisticsp

4.723 rdirectories/1

- lgtdocp

4.724 rdirectories/2

- lgtdocp

4.725 rdirectory/1

- `code__metric`
- `dead__code__scanner`
- `diagram(Format)`
- `diagrams(Format)`
- `lgtdocp`
- `wrapper`

4.726 rdirectory/2

- `code__metric`
- `dead__code__scanner`
- `diagram(Format)`
- `diagrams(Format)`
- `lgtdocp`
- `wrapper`

4.727 rdirectory/3

- `diagram(Format)`
- `diagrams(Format)`

4.728 rdirectory__score/2

- `code__metric`

4.729 read__file/2

- `csv__protocol`
- `read__file`
- `tsv__protocol`

4.730 read__file/3

- csv_protocol
- tsv_protocol

4.731 read__file__by__line/2

- csv_protocol
- tsv_protocol

4.732 read__file__by__line/3

- csv_protocol
- tsv_protocol

4.733 read__from__atom/2

- term_io_protocol

4.734 read__from__chars/2

- term_io_protocol

4.735 read__from__codes/2

- term_io_protocol

4.736 read__only__device__path/1

- osp

4.737 read_stream/2

- csv_protocol
- tsv_protocol

4.738 read_stream/3

- csv_protocol
- tsv_protocol

4.739 read_stream_by_line/2

- csv_protocol
- tsv_protocol

4.740 read_stream_by_line/3

- csv_protocol
- tsv_protocol

4.741 read_term_from_atom/3

- term_io_protocol

4.742 read_term_from_chars/3

- term_io_protocol

4.743 read_term_from_chars/4

- term_io_protocol

4.744 read_term_from_codes/3

- term_io_protocol

4.745 read_term_from_codes/4

- term_io_protocol

4.746 readme/1

- packs_common

4.747 readme/2

- packs_common

4.748 recorda/2

- recorded_database_core

4.749 recorda/3

- recorded_database_core

4.750 recorded/2

- recorded_database_core

4.751 recorded/3

- recorded_database_core

4.752 recordz/2

- recorded_database_core

4.753 recordz/3

- recorded_database_core

4.754 relative_standard_deviation/2

- statisticsp

4.755 removeDependent/1

- subject

4.756 remove_duplicates/2

- listp
- varlistp

4.757 rename_file/2

- osp

4.758 replace/3

- zipperp

4.759 replace_sub_atom/4

- atom

4.760 rescale/3

- numberlistp

4.761 reset/0

- counter
- debuggerp
- packs_common
- ports_profiler

4.762 reset/1

- ports_profiler

4.763 reset_counter/1

- counters

4.764 reset_counters/0

- counters

4.765 reset_flags/0

- flags

4.766 reset_flags/1

- flags

4.767 reset_genint/0

- genint_core

4.768 reset_genint/1

- genint_core

4.769 reset_gensym/0

- gensym_core

4.770 reset_gensym/1

- gensym_core

4.771 reset_monitor/0

- monitorp

4.772 reset_seed/0

- fast_random
- random

4.773 restore/1

- packs

4.774 restore/2

- packs

4.775 reverse/2

- listp
- varlistp

4.776 rewind/2

- zipperp

4.777 rewind/3

- zipperp

4.778 rlibraries/1

- lgtdocp

4.779 rlibraries/2

- lgtdocp

4.780 rlibrary/1

- code_metric
- dead_code_scanner
- diagram(Format)
- diagrams(Format)
- lgtdocp

4.781 rlibrary/2

- code_metric
- dead_code_scanner
- diagram(Format)
- diagrams(Format)
- lgtdocp

4.782 rlibrary_score/2

- code_metric

4.783 rule/2

- databasep

4.784 rule/3

- databasep

4.785 rule/4

- databasep

4.786 run/0

- lgtunit

4.787 run/1

- lgtunit

4.788 run/2

- lgtunit

4.789 run_test_sets/1

- lgtunit

4.790 same_length/2

- listp
- varlistp

4.791 same_length/3

- listp

4.792 save/0

- wrapper

4.793 save/1

- packs
- wrapper

4.794 save/2

- packs

4.795 scalar_product/3

- numberlistp

4.796 scan_left/4

- metap

4.797 scan_left_1/3

- metap

4.798 scan_right/4

- metap

4.799 scan_right_1/3

- metap

4.800 search/1

- packs

4.801 select/3

- listp
- random_protocol
- setp
- varlistp

4.802 select/4

- listp
- random_protocol

4.803 selectchk/3

- listp
- setp

4.804 selectchk/4

- listp

4.805 send/3

- redis

4.806 sequence/3

- integer

4.807 sequence/4

- float
- integer
- random_protocol

4.808 sequence/5

- float

4.809 sequential_occurrences/2

- listp

4.810 sequential_occurrences/3

- listp

4.811 serve/3

- queuep

4.812 set/1

- counter

4.813 set/4

- random_protocol

4.814 set_element/2

- java_utils_protocol

4.815 set_field/2

- java_access_protocol

4.816 set_flag_value/2

- flags

4.817 set_flag_value/3

- flags

4.818 set_monitor/4

- event_registry

4.819 set_seed/1

- arbitrary
- pseudo_random_protocol

4.820 set_spy_point/4

- monitorp

4.821 set_write_max_depth/1

- debuggerp

4.822 setup/0

- packs_common

4.823 shell/1

- osp

4.824 shell/2

- osp

4.825 shell_command/1

- doclet

4.826 shrink/3

- arbitrary

4.827 shrink_sequence/3

- arbitrary

4.828 shrinker/1

- arbitrary

4.829 sign//1

- number__grammars(Format)

4.830 singletons/2

- term_p

4.831 size/2

- dictionary_p
- heap_p
- set_p

4.832 skewness/2

- statistics_p

4.833 sleep/1

- osp

4.834 softmax/2

- numberlist_p

4.835 softmax/3

- numberlist_p

4.836 sort/2

- list_p

4.837 sort/3

- listp

4.838 sort/4

- listp

4.839 source_file_extension/1

- modules_diagram_support

4.840 space//0

- blank_grammars(Format)

4.841 spaces//0

- blank_grammars(Format)

4.842 split/3

- atom

4.843 split/4

- listp

4.844 spy/1

- debuggerp

4.845 spy/3

- debuggerp

4.846 spy/4

- debuggerp

4.847 spy__point/4

- monitorp

4.848 spying/1

- debuggerp

4.849 spying/3

- debuggerp

4.850 spying/4

- debuggerp

4.851 standard__cauchy/3

- sampling__protocol

4.852 standard_deviation/2

- statisticsp

4.853 standard_exponential/1

- sampling_protocol

4.854 standard_gamma/2

- sampling_protocol

4.855 standard_normal/1

- sampling_protocol

4.856 standard_t/2

- sampling_protocol

4.857 start/0

- ports_profiler
- shell

4.858 start_redirect_to_file/2

- dump_trace

4.859 started_by/2

- intervalp

4.860 starts/2

- intervalp

4.861 stop/0

- ports_profiler

4.862 stop_redirect_to_file/0

- dump_trace

4.863 stream_to_bytes/2

- reader

4.864 stream_to_bytes/3

- reader

4.865 stream_to_chars/2

- reader

4.866 stream_to_chars/3

- reader

4.867 stream_to_codes/2

- reader

4.868 stream_to_codes/3

- reader

4.869 stream_to_terms/2

- reader

4.870 stream_to_terms/3

- reader

4.871 subclass/1

- class_hierarchy

4.872 subclasses/1

- class_hierarchy

4.873 sublist/2

- listp
- varlistp

4.874 subsequence/3

- listp

4.875 subsequence/4

- listp

4.876 subset/2

- setp

4.877 substitute/4

- listp

4.878 subsumes/2

- term p

4.879 subterm/2

- term p
- xml

4.880 subtract/3

- listp
- setp
- varlistp

4.881 succ/2

- integer

4.882 suffix/2

- listp
- varlistp

4.883 suffix/3

- listp

4.884 `sum/2`

- `numberlistp`
- `statisticsp`

4.885 `superclass/1`

- `class_hierarchyp`

4.886 `superclasses/1`

- `class_hierarchyp`

4.887 `suspend_monitor/0`

- `monitorp`

4.888 `swap/2`

- `random_protocol`

4.889 `swap_consecutive/2`

- `random_protocol`

4.890 `syndiff/3`

- `setp`

4.891 `tab//0`

- `blank_grammars(Format)`

4.892 tabs//0

- blank_grammars(Format)

4.893 take/3

- listp

4.894 temporary_directory/1

- osp

4.895 term_expansion/2

- expanding

4.896 terms_to_array/2

- java_utils_protocol

4.897 test/1

- lgtunit

4.898 time_stamp/1

- osp

4.899 timeout/1

- metagol

4.900 timestamp/2

- ulid_protocol

4.901 timestamp/8

- ulid_protocol

4.902 today/3

- datep

4.903 tolerance_equal/4

- lgtunit
- number

4.904 top/3

- heapp

4.905 top_next/5

- heapp

4.906 trace/0

- debuggerp

4.907 trace_event/2

- logtalk

4.908 transpose/2

- pairs

4.909 triangular/4

- sampling_protocol

4.910 true/1

- java_utils_protocol

4.911 type/1

- type

4.912 unexpected/1

- expected(Expected)

4.913 unexpecteds/2

- either

4.914 uniform/1

- sampling_protocol

4.915 uniform/3

- sampling_protocol

4.916 `uninstall/0`

- `packs`

4.917 `uninstall/1`

- `packs`

4.918 `uninstall/2`

- `packs`

4.919 `union/3`

- `setp`

4.920 `union/4`

- `setp`
- `union_find_protocol`

4.921 `union_all/3`

- `union_find_protocol`

4.922 `unpin/0`

- `packs_common`

4.923 `unpin/1`

- `packs_common`

4.924 unzip/2

- zipperp

4.925 update/0

- doclet
- packs
- registries

4.926 update/1

- observer
- packs
- registries

4.927 update/2

- packs
- registries

4.928 update/3

- dictionaryp
- packs

4.929 update/4

- dictionaryp

4.930 update/5

- dictionaryp

4.931 update_in/4

- nested_dictionary_protocol

4.932 update_in/5

- nested_dictionary_protocol

4.933 uuid_null/1

- uuid_protocol

4.934 uuid_v1/2

- uuid_protocol

4.935 uuid_v4/1

- uuid_protocol

4.936 valid/1

- intervalp
- statisticsp
- term p
- varlistp

4.937 valid/2

- type

4.938 valid/3

- datep
- timep

4.939 valid_date/3

- iso8601

4.940 valid_option/1

- options_protocol

4.941 valid_options/1

- options_protocol

4.942 validate/1

- flags_validator

4.943 value/1

- counter

4.944 value/3

- pairs

4.945 value_reference/2

- java_utils_protocol

4.946 values/2

- dictionaryp
- pairs

4.947 variables/2

- term

4.948 variance/2

- statisticsp

4.949 variant/2

- lgtunit
- term

4.950 varnumbers/2

- term

4.951 varnumbers/3

- term

4.952 verify__commands__availability/0

- packs__common

4.953 version/6

- pack__protocol

4.954 versions/3

- packs

4.955 void/1

- java_utils_protocol

4.956 void_element/1

- html

4.957 von_mises/3

- sampling_protocol

4.958 wald/3

- sampling_protocol

4.959 wall_time/1

- osp

4.960 weibull/3

- sampling_protocol

4.961 weighted_mean/3

- statisticsp

4.962 welcome/0

- shell

4.963 when/2

- coroutining

4.964 whiledo/2

- looppp

4.965 white_space//0

- blank_grammars(Format)

4.966 white_spaces//0

- blank_grammars(Format)

4.967 with_output_to/2

- term_io_protocol

4.968 without//2

- sequence_grammars

4.969 working_directory/1

- osp

4.970 write__file/3

- csv_protocol
- tsv_protocol

4.971 write__max__depth/1

- debuggerp

4.972 write__stream/3

- csv_protocol
- tsv_protocol

4.973 write__term__to__atom/3

- term_io_protocol

4.974 write__term__to__chars/3

- term_io_protocol

4.975 write__term__to__chars/4

- term_io_protocol

4.976 write__term__to__codes/3

- term_io_protocol

4.977 write__term__to__codes/4

- term_io_protocol

4.978 write_to_atom/2

- term_io_protocol

4.979 write_to_chars/2

- term_io_protocol

4.980 write_to_codes/2

- term_io_protocol

4.981 z_normalization/2

- statisticsp

4.982 zero_or_more//0

- sequence_grammars

4.983 zero_or_more//1

- sequence_grammars

4.984 zero_or_more//2

- sequence_grammars

4.985 zip/2

- zipperp

4.986 zip/3

- zipperp

4.987 zip_at_index/4

- zlist

INDICES AND TABLES

- `genindex`
- `search`

Generated on Wed May 28 18:07:02 WEST 2025

Symbols

(/)/2, 358
 (//)/2, 358
 (<)/2, 872
 (<=)/2, 15, 552
 (:=)/2, 873
 (=<)/2, 872
 (=>)/2, 16, 553
 (=\\=)/2, 873
 (>)/2, 872
 (>=)/2, 873
 =~= / 2, 498, 914

A

a_star_interpreter(W), 976
 absolute_file_name/2, 645
 acc_info/5, 270
 acc_info/7, 269
 activate_debug_handler/1, 75
 activate_monitor/0, 281
 active_debug_handler/1, 74
 active_debug_handler_/1, 81
 add/1, 711
 add/2, 711
 add/3, 710, 877
 add_directive_/2, 1018
 add_directive_/3, 1019
 add_directive_before_entity_/2, 1018
 add_library_documentation_url/4, 229
 add_link_options/3, 175
 add_node_zoom_option/4, 176
 addDependent/1, 151
 after/2, 416
 after/3, 83
 after_event_registry, 271
 all/0, 32, 118, 479
 all/1, 31, 117, 479
 all_files/0, 165, 188
 all_files/1, 165, 188
 all_libraries/0, 159, 182
 all_libraries/1, 158, 182
 all_score/1, 34

ancestor/1, 375
 ancestor/4, 42
 ancestors/1, 375
 apis/0, 364
 apis/1, 364
 append/2, 890
 append/3, 739, 890, 949
 apply/2, 1034
 apply/4, 260
 approximately_equal/2, 496, 912
 approximately_equal/3, 496, 912
 arbitrary, 1
 arbitrary/1, 4
 arbitrary/2, 4
 archive/1, 722
 arithmetic_mean/2, 815
 arithmetic_mean/5, 810
 array_list/2, 449
 array_to_list/2, 449
 array_to_terms/2, 448
 array_to_terms/3, 448
 as_curly_bracketed/2, 251, 612
 as_dictionary/2, 251
 as_difflist/2, 885
 as_heap/2, 352
 as_list/2, 251, 352, 740, 797, 877
 as_nested_dictionary/2, 611
 as_set/2, 797
 ask_question/5, 72
 assertion/1, 10, 491
 assertion/2, 10, 491
 assertions, 7
 assertions(Mode), 9
 assertions_messages, 11
 assignable/1, 14
 assignable/2, 15
 assignvars, 12
 assignvarsp, 13
 atom, 856
 atomic, 858
 automation_report, 480
 auxiliary_predicate_counter_/1, 529

available/0, 667
available/1, 666
available/2, 666
average/2, 920
average_deviation/3, 817
avltree, 245

B

backend_adapter_hook, 384
backend_random, 742
base64, 17
base64url, 19
base_/2, 323
before/2, 416
before/3, 83
before_event_registry, 272
bench_goal/1, 989
benchmark/2, 494
benchmark/3, 495
benchmark/4, 495
benchmark_generators, 978
benchmark_reified/3, 494
bernoulli/2, 765
best_first, 979
beta/3, 765
between/3, 753, 881
between/4, 879
bfs_interpreter, 981
binary_file_assertion/3, 525
binary_input_assertion/2, 509
binary_input_assertion/3, 509
binary_output_assertion/2, 520
binary_output_assertion/3, 519
binary_output_contents/1, 520
binary_output_contents/2, 520
binomial/3, 765
bintree, 246
bit//1, 339
bits//1, 339
blank//0, 333
blank_grammars(Format), 329
blanks//0, 333
body_pred/1, 590
body_pred_call/2, 593
branch/2, 326
breakpoint_/2, 128
built_in_directive/4, 359
built_in_flag/2, 309
built_in_method/4, 360
built_in_non_terminal/4, 360
built_in_predicate/4, 359
bup_interpreter, 982

C

c/1, 986
calendar_month/3, 431
call_with_timeout/2, 835
call_with_timeout/3, 836
callable, 859
cat/2, 617
cbor, 21
cbor(StringRepresentation), 22
cc_metric, 24
cdata_generation//1, 1027
change_directory/1, 648
changed/0, 151
changed/1, 151
character, 860
character_data_format/3, 1027
characterp, 861
chebyshev_distance/3, 922
chebyshev_norm/2, 921
check/1, 937, 957
check/2, 945
check/3, 945
check_binary_file/2, 524
check_binary_input/1, 508
check_binary_input/2, 508
check_binary_output/1, 519
check_binary_output/2, 518
check_option/1, 633
check_options/1, 633
check_text_file/2, 523
check_text_file/3, 522
check_text_input/1, 505
check_text_input/2, 504
check_text_output/1, 513
check_text_output/2, 512
check_text_output/3, 512
chi_squared/2, 763
chr_is/2, 838
chr_next_state/1, 841
chr_no_spy/1, 839
chr_nospy/0, 839
chr_notrace/0, 838
chr_option/2, 839
chr_option_allow_deep_guards/0, 841
chr_option_optimization_level/1, 840
chr_option_print_trace/0, 839
chr_option_show_history/0, 840
chr_option_show_id/0, 841
chr_option_show_stack/0, 840
chr_option_show_store/0, 840
chr_option_trace_interactive/0, 840
chr_rule_/1, 842
chr_spy/1, 839
chr_spy_point/1, 841

chr_trace/0, 838
 circular_uniform_cartesian/3, 770
 circular_uniform_polar/3, 770
 class/1, 368
 class_hierarchy, 366
 class_hierarchyp, 367
 classes/1, 368
 clause/5, 732
 clause_/5, 733
 clause_location/6, 731
 clause_location_/6, 732
 clean/0, 685, 716
 clean/1, 684, 716
 clean/2, 684
 clean_binary_input/0, 510
 clean_binary_output/0, 521
 clean_directory/1, 526
 clean_file/1, 525
 clean_text_input/0, 506
 clean_text_output/0, 516
 cleanup/0, 500
 clone/1, 547, 722
 clone/3, 252
 clone/4, 252
 cloning, 546
 closed_input_stream/2, 526
 closed_output_stream/2, 527
 code_metric, 25
 code_metrics, 38
 code_metrics_messages, 40
 code_metrics_utilities, 41
 coefficient_of_variation/2, 818
 command/2, 701
 command_line_arguments/1, 658
 commit_author/2, 326
 commit_date/2, 327
 commit_hash/2, 327
 commit_hash_abbreviated/2, 328
 commit_log/3, 328
 commit_message/2, 328
 comparingp, 871
 compile_aux_clauses/1, 78
 compile_predicate_heads/4, 79
 compile_predicate_indicators/3, 79
 compiled_pred_call/2, 592
 completion/2, 358
 completions/2, 359
 compound, 874
 condition/0, 500
 conditional_breakpoint_/3, 131
 connect/1, 790
 connect/3, 790
 console/1, 791
 contains/2, 419

control//0, 334
 control_construct/4, 360
 controls//0, 335
 copy_file/2, 654
 core_messages, 63
 coroutining, 85
 counter, 983
 counter/2, 548, 605
 counter_/2, 320, 550, 606
 counters, 547
 coupling_metric, 46
 cover/1, 487
 coverage_report, 481
 covered_/4, 531
 cpu_time/1, 110, 656
 create_binary_file/2, 522
 create_text_file/2, 522
 create_text_file/3, 521
 csv, 88
 csv(Header,Separator,IgnoreQuotes), 90
 csv_guess_questions, 91
 csv_protocol, 92
 current/2, 1031
 current_entity/1, 43
 current_prog/1, 839

D

d2_graph_language, 153
 data/0, 729
 data/1, 730
 data/2, 730
 databasep, 987
 date, 103
 date/4, 423
 date/5, 424
 date/6, 424
 date/7, 426
 date_string/3, 427
 date_time/7, 656
 datep, 104
 days_in_month/3, 106
 deactivate_debug_handler/0, 75
 dead_code_scanner, 111
 dead_code_scanner_messages, 119
 debug/0, 137
 debug_expansion(Mode), 989
 debug_handler/1, 74
 debug_handler/3, 75
 debug_messages, 120
 debugger, 125
 debugger_messages, 133
 debuggerp, 134
 debugging/0, 137
 debugging/1, 137

debugging_/0, 126
decide/1, 303
decide/2, 303
declares_predicate/2, 43
decode_exception/2, 451
decode_exception/3, 451
decode_url_spaces/2, 704
decompile_predicate_heads/4, 79
decompile_predicate_indicators/4, 80
decompose_file_name/3, 645
decompose_file_name/4, 645
decrement_counter/1, 549
default_atom_mutations, 595
default_compound_mutations, 596
default_float_mutations, 598
default_integer_mutations, 599
default_list_mutations, 600
default_option/1, 634, 1014
default_options/1, 635, 1014
default_workflow_hook, 386
define_flag/1, 310
define_flag/2, 311
define_log_file/2, 562
defined/4, 709
defined_flag/6, 309
defined_flag_/6, 311
defines_predicate/2, 43
defines_predicate/3, 44
del_monitors/0, 278
del_monitors/4, 277
del_spy_points/4, 283
delete/0, 715
delete/1, 715
delete/2, 714
delete/3, 798, 890, 949
delete/4, 253, 350
delete_all_after/2, 1037
delete_all_after_and_unzip/2, 1037
delete_all_before/2, 1036
delete_all_before_and_unzip/2, 1037
delete_and_next/2, 1036
delete_and_previous/2, 1035
delete_and_unzip/2, 1036
delete_directory/1, 647
delete_directory_and_contents/1, 648
delete_directory_contents/1, 648
delete_file/1, 654
delete_in/4, 613
delete_matches/3, 891
delete_max/4, 258
delete_min/4, 258
demodb, 990
dependent_/1, 152
dependents/1, 151, 689
dependents/2, 689
dependents/3, 688
depth/2, 935
descendant/1, 376
descendant_class/1, 373
descendant_classes/1, 373
descendant_instance/1, 372
descendant_instances/1, 372
descendants/1, 377
describe/1, 674, 708
describe/2, 674
description/1, 661, 721
deterministic/1, 490
deterministic/2, 490
dfs_interpreter, 992
diagram(Format), 154
diagram_caption/3, 167
diagram_description/1, 166
diagram_name_suffix/1, 166
diagrams, 178
diagrams(Format), 179
dictionary, 249
dif, 263
dif/1, 86, 264
dif/2, 86, 264
difflist, 875
digit//1, 339
digits//1, 340
directories/1, 476, 1011
directories/2, 161, 184, 475, 1011
directories/3, 160, 184
directory/1, 29, 115, 163, 186, 477, 697, 1011
directory/2, 28, 114, 163, 186, 476, 697, 1010
directory/3, 162, 186
directory_dependency_diagram, 189
directory_dependency_diagram(Format), 190
directory_diagram(Format), 192
directory_entity_/4, 466
directory_exists/1, 651
directory_files/2, 650
directory_files/3, 651
directory_load_diagram, 196
directory_load_diagram(Format), 197
directory_score/2, 33
dirichlet/2, 769
disable/1, 122
disable/2, 123
disable_logging/1, 564
disconnect/1, 791
disjoint/2, 798
disjoint_sets/2, 970
dit_metric, 48
doc_goal/1, 266
doc_metric, 49

doclet, 265
 doctype/1, 406
 document_generation//2, 1026
 dot//1, 342
 dot_graph_language, 199
 dowhile/2, 567
 drop/3, 909
 dump_trace, 146
 during/2, 419
 dynamic_directive_/3, 1017

E

easter_day/3, 431
 edcg, 267
 edge/5, 170
 edge/6, 219
 edge_/5, 177
 edge_case/2, 5
 either, 285
 either/3, 298
 empty/1, 254, 351, 611, 619, 737, 799, 891, 950
 empty_map/1, 1024
 enable/1, 121
 enable/2, 122
 enable_logging/1, 564
 enabled/1, 122
 enabled/2, 123
 enabled_/1, 124
 enabled_/2, 124
 ensure_directory/1, 652
 ensure_file/1, 655
 entity/1, 27, 113, 243, 361
 entity/2, 243
 entity_calls/3, 44
 entity_defines_/2, 733
 entity_diagram, 201
 entity_diagram(Format), 202
 entity_info_pair_score_hook/3, 51
 entity_info_score_hook/2, 51
 entity_kind/2, 45
 entity_predicates_weights_hook/2, 51
 entity_prefix/2, 78
 entity_property/2, 45
 entity_score/2, 32
 entity_updates/3, 45
 enumerate/2, 755
 environment_variable/2, 655
 epsilon/1, 498
 equal/2, 420, 798
 erase/1, 787
 essentially_equal/3, 497, 913
 euclidean_distance/3, 922
 euclidean_norm/2, 921
 event_registry, 273

event_registryp, 275
 exception/4, 1026
 exclude/3, 575
 execution_context/7, 80
 expand_library_alias_paths, 284
 expand_library_path/2, 76
 expanding, 64
 expected, 288
 expected(Expected), 293
 expected/1, 296
 expecteds/2, 286
 explain//1, 855
 exponential/2, 764
 extension/1, 380
 extensions/1, 381
 external_predicate_/1, 244

F

f/4, 980
 failed_/3, 530
 false/1, 445
 fast_random, 743
 fault/5, 1026
 fcube, 301
 fcube/0, 303
 file/1, 28, 114, 204, 478, 1013
 file/2, 28, 113, 203, 478, 1013
 file_being_advised_/4, 1019
 file_dependency_diagram, 206
 file_dependency_diagram(Format), 207
 file_diagram(Format), 209
 file_exists/1, 652
 file_footer/3, 218
 file_header/3, 218
 file_line_hit_count_/3, 133
 file_load_diagram, 213
 file_load_diagram(Format), 214
 file_modification_time/2, 652
 file_path/2, 501
 file_permission/2, 653
 file_score/2, 33
 file_size/2, 653
 file_to_bytes/2, 776
 file_to_bytes/3, 776
 file_to_chars/2, 775
 file_to_chars/3, 775
 file_to_codes/2, 774
 file_to_codes/3, 774
 file_to_terms/2, 775
 file_to_terms/3, 776
 file_type_extension/2, 77
 files/1, 164, 188, 477, 1012
 files/2, 164, 187, 477, 1012
 files/3, 164, 187

- filter/2, 625
- filter_external_file_extension/3, 174
- filter_file_extension/3, 174
- find/4, 969
- find/5, 969
- findall_member/4, 575
- findall_member/5, 576
- finished_by/2, 420
- finishes/2, 419
- fired_/3, 531
- fisher/3, 763
- fix_option/2, 637
- fix_options/2, 636
- flag_group_chk/1, 308
- flag_groups/1, 308
- flag_value_/2, 311
- flags, 305
- flags_validator, 312
- flaky_/1, 531
- flat_map/2, 297, 626
- flatten/2, 891, 950
- flatten_goals//1, 994
- flatting, 993
- float, 878
- float//1, 341
- fold_left/4, 577
- fold_left_1/3, 577
- fold_right/4, 579
- fold_right_1/3, 579
- fordownto/3, 570
- fordownto/4, 570
- fordownto/5, 571
- foreach/3, 568
- foreach/4, 568
- format, 314
- format/2, 315
- format/3, 315
- format_entity_score//2, 35
- format_object/1, 165
- format_to_atom/3, 831
- format_to_chars/3, 832
- format_to_chars/4, 832
- format_to_codes/3, 833
- format_to_codes/4, 833
- forto/3, 569
- forto/4, 569
- forto/5, 569
- forward/1, 67
- forward/2, 1033
- forward/3, 1033
- forwarding, 66
- fractile/3, 821
- freeze/2, 87
- from_generator/2, 292, 621

- from_generator/3, 291, 620
- from_generator/4, 291
- from_goal/2, 291, 620
- from_goal/3, 290, 620
- from_goal/4, 290
- frozen/2, 87
- full_device_path/1, 650
- func_test/3, 591
- functional/0, 591

G

- gamma/3, 766
- generate/1, 412, 962
- generate/2, 18, 20, 23, 405, 457, 463, 962
- generate/8, 962
- generated_predicate_/1, 585
- generating_/0, 536
- genint, 316
- genint/2, 319
- genint_core, 317
- gensym, 320
- gensym/2, 323
- gensym_core, 321
- geometric/2, 764
- geometric_mean/2, 815
- get/1, 627
- get_field/2, 439
- get_flag_value/2, 306
- get_seed/1, 6, 747
- git, 324
- git_protocol, 325
- gnu/0, 302
- goal_expansion/2, 65
- grammar_rules_hook, 387
- graph_footer/5, 218
- graph_header/5, 218
- graph_language_protocol, 216
- graph_language_registry, 220
- ground/1, 935
- ground_entity_identifier/3, 174
- group_by_key/2, 931
- group_consecutive_by_key/2, 931
- group_sorted_by_key/2, 930
- guess_arity/2, 102
- guess_separator/2, 101
- gumbel/3, 769

H

- halstead_metric, 54
- halstead_metric(Stroud), 55
- hamming_distance/3, 892
- handbook/0, 364
- handbook/1, 364
- harmonic_mean/2, 815

head/2, 737
 head_pred/1, 590
 heap(Order), 347
 heapp, 348
 help, 356
 help/0, 358, 694
 help_info_support, 362
 heuristic_expansion(Mode), 994
 hex_digit//1, 340
 hex_digits//1, 340
 hierarchyp, 374
 home/1, 662, 721
 hook_pipeline(Pipeline), 381
 hook_set(Set), 383
 html, 404
 html5, 407
 hypergeometric/4, 764

I

ibk/3, 590
 iddfs_interpreter(Increment), 996
 identity_hook, 388
 ids, 409
 ids(Representation,Bytes), 410
 if_empty/1, 624
 if_expected/1, 295
 if_expected_or_else/2, 296
 if_present/1, 624
 if_present_or_else/2, 625
 if_unexpected/1, 295
 include/3, 575
 included_directory_/1, 195
 included_entity_/1, 204
 included_file_/1, 212
 included_library_/2, 230
 included_module_/1, 204
 included_predicate_/1, 243
 increase/1, 985
 increment/0, 984
 increment_counter/1, 548
 inheritance_diagram, 221
 inheritance_diagram(Format), 223
 init/0, 1006
 init_log_file/2, 562
 inorder/2, 248
 insert/3, 799
 insert/4, 252, 350
 insert_after/3, 1035
 insert_all/3, 350, 799
 insert_before/3, 1034
 insert_in/4, 613
 install/1, 678
 install/2, 677
 install/3, 677
 install/4, 675
 installed/0, 669
 installed/1, 668
 installed/3, 668
 installed/4, 667
 instance/1, 369
 instance/2, 787
 instances/1, 369
 integer, 880
 integer//1, 341
 internal_os_path/2, 646
 interpreterp, 997
 intersect/2, 800
 intersection/2, 255
 intersection/3, 256, 800
 intersection/4, 800
 interval, 412
 intervalp, 414
 invocation_number_/1, 130
 invoke/1, 440
 invoke/2, 441
 ip_grammars(Format), 335
 ipv4//1, 336
 ipv6//1, 337
 is_absolute_file_name/1, 644
 is_alpha/1, 864
 is_alphanumeric/1, 863
 is_ascii/1, 863
 is_bin_digit/1, 864
 is_control/1, 868
 is_dec_digit/1, 865
 is_empty/0, 623
 is_end_of_line/1, 869
 is_expected/0, 294
 is_false/1, 446
 is_hex_digit/1, 865
 is_layout/1, 867
 is_letter/1, 864
 is_lower_case/1, 866
 is_newline/1, 869
 is_null/1, 447
 is_object/1, 447
 is_octal_digit/1, 865
 is_period/1, 868
 is_present/0, 623
 is_punctuation/1, 868
 is_quote/1, 867
 is_true/1, 446
 is_unexpected/0, 294
 is_upper_case/1, 866
 is_validator/1, 312
 is_void/1, 446
 is_vowel/1, 866
 is_white_space/1, 867

iso8601, 421
issue_creator, 432
iterator_element/2, 450

J

java, 434
java(Reference), 435
java(Reference,ReturnValue), 436
java_access_protocol, 438
java_hook, 441
java_utils_protocol, 443
join/3, 737
join_all/3, 738
json, 452
json(ObjectRepresentation,PairRepresentation,StringRepresentation), 454
json(StringRepresentation), 453
json_lines, 458
json_lines(ObjectRepresentation,PairRepresentation,StringRepresentation), 460
json_lines(StringRepresentation), 459
json_lines_protocol, 461
json_protocol, 456
jump/3, 738
jump_all/3, 738
jump_all_block/3, 739
jump_to_invocation_number_/1, 130

K

key/2, 929
keys/2, 258, 929
keys_values/3, 928
keysort/2, 892
kurtosis/2, 819

L

language_object/2, 221
last/2, 892, 950
leaf/1, 376
leaf_class/1, 371
leaf_classes/1, 372
leaf_instance/1, 371
leaf_instances/1, 371
leap_year/1, 105, 430
leaping_/1, 128
learn/0, 594
learn/1, 594
learn/2, 588
learn/3, 588
learn_seq/2, 588
learn_with_timeout/4, 589
leash/1, 138
leashing/1, 139

leashing_/1, 129
least_common_multiple/2, 925
leaves/1, 376
length/2, 739, 893, 951
lgtdoc, 464
lgtdoc_messages, 467
lgtdocp, 468
lgtunit, 483
lgtunit_messages, 532
libraries/1, 158, 181, 472
libraries/2, 158, 181, 472
libraries/3, 157, 181
library/0, 361
library/1, 30, 116, 160, 183, 361, 473
library/2, 30, 116, 160, 183, 473
library_dependency_diagram, 224
library_dependency_diagram(Format), 225
library_diagram(Format), 227
library_entity/4, 465
library_load_diagram, 231
library_load_diagram(Format), 233
library_score/2, 32
license/1, 661
line_to_chars/2, 780
line_to_chars/3, 780
line_to_codes/2, 780
line_to_codes/3, 781
lint/0, 691, 718
lint/1, 690, 717
lint/2, 690
list, 884
list(Type), 886
list/0, 708
list_to_array/2, 449
listing, 554
listing/0, 555
listing/1, 555
listp, 887
load_registry/1, 702
loaded_file/1, 76
loaded_file_property/2, 76, 236
locate_directory/2, 173
locate_file/5, 173
locate_library/2, 173
log/3, 143
log_event/2, 563
log_file/2, 562
log_file_/2, 558, 560
log_point_/3, 131
logger, 557
logging, 559
logging/1, 563
logging/3, 144
logging_to_file_/2, 558, 560

[loggingp](#), 561
[logistic/3](#), 766
[lognormal/3](#), 762
[logseries/2](#), 763
[logtalk](#), 67
[logtalk_packs/0](#), 699
[logtalk_packs/1](#), 699
[lookup/2](#), 255
[lookup/3](#), 255
[lookup_in/3](#), 612
[loop](#), 565
[loopp](#), 566
[lower_upper/2](#), 870

M

[magic](#), 999
[magic/2](#), 1000
[magic_expansion\(Mode\)](#), 1001
[magicise/4](#), 1000
[make/1](#), 501
[make_directory/1](#), 646
[make_directory_path/1](#), 647
[make_set/3](#), 968
[man/1](#), 365
[manhattan_distance/3](#), 923
[manhattan_norm/2](#), 922
[manuals/0](#), 362
[map/2](#), 259, 297, 580, 625, 740
[map/3](#), 259, 581, 741, 932
[map/4](#), 581
[map/5](#), 581
[map/6](#), 582
[map/7](#), 582
[map/8](#), 583
[map_element/2](#), 450
[map_member/3](#), 1024
[map_reduce/5](#), 583
[map_store/4](#), 1025
[max/2](#), 814, 893, 918
[max/3](#), 257
[max_clauses/1](#), 591
[max_inv_preds/1](#), 591
[max_size/1](#), 7
[maxheap](#), 353
[maybe](#), 616
[maybe/0](#), 757
[maybe/1](#), 758
[maybe/2](#), 758
[maybe_call/1](#), 758
[maybe_call/2](#), 759
[mean_deviation/2](#), 817
[median/2](#), 816, 920
[median_deviation/2](#), 818
[meets/2](#), 417

[member/2](#), 753, 801, 893
[memberchk/2](#), 802, 894, 951
[merge/3](#), 351
[merge_options/2](#), 636, 1015
[message_cache_/1](#), 540, 542, 543, 545
[message_diagram_description/1](#), 176
[message_hook/4](#), 72
[message_prefix_file/6](#), 71
[message_prefix_stream/4](#), 71
[message_tokens//2](#), 71
[met_by/2](#), 417
[meta](#), 572
[meta_compiler](#), 584
[meta_type/3](#), 944
[metagol](#), 586
[metagol_example_protocol](#), 593
[metap](#), 573
[metarule/6](#), 590
[metarule_next_id/1](#), 592
[min/2](#), 813, 894, 918
[min/3](#), 257
[min_clauses/1](#), 591
[min_max/3](#), 814, 919
[minheap](#), 355
[minimal_output](#), 533
[missing_predicate_directive_/3](#), 1017
[modes/2](#), 817, 920
[module_predicate_called_/3](#), 1016
[module_property/2](#), 236
[modules_diagram_support](#), 235
[monitor](#), 278
[monitor/1](#), 276
[monitor/4](#), 277
[monitor_activated/0](#), 281
[monitored/1](#), 276
[monitoring](#), 82
[monitorp](#), 280
[monitors/1](#), 276
[msort/2](#), 894
[msort/3](#), 895
[multifile_directive_/3](#), 1018
[mutation/3](#), 603, 605
[mutation/4](#), 606
[mutations](#), 602
[mutations_store](#), 604

N

[name/1](#), 661, 721
[name_of_day/3](#), 106
[name_of_month/3](#), 106
[natural](#), 910
[natural//1](#), 341
[navltree](#), 607
[nbintree](#), 608

- nested_dictionary_protocol, 609
- new/1, 440, 552, 611, 936
- new/2, 440, 552, 968
- new/3, 415
- new_line//0, 332
- new_lines//0, 333
- next/2, 1031
- next/3, 1031
- next/4, 256
- nextto/3, 895, 951
- noc_metric, 57
- node/6, 170
- node/7, 219
- node_/6, 177
- node_path_/2, 177
- nodebug/0, 137
- nolog/3, 144
- nologall/0, 144
- non_blank//1, 334
- non_blanks//1, 334
- non_standard_predicate_call_/2, 1017
- nor_metric, 58
- normal/3, 762
- normal_element/2, 406
- normalize_range/2, 923
- normalize_range/4, 924
- normalize_scalar/2, 925
- normalize_unit/2, 924
- nospy/1, 140
- nospy/3, 141
- nospy/4, 142
- nospyall/0, 143
- not_excluded_file/3, 46
- not_excluded_file/4, 172
- note/1, 501
- note/2, 722
- note/3, 663
- notrace/0, 138
- now/3, 110
- nrbtree, 614
- nth0/3, 896, 952
- nth0/4, 896, 952
- nth1/3, 896, 953
- nth1/4, 897, 953
- null/1, 445
- null_device_path/1, 649
- number, 911
- number//1, 342
- number_grammars(Format), 337
- number_of_tests/1, 489
- numberlist, 915
- numberlistp, 916
- numbervars/1, 939
- numbervars/3, 939

O

- object_file_/2, 483
- object_predicate_called_/3, 1016
- object_wrapper_hook, 390
- object_wrapper_hook(Name,Relations), 393
- object_wrapper_hook(Protocol), 391
- observer, 148
- occurrences/2, 898
- occurrences/3, 898
- occurs/2, 936
- of/2, 619
- of_expected/2, 289
- of_unexpected/2, 289
- omit_path_prefix/3, 175
- one_or_more//0, 346
- one_or_more//1, 345
- one_or_more//2, 344
- operating_system_machine/1, 658
- operating_system_name/1, 657
- operating_system_release/1, 658
- operating_system_type/1, 657
- option/2, 635
- option/3, 635
- optional, 618
- optional(Optional), 622
- options, 630
- options_protocol, 631
- or/2, 626
- or_else/2, 298, 627
- or_else_call/2, 299, 628
- or_else_fail/1, 300, 629
- or_else_get/2, 299, 628
- or_else_throw/1, 300
- or_else_throw/2, 629
- orphaned/0, 673
- orphaned/2, 672
- os, 637
- os_types, 639
- osp, 641
- outdated/0, 672
- outdated/1, 672
- outdated/2, 671
- outdated/4, 670
- outdated/5, 669
- output_edges/1, 171
- output externals/1, 168
- output_file/4, 169
- output_file_name/2, 217
- output_file_path/4, 172
- output_files/2, 168
- output_library/3, 167
- output_missing externals/1, 171
- output_node/6, 170
- output_rdirectory/3, 168

output_rlibrary/3, 167
 output_sub_diagrams/1, 169
 overlapped_by/2, 418
 overlaps/2, 417

P

pack_protocol, 660
 packs, 664
 packs_common, 692
 packs_messages, 704
 packs_specs_hook, 705
 pairs, 927
 parent/1, 380
 parenthesis/2, 869
 parents/1, 380
 parse/2, 18, 20, 23, 457, 462, 1022
 parse/3, 1022
 parse_domain/2, 724
 parse_domain/3, 724
 parse_problem/2, 725
 parse_problem/3, 725
 partial_/1, 536, 538
 partial_map/4, 262
 partition/3, 287
 partition/4, 576, 795
 partition/5, 899
 partition/6, 577
 pass_info/1, 270
 pass_info/2, 270
 passed_/3, 530
 path_concat/3, 646
 pcd_data_7bit//1, 1027
 pddl, 723
 permutation/2, 755, 899, 953
 pid/1, 643
 pin/0, 695
 pin/1, 695
 pinned/1, 696
 plus/3, 882
 poisson/2, 766
 population, 806
 port/5, 731
 port_/5, 733
 portray_clause/1, 556
 ports_profiler, 728
 postorder/2, 248
 power/2, 767
 power_sequence/4, 883
 powerset/2, 802
 pp/1, 1023
 pp_string/1, 1025
 pprint/1, 589
 pprint_clause/1, 592
 pprint_clauses/1, 592

pred_info/3, 269
 predicate/2, 118
 predicate_called_but_not_defined_/2, 1015
 predicate_entity_/4, 466
 predicate_info_pair_score_hook/4, 53
 predicate_info_score_hook/3, 52
 predicate_mode_score_hook/3, 52
 predicate_mode_score_hook/5, 52
 predicates/2, 118
 prefix/0, 700
 prefix/1, 700
 prefix/2, 899, 954
 prefix/3, 900
 preorder/2, 247
 previous/2, 1032
 previous/3, 1032
 previous/4, 256
 print_flags/0, 308, 313
 print_flags/1, 309
 print_goal_hook, 394
 print_message/3, 70
 print_message_token/4, 70
 print_message_tokens/3, 70
 print_readme_file_path/1, 701
 process_all/1, 37
 process_directory/2, 36
 process_entity/2, 35
 process_file/2, 35
 process_library/2, 36
 process_rdirectory/2, 36
 process_rlibrary/2, 37
 product/2, 813, 919
 product/3, 802
 program_to_clauses/2, 589
 prolog_module_hook(Module), 396
 proper_prefix/2, 900
 proper_prefix/3, 901
 proper_suffix/2, 908
 proper_suffix/3, 908
 proto_hierarchy, 377
 proto_hierarchyp, 378
 prove/2, 998
 prove/3, 998
 provides/2, 717
 pseudo_random_protocol, 746

Q

quasi_skipping_/0, 128
 question_hook/6, 73
 question_prompt_stream/4, 73
 queue, 734
 queuep, 735
 quick_check/1, 493
 quick_check/2, 492

quick_check/3, 492

R

random, 748

random/1, 752

random/3, 756

random_node/1, 976

random_protocol, 751

random_tree/1, 979

randomize/1, 745, 750

randseq/4, 757

randset/4, 757

range/2, 814

rbtree, 261

rdirectories/1, 474

rdirectories/2, 474

rdirectory/1, 30, 115, 162, 185, 475, 1010

rdirectory/2, 29, 115, 162, 185, 474, 1010

rdirectory/3, 161, 185

rdirectory_score/2, 34

read_file, 726

read_file/2, 95, 727, 847

read_file/3, 94, 846

read_file_by_line/2, 98, 850

read_file_by_line/3, 97, 849

read_from_atom/2, 825

read_from_chars/2, 827

read_from_codes/2, 828

read_only_device_path/1, 650

read_stream/2, 96, 848

read_stream/3, 95, 846

read_stream_by_line/2, 99, 851

read_stream_by_line/3, 98, 850

read_term_from_atom/3, 825

read_term_from_chars/3, 826

read_term_from_chars/4, 826

read_term_from_codes/3, 827

read_term_from_codes/4, 827

reader, 773

readme/1, 698

readme/2, 698

readme_file_path/2, 701

record_/3, 788

recorda/2, 785

recorda/3, 784

recorded/2, 786

recorded/3, 786

recorded_database, 782

recorded_database_core, 783

recordz/2, 786

recordz/3, 785

redis, 789

reference_/1, 788

referenced_entity_/2, 205

referenced_logtalk_directory_/1, 195

referenced_logtalk_file_/1, 212

referenced_logtalk_library_/2, 230

referenced_module_/2, 205

referenced_predicate_/1, 244

referenced_prolog_directory_/1, 195

referenced_prolog_file_/1, 212

referenced_prolog_library_/2, 231

registries, 707

registry_loader_hook, 718

registry_protocol, 719

relative_standard_deviation/2, 819

remember_included_directory/1, 194

remember_included_file/1, 211

remember_included_library/2, 229

remember_referenced_logtalk_directory/1, 194

remember_referenced_logtalk_file/1, 211

remember_referenced_logtalk_library/2, 229

remember_referenced_prolog_directory/1, 194

remember_referenced_prolog_file/1, 211

remember_referenced_prolog_library/2, 230

remove_directive_/2, 1019

remove_duplicates/2, 901, 954

removeDependent/1, 152

rename_file/2, 654

replace/3, 1035

replace_sub_atom/4, 857

rescale/3, 925

reset/0, 136, 169, 694, 730, 986

reset/1, 731

reset_counter/1, 549

reset_counters/0, 549

reset_flags/0, 307

reset_flags/1, 307

reset_genint/0, 319

reset_genint/1, 319

reset_gensym/0, 322

reset_gensym/1, 322

reset_monitor/0, 282

reset_seed/0, 745, 750

restore/1, 687

restore/2, 686

reverse/2, 901, 954

rewind/2, 1032

rewind/3, 1033

rlibraries/1, 470

rlibraries/2, 470

rlibrary/1, 31, 117, 159, 183, 471

rlibrary/2, 31, 116, 159, 182, 471

rlibrary_score/2, 33

rule/2, 988

rule/3, 988

rule/4, 988

rule_expansion(Mode), 1002

[run/0](#), 487
[run/1](#), 488
[run/2](#), 488
[run_quick_check_tests/5](#), 499
[run_test_set/0](#), 499
[run_test_sets/1](#), 489
[run_tests/0](#), 499
[run_tests/1](#), 499
[running_test_sets_/0](#), 528

S

[same_length/2](#), 902, 955
[same_length/3](#), 902
[sample](#), 807
[sampling_protocol](#), 760
[save/0](#), 1014
[save/1](#), 686, 1013
[save/2](#), 685
[save_edge/5](#), 171
[scalar_product/3](#), 923
[scan_left/4](#), 578
[scan_left_1/3](#), 578
[scan_right/4](#), 579
[scan_right_1/3](#), 580
[search/1](#), 675
[seed_/3](#), 746, 750
[select/3](#), 753, 803, 902, 955
[select/4](#), 754, 903
[selectchk/3](#), 803, 903
[selectchk/4](#), 903
[selected_test_/1](#), 529
[send/3](#), 791
[sequence/3](#), 882
[sequence/4](#), 756, 879, 883
[sequence/5](#), 879
[sequence_grammars](#), 343
[sequential_occurrences/2](#), 897
[sequential_occurrences/3](#), 897
[serve/3](#), 740
[set](#), 792
[set\(Type\)](#), 793
[set/1](#), 985
[set/4](#), 756
[set_binary_input/1](#), 507
[set_binary_input/2](#), 507
[set_binary_input/3](#), 506
[set_binary_output/1](#), 518
[set_binary_output/2](#), 517
[set_binary_output/3](#), 517
[set_element/2](#), 450
[set_field/2](#), 439
[set_flag_value/2](#), 306
[set_flag_value/3](#), 307
[set_monitor/4](#), 277
[set_seed/1](#), 6, 747
[set_spy_point/4](#), 283
[set_text_input/1](#), 504
[set_text_input/2](#), 503
[set_text_input/3](#), 503
[set_text_output/1](#), 511
[set_text_output/2](#), 511
[set_text_output/3](#), 510
[set_write_max_depth/1](#), 145
[setp](#), 796
[setup/0](#), 500, 694
[sha256sum_command/1](#), 702
[shell](#), 1003
[shell\(Interpreters\)](#), 1005
[shell/1](#), 644
[shell/2](#), 643
[shell_command/1](#), 266
[shell_expansion\(Mode\)](#), 1006
[shrink/3](#), 5
[shrink_sequence/3](#), 5
[shrinker/1](#), 4
[sign//1](#), 342
[singletons/2](#), 939
[size/2](#), 260, 351, 801
[size_metric](#), 60
[skewness/2](#), 819
[skipped_/1](#), 530
[skipping_/0](#), 127
[skipping_unleashed_/1](#), 127
[sleep/1](#), 659
[softmax/2](#), 926
[softmax/3](#), 926
[sort/2](#), 795, 904
[sort/3](#), 904
[sort/4](#), 905
[source_file_extension/1](#), 236
[space//0](#), 331
[spaces//0](#), 331
[split/3](#), 857
[split/4](#), 905
[spy/1](#), 139
[spy/3](#), 140
[spy/4](#), 142
[spy_point/4](#), 282
[spy_point_/4](#), 280
[spying/1](#), 140
[spying/3](#), 141
[spying/4](#), 142
[spying_context_/4](#), 129
[spying_predicate_/3](#), 129
[squares_and_cubes/6](#), 810
[squares_and_hypers/6](#), 810
[standard_cauchy/3](#), 771
[standard_deviation/2](#), 818

- standard_exponential/1, 771
- standard_gamma/2, 771
- standard_normal/1, 772
- standard_t/2, 770
- start/0, 729, 1004
- start_redirect_to_file/2, 147
- started_by/2, 418
- starts/2, 418
- statistics, 808
- statisticsp, 811
- stop/0, 729
- stop_redirect_to_file/0, 147
- stream_position/1, 527
- stream_to_bytes/2, 779
- stream_to_bytes/3, 779
- stream_to_chars/2, 778
- stream_to_chars/3, 778
- stream_to_codes/2, 777
- stream_to_codes/3, 777
- stream_to_terms/2, 778
- stream_to_terms/3, 779
- streamvars, 550
- sub_diagram_/1, 209, 216, 227, 234
- sub_diagram_/2, 192, 199
- sub_directory/2, 37
- sub_library/2, 38
- subclass/1, 369
- subclasses/1, 370
- subject, 149
- sublist/2, 905, 955
- subsequence/3, 906
- subsequence/4, 906
- subset/2, 803
- substitute/4, 907
- subsumes/2, 936
- subterm/2, 937, 1023
- subtract/3, 804, 907, 956
- succ/2, 882
- suffix/2, 907, 956
- suffix/3, 908
- sum/2, 813, 919
- superclass/1, 370
- superclasses/1, 370
- supported_archive/1, 703
- supported_editor_url_scheme_prefix/1, 175
- supported_url_archive/1, 703
- suppress_binary_output/0, 502
- suppress_goal_hook, 397
- suppress_text_output/0, 502
- suspend_monitor/0, 282
- swap/2, 754
- swap_consecutive/2, 754
- syndiff/3, 804

T

- tab//0, 332
- tabs//0, 332
- take/3, 909
- tap_output, 534
- tap_report, 537
- tar_command/1, 703
- temporary_directory/1, 649
- temporary_file_/1, 823
- term, 932
- term_expansion/2, 65
- term_io, 822
- term_io_protocol, 824
- termp, 934
- terms_to_array/2, 447
- test/1, 489
- test/2, 528
- test/3, 528
- test_/2, 529
- test_count_/1, 536, 538
- text_file_assertion/3, 524
- text_file_assertion/4, 523
- text_input_assertion/2, 506
- text_input_assertion/3, 505
- text_output_assertion/2, 514
- text_output_assertion/3, 514
- text_output_assertion/4, 513
- text_output_contents/1, 516
- text_output_contents/2, 515
- text_output_contents/3, 515
- time, 108
- time_stamp/1, 655
- timeout, 834
- timeout/1, 592
- timep, 109
- timestamp/2, 963
- timestamp/8, 963
- timestamp_/6, 482
- today/3, 105
- tolerance_equal/4, 497, 913
- top/3, 352
- top_next/5, 353
- toychrdb, 836
- trace/0, 138
- trace_event/2, 73
- tracing_/0, 127
- transpose/2, 930
- triangular/4, 768
- triggered_breakpoint_/4, 132
- triggered_breakpoint_enabled_/2, 132
- true/1, 444
- tsv, 842
- tsv(Header), 843
- tsv_protocol, 844

tutor, 854
 type, 941
 type/1, 944
 type/3, 593
 type_entity_/4, 466

U

ulid, 958
 ulid(Representation), 959
 ulid_protocol, 960
 ulid_types, 964
 unexpected/1, 296
 unexpecteds/2, 287
 uniform/1, 768
 uniform/3, 767
 uninstall/0, 683
 uninstall/1, 683
 uninstall/2, 682
 union/3, 804
 union/4, 805, 968
 union_all/3, 969
 union_find, 965
 union_find_protocol, 966
 unknown_predicate_called_/2, 1016
 unpin/0, 696
 unpin/1, 696
 unsafe_set_flag_value/2, 310
 unzip/2, 1030
 update/0, 266, 682, 714
 update/1, 149, 681, 713
 update/2, 680, 712
 update/3, 254, 679
 update/4, 253
 update/5, 253
 update_in/4, 612
 update_in/5, 613
 upn_metric, 61
 user, 84
 uses_diagram, 237
 uses_diagram(Format), 238
 uuid, 971
 uuid(Representation), 972
 uuid_null/1, 975
 uuid_protocol, 973
 uuid_v1/2, 975
 uuid_v4/1, 975

V

valid/1, 416, 821, 937, 956
 valid/2, 944
 valid/3, 107, 111
 valid_date/3, 429
 valid_option/1, 634
 valid_options/1, 634

validate/1, 313
 validate/3, 312
 validate_type/1, 312
 value/1, 985
 value/3, 930
 value_reference/2, 444
 values/2, 259, 929
 variables/2, 938
 variance/2, 820
 variance/6, 811
 variant/2, 495, 938
 varlist, 946
 varlistp, 947
 varnumbers/2, 940
 varnumbers/3, 940
 verify_commands_availability/0, 694
 version/6, 662
 versions/3, 673
 void/1, 445
 void_element/1, 405
 von_mises/3, 769

W

wald/3, 762
 wall_time/1, 656
 weibull/3, 767
 weighted_mean/3, 816
 welcome/0, 1004
 when/2, 88
 whiledo/2, 567
 white_space//0, 331
 white_spaces//0, 331
 with_output_to/2, 833
 without//2, 346
 working_directory/1, 649
 wrapper, 1008
 write_file/3, 100, 852
 write_max_depth/1, 145
 write_max_depth_/1, 131
 write_stream/3, 100, 852
 write_term_to_atom/3, 828
 write_term_to_chars/3, 829
 write_term_to_chars/4, 829
 write_term_to_codes/3, 830
 write_term_to_codes/4, 831
 write_to_atom/2, 829
 write_to_chars/2, 830
 write_to_codes/2, 831
 write_to_file_hook(File), 398
 write_to_file_hook(File,Options), 400
 write_to_stream_hook(Stream), 401
 write_to_stream_hook(Stream,Options), 402

X

xhtml11, [408](#)
xml, [1020](#)
xml_to_document/3, [1024](#)
xref_diagram, [240](#)
xref_diagram(Format), [241](#)
xunit_net_v2_output, [539](#)
xunit_net_v2_report, [541](#)
xunit_output, [542](#)
xunit_report, [544](#)

Z

z_normalization/2, [820](#)
zap_to_port_/1, [130](#)
zero_or_more//0, [346](#)
zero_or_more//1, [345](#)
zero_or_more//2, [344](#)
zip/2, [1030](#)
zip/3, [1030](#)
zip_at_index/4, [1039](#)
zipperp, [1028](#)
zlist, [1038](#)